Intelligent Energy Management Systems: Optimizing Energy Consumption through AI

By Adam Ben Rhaiem - University: SUP'COM - Company: ACTIA ES

Introduction

As the world moves toward smarter and more sustainable energy solutions, optimizing energy consumption has become a crucial challenge. Intelligent Energy Management Systems (IEMS) leverage advanced data analytics, artificial intelligence, and machine learning to improve efficiency and reduce waste. By analyzing energy usage patterns, these systems enable better decision-making, enhance appliance monitoring, and contribute to demand-side management in smart grids. This paper explores key methodologies, including data preprocessing, clustering techniques, and AI-driven classification models, to improve energy management and promote a more efficient and intelligent energy ecosystem.

Visualization for understanding user behavior

Visualization is seen to be the most effective way to assimilate increasingly large datasets with the aim of interactively and perfectly conveying insights to end-users and consumers.

Data Preprocessing

Energy datasets often contain errors such as **timestamp disordering, spikes, missing data points, and asynchronous subfields**. To ensure accurate model training, **preprocessing** is essential.

First, data points need to be **reordered** based on ascending timestamps. Identifying and handling missing data is crucial; if the gap is shorter than half the **minimum activation length** of an appliance, forward filling is applied. Otherwise, long-duration missing data in the main energy and target appliance signals should be **removed** from the dataset.

For effective model training, **equally spaced data points** improve learning and accelerate convergence. One common approach is to **average the data over fixed intervals**, such as every 4 seconds.

The **sparse nature** of certain appliance signals (e.g., microwave, dishwasher) can negatively impact training. To address this, tools like **NILMTK** help extract **appliance activation signals** and merge them to reduce sparsity, leading to more efficient training and improved disaggregation performance.

Elbow Method

The elbow method is a graphical method for finding the optimal K value in a k-means clustering algorithm. The elbow graph shows the within-cluster-sum-of-square (WCSS) values on the y-axis corresponding to the different values of K (on the x-axis). The optimal K value is the point at which the graph forms an elbow.

Within-Cluster Sum of Squares (WCSS)

The **Within-Cluster Sum of Squares (WCSS)** is a metric used in clustering algorithms, particularly in **K-Means clustering**, to measure the compactness of clusters. It quantifies the variance within each cluster by calculating the sum of squared differences between each data point and the cluster centroid.

$$WCSS_k = \sum_{i \in C_k} ||x_i - \mu_k||^2$$

where:

- x_i is a data point in cluster C_k,
- μ_k is the centroid of cluster C_k,
- $||x_i - \mu_k||^2$ is the squared Euclidean distance between the data point and the centroid.

The **total WCSS** for all clusters in the dataset is:

$$WCSS = \sum_{k=1}^{K} WCSS_k$$

where K is the number of clusters.

- **Lower WCSS** indicates that clusters are compact and well-formed.
- **Higher WCSS** suggests that the data points within clusters are more spread out.

The **Elbow Method** is commonly used to determine the optimal number of clusters K by plotting WCSS against different values of K.

- The "elbow point" in the plot indicates the optimal number of clusters, where adding more clusters does not significantly reduce WCSS.

Drawbacks

In most of the the real-world data sets, there's not a clear elbow inflection point to identify the right 'K' using the elbow method. This makes it easier to find the wrong K.

Solution

The Silhouette score is a very useful method to find the number of K when the elbow method doesn't show the elbow point.

The value of the Silhouette score ranges from -1 to 1. Following is the interpretation of the Silhouette score.

- **1:** Points are perfectly assigned in a cluster and clusters are easily distinguishable.
- **0:** Clusters are overlapping.
- **-1:** Points are wrongly assigned in a cluster.

```
Silhouette Score = (b-a)/max(a,b)
```

Where:

- `a` = average intra-cluster distance, i.e. the average distance between each point within a cluster.
- `b` = average inter-cluster distance i.e. the average distance between all clusters.

References

https://ieeexplore.ieee.org/document/10220150

https://www.mdpi.com/1424-8220/22/2/473

https://builtin.com/data-science/elbow-method#:~:text=The%20elbow%20method%20is%20a%20graphical%20method%20for%20finding%20the,the%20graph%20forms%20an%20elbow.

Summary of a paper

Appliance identification and classification are crucial for the effective implementation of demand-side management in smart grids. Traditionally, this process involves extracting handcrafted features from electrical signals, followed by classification algorithms, which is both labor-intensive and time-consuming. To overcome these limitations, this paper introduces a 1D convolutional neural network (CNN) with sinusoidal kernel initializers for classifying household appliances operating individually or in combination with other devices.

To enhance performance, the proposed CNN architecture incorporates 15 primary and 225 multiscale sinusoidal kernels (MSK) to extract key discriminative features from current signals. Classification accuracy is further improved by integrating a novel non-linear activation function, SL-ReLU, which combines an adjustable logarithmic function with **softsign** and **ReLU** functions. The effectiveness of the proposed MSK-CNN model is validated on a real-world dataset created by the authors, consisting of current signals from various residential appliances. The results demonstrate that **MSK-CNN** successfully distinguishes 18 single appliances and 12 appliance combinations, achieving an accuracy of 98.61%. Experimental findings highlight the superiority of MSK-CNN over conventional CNN models with other kernel initializers and activation functions in terms of classification accuracy and training convergence.

Reference

D. Yang, X. Gao, L. Kong, Y. Pang and B. Zhou, "An event-driven convolutional neural architecture for non-intrusive load monitoring of residential appliance", *IEEE Trans. Consum. Electron.*, vol. 66, no. 2, pp. 173-182, May 2020.

Conclusion

The integration of AI and data-driven approaches in energy management presents significant opportunities for optimizing consumption and enhancing efficiency. By utilizing advanced machine learning techniques such as convolutional neural networks and clustering algorithms, Intelligent Energy Management Systems can accurately classify appliances and identify consumption patterns.