Eaton C25DND330B

Catalog Number: C25DND330B

Eaton definite purpose contactor, Quick, 30A,208-240 Vac, 50/60 Hz,Open with metal mounting plate, 15-50A, two- and three-pole, 30A, Contactor, Three-pole, 40A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing





Eaton definite purpose contactor

UPC

782116300617

Product Height

2.5 in

Product Weight

1.3 lb

Compliances

RoHS Compliant

Catalog Number

C25DND330B

Product Length/Depth

3.35 in

Product Width

2.4 in

Warranty

1 year

Certifications

CSA Certified UL Recognized



Product specifications

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

30 A

Model

Contactor

Connection

Quick

Enclosure

Open with metal mounting plate

Screw/pressure plate and quick connect terminals (side-by-side)

Amperage Rating

30A

Resistive load

40 A

Number Of Poles

Three-pole

Coil

208-240 Vac, 50/60 Hz

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

C25DND3 AutoCAD 2D Footprint (mm)

C25DND3 AutoCAD 2D Footprint

C25DND3 3D Model Xchange

C25DND3 2D PDF

C25DND3 3D Inventor

C25DND3 2D Drawing Xchange

Specifications and datasheets

Eaton Specification Sheet - C25DND330B



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia