

<b>Object: pos.order</b> <b>Name: Point of Sale Orders</b>	Type: Base Object  Transient: False  Apps: cortes_x_z, cryo_sv, point_of_sale, pos_mercury, pos_sale, pos_wallet_management
---	---

### **Security**

Group	R	W	C	U	Name
Point of Sale / User	X	X	X	X	pos.order
Inventory / User	X				pos.order stock_worker

### **Fields**

Name	Label	Type	Attribute	Rq	Ro	Tr	Idx	Apps
__last_update	Last Modified on	datetime			X			point_of_sale
account_move	Journal Entry	many2one	- relation = account.move - ondelete = Set NULL		X			point_of_sale
amount_paid	Paid	float		X	X			point_of_sale
amount_return	Returned	float		X	X			point_of_sale
amount_tax	Taxes	float		X	X			point_of_sale
amount_total	Total	float		X	X			point_of_sale
company_id	Company	many2one	- relation = res.company - ondelete = Set NULL	X	X			point_of_sale
config_id	Point of Sale	many2one	- relation = pos.config - ondelete = Set NULL					point_of_sale
create_date	Created on	datetime			X			point_of_sale

create_uid	Created by	many2one	- relation = res.users - ondelete = Set NULL		X			point_of_sale
currency_rate	Currency Rate	float			X			pos_sale
date_order	Order Date	datetime			X		X	point_of_sale
display_name	Display Name	char			X			point_of_sale
fiscal_position_id	Fiscal Position	many2one	- relation = account.fiscal.position - ondelete = Set NULL		X			point_of_sale
id	ID	integer			X			point_of_sale
invoice_group	Invoicing	boolean						point_of_sale
invoice_id	Invoice	many2one	- relation = account.invoice - ondelete = Set NULL					point_of_sale
lines	Order Lines	one2many	- relation = pos.order.line - field = order_id		X			point_of_sale
location_id	Location	many2one	- relation = stock.location - ondelete = Set NULL		X			point_of_sale
name	Order Ref	char		X	X			point_of_sale
nb_print	Number of Print	integer			X			point_of_sale
note	Internal Notes	text						point_of_sale
partner_id	Customer	many2one	- relation = res.partner - ondelete = Set NULL				X	point_of_sale
picking_id	Picking	many2one	- relation = stock.picking - ondelete = Set NULL		X			point_of_sale

picking_type_id	Operation Type	many2one	- relation = stock.picking.type - ondelete = Set NULL					point_of_sale
pos_reference	Receipt Ref	char			X			point_of_sale
pricelist_id	Pricelist	many2one	- relation = product.pricelist - ondelete = Set NULL	X	X			point_of_sale
recibo_number	Numero recibo	integer						cryo_sv
sale_journal	Sales Journal	many2one	- relation = account.journal - ondelete = Set NULL		X			point_of_sale
sequence_number	Sequence Number	integer						point_of_sale
session_id	Session	many2one	- relation = pos.session - ondelete = Set NULL	X	X		X	point_of_sale
state	Status	selection			X			point_of_sale
statement_ids	Payments	one2many	- relation = account.bank.statement.line - field = pos_statement_id		X			point_of_sale
ticket_number	Numero ticket	integer						cryo_sv
user_id	Salesperson	many2one	- relation = res.users - ondelete = Set NULL					point_of_sale
write_date	Last Updated on	datetime			X			point_of_sale
write_uid	Last Updated by	many2one	- relation = res.users - ondelete = Set NULL		X			point_of_sale
<b><u>Views</u></b>								
<b>Seq</b>	<b>Type</b>	<b>Name</b>	<b>XML ID</b>	<b>Inherited</b>				

16	Form	POS orders	pos_mercury.view_pos_order	point_of_sale.view_pos_pos_form
16	Form	pos.order.form	point_of_sale.view_pos_pos_form	
16	Kanban	pos.order.kanban	point_of_sale.view_pos_order_kanban	
16	Search	pos.order.list.select	point_of_sale.view_pos_order_filter	
16	Search	pos.order.search.view	point_of_sale.view_pos_order_search	
16	Tree	pos.order.tree	point_of_sale.view_pos_order_tree	