Genesis OS / Relationship Scores
ExsAnonymous Official Companion Contract v1

Sanctuary Module Family - Room Objects, Anonymous Identity Policy, Protected Data Boundaries, Event Schema, Moderation, State Machine, and Write-Back Law

Purpose. Promote ExsAnonymous from useful feature architecture into a strict companion-system contract inside Sanctuary. This document defines the exact room objects, anonymous identity model, protected data boundaries, moderation objects, runtime states, event packets, write-back rules, and downstream permissions developers must implement so the module is turnkey rather than interpretive.

Authoritative stance: Workbook and unified master blueprint remain upstream law. ExsAnonymous may generate governed emotional evidence, but it may not freeload into score law, expose identifying trauma details, or silently rewrite slow identity variables.

Executive lock summary

Area	Locked rule
Module family position	ExsAnonymous is a first-class Sanctuary family with three governed room families: Private, Circle, and Partner.
Identity policy	No room may expose legal name, RS code, username, relationship handle, photo, location, contact fields, or directly identifying text to other participants.
Room objects	Every room is a typed object with room_family, topic, safety profile, admission policy, moderation policy, logging policy, and archive/write-back posture.
Protected data boundary	Raw disclosures remain owner-visible and policy-scoped. Only approved derived features, moderation events, and anonymized pattern packets may cross into Genome, clusters, readiness, or forecast lanes.
Write-back discipline	ExsAnonymous may create fast-state and medium-pattern evidence; it may not directly overwrite workbook baseline answer truth or

Area	Locked rule
	match score outputs.
Moderation stance	All modes require automated moderation, escalation classes, suppression paths, and audit logs. Circle Mode adds room-level moderation and admission controls.

1. Scope and system role

ExsAnonymous is the emotional detox chamber inside Sanctuary. It exists to convert emotionally charged disclosure into governed clarity rather than leakage, rumination, or social harm. The module is intentionally useful to the user first and useful to the operating system second.

It is not a public feed, not a confession dump without guardrails, and not a hidden backdoor for unrestricted AI profiling. The contract treats ExsAnonymous as a therapeutic-adjacent reflection system under product governance, not clinical treatment and not an identity-free free-for-all.

The module operates in three room families already established in the feature architecture: Private Mode for individual release, Circle Mode for anonymous group share, and Partner Mode for structured relational autopsy and closure work. Each family has its own object model, state machine, moderation rules, and write-back boundaries.

2. Sanctuary placement and interlock model

ExsAnonymous belongs inside Sanctuary, not beside it. That means it must use the Sanctuary session envelope, module state machine discipline, logging object, consent gates, and AI safety posture already defined for Stillness, Emotional Mirror, Whisper Window, Archive of Self, Last Light, and related modes.

ExsAnonymous may feed the following downstream systems only through governed packets: Human Emotion Genome feature extraction, reflection clusters, drift tracking, E_GRIEF context, readiness support signals, and forecast support signals. It may also generate Archive of Self entries and private AI reflections for the owner.

ExsAnonymous must never directly mutate the deterministic compatibility engine, alter raw workbook answer selections, or expose internal risk fields to another user. It enriches the ecosystem; it does not seize the throne.

3. Canonical room families and objects

3.1 Room family registry

Room family	Primary purpose	Participants	Identity exposure	AI role	Default write-back posture
Private	Individual release,	1 owner + AI	Owner only	High	Owner archive + governed

Room family	Primary purpose	Participants	Identity exposure	AI role	Default write-back posture
	pattern extraction, stabilization, ritual suggestion				derived features
Circle	Anonymous group emotional processing around a topic room	Many participants + AI moderator	Masked peer identity only	High	Room moderation logs + optional owner archive + aggregate pattern packets
Partner	Structured analysis of an ex, situationship, breakup, or unresolved bond	1 owner + AI	Owner only	High	Owner archive + relational pattern packets + closure outputs

3.2 Room object schema

Each ExsAnonymous room must be represented as a durable typed object. Developers should not treat rooms as loose chat threads. The room object is the policy container that tells every downstream service how to behave.

Required room object fields:

room_id; sanctuary_session_id; room_family; submode_id; topic_id; title_render; owner_user_id; pair_context_id if any; admission_policy; anonymity_policy; moderation_profile_id; ai_profile_id; archive_policy_id; writeback_policy_id; protected_data_policy_id; state; created_at; activated_at; closed_at; expires_at; version_tag.

Recommended auxiliary fields:

prompt_set_id; ritual_pack_id; grief_context_id; cluster_context_ids; drift_context_id; owner_visibility_scope; moderation_hold_flag; escalation_class_max; participant_count_current; participant_cap; last_activity_at; aggregate_sentiment_state; evidence_confidence_band; export_block_flag.

3.3 Circle room topic registry

Circle Mode should not allow arbitrary untyped room creation in v1. Start with controlled room topics and controlled moderation profiles.

Topic ID	Default title	Primary emotional band	Moderation intensity
CIR_BREAKUP_RECOVERY	Breakup Recovery	grief + rupture	high
CIR_EX_GUILT	Ex Guilt & Self-Blame	guilt + regret	high
CIR_SITUATIONSHIP	The Situationship Spiral	ambiguity + attachment strain	high
CIR_MISS_HURT	Why do I miss someone who hurt me?	trauma bond risk + longing	very high
CIR_NIGHT_ANXIETY	Night-Time Anxiety Room	rumination + panic-adjacent distress	very high
CIR_HEALING_DELAY	Am I healing or delaying?	stuckness + avoidance	high

4. Anonymous identity policy

Anonymous does not mean ungoverned. The system must conceal personal identity from other users while still maintaining internal traceability for abuse prevention, account security, moderation, and lawful operations.

The policy therefore splits identity into three lanes: internal true identity, room pseudonymous identity, and derived feature identity. Only the second is exposed inside Circle Mode, and even that is tightly constrained.

4.1 Identity lanes

Lane	Who can access	Contains	May be shown in-room	Notes
True identity lane	Auth, trust/safety, authorized admin only	user_id, account linkage, consent flags, moderation history	No	Never exposed to peers or AI copy output
Room pseudonym lane	Participants in same Circle room,	ephemeral alias, avatar token, join	Yes, limited	Alias rotates by room; no cross-

	moderation, AI moderation	timestamp, role state		room persistence by default
Derived feature lane	Scoring-adjacent governed services	archetype evidence, cluster hints, grief indicators, drift support, aggregate pattern keys	No direct display	Contains patterns, not autobiographical detail

4.2 Anonymous identity rules developers must enforce

No room payload returned to another participant may include legal name, username, RS code, relationship handle, profile photo, geolocation, age exact date, contact methods, linked socials, or transcript excerpts from other rooms.

Circle aliases must be room-scoped and non-reusable by default. A user entering Room A as 'North Lantern' must not automatically be 'North Lantern' in Room B.

Voice submissions must be transformed or transcribed into a non-identifying moderation artifact before any peer playback is allowed in v1. If raw voice is supported later, it requires an explicit policy version and separate risk review.

Partner Mode and Private Mode are owner-facing; anonymity there means the system strips identifying references from downstream packets and AI outputs, not that the owner is hidden from themselves.

Ex or partner names supplied by the owner must never be stored as plain protected fields for cross-user lookup. Use redacted placeholders or local-only masked fragments unless a future legal/compliance design explicitly requires otherwise.

5. Protected data boundaries

This module handles some of the most sensitive free-text in the system. Developers need exact boundaries so the operating system captures pattern intelligence without becoming a surveillance diary.

Protected data should be classified before storage or downstream use. Raw personal disclosure belongs in the owner-protected lane. Derived emotional features belong in the governed feature lane. Moderation objects belong in the trust-and-safety lane.

5.1 Protected data classes

Class	Examples	Default retention	Downstream permission	Notes
P0 operational	room_id, timestamps, state changes, policy	standard system retention	broad internal	No emotional content

	ids			
P1 owner narrative protected	raw confession text, raw transcript, named ex details, autobiographical events	owner-scoped protected retention	owner tools + moderation if needed	Never directly fed to matching or peer display
P2 derived emotional features	emotion families, cluster hints, grief tier support, attachment loop evidence, anger signals	governed feature retention	Genome, clusters, readiness/forecast support under consent	Patterns only; no quotes by default
P3 trust/safety moderation	abuse flags, self-harm escalation, harassment events, bans, room removal logs	security retention	trust/safety only	Strict least-privilege access
P4 aggregate analytics	room-level theme counts, anonymized trend packets, completion stats	analytics retention	product/data	Must be de-identified and k-anonymized where needed

5.2 Source-to-boundary policy

Raw text or audio from Private and Partner rooms may be stored for the owner experience, but only derived packets may cross into Genome or rule engines. Circle Mode participant content may be stored for moderation and optional owner archive, but room-level analytics should prefer aggregate packets over transcript recycling.

No ExsAnonymous content may be used for public match marketing, user acquisition content, or partner-visible explanations without a separately governed opt-in product surface. Protected pain is not ad copy.

AI summaries shown back to the owner may include paraphrase. Downstream feature packets must prefer normalized keys, counts, evidence bands, and confidence values over storing rich narrative excerpts.

6. Module state machine

ExsAnonymous uses the Sanctuary root session but also needs its own room-state machine. The same room family should not improvise its own states ad hoc in code.

Canonical states: drafted -> available -> admitted -> active -> awaiting_ai -> stabilized -> archived -> closed, with moderation detours hold, suppressed, escalated, and removed when necessary.

6.1 State definitions

State	Meaning	Allowed entrants	Primary exits
drafted	Room/session created but not yet entered	owner/system	available, closed
available	Ready for admission or launch	owner/system	admitted, closed, suppressed
admitted	User admitted to room; session envelope open	owner	active, closed
active	User is interacting with prompts, text, or voice	owner/participants	awaiting_ai, stabilized, hold, escalated
awaiting_ai	Input received; AI reflection or moderation job pending	system	stabilized, hold, escalated
stabilized	Output delivered; user may continue, archive, or close	owner	active, archived, closed
archived	Owner-visible record created under archive policy	system	closed, active
hold	Temporary moderation pause	system/mod	active, removed, escalated
suppressed	Access blocked or content hidden	system/mod	closed, escalated
escalated	Safety/trust review path engaged	system/mod	hold, closed, removed
removed	Participant or room removed from	system/mod	closed

	circulation		
closed	Terminal state for room session	system	-

6.2 Family-specific state notes

Private Mode may cycle active -> awaiting_ai -> stabilized repeatedly within one session as the user vents, reflects, and continues.

Circle Mode adds participant admission and room moderation detours. A user can be admitted while a room itself is on hold for content review.

Partner Mode may create multiple structured steps inside one active state: target framing, event timeline, conflict loop mapping, trigger extraction, and closure ritual output. These steps should be recorded as submode checkpoints, not independent untyped sessions.

7. Production event catalog and packet schemas

This module needs explicit event names. 'user used ExsAnonymous' is useless telemetry. Events must be typed enough to drive moderation, archive behavior, and derived feature extraction.

7.1 Required event families

Event family	Examples	Produced by	Storage lane	Primary consumers
Room lifecycle	room_created, room_opened, room_closed, room_expired	system/client	P0	sanctuary runtime, analytics
Admission	room_requested, room_admitted, room_denied, participant_removed	system/mod	P0/P3	circle moderation
Disclosure	text_submitted, voice_submitted, prompt_answered, target_declared	owner/client	P1	AI reflection, moderation
AI operations	ai_reflection_started, ai_reflection_completed, ai_prompted_rew	system/AI	P0/P2	owner output, archive

	rite, ai_ritual_generated			
Moderation	mod_flag_raised, mod_hold_started, mod_action_taken, mod_escalated	system/mod	P3	trust/safety
Derived features	pattern_packet_emitted, cluster_hint_emitted, grief_signal_emitted, drift_support_emitted	extractors	P2	Genome, clusters, readiness/forecast support
Archive/write-back	archive_entry_created, archive_entry_suppressed, writeback_applied, writeback_blocked	system	P0/P2	Archive, state engines

7.2 Canonical event envelope

Every event emitted from ExsAnonymous must carry the standard envelope:

event_id; event_name; event_family; occurred_at; user_id; room_id; sanctuary_session_id; room_family; submode_id; actor_type; source_client; policy_version; consent_scope; moderation_profile_id; protected_data_class; payload_version; provenance_ref.

Room-family-specific payloads sit inside the envelope and should never smuggle prohibited identity data into public or analytics lanes.

7.3 Core payloads by room family

Private payload

input_modality; prompt_id if any; disclosure_length_band; emotional_intensity_band; self-report emotion if present; ai_requested_flag; archive_opt_in_flag; derived_feature_request_flag.

Optional private extraction block: emotion_family_counts; contradiction_candidates; grief_candidates; attachment_loop_candidates; closure_need_flag; ritual_type_suggested.

Circle payload

topic_id; participant_alias_id; participation_mode (share/listen/ai_assisted_share); message_length_band; room_sentiment_band; moderation_risk_band; share_visibility_scope; archive_opt_in_flag.

Circle payloads must exclude anything that could reveal account identity to peers.

Partner payload

target_type (ex/almost-relationship/recent breakup/current confusion); timeline_step_id; conflict_loop_step_id; polarity_role_hypothesis; closure_stage; ritual_eligibility_flag; archive_opt_in_flag.

8. Moderation tables and enforcement model

ExsAnonymous is only viable if moderation is product law rather than an afterthought. The module handles heartbreak, longing, blame, obsession, and occasionally harassment or self-harm content. Moderation must therefore be first-class data, not a side-channel.

Moderation applies across all modes, but Circle Mode requires the strictest room-level enforcement because users can affect one another there.

8.1 Moderation severity table

Severity	Definition	Typical triggers	Default action	Audit requirement
M0 informational	No policy breach; normal emotional distress	heartbreak, sadness, confusion	allow + standard reflection	none beyond event log
M1 caution	Content needs tone stabilization or lighter intervention	spiraling rumination, intense blame without threats	soft AI de-escalation + possible prompt redirect	log action
M2 hold	Potential harm or peer destabilization risk	repeated shaming, hostile room behavior, coercive language	temporary hold + AI pause	moderation event + reason code
M3 escalation	Material safety or abuse concern	self-harm references, threats, stalking language, doxxing attempts	escalate to trust/safety workflow	full audit packet
M4 removal	Access must be terminated for	targeted harassment,	remove participant or	mandatory audit + review

	session/room/account	repeated policy evasion, dangerous content	room + account action as needed	

8.2 Moderation policy objects

Required moderation tables: moderation_profile, moderation_rule, moderation_reason_code, room_action, participant_action, escalation_queue, appeal_record, and audit_log.

Every moderation outcome should store: room_id, participant_id or alias_id, triggering_event_id, severity, reason_code, model_signal_summary, human_review_flag, action_taken, action_duration, restored_at if any, and notes scope.

Circle Mode must support room-level tone stabilization actions such as slow mode, temporary share freeze, AI grounding injection, and room closure. Private and Partner Mode focus more on safety escalation and redirection than peer protection.

9. Write-back law and downstream permissions

The purpose of ExsAnonymous is not just catharsis. It should create useful downstream intelligence. But useful is not the same as unrestricted. Write-back law defines what may leave the room and how.

Write-backs must be derived, policy-scoped, and typed. The operating system should store pattern intelligence, not a scrapbook of protected pain.

9.1 Write-back classes

Class	May contain	Targets	Persistence	Blocked from
W0 session-only	ephemeral UI state, current prompt, current calming suggestion	active Sanctuary session	session	all downstream systems
W1 owner archive	paraphrased summary, ritual recommendation, owner reflection card	Archive of Self	owner retention policy	peer surfaces
W2 derived feature packet	normalized feature keys, evidence counts, confidence band, recency	Genome, clusters, drift, readiness support, forecast support	feature TTL + policy	peer transcript surfaces
W3 moderation	reason codes,	trust/safety	security retention	product

packet	actions, severity, appeal refs			explanation surfaces except limited owner notices
W4 aggregate analytics	de-identified topic trends and counts	analytics/data	analytics retention	owner narrative export

9.2 Downstream permission matrix

Human Emotion Genome may ingest W2 feature packets only. It should never ingest raw room transcript text unless a separate research lane and explicit opt-in are defined.

Reflection clusters may consume cluster_hint packets, contradiction candidates, avoidance patterns, grief-support indicators, and repair blockers. They may not quote raw confession text back to the user as proof.

Readiness and forecast families may use ExsAnonymous as support evidence only. This module can raise or soften confidence, create reflection requirements, and inform care posture; it may not singlehandedly create a public readiness collapse or a partner-facing scarlet letter.

E_GRIEF may ingest grief-signal packets from Private, Partner, Last Light, and specific Circle topics, subject to influence caps already defined in the E_GRIEF companion contract.

AI explanation surfaces may reference patterns in softened language for the owner only. Match partners do not get direct access to ExsAnonymous-derived autobiographical insights.

10. Room-family implementation detail

10.1 Private Mode - The Quiet Confessional

Entry: owner enters from Sanctuary. No peer visibility. AI may operate in reflection, stabilization, and ritual suggestion lanes.

Core actions: free-write, voice-to-text submission, guided prompt answer, AI-assisted reformulation, ritual selection, archive save, session close.

Write-back posture: strongest owner archive value and strongest derived feature potential, because the room often contains subconscious material that structured assessments miss.

Critical safety rule: private catharsis must not be mistaken for permanent identity. High-intensity disclosures create event candidates and medium-pattern evidence, not instant identity rewrites.

10.2 Circle Mode - Anonymous Group Share

Entry: user requests or is admitted to a controlled topic room. Peers see only room alias and limited participation state.

Core actions: share, listen, AI-assisted share, acknowledge, guided prompt response, room exit.

Write-back posture: moderation-heavy, archive-optional, aggregate-feature-friendly. Direct raw content export should be tightly minimized.

Critical safety rule: Circle Mode must favor collective stabilization over engagement addiction. Do not design the room like a doom-scroll grief casino.

10.3 Partner Mode - Emotional Autopsy Room

Entry: owner chooses target type and begins structured walkthrough. No peer visibility.

Core actions: target framing, timeline decomposition, conflict-loop mapping, trigger mapping, power-balance reading, polarity-role review, closure ritual generation.

Write-back posture: high value for relational loop extraction, drift support, attachment/repair pattern hints, and grief clarification.

Critical safety rule: Partner Mode may analyze a relationship dynamic, but it must not become a revenge machine or a defamation archive.

11. Admin review, audits, and protected operations

Because ExsAnonymous involves anonymity, moderation, and deeply personal content, admin operations must be explicit. Admins should review policy events, not casually browse human pain.

Protected operations must be role-based. Most internal users should never see raw content. Trust/safety staff may access raw protected material only when triggered by an escalation, appeal, or lawful review path.

All admin access to protected room content must produce an access audit event with actor_id, reason_code, content_scope, time_opened, and time_closed.

12. Build sequence and rollout boundaries

Phase	Build	Why now	Must wait until
v1a	Private Mode with archive, AI reflection, moderation, and W2 feature packets	lowest peer risk, highest utility	none
v1b	Partner Mode structured walkthrough with closure outputs	strong relational insight with owner-only exposure	after private mode packet stability
v1c	Circle Mode controlled topic rooms with aliases and moderation console	highest complexity and peer-risk lane	after moderation tables and alias policy are proven
v1.5+	expanded room topics, voice policy upgrades, deeper aggregate	matures safely	after review of moderation and privacy outcomes

	analytics		

13. Final implementation stance

ExsAnonymous is useful because it catches emotional truth people do not reveal in structured assessments. It is dangerous if left vague because the same truth can become leakage, over-inference, or social harm.

This contract solves that by giving developers strict room objects, anonymity law, moderation tables, protected data boundaries, event schemas, state machines, and write-back rules. Build it like a governed system, not an emotional freeform sandbox.