Genesis OS / Relationship Scores

Human Emotion Genome

Canonical Registry, Taxonomy, Capture Families, Evidence Bands, Lanes, Extractor Thresholds, and Source-to-Feature Mapping Specification v1

Purpose	**Lock the Human Emotion Genome as a governed feature registry, not a poetic blob. This document defines the canonical feature tables, source lanes, evidence bands, extractor thresholds, and source-to-feature mapping that developers must implement in code and data storage.**
Upstream references	Workbook v10 polarity package; corrected unified master blueprint; Quantum Mirror governance stack; missing layers runtime blueprint; readiness, forecast, cluster, drift, and Sanctuary contracts.
Implementation posture	Deterministic first. Extracted features enrich the engine under policy. Genome signals may explain, forecast, and personalize, but they do not freestyle rewrite workbook law.
Build use	Backend registry import, extractor logic, validators, feature-store schemas, packet builders, audit trails, ML-ready feature snapshots, and admin review tooling.

Executive closure: the Human Emotion Genome is the governed, versioned representation of how a user tends to perceive, signal, regulate, pursue, protect, bond, rupture, repair, and remember inside relationships. Every saved signal must carry provenance, lane, freshness, consent scope, evidence band, extractor version, validator result, and writeback reason.

1. System authority and why this registry exists

The workbook already governs the scored assessment, archetype logic, shadow logic, pair quantum math, chemistry logic, and polarity dimensions. The Human Emotion Genome does not replace those foundations. It gives the runtime somewhere disciplined to put everything the questionnaire cannot fully know on day one: message rhythm, reassurance demand, rupture and repair behavior, Sanctuary reflections, grief or anger telemetry, drift evidence, ExsAnonymous residue, and downstream outcome data.

The registry exists because a feature only becomes operational when the system knows exactly what it is called, where it came from, which lane it belongs to, how strong the evidence is, how long it stays fresh, and what it is allowed to influence. If those things are not frozen in code tables, the system becomes a story people tell themselves in meetings instead of something production can trust.

2. Core design law

- Assessment anchors slow identity. Runtime signals enrich confidence, state, and patterning under update-lane rules.
- No single emotional session, message run, or AI exchange may hard-edit a user's slow identity profile.
- Every genome feature is versioned. Prompts, extractor recipes, validators, and thresholds are versioned beside the feature registry.
- Every feature must carry mandatory metadata: feature_key, feature_family, lane, source_system, source_event_ids, evidence_band, confidence_score, consent_scope, freshness_class, created_at, updated_at, taxonomy_version, extractor_version, validator_version, and writeback_reason.
- Structured features are the production truth for ML and packet building. Raw prose may support offline research under stricter policy, but raw prose is not the main runtime substrate.
- ExsAnonymous, Sanctuary, messaging, games, anger, grief, drift, and pair outcomes are controlled signal producers with influence caps, not free-form score mutators.

3. Canonical lanes and mutation discipline

Lane	Purpose	Typical sources	Persistence	Allowed influence	Overwrite rule
Slow identity	Stable profile tendencies and baseline architecture	Assessment answers, repeated validated medium-pattern rollups, governed drift jobs	Long-lived; versioned	readiness explanation, matching context, premium reports	Only changed by governed jobs meeting minimum evidence and recency requirements
Medium pattern	Repeated behaviors observed across windows	messaging telemetry, Sanctuary patterns, ExsAnonymous outputs, cluster	Rolling 30-180 day windows	forecast, coaching, reflection priorities, moderation context	Requires repeat evidence across time windows or multi-source confirmation

		recurrences, games, pair history			
Fast state	Transient current emotional condition	Sanctuary check-ins, post-chat reflections, grief state, acute anger state, acute rupture events	Hours to days	reflection tone, short-term gating, nudges, cooldowns	Expires quickly; cannot rewrite slow identity
Narrative memory	Important self-authored stories and event-linked meaning	Sanctuary reflections, ExsAnonymous entries, Last Light, Whisper Window, Archive of Self	Session or artifact based	contextual explanation, Archive recall, reflection continuity	Stored with source scope and visibility; not treated as hard trait
Safety / governance	Risk flags, policy controls, abuse indicators, moderation artifacts	moderation actions, coercion detection, crisis routing, admin review	Policy-defined	suppression, routing, safe fallback	Never exposed as open feature text to another user

4. Evidence bands and confidence language

The engine must separate confidence from charisma. A vivid statement is not automatically a strong feature. Evidence bands below are binding for writeback and display policy.

Band	Internal code	Typical basis	Confidence range	Eligible lanes	Product stance
E0	none	insufficient or disallowed evidence	0.00-0.19	no writeback	do not save as feature
E1	weak	single light signal, incomplete context, or low-agreement extractor output	0.20-0.39	fast state only	internal hint; never presented as stable truth
E2	moderate	single strong source or repeated weak observations within window	0.40-0.64	fast state / medium pattern candidate	soft reflection language only
E3	strong	repeat pattern, cross-source support, or validated	0.65-0.84	medium pattern and selected narrative memory	may inform forecast and owner-facing

		structured source			insight
E4	very strong	multi-source, repeated, recent, validator-approved evidence with low contradiction	0.85-1.00	slow identity candidate via governed job; medium pattern; narrative memory	eligible for controlled profile enrichment and stronger explanation

4.1 Evidence-band operating rules

- E1 and E2 may guide reflection prompts or temporary fast-state context, but they may not promote a new slow-identity trait.
- E3 may seed medium-pattern features, cluster support evidence, forecast modifiers, and owner-only explanation packets.
- E4 is required for any slow-identity mutation proposal, and even then it must pass update-lane policy, recency checks, contradiction checks, and admin-safe auditability.
- If sources disagree, the stronger source wins only when freshness and consent also qualify. Older E4 may be downgraded if contradicted by a newer repeated pattern.
- Confidence ranges are defaults; service code may apply stricter thresholds per feature family, but may not go looser without a versioned policy update.

5. Canonical source families

Source family	Examples	Typical cadence	Primary lane output	Consent requirement	Notes
Assessment core	60 scored questions, answer vectors, archetype/shadow labels	onboarding + permitted retakes	slow identity anchor	required for scored experience	atomic feature registry already lives in AnswerBank
Polarity	32 prompts, 10 axes, 5 role seeds	onboarding + governed retakes	chemistry / medium pattern context	required for polarity-enabled features	used for pair chemistry, pursuit rhythm, surrender safety, drift context
Onboarding metadata	relationship intent, availability, demographics, DOB, status selectors	profile create / edit	slow identity context + routing	user supplied	not all fields are scored but many affect packet routing and eligibility
Messaging telemetry	reply latency, initiation balance, reassurance requests, rupture/repair markers,	continuous event stream	medium pattern / fast state	messaging consent + platform usage	never use raw text alone without provenance

	withdrawal patterns				
Sanctuary	Stillness, Emotional Mirror, Whisper Window, Archive, Alignment Compass, Last Light, DM Reflection, Truth Signal	session based	fast state, narrative memory, medium pattern	module-specific consent	self-owned reflective data with strict visibility
ExsAnonymous	ex-story capture, residue extraction, closure passes, pattern summaries	session based	medium pattern + narrative memory	explicit module consent	part of Sanctuary family in governance
Anger / grief / depletion	anger hex, grief tier, depletion pass, state check-ins	session or trigger based	fast state with bounded medium-pattern rollups	explicit or implied module consent per policy	strong for safety and readiness context; weak for direct trait rewrites
RS Game ecosystem	co-op games, reflective mini-games, turn-taking telemetry, choice-path data	session based	medium pattern + pair behavior evidence	game-play consent	controlled signal producer only
Pair outcome telemetry	conversation counts, reveal usage, knocks, match conversion, repair success, dropout, ghosting, report feedback	continuous / cohort windows	medium pattern + calibration labels	platform terms and product policy	used for model calibration and forecast feedback loops
Admin / moderation	appeals, reversals, abuse reports, policy outcomes	as needed	safety/governance lane	policy basis	never exposed directly as social profile content

6. Canonical genome families and registry codes

Each feature belongs to exactly one canonical family and may optionally reference one or more supporting tags. Family membership is not decorative. It controls writeback behavior, freshness, display rules, and allowed score influence.

Family code	Family name	What it stores	Typical lane	Main sources	Example keys
IDN	Identity architecture	archetype/shadow distributions, communication and regulation	slow identity	assessment, governed drift jobs	idn.archetype_primary, idn.regulation_nor

		norms, readiness anchor values			m
POL	Polarity architecture	10 polarity axes, role-seed distributions, chemistry-relevant posture	slow identity + medium pattern	polarity prompts, paired behavior confirmation	pol.initiation_axis, pol.surrender_safety_axis
BHV	Behavioral rhythm	initiation balance, reciprocity, pacing, consistency, rupture/repair behavior	medium pattern	messaging, games, pair telemetry	bhv.reply_latency_p50, bhv.repair_completion_rate
NRV	Nervous-system / regulation state	calm-seeking, strain load, escalation patterns, decompression need	fast state + medium pattern	Sanctuary, anger/grief/depletion, messaging	nrv.current_activation_band, nrv.decompression_need
NAR	Narrative theme memory	self-authored meaning, repeated story frames, remembered relational motifs	narrative memory + medium pattern	Sanctuary, ExsAnonymous, Archive	nar.theme_abandonment, nar.lesson_reciprocity
TRG	Trigger and sensitivity patterns	delay sensitivity, ambiguity strain, criticism reactivity, closeness threat	medium pattern	assessment, Sanctuary, messaging, ExsAnonymous	trg.delay_response, trg.criticism_reactivity
BND	Boundary / need signaling	need expression style, hidden-scorekeeping, directness, access style	slow identity + medium pattern	assessment, messaging, Sanctuary	bnd.access_style, bnd.need_directness
CLS	Cluster support features	inputs that seed or confirm contradiction/reflection clusters	medium pattern	assessment, polarity, messaging, Sanctuary	cls.vulnerability_loop_support
SFT	Safety / trust	coercion markers, instability indicators, moderation-sensitive outputs	safety/governance	moderation, messaging, Sanctuary safety flows	sft.coercion_indicator

OUT	Outcome and calibration	pair outcomes, retention, repair completion, break rate, satisfaction targets	medium pattern + research	pair telemetry, feedback datasets	out.match_score_target, out.repair_success_30d

7. Canonical registry metadata - mandatory columns

Column	Type	Required	Description	Example
feature_key	string	yes	stable machine key	pol.initiation_axis
feature_family	enum	yes	IDN, POL, BHV, NRV, NAR, TRG, BND, CLS, SFT, OUT	POL
lane	enum	yes	slow_identity, medium_pattern, fast_state, narrative_memory, safety	medium_pattern
value_type	enum	yes	number, enum, bool, text_ref, band, count	number
value	varies	yes	stored feature value	0.72
value_band	enum	recommended	mapped bucket if applicable	High
source_system	enum	yes	assessment, polarity, messaging, sanctuary, exs, game, grief, anger, admin	messaging
source_event_ids	array<string>	yes	authoritative events supporting this feature	['msg_44','msg_48']
evidence_band	enum	yes	E0-E4	E3
confidence_score	number	yes	0.00-1.00	0.81
consent_scope	enum	yes	self, pair_limited, research_opt_in, admin_only	self
freshness_class	enum	yes	session, 7d, 30d, 90d, evergreen	30d
taxonomy_version	string	yes	registry version	heg_tax_v1

extractor_version	string	conditional	parser or prompt recipe version if inferred	qm_ext_v1.3
validator_version	string	conditional	rule/validator version	heg_val_v1.1
writeback_reason	enum	yes	assessment_import, threshold_hit, user_saved, policy_hold, backfill	threshold_hit

8. Canonical registry code tables from the workbook

8.1 Assessment-root code tables

The v10 workbook currently exposes 50 core scored questions and 10 shadow questions (60 unique question IDs total) with 5 answers each, yielding 310 atomic answer rows.

Registry area	Canonical values	Source	Use in genome
Archetypes	Analyzer, Fixer, Icebox, Performer, Phantom Seeker, Quiet Exit, Regulated Grown-Up, Romantic Idealist, Survivor, Translator	AnswerBank.archetype	slow-identity architecture, pair explanations, cluster support
Shadow types	Chameleon, Love Bomber, Manipulator, Scorekeeper, Self-Saboteur, Stonewaller	AnswerBank.shadow_type	risk patterning, cluster support, forecast drag
Access style	Guarded, Measured, Open, Selective	access_style_label_v8	boundary/need signaling
Conflict style	Avoidant, Direct, Emotional, Indirect, Logical, Mixed	conflict_style_label_v8	rupture / repair patterning
Repair style	Co-repair, Delay, Re-engage, Suppress	repair_style_label_v8	repair completion logic
Attachment style labels	Mixed, Rush-risk, Slow-build	attachment_style_label_v8	attachment pacing and safety logic
Nervous system bias	Calm-seeking, Mixed	nervous_system_bias_label_v8	regulation and fast-state context
Risk / positive / chemistry bands	risk=Low, Medium; pos=High, Low, Medium, Very Low; chem=High, Low, Medium, Very Low	AnswerBank band fields	bucketed interpretation and UI copy routing

8.2 Assessment dimension map

Primary dimension	Question count	Representative role in genome	Notes
CommitmentPace	8	source family = assessment	feeds timing, availability, seriousness, escalation readiness
CommunicationHealth	8	source family = assessment	feeds directness, clarity, response stance, confrontation posture
ConflictRepair	8	source family = assessment	feeds rupture handling, re-engagement, delay, co-repair capacity
EmotionalNeeds	10	source family = assessment	feeds reassurance, closeness needs, expression expectations
EmotionalRegulation	8	source family = assessment	feeds activation management, calm-seeking, overwhelm behavior
ShadowPattern	10	source family = assessment	feeds hidden risk profiles and specific shadow activations
ValuesLifestyle	8	source family = assessment	feeds compatibility filters, stability, future alignment

8.3 Polarity code tables

Registry area	Canonical values	Source	Use in genome
Polarity axes	initiation_axis, pursuit_axis, leadership_axis, surrender_safety_axis, calm_receptivity_axis, tension_attraction_axis, structure_preference_axis, flexibility_axis, validation_dependency_axis, erotic_safety_alignment_axis	Polarity_Axes_v10.Field	chemistry architecture, pursuit rhythm, drift and attraction mapping
Role seeds	Dr, Fa, Fr, MS, Mm	Polarity_AnswerBank_v10.redesigned_role	describes patterned posture across polarity answers
Genesis labels	steady initiator; adaptive lead; relationally sensing; settled receiver; confused	Polarity_AnswerBank_v10.genesis_labels	compact feature tags and explanation labels

	signal		
Block IDs	1-? as defined in Polarity_QuestionMap_v10	block_id/block_multiplier	groups related prompts for threshold logic

8.4 Polarity axis registry

Axis field	Fit type	Inside chemistry weight	Definition	Why it matters
initiation_axis	complement	0.18	Who naturally moves first. Low = waits; high = initiates.	Tells whether the connection stalls, chases, or flows.
pursuit_axis	complement	0.14	Whether they want to pursue, be pursued, alternate, or test before engaging.	Separates mutual passivity from magnetic pursuit rhythm.
leadership_axis	complement	0.12	Comfort directing or holding shape in the dynamic.	Predicts whether one person can carry structure without triggering the other.
surrender_safety_axis	similarity	0.12	How safe it feels to relax into another person's presence.	Attraction dies fast if closeness feels dangerous.
calm_receptivity_axis	similarity	0.12	Ability to feel attraction in grounded, stable energy.	Distinguishes chemistry from nervous-system activation.
tension_attraction_axis	balance@0.45	0.1	How much uncertainty, mystery, challenge, or emotional distance reads as exciting.	Too high on both sides often creates drama addiction.
structure_preference_axis	similarity	0.08	Preference for the connection to feel led, fluid, mirrored, undefined, or charged.	Measures whether both people want the same kind of relational shape.
flexibility_axis	similarity	0.06	Ability to move between leading, softening, and receiving.	Rigidity creates stalemates; flexibility makes repair easier.
validation_dependency_axis	balance@0.40	0.04	How much attraction depends on feeling wanted, chosen, or admired.	High dependency can inflate chemistry while weakening stability.
erotic_safety_alignment_axis	similarity	0.04	Whether what excites them also makes them	Strong pairings align desire with safety

			feel safe.	rather than splitting them apart.

9. Canonical feature registry - v1 feature groups

The table below is the publishable registry skeleton the codebase should implement. It is intentionally explicit. A feature not present in a canonical registry table should not silently appear in production packets.

Feature group	Key pattern	Value type	Default lane	Primary sources	Threshold posture	Allowed influence
Archetype distribution	idn.archetype_*	number/band	slow_identity	assessment, governed drift job	assessment import or E4 governed update	reports, match context, private insights
Shadow distribution	idn.shadow_*	number/band	slow_identity	assessment, governed drift job	assessment import or E4 governed update	forecast drag, coaching priorities, owner insight
Communication posture	idn.comm_* / bnd.*	number/enum	slow_identity or medium_pattern	assessment, messaging, Sanctuary	E3+ for medium-pattern writeback	readiness explanation, cluster support
Repair posture	idn.repair_* / bhv.repair_*	number/enum	slow_identity + medium_pattern	assessment, messaging, pair outcomes	E3 repeated or structured source	forecast, reflection, safety gating
Polarity axes	pol.*	number	slow_identity	polarity onboarding, governed drift job	assessment-like import; E4 for mutation	chemistry, drift context, pair packets
Pursuit rhythm / initiation	bhv.initiation_*	number/band	medium_pattern	messaging, games, pair telemetry	>=12 qualifying events in 30d or cross-source E3	forecast, cluster support, prompts
Delay / ambiguity strain	trg.delay_* / trg.ambiguity_*	number/band	medium_pattern	assessment, messaging, ExsAnonymous, Sanctuary	cross-source or repeated event threshold	forecast and reflection
State activation / depletion	nrv.current_*	band/number	fast_state	Sanctuary, anger, grief, depletion	single strong session allowed	temporary guidance, cooldowns
Narrative themes	nar.theme_*	enum/count	narrative_memory or medium_pattern	Sanctuary, ExsAnonymous, Archive	extractor+validator agreement; E2+ for memory,	reflection continuity, owner insight

					E3+ for pattern	
Cluster support	cls.*	bool/score	medium_pattern	assessment, polarity, messaging, Sanctuary, ExsAnonymous	cluster-specific threshold packs	cluster engine only
Safety / policy	sft.*	bool/band	safety	moderation, crisis routing, coercion detection	policy-specific, often deterministic	suppression and safety routing only
Outcome labels	out.*	number/label	medium_pattern /research	feedback, cohort outcomes, pair telemetry	data pipeline thresholds	calibration, model evaluation, admin dashboards

10. Extractor thresholds and code-table policy

Extractors may propose features, but validators decide whether those proposals become durable genome records. Thresholds must live in code tables, not in prompt folklore.

Class	What it covers	Minimum writeback threshold	Escalation threshold	Decay / review	Default lane	Notes
Deterministic imports	assessment answers, polarity values, workbook labels	import on save	n/a	version-based, no decay unless replaced	slow_identity	authoritative workbook-bound values
Single-session state extractors	current activation, grief pulse, acute repair fatigue	confidence >=0.40 and allowed source	confidence >=0.65 for stronger prompting	7d or session expiry	fast_state	never mutates slow identity
Narrative-theme extractors	themes from Sanctuary or ExsAnonymous	confidence >=0.45 plus validator pass	repeat theme in 2+ sessions for medium-pattern promotion	90d review or archive only	narrative_memory / medium_pattern	self-authored meaning is valuable but not instant truth
Behavior pattern rollups	reply latency, initiation asymmetry, reassurance demand	minimum event count met and E3 pattern	repeat across 2 windows or cross-source confirmation	30-90d rolling	medium_pattern	telemetry beats vibes
Cluster support features	inputs that seed cluster logic	as defined by cluster rule pack	as defined by severity ladder	per-cluster	medium_pattern	cluster packs are the law here

Slow-identity mutation proposals	promotion of stable trait outside initial assessment	E4 evidence, multi-source, contradiction check, governed job only	admin-safe audit + drift eligibility if identity movement implied	quarterly or governed review	slow_identity	hardest threshold in the system
Safety flags	coercion, crisis, self-harm, abuse markers	policy trigger	immediate routing or suppression	policy-specific	safety	safety outranks product flourish every time

10.1 Default numeric code-table recommendations

These defaults are meant to be implemented as versioned code tables and tightened by empirical review, not hard-coded into UI copy.

Threshold key	Default	Use	Applies to	Comment
min_message_events_30d	12	minimum event count for medium-pattern telemetry writeback	messaging	below this, keep as exploratory only
min_cross_window_repeats	2	number of qualifying windows before promotion	behavior rollups	protects against one weird week becoming destiny
min_multi_source_support	2	distinct source families required for E4 stable-promotion candidates	slow-identity proposals	example: messaging + Sanctuary, or assessment + ExsAnonymous
narrative_theme_repeat_sessions	2	sessions required before theme promotion beyond narrative memory	Sanctuary/ ExsAnonymous	single session may still stay as memory artifact
fast_state_ttl_days	7	default expiration for acute state features	fast state	can be shorter for high-volatility states
medium_pattern_review_days	30	default review cadence	medium patterns	recompute with rolling windows
slow_identity_review_days	90	governed review cadence for non-assessment mutations	slow identity	assessment retake still handled separately
extractor_validator_agreement_min	0.65	minimum blended confidence for E3 candidate	narrative/behavior extractors	below this, keep E1-E2

11. Source-to-feature mapping - canonical packet map

This is the registry the engineering team should wire into packet builders. It answers the five questions that matter in production: what do we capture, where does it come from, when do we write it, why do we need it, and what may it influence.

Source system	Capture object	Primary feature outputs	Write timing	Lane	Why it exists	Downstream consumers
Assessment core	answer_id row import	idn.*, bnd.*, trg.*, cls.* support, readiness anchor signals	on answer save and score finalize	slow_identity + cluster support	creates the stable base architecture and scored norms	scoring, matching, readiness, reports, cluster engine
Polarity onboarding	polarity answer row import	pol.*, chemistry support, drift support, cls.* support	on answer save and polarity finalize	slow_identity	locks initiation/pursuit/surrender/structure baseline	chemistry engine, drift, forecast, explanation
Onboarding profile	profile field save	intent, availability, age bands, relationship status, route flags	on save	slow_identity context	eligibility, safety routing, packet scoping	matching, moderation, UI routing
Messaging telemetry	event normalizer over messages and interactions	bhv.*, trg.*, nrv.*, cls.* support, out.* labels	continuous; rollups nightly and on window close	medium_pattern / fast_state	observes how people actually behave once the score report ends	forecast, cluster engine, nudges, admin analytics
Sanctuary Stillness / Mirror	session events + structured check-ins	nrv.*, nar.*, trg.*, cls.* support	session end and scheduled rollups	fast_state / narrative_memory / medium_pattern	captures current state and self-perceived pattern without pretending one session is permanent	reflection, readiness tone, cluster context
Whisper Window	draft artifacts + reflection outputs	nar.*, bnd.*, trg.*, nrv.*, cls.* support	session save or explicit archive	narrative_memory + medium_pattern candidate	reveals unsent truth and friction points	Sanctuary continuity, owner-only insight
ExsAnonymous	entry forms, structured extraction, closure artifacts	nar.*, trg.*, bnd.*, cls.*, nrv.*, possible slow-identity review support	session end + governed batch validation	narrative_memory / medium_pattern	captures residue, repeated ex-patterns, and unresolved loops	cluster engine, coaching, forecast context
Anger / grief / depletion	state check-ins and module telemetry	nrv.*, fast-state burdens, repair-fatigue context, cls.* support	immediate + short TTL	fast_state	lets the engine know whether this is identity or just a person on fire today	cooldowns, response tone, temporary suppression

RS games	round telemetry, turn order, choice paths	bhv.*, pol confirmation support, cls.* support, out.*	session close + weekly rollups	medium_pattern	structured behavior under game constraints can confirm or challenge self-report	forecast, pair insights, experimental models
Pair outcomes / feedback	feedback forms, reveal usage, repair outcomes, retention	out.*, bhv.*, calibration labels	cohort windows	medium_pattern / research	calibrates forecast and helps tune thresholds	ML calibration, admin dashboards, score QA
Moderation / admin	review outcomes and overrides	sft.*, audit artifacts, policy routing flags	event based	safety	keeps risk separated from social product surfaces	governor service, support, audit

12. Feature registry detail by family

IDN / identity architecture

Feature key	Value type	Definition	Writeback threshold	Consumers
idn.archetype_primary	enum	primary archetype label from assessment distribution	assessment import; E4 drift job for mutation	private report, pair explanation
idn.archetype_distribution	json<number>	full archetype weights	assessment import; governed updates only	analytics, pair packet
idn.shadow_primary	enum	dominant shadow type	assessment import; governed updates only	forecast and coaching
idn.readiness_anchor	number	assessment-root readiness baseline before runtime overlays	score finalize	readiness contract
idn.conflict_style	enum	dominant conflict stance	assessment import; E3 repeated telemetry may support secondary tag	explanation, cluster support
idn.repair_style	enum	dominant repair style	assessment import; E3 repeated telemetry may support secondary tag	forecast, coaching

POL / polarity architecture

Feature key	Value type	Definition	Writeback threshold	Consumers
pol.initiation_axis	number	who moves first	polarity finalize; E4 governed changes only	chemistry, drift

pol.pursuit_axis	number	pursue / be pursued preference	polarity finalize; E4 governed changes only	chemistry, attraction rhythm
pol.leadership_axis	number	comfort carrying structure	polarity finalize	chemistry, drift, pair gating
pol.surrender_safety_axis	number	safety relaxing into closeness	polarity finalize + E3 paired confirmation note	chemistry, tension analysis
pol.calm_receptivity_axis	number	ability to feel attraction in calm energy	polarity finalize	chemistry and drama-risk framing
pol.role_seed_distribution	json<number>	MS/Mm/Fa/Fr/Dr weight map	polarity finalize	explanations, experimental models

BHV / behavioral rhythm

Feature key	Value type	Definition	Writeback threshold	Consumers
bhv.reply_latency_p50	number	median reply latency window	>=12 message events in 30d	forecast, reciprocity insights
bhv.initiation_balance	number	share of thread starts / first moves	>=12 qualifying events or game confirmations	forecast, drift, cluster support
bhv.repair_attempt_rate	number	rate of actual re-engagement after rupture	>=2 rupture opportunities	forecast, repair gap cluster
bhv.reassurance_request_rate	number	patterned reassurance demand	>=3 qualifying behaviors within 30d	trigger patterns, forecast
bhv.withdraw_after_closeness_rate	number	retreat following intimacy or conflict	repeat in 2 windows or cross-source support	push-pull / vulnerability loop support
bhv.consistency_index	number	signal stability over time	windowed rollup	readiness overlay, drift

NRV / nervous system and fast state

Feature key	Value type	Definition	Writeback threshold	Consumers
nrv.current_activation_band	band	present activation intensity	single module session allowed	reflection tone, cooldown
nrv.decompression_need	band	need for stillness / pacing	single strong session or repeated check-ins	Sanctuary routing
nrv.repair_fatigue	band	capacity strain around repair	session or recent rupture rollup	temporary forecast softening
nrv.anger_state_band	band	anger module output	single session, short TTL	safety and response

				framing
nrv.grief_state_band	band	grief tier output	single session, short TTL	care language and temporary suppression
nrv.depletion_state_band	band	overall emotional depletion	single session, short TTL	temporary gating

NAR / narrative memory

Feature key	Value type	Definition	Writeback threshold	Consumers
nar.theme_abandonment	enum/count	abandonment or disappearance as recurring self-story	theme repeat in 2 sessions for medium-pattern promotion	reflection, coaching
nar.theme_self_protection	enum/count	story of self-guarding / emotional armor	same as above	context, cluster support
nar.theme_reciprocity	enum/count	story about fairness, mutual effort, or imbalance	same as above	pair explanation
nar.lesson_extraction	text_ref	owner-facing distilled lesson artifact	explicit save or archive action	Archive only
nar.memory_anchor	text_ref	important memorialized entry from Archive or Last Light	explicit archive action	Sanctuary continuity
nar.unfinished_conversation_marker	bool	unsent or unresolved relational thread	explicit Whisper / ExsAnonymous save	Whisper routing, coaching

TRG / trigger and sensitivity patterns

Feature key	Value type	Definition	Writeback threshold	Consumers
trg.delay_response	band	sensitivity to delayed response	assessment support + telemetry pattern	forecast, cluster support
trg.ambiguity_strain	band	strain under mixed signals or undefined connection	assessment + Sanctuary + messaging	forecast, reflection
trg.criticism_reactivity	band	sensitivity to blame, critique, or harsh tone	E3 cross-source recommended	repair guidance
trg.closeness_threat	band	tension when intimacy becomes real	assessment + Sanctuary + messaging	push-pull, vulnerability loop support
trg.validation_dependency	band	need for external reassurance to stabilize	assessment + narrative	readiness and forecast

		connection	support	
trg.control_sensitivity	band	reactivity to pressure or relational control	assessment + ExsAnonymous + messaging	control-avoidance cluster support

BND / boundary and need signaling

Feature key	Value type	Definition	Writeback threshold	Consumers
bnd.access_style	enum	guarded/measured/ open/selective posture	assessment import + repeated telemetry support	reports and matching
bnd.need_directness	band	how clearly needs are spoken	assessment + Sanctuary + messaging	coaching, reflection
bnd.hidden_scorekeeping	band	keeping emotional score quietly	assessment + ExsAnonymous + messaging	shadow and readiness context
bnd.boundary_enforcement	band	ability to hold limits cleanly	assessment + repeated evidence	readiness, safety
bnd.bid_for_closeness_style	enum	direct, indirect, withdrawn, compensatory	assessment + telemetry	pair explanation
bnd.exit_signal_style	enum	clear exit, quiet drift, rupture exit, looping	assessment + telemetry	drift and closure systems

CLS / cluster support features

Feature key	Value type	Definition	Writeback threshold	Consumers
cls.vulnerability_loop_support	score	supports vulnerability loop cluster	cluster-specific rule pack	cluster engine only
cls.control_avoidance_support	score	supports control-avoidance cluster	cluster-specific rule pack	cluster engine only
cls.slow_drift_support	score	supports slow drift cluster	cluster-specific rule pack	drift and cluster engines
cls.push_pull_support	score	supports push-pull cluster	cluster-specific rule pack	forecast and cluster engines
cls.repair_gap_support	score	supports repair-gap cluster	cluster-specific rule pack	forecast and readiness overlays
cls.readiness_overstatement_support	score	supports readiness overstatement cluster	cluster-specific rule pack	readiness governance

SFT / safety and trust

Feature key	Value type	Definition	Writeback threshold	Consumers
sft.coercion_indicator	bool/band	pressure, coercion, or manipulation risk	policy or validated detection only	suppression/routing
sft.crisis_marker	bool	self-harm or crisis routing marker	policy trigger	crisis path
sft.harassment_risk	band	abuse or harassment signal	policy trigger	moderation only
sft.override_lock	bool	manual governance hold preventing feature surfacing	admin action	admin only
sft.retention_hold_reason	enum	reason a record cannot be auto-purged yet	policy only	audit
sft.visibility_restriction	enum	owner_only, suppressed, admin_only	policy or admin	packet builder

OUT / outcome and calibration

Feature key	Value type	Definition	Writeback threshold	Consumers
out.match_score_target	number	actual or prior match score used for calibration	telemetry import	model QA
out.repair_success_30d	bool/number	whether rupture converted into stable repair within 30d	pair telemetry	forecast tuning
out.conversation_survival_14d	bool	conversation longevity benchmark	pair telemetry	forecast tuning
out.knock_conversion_rate	number	rate of knock acceptance or conversion	pair telemetry	gating strategy
out.feedback_satisfaction_band	band	user-reported satisfaction with interaction	feedback import	cohort analytics
out.dropout_after_reveal	bool	whether richer insight caused exit	product analytics	product tuning

13. Assessment and polarity source maps

13.1 Scored assessment family map

Question family	Question IDs	Weight pattern	Primary genome outputs
CommunicationHealth	1, 2, 3, 4, 5, 6, 7, 8	avg question_weight_v3=1.00	communication posture, boundary signaling, directness, trigger support
EmotionalNeeds	41, 42, 43, 44, 45, 46, 47, 48, 49, 50	avg question_weight_v3=1.34	reassurance style, closeness needs, need-expression patterns
EmotionalRegulation	17, 18, 19, 20, 21, 22, 23, 24	avg question_weight_v3=1.10	regulation bias, activation management, state vulnerability markers
ConflictRepair	9, 10, 11, 12, 13, 14, 15, 16	avg question_weight_v3=1.05	repair style, rupture handling, repair-gap support
CommitmentPace	33, 34, 35, 36, 37, 38, 39, 40	avg question_weight_v3=1.17	availability, pacing, escalation readiness, readiness overlays
ValuesLifestyle	25, 26, 27, 28, 29, 30, 31, 32	avg question_weight_v3=1.14	stability filters, alignment constraints, future-fit context
ShadowPattern	100, 101, 102, 103, 104, 105, 106, 107, 108, 109	avg question_weight_v3=1.34	shadow distribution, manipulative/avoidant/self-sabotage support, risk context

13.2 Polarity prompt block map

Block	Question IDs	Primary axes	Secondary axes	Why it matters
1	q1	structure_preference_axis;flexibility_axis	initiation_axis;leadership_axis	Plan shifts / adaptation
1	q2	calm_receptivity_axis;surrender_safety_axis	flexibility_axis;structure_preference_axis	Silence and pause
1	q3	initiation_axis;leadership_axis	flexibility_axis;validation_dependency_axis	Choice under uncertainty
1	q4	tension_attraction_axis;calm_receptivity_axis	surrender_safety_axis;structure_preference_axis	Early friction / unresolved tension
1	q5	initiation_axis;structure_preference_axis	flexibility_axis;repair_endurance	Time pressure
1	q6	surrender_safety_axis;erotic_safety_alignment_axis	calm_receptivity_axis;validation_dependency_axis	Emotional disclosure
1	q7	leadership_axis;structure	tension_attraction_axis;ca	Conflicting preferences

		_preference_axis	lm_receptivity_axis	
1	q8	validation_dependency_axis;flexibility_axis	surrender_safety_axis;structure_preference_axis	Being observed / exposure
2	q9	structure_preference_axis;flexibility_axis	initiation_axis;leadership_axis	Plan shifts / adaptation
2	q10	calm_receptivity_axis;surrender_safety_axis	flexibility_axis;structure_preference_axis	Silence and pause
2	q11	initiation_axis;leadership_axis	flexibility_axis;validation_dependency_axis	Choice under uncertainty
2	q12	tension_attraction_axis;calm_receptivity_axis	surrender_safety_axis;structure_preference_axis	Early friction / unresolved tension
2	q13	initiation_axis;structure_preference_axis	flexibility_axis;repair_endurance	Time pressure
2	q14	surrender_safety_axis;erotic_safety_alignment_axis	calm_receptivity_axis;validation_dependency_axis	Emotional disclosure
2	q15	leadership_axis;structure_preference_axis	tension_attraction_axis;calm_receptivity_axis	Conflicting preferences
2	q16	validation_dependency_axis;flexibility_axis	surrender_safety_axis;structure_preference_axis	Being observed / exposure
3	q17	structure_preference_axis;flexibility_axis	initiation_axis;leadership_axis	Plan shifts / adaptation
3	q18	calm_receptivity_axis;surrender_safety_axis	flexibility_axis;structure_preference_axis	Silence and pause
3	q19	initiation_axis;leadership_axis	flexibility_axis;validation_dependency_axis	Choice under uncertainty
3	q20	tension_attraction_axis;calm_receptivity_axis	surrender_safety_axis;structure_preference_axis	Early friction / unresolved tension
3	q21	initiation_axis;structure_preference_axis	flexibility_axis;repair_endurance	Time pressure
3	q22	surrender_safety_axis;erotic_safety_alignment_axis	calm_receptivity_axis;validation_dependency_axis	Emotional disclosure
3	q23	leadership_axis;structure_preference_axis	tension_attraction_axis;calm_receptivity_axis	Conflicting preferences
3	q24	validation_dependency_axis;flexibility_axis	surrender_safety_axis;structure_preference_axis	Being observed / exposure
4	q25	structure_preference_axis	initiation_axis;leadership	Plan shifts / adaptation

		;flexibility_axis	_axis	
4	q26	calm_receptivity_axis;surrender_safety_axis	flexibility_axis;structure_preference_axis	Silence and pause
4	q27	initiation_axis;leadership_axis	flexibility_axis;validation_dependency_axis	Choice under uncertainty
4	q28	tension_attraction_axis;calm_receptivity_axis	surrender_safety_axis;structure_preference_axis	Early friction / unresolved tension
4	q29	initiation_axis;structure_preference_axis	flexibility_axis;repair_endurance	Time pressure
4	q30	surrender_safety_axis;erotic_safety_alignment_axis	calm_receptivity_axis;validation_dependency_axis	Emotional disclosure
4	q31	leadership_axis;structure_preference_axis	tension_attraction_axis;calm_receptivity_axis	Conflicting preferences
4	q32	validation_dependency_axis;flexibility_axis	surrender_safety_axis;structure_preference_axis	Being observed / exposure

14. Packet-building rules

- Packet builders may only emit canonical feature keys listed in the active registry table version.
- Every packet must include its source family, lane, evidence band, consent scope, and references to authoritative source events.
- When multiple sources contribute to one feature, packet builders must preserve both the canonical aggregate and the contributing evidence set.
- Pair-facing packets may include only match-visible or shared-couple classes authorized by product policy. Most genome features remain owner-private or internal.
- AI explanation packets read genome features; they do not invent non-canonical keys on the fly.

15. Registry implementation sequence

1. Create versioned code tables for canonical families, feature keys, evidence bands, freshness classes, source systems, consent scopes, and update lanes.
2. Import workbook-backed registries: AnswerBank, polarity axes, polarity role seeds, question maps, matrices, and score-law versions.
3. Implement event normalizers per source family with stable source_event_id creation.
4. Implement extractor recipes and validators as separate versioned modules; never let prompt text become the only place a rule exists.
5. Publish feature-store schemas and packet contracts. Add admin-facing registry browser and audit trail views.
6. Turn on medium-pattern writebacks first, then narrative memory, then controlled slow-identity mutation jobs once evidence tables and drift governance are proven.

16. Anti-patterns the build must avoid

- Do not save raw emotional monologues as permanent analytics labels. Save canonical labels with provenance instead.
- Do not merge slow identity, medium pattern, fast state, and narrative memory into one giant profile blob.
- Do not let ExsAnonymous or Sanctuary text rewrite archetype or shadow in a single shot.
- Do not bury thresholds only inside prompts. If the threshold matters, put it in a versioned code table.
- Do not expose internal safety flags as social product copy.
- Do not let one message burst or one reflective night become the user's whole truth.

17. Required appendix pack to maintain beside this registry

Appendix	What it contains	Why it must exist
Registry code-table export	machine-readable CSV/JSON of feature keys, enums, families, and thresholds	lets backend, AI, and analytics all read the same law
Extractor recipe ledger	prompt IDs, parser versions, validator versions, thresholds, test cases	stops extraction logic from becoming undocumented folklore
Source event contracts	payload schemas for messaging, Sanctuary, ExsAnonymous, anger, grief, games, outcomes	lets provenance survive every hop
User-facing copy library	owner-safe language for genome-backed insights	prevents the app from talking like a manipulative horoscope
Migration ledger	version-by-version changes to feature keys or thresholds	keeps history auditable when rules evolve