

```
In [1]: import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.linear_model import Ridge, RidgeCV, Lasso
from sklearn.preprocessing import StandardScaler
```

```
In [2]: data=pd.read_csv(r"C:\Users\Mastan Reddy\Downloads\Advertising.csv")
data
```

```
Out[2]:
```

	TV	Radio	Newspaper	Sales
0	230.1	37.8	69.2	22.1
1	44.5	39.3	45.1	10.4
2	17.2	45.9	69.3	12.0
3	151.5	41.3	58.5	16.5
4	180.8	10.8	58.4	17.9
...	...	...	...	...
195	38.2	3.7	13.8	7.6
196	94.2	4.9	8.1	14.0
197	177.0	9.3	6.4	14.8
198	283.6	42.0	66.2	25.5
199	232.1	8.6	8.7	18.4

200 rows × 4 columns

```
In [3]: data.head()
```

```
Out[3]:
```

	TV	Radio	Newspaper	Sales
0	230.1	37.8	69.2	22.1
1	44.5	39.3	45.1	10.4
2	17.2	45.9	69.3	12.0
3	151.5	41.3	58.5	16.5
4	180.8	10.8	58.4	17.9


```
In [4]: data.tail()
```

```
Out[4]:
```


	TV	Radio	Newspaper	Sales
195	38.2	3.7	13.8	7.6
196	94.2	4.9	8.1	14.0
197	177.0	9.3	6.4	14.8
198	283.6	42.0	66.2	25.5
199	232.1	8.6	8.7	18.4

```
In [5]: plt.figure(figsize = (10, 10))  
sns.heatmap(data.corr(), annot = True)
```

```
Out[5]: <AxesSubplot:>
```



```
In [6]: data.drop(columns = ["Radio", "Newspaper"], inplace = True)
#pairplot
sns.pairplot(data)
data.Sales = np.log(data.Sales)
```



```
In [7]: features = data.columns[0:2]
target = data.columns[-1]
#X and y values
X = data[features].values
y = data[target].values
#split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random
print("The dimension of X_train is {}".format(X_train.shape))
print("The dimension of X_test is {}".format(X_test.shape))
#Scale features
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)
```

The dimension of X\_train is (140, 2)

The dimension of X\_test is (60, 2)

```
In [8]: lr = LinearRegression()

lr.fit(X_train, y_train)

actual = y_test

train_score_lr = lr.score(X_train, y_train)
test_score_lr = lr.score(X_test, y_test)

print("\nLinear Regression Model:\n")
print("The train score for lr model is {}".format(train_score_lr))
print("The test score for lr model is {}".format(test_score_lr))
```

Linear Regression Model:

The train score for lr model is 1.0

The test score for lr model is 1.0

```
In [9]: ridgeReg = Ridge(alpha=10)

ridgeReg.fit(X_train,y_train)

train_score_ridge = ridgeReg.score(X_train, y_train)
test_score_ridge = ridgeReg.score(X_test, y_test)

print("\nRidge Model:\n")
print("The train score for ridge model is {}".format(train_score_ridge))
print("The test score for ridge model is {}".format(test_score_ridge))
```

Ridge Model:


The train score for ridge model is 0.990287139194161

The test score for ridge model is 0.9844266285141221

```
In [11]: plt.figure(figsize = (10, 10))
plt.plot(features,ridgeReg.coef_,alpha=0.7,linestyle='none',marker='*',markersize=7,
color='red')

plt.plot(features,lr.coef_,alpha=0.4,linestyle='none',marker='o',markersize=7,
color='green')

plt.xticks(rotation = 90)
plt.legend()
plt.show()
```



In [16]:

```
#Lasso regression model
print("\nLasso Model: \n")
lasso = Lasso(alpha = 10)
lasso.fit(X_train,y_train)
train_score_ls =lasso.score(X_train,y_train)
test_score_ls =lasso.score(X_test,y_test)
print("The train score for ls model is {}".format(train_score_ls))
print("The test score for ls model is {}".format(test_score_ls))
```


Lasso Model:

The train score for ls model is 0.0

The test score for ls model is -0.0042092253233847465

In [17]: `pd.Series(lasso.coef_, features).sort_values(ascending = True).plot(kind = "bar")`

Out[17]: &lt;AxesSubplot:&gt;



```
In [20]: #Using the Linear CV model
from sklearn.linear_model import LassoCV

#Lasso Cross validation
lasso_cv = LassoCV(alphas = [0.0001, 0.001,0.01, 0.1, 1, 10], random_state=0).

#score
print(lasso_cv.score(X_train, y_train))
print(lasso_cv.score(X_test, y_test))


0.9999999343798134
0.9999999152638072
```

```
In [26]: #plot size
plt.figure(figsize = (10, 10))
#add plot for ridge regression
plt.plot(features,ridgeReg.coef_,alpha=0.7,linestyle='none',marker='*',markersize=10,color='red')

plt.plot(lasso_cv.coef_,alpha=0.5,linestyle='none',marker='d',markersize=6,color='blue')

plt.plot(features,lr.coef_,alpha=0.4,linestyle='none',marker='o',markersize=7,color='green')

plt.xticks(rotation = 90)
plt.legend()
plt.title("Comparison plot of Ridge, Lasso and Linear regression model")
plt.show()
```





In [ ]: