

Sample documentation for RestApi

Damian Langer - <damian.langer@gmail.com>

Version 0.1, 2016-10-01

Table of Contents

1. Employee resources	1
1.1. Employee details	1
1.2. New employee.....	4
1.3. Update employee	6
1.4. Employees collection	8
1.5. Assign office to Employee	9

Welcome to sample documentation for educational rest api.

1. Employee resources

1.1. Employee details

Provide details of a requested employee

1.1.1. Request

Path parameters

Table 1. /api/employee/{id}

Parameter	Description
id	Employee id (number)

Sample http request

```
GET /api/employee/1 HTTP/1.1
Accept: application/json;charset=UTF-8
Host: localhost:8080
```

Sample curl request

```
$ curl 'http://localhost:8080/api/employee/1' -i -H 'Accept:
application/json;charset=UTF-8'
```

1.1.2. Response

Fields

Path	Type	Description
source_path	String	Request path
message	String	Human readable message
content	Object	Employee
content.id	Number	Employee id
content.name	String	Employee name, should be unique
content.address	Object	Employee address

Path	Type	Description
content.address.street	String	Street address (without number)
content.address.street_no	Varies	Street number
content.address.city	String	City
content.address.country	String	Country
content.email	String	Employee email address
content.phone	String	Employee phone number
content.offices	Array	Employee workplaces collection
content.offices[].id	Number	Office id
content.offices[].name	String	Unique office name
content.offices[].address	Object	Office address
content.offices[].address.street	String	Street address (without number)
content.offices[].address.street_no	String	Street number
content.offices[].address.city	String	City
content.offices[].address.country	String	Country

Headers

Name	Description
Content-Type	Always application/json;charset=UTF-8

Sample response

HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Content-Length: 957

```
{
  "source_path" : "/api/employee/1",
  "message" : "Employee with id 1 details",
  "content" : {
    "id" : 1,
    "name" : "DAMIAN1",
    "address" : {
      "street" : "street1",
      "street_no" : null,
      "city" : "KATOWICE",
      "country" : "POLAND"
    },
    "email" : "damian1@email.pl",
    "phone" : "11234567",
    "offices" : [ {
      "id" : 2,
      "name" : "OFFICCE2",
      "address" : {
        "street" : "officestreet2",
        "street_no" : "2",
        "city" : "KATOWICE",
        "country" : "POLAND"
      }
    }, {
      "id" : 3,
      "name" : "OFFICCE3",
      "address" : {
        "street" : "officestreet3",
        "street_no" : "3",
        "city" : "KATOWICE",
        "country" : "POLAND"
      }
    }, {
      "id" : 1,
      "name" : "OFFICCE1",
      "address" : {
        "street" : "officestreet1",
        "street_no" : "1",
        "city" : "KATOWICE",
        "country" : "POLAND"
      }
    }
  ]
}
```

1.2. New employee

Add new employee to system

1.2.1. Request

Path parameters

Request fields

Path	Type	Description
name	String	Employee name, should be unique
address	Object	Employee address
address.street	Varies	Street address (without number)
address.street_no	Varies	Street number
address.city	Varies	City
address.country	Varies	Country
email	Varies	Employee email address
phone	Varies	Employee phone number

Sample http request

```
POST /api/employee HTTP/1.1
Accept: application/json;charset=UTF-8
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
Content-Length: 189
```

```
{
  "name" : "new employee",
  "address" : {
    "street" : "new street",
    "street_no" : null,
    "city" : null,
    "country" : null
  },
  "email" : "new@email.pl",
  "phone" : null
}
```

Sample curl request

```
$ curl 'http://localhost:8080/api/employee' -i -X POST -H 'Accept: application/json;charset=UTF-8' -H 'Content-Type: application/json;charset=UTF-8' -d '{
  "name" : "new employee",
  "address" : {
    "street" : "new street",
    "street_no" : null,
    "city" : null,
    "country" : null
  },
  "email" : "new@email.pl",
  "phone" : null
}'
```

1.2.2. Response

Fields

Path	Type	Description
source_path	String	Request path
message	String	Human readable message
content	Number	Created employee id

Headers

Name	Description
Content-Type	Always application/json;charset=UTF-8

Sample response

```
HTTP/1.1 201 Created
Content-Type: application/json;charset=UTF-8
Content-Length: 88

{
  "source_path" : "/api/employee",
  "message" : "Employee created",
  "content" : 5
}
```

1.3. Update employee



Unrecoverable operation



name is ignored, you can not change Employee name

Update employee details

1.3.1. Request

Path parameters

Table 2. `/api/employee/{id}`

Parameter	Description
<code>id</code>	Employee id

Request fields

Path	Type	Description
<code>name</code>	String	Ignored during update process
<code>address</code>	Object	Employee address
<code>address.street</code>	Varies	Street address (without number)
<code>address.street_no</code>	Varies	Street number
<code>address.city</code>	Varies	City
<code>address.country</code>	Varies	Country
<code>email</code>	Varies	Employee email address
<code>phone</code>	Varies	Employee phone number

Sample http request


```
PUT /api/employee/1 HTTP/1.1
Accept: application/json;charset=UTF-8
Content-Type: application/json;charset=UTF-8
Host: localhost:8080
Content-Length: 189
```

```
{
  "name" : "new employee",
  "address" : {
    "street" : "new street",
    "street_no" : null,
    "city" : null,
    "country" : null
  },
  "email" : "new@email.pl",
  "phone" : null
}
```

Sample curl request

```
$ curl 'http://localhost:8080/api/employee/1' -i -X PUT -H 'Accept:
application/json;charset=UTF-8' -H 'Content-Type: application/json;charset=UTF-8' -d
'{
  "name" : "new employee",
  "address" : {
    "street" : "new street",
    "street_no" : null,
    "city" : null,
    "country" : null
  },
  "email" : "new@email.pl",
  "phone" : null
}'
```

1.3.2. Response

Fields

Path	Type	Description
<code>source_path</code>	<code>String</code>	Request path
<code>message</code>	<code>String</code>	Human readable message
<code>content</code>	<code>Null</code>	Always null

Headers

Name	Description
Content-Type	Always application/json;charset=UTF-8

Sample response

```
HTTP/1.1 202 Accepted
Content-Type: application/json;charset=UTF-8
Content-Length: 103

{
  "source_path" : "/api/employee/1",
  "message" : "Employee with id 1 updated",
  "content" : null
}
```

1.4. Employees collection

Provide collection of all registered employees.

1.4.1. Request

Sample http request

```
GET /api/employees HTTP/1.1
Accept: application/json;charset=UTF-8
Host: localhost:8080
```

Sample curl request

```
$ curl 'http://localhost:8080/api/employees' -i -H 'Accept:
application/json;charset=UTF-8'
```

1.4.2. Response

Fields

Path	Type	Description
source_path	String	Request path
message	String	Human readable message
content	Array	Employees collection
content[].id	Number	Employee id

Path	Type	Description
<code>content[].name</code>	String	Employee name, should be unique
<code>content[].email</code>	String	Employee email address

Headers

Name	Description
<code>Content-Type</code>	Always application/json;charset=UTF-8

Sample response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Content-Length: 399
```

```
{
  "source_path" : "/api/employees",
  "message" : "All employees",
  "content" : [ {
    "id" : 1,
    "name" : "DAMIAN1",
    "email" : "damian1@email.pl"
  }, {
    "id" : 2,
    "name" : "DAMIAN2",
    "email" : "damian2@email.pl"
  }, {
    "id" : 3,
    "name" : "DAMIAN3",
    "email" : "damian3@email.pl"
  }, {
    "id" : 4,
    "name" : "DAMIAN4",
    "email" : "damian4@email.pl"
  } ]
}
```

1.5. Assign office to Employee



Unrecoverable operation

Assign office to employee, one employee can work in many offices.

1.5.1. Request

Path parameters

Table 3. /api/employee/{id}/workplace/{wid}

Parameter	Description
id	Employee id
wid	Office id

Sample http request

```
POST /api/employee/4/workplace/1 HTTP/1.1
Accept: application/json;charset=UTF-8
Host: localhost:8080
```

Sample curl request

```
$ curl 'http://localhost:8080/api/employee/4/workplace/1' -i -X POST -H 'Accept:
application/json;charset=UTF-8'
```

1.5.2. Response

Fields

Path	Type	Description
source_path	String	Request path
message	String	Human readable message
content	Boolean	Success indicator

Headers

Name	Description
Content-Type	Always application/json;charset=UTF-8

Sample response

```
HTTP/1.1 202 Accepted
Content-Type: application/json;charset=UTF-8
Content-Length: 115
```

```
{
  "source_path" : "/api/employee/4/workplace/1",
  "message" : "Employee with id 4 updated",
  "content" : true
}
```