

4 & 8 channel dimmer range learn enabled

The 4 channel dimmer units are DIN rail mounted units employing leading edge phase control circuitry for dimming control. These dimmer units feature learn mode, local and remote overrides for on/off control, channel, C-Bus and unit status indicators.

Each dimmer channel is rated at 2 Amps and is suitable for incandescent and low voltage lighting using magnetic and leading edge compatible transformers. The dimmer output is controllable over the range of 2-98%, while frequency tracking algorithms ensure flicker-free operation and smooth dimming control.

The dimmer units are available as passive and current sourcing models that source up to 200mA to the C-Bus network.



Technical Information

Catalogue number	L5508D1A/L5504D1A	L5508D1AP/ L5504D1AP
Line Supply Voltage	220-240VAC	
Supply Frequency	47-53Hz and 57-63Hz	
Frequency Drift	3Hz/minute (maximum)	
Frequency Step Change	0.1Hz (maximum)	
C-Bus Supply Voltage	15-36VDC @ 0mA	
Load Rating per Channel	1A	
Minimum Load	15W per channel	
Control Range	2 - 98%	
Compatible Loads	Incandescent and low voltage lighting. Ensure compatible leading edge electronic transformers are used.	
C-Bus Source Current	200mA	0mA
Maximum Number of Units on a Single C-Bus Network	10	100
Warm Up Time	5 seconds	
Network Clock	Software selectable	
Network Burden	Software selectable	
C-Bus Termination	2 x RJ45 Socket	
Load Termination	2 x 1.5mm ² or 1 x 2.5mm ²	
Operating Temperature Range	0°C to 45°C	
Operating Humidity Range	0 - 95% RH, non-condensing	

Product Features

- Programmable via the learn mode feature or using the C-Bus Toolkit Software
- Programmed variables are stored in non-volatile memory and are retained in case of loss of mains or C-Bus power
- Local and remote on/off control independent of C-Bus communications
- Programmable power up state following power cycling
- Logic states (max/min) programmable using the C-Bus Toolkit Software
- Employs frequency-tracking algorithms for smooth flicker free operation
- Designed to fit standard 35mm top hat DIN rail, measures just 12M in size
- Designed to fit into standard electrical switchboards

Catalogue Number	Description
L5508D1AP	8 Channel dimmer 1A, 220/240VAC 50/60Hz
L5508D1A	8 Channel dimmer 1A, 220/240VAC 50/60Hz, C-Bus 200mA
L5504D2AP	4 Channel dimmer 2A, 220/240VAC 50/60Hz
L5504D2A	4 Channel dimmer 2A, 220/240VAC

Accessories	Description
S31LCDA	Load Correction Device