

## CBS-50 Electrolyte Analyzer ( $K^+$ $Na^+$ $Cl^-$ $Ca^{2+}$ pH $TCO_2$ )



### Products Characteristics

- Advanced Multi- Biosensor Technology (MBT) permits maintenance-free electrode.
- Close reagent pack is easy to replace.
- Multi-level calibrators and controls secure results accuracy.
- User friendly operation and quick trouble shooting.
- High throughput gives each test result within half a minute.
- Up to 6000 sample results storage and easy to review.
- 5.6 inch touch screen makes operation more convenient

B&E Diagnostics Inc.

### Specifications

|                           |                                                              |                         |               |                    |
|---------------------------|--------------------------------------------------------------|-------------------------|---------------|--------------------|
| Method                    | Multi-Biosensor Technology + Pressure Sensors Technolgy      |                         |               |                    |
| Sample Size               | 60-120μl                                                     |                         |               |                    |
| Speed                     | ISE≥80 tests/hour, TCO2≥40 tests/hour                        |                         |               |                    |
| Measure scope & Precision | Performance                                                  | Detection Range(mmol/L) | Precision(CV) | Resolution(mmol/L) |
|                           | K <sup>+</sup>                                               | 0.50 ~ 20.00            | ≤1.0%         | 0.01               |
|                           | Na <sup>+</sup>                                              | 15.0 ~ 200.0            | ≤1.0%         | 0.1                |
|                           | Cl <sup>-</sup>                                              | 15.0 ~ 200.0            | ≤1.0%         | 0.1                |
|                           | Ca <sup>2+</sup>                                             | 0.10 ~ 6.00             | ≤1.0%         | 0.01               |
|                           | pH                                                           | 4.00 ~ 9.00             | ≤1.0%         | 0.01               |
|                           | TCO <sub>2</sub>                                             | 5.00 ~ 70.00            | ≤3.0%         | 0.01               |
| Printer                   | Inner thermal printer                                        |                         |               |                    |
| Expand Function           | RS232 & COM Connector, Computer and Barcode reader available |                         |               |                    |
| Ambient Conditions        | 0-40℃, Relative humidity ≤ 85%                               |                         |               |                    |
| Power                     | AC 80V ~ 260V , 50-60Hz, ≤80W                                |                         |               |                    |

