

ITCT Lecture 10.4: Fast Algorithm for the DCT

Prof. Ja-Ling Wu

Department of Computer Science
and Information Engineering
National Taiwan University



1

Fast Algorithm for the DCT

- The DCT matrix is **orthogonal**; its **inverse** is its **transpose**.

Definition : **N - point DCT**

$$y_n = C_n \sum_{k=0}^{N-1} x_k \cos \frac{2\pi n(2k+1)}{4N} \quad (1)$$

N - point IDCT

$$x_k = \sum_{n=0}^{N-1} C_n y_n \cos \frac{2\pi n(2k+1)}{4N} \quad (2)$$

Let us focus on the case of $N = 8$.


Data Compression



2

Set $r(k) = \cos(2\pi k / 32) = \cos(\pi k / 16)$
 then, the 8-point DCT matrix is


$$C_8 = \frac{1}{2} \begin{bmatrix} r(4) & r(4) & r(4) & r(4) & r(4) & r(4) & r(4) & r(4) \\ r(1) & r(3) & r(5) & r(7) & -r(7) & -r(5) & -r(3) & -r(1) \\ r(2) & r(6) & -r(6) & -r(2) & -r(2) & -r(6) & r(6) & r(2) \\ r(3) & -r(7) & -r(1) & -r(5) & r(5) & r(1) & r(7) & -r(3) \\ r(4) & -r(4) & -r(4) & r(4) & r(4) & -r(4) & -r(4) & r(4) \\ r(5) & -r(1) & r(7) & r(3) & -r(3) & -r(7) & r(1) & -r(5) \\ r(6) & -r(2) & r(2) & -r(6) & -r(6) & r(2) & -r(2) & r(6) \\ r(7) & -r(5) & r(3) & -r(1) & r(1) & -r(3) & r(5) & -r(7) \end{bmatrix} \quad (3)$$

Data Compression 


3

$P(8,1)$: permutation matrix $\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 & 6 & 7 \\ & & & & \downarrow & & & \\ & 0 & 2 & 4 & 6 & 1 & 3 & 5 & 7 \end{matrix}$
 $P(8,2)$: permutation matrix $\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 & 6 & 7 \\ & & & & \downarrow & & & \\ & 0 & 1 & 2 & 3 & 7 & 6 & 5 & 4 \end{matrix}$

$$P(8,1)C_8P(8,2) = \begin{bmatrix} 4 & 4 & 4 & 4 & 4 & 4 & 4 & 4 \\ 1 & 3 & 5 & 7 & -7 & -5 & -3 & -1 \\ 2 & 6 & -6 & -2 & -2 & -6 & 6 & 2 \\ 3 & -7 & -1 & -5 & 5 & 1 & 7 & -3 \\ 4 & -4 & -4 & 4 & 4 & -4 & -4 & 4 \\ 5 & -1 & 7 & 3 & -3 & -7 & 1 & -5 \\ 6 & -2 & 2 & -6 & -6 & 2 & -2 & 6 \\ 7 & -5 & 3 & -1 & 1 & -3 & 5 & -7 \end{bmatrix}$$

Data Compression 


4



$$= \left[\begin{array}{cccc|cccc} 4 & 4 & 4 & 4 & 4 & 4 & 4 & 4 \\ 2 & 6 & -6 & -2 & 2 & 6 & -6 & -2 \\ 4 & -4 & -4 & 4 & 4 & -4 & -4 & 4 \\ 6 & -2 & 2 & -6 & 6 & -2 & 2 & -6 \\ \hline 1 & 3 & 5 & 7 & -1 & -3 & -5 & -7 \\ 3 & -7 & -1 & -5 & -3 & 7 & 1 & 5 \\ 5 & -1 & 7 & 3 & -5 & 1 & -7 & -3 \\ 7 & -5 & 3 & -1 & -7 & 5 & -3 & 1 \end{array} \right]$$

$$= \begin{bmatrix} A & A \\ B & -B \end{bmatrix} = \begin{bmatrix} A & \\ & B \end{bmatrix} \otimes \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$

Data Compression



5

Let I_n denote the $n \times n$ identity matrix,

$$F \triangleq \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$$


and define $R_8 = F \otimes I_4$

(if $A=(a_{i,j})_{m \times n}$, $B=(b_{i,j})_{p \times q}$, then the **tensor product** $A \otimes B$ is the $mp \times nq$ matrix composed of the $m \times n$ blocks $(a_{i,j} B)$)

Then

$$P(8,1)C_8P(8,2)R_8 = \begin{bmatrix} r(4) & r(4) & r(4) & r(4) \\ r(2) & r(6) & -r(6) & -r(2) \\ r(4) & -r(4) & -r(4) & r(4) \\ r(6) & -r(2) & r(2) & -r(6) \\ r(1) & r(3) & r(5) & r(7) \\ r(3) & -r(7) & -r(1) & -r(5) \\ r(5) & -r(1) & r(7) & r(3) \\ r(7) & -r(5) & r(3) & -r(1) \end{bmatrix} \quad (4)$$

Data Compression



6

Consider the cyclic subgroup of U_{32} (multiplicative group mod 32) generated by 3 :

$$\begin{array}{ccc} 3^0, 3^1, 3^2, 3^3, 3^4, 3^5, 3^6, 3^7 & \text{Notice that} & \\ \{ 1, 3, 9, 27, 17, 19, 25, 11 \} & & 3^8 = 1 \text{ mod } 32 \\ -5 & -7 & \end{array}$$

Then, the bottom right 4x4 block can be written as

$$\begin{pmatrix} r(3^0) & r(3^1) & r(3^3) & -r(3^2) \\ r(3^1) & r(3^2) & -r(3^0) & -r(3^3) \\ r(3^3) & -r(3^0) & -r(3^2) & r(3^1) \\ -r(3^2) & -r(3^3) & r(3^1) & -r(3^0) \end{pmatrix} \triangleq \tilde{G}_4$$

Data Compression



7

With the add of the following facts :

1. $3^8=1 \rightarrow 3^4=17 \text{ mod } 32$

2. $\cos(-\theta)=\cos(\theta)$

$$\begin{aligned} \Rightarrow r(3^{4+j}) &= \cos \frac{2\pi[3^{4+j}]}{32} = \cos \frac{2\pi[17 \cdot 3^j]}{32} \\ &= \cos \left[\pi + \frac{2\pi[1 \cdot 3^j]}{32} \right] = -r(3^j), j = 0,1,2,3 \end{aligned}$$

3. $r(27) = r(-5) = r(5) = r(3^3)$

4. $r(7) = r(25) = r(3^6) = -r(3^2) = -r(9)$

Data Compression



8

Define


$$P(4,1) = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & -1 \\ 0 & 0 & 1 & 0 \end{pmatrix}$$

$$P(4,1) \begin{pmatrix} r(1) \\ r(3) \\ r(5) \\ r(7) \end{pmatrix} = \begin{pmatrix} r(1) \\ r(3) \\ -r(7) \\ r(5) \end{pmatrix} = \begin{pmatrix} r(3^0) \\ r(3^1) \\ r(3^2) \\ r(3^3) \end{pmatrix}$$

Then,

$$P(4,1)\tilde{G}_4P(4,1)^{-1} = \begin{pmatrix} r(3^0) & r(3^1) & r(3^2) & r(3^3) \\ r(3^1) & r(3^2) & r(3^3) & -r(3^0) \\ r(3^2) & r(3^3) & -r(3^0) & -r(3^1) \\ r(3^3) & -r(3^0) & -r(3^1) & -r(3^2) \end{pmatrix}$$

: signed-circulant matrix

Data Compression 

9


Reversing the order of the columns in $P(4,1)\tilde{G}_4P(4,1)^{-1}$ yields

$$G_4 = \begin{pmatrix} r(3^3) & r(3^2) & r(3^1) & r(3^0) \\ -r(3^0) & r(3^3) & r(3^2) & r(3^1) \\ -r(3^1) & -r(3^0) & r(3^3) & r(3^2) \\ -r(3^2) & -r(3^1) & -r(3^0) & r(3^3) \end{pmatrix} \quad (5)$$

G_4 can be viewed as an element in the regular representation of the polynomial ring in the variable u modulo (u^4+1) .

$$\begin{pmatrix} w_0 \\ w_1 \\ w_2 \\ w_3 \end{pmatrix} = \begin{pmatrix} r(3^3) & r(3^2) & r(3^1) & r(3^0) \\ -r(3^0) & r(3^3) & r(3^2) & r(3^1) \\ -r(3^1) & -r(3^0) & r(3^3) & r(3^2) \\ -r(3^2) & -r(3^1) & -r(3^0) & r(3^3) \end{pmatrix} \begin{pmatrix} v_0 \\ v_1 \\ v_2 \\ v_3 \end{pmatrix}, \text{ then}$$

$$\begin{aligned} & (r(3^3) - r(3^0)u - r(3^1)u^2 - r(3^2)u^3) \cdot (v_0 + v_1u + v_2u^2 + v_3u^3) \\ & = (w_0 + w_1u + w_2u^2 + w_3u^3) \mod (u^4 + 1) \end{aligned} \quad (6)$$

Data Compression 

10

The above equation can be rewritten as :

$$\sum_{j=0}^3 r(3^{3+j}) u^j$$

- The top-left 4×4 block of (4) equals $\sqrt{2}$ times the 4-point DCT matrix C_4 . Itself yields a similar **block diagonalization**.

Let $P(4,2) : 0 \downarrow 1 \ 2 \ 3$

$0 \ 2 \ 1 \ 3$

$P(4,3) : 0 \downarrow 1 \ 2 \ 3$

$0 \ 1 \ 3 \ 2$

$$R(4,1) = F \otimes I_2$$

Data Compression



11

Then

$$P(4,2)(\sqrt{2}C_4)P(4,3) \cdot R(4,1)$$

$$= 2 \begin{pmatrix} r(4) & r(4) \\ r(4) & -r(4) \end{pmatrix} \begin{pmatrix} r(2) & r(6) \\ r(6) & -r(2) \end{pmatrix} \quad (7)$$

signed - circulant matrix \tilde{G}_2

$$G_2 = \begin{pmatrix} r(6) & r(2) \\ -r(2) & r(6) \end{pmatrix}$$

$$\begin{pmatrix} w_0 \\ w_1 \end{pmatrix} = \begin{pmatrix} r(6) & r(2) \\ -r(2) & r(6) \end{pmatrix} \begin{pmatrix} v_0 \\ v_1 \end{pmatrix}$$

in polynomial form

\Rightarrow

$$(r(6) - r(2)u)(v_0 + v_1u) = (w_0 + w_1u) \mod (u^2 + 1)$$


Data Compression



12

Also, the 2x2 subblock on the top left of (7) is the 2-point DCT matrix C2, and it yields the diagonalization

$$C_2 F = 2 \begin{pmatrix} r^{(4)} & \\ & r^{(4)} \end{pmatrix} \quad (8)$$



Putting all these factorizations together yields, after slight arithmetic manipulation, the following factorization for the 8-point DCT matrix :

$$C_8 = P_8 K_8 B$$

where P_8 is the **signed-permutation matrix**

$$P_8 = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & -1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \end{bmatrix}$$

Data Compression



13

$$K_8 = \frac{1}{2} \begin{pmatrix} G_1 & & & \\ & G_1 & & \\ & & G_2 & \\ & & & G_4 \end{pmatrix}$$

and B is the rational matrix

$$B = B_1 B_2 B_3$$

where


$$B_1 = \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & -1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & -1 & 0 & 0 \\ 0 & 0 & 0 & 0 & -1 & 0 & 0 & 0 \end{bmatrix}$$

2 adds

Data Compression



14




$$B_2 = \begin{bmatrix} 1 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & -1 & 0 & 0 & 0 & 0 \\ 0 & 1 & -1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \quad 4 \text{ adds}$$


$$B_3 = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & -1 \\ 0 & 1 & 0 & 0 & 0 & 0 & -1 & 0 \\ 0 & 0 & 1 & 0 & 0 & -1 & 0 & 0 \\ 0 & 0 & 0 & 1 & -1 & 0 & 0 & 0 \end{bmatrix} \quad 8 \text{ adds}$$

This factorization leads to an algorithm for computing the product of an arbitrary vector by C_8 .

Data Compression



15




3-step Algorithm for computing 8-point DCT

1. Compute the product by the matrix B, which can be done (via its factorization) with $2+4+8=14$ additions
2. Compute the product of the above result by K_8
3. Finish the computation with a signed permutation.

Multiplication by K_8 will be done by computing independently the various products by $\frac{1}{2} G_j$. Each of these is equivalent to **the multiplication of polynomials modulo an irreducible polynomial.**

Data Compression



16

The product of $\frac{1}{2} G_2$ is in the form of $\begin{pmatrix} x_0 & -x_1 \\ x_1 & x_0 \end{pmatrix} \begin{pmatrix} y_0 \\ y_1 \end{pmatrix}$, and can be done with

3 adds and 3 multis. as follows,

$$\begin{pmatrix} x_0 & -x_1 \\ x_1 & x_0 \end{pmatrix} \begin{pmatrix} y_0 \\ y_1 \end{pmatrix} = \begin{pmatrix} 1 & -1 & 0 \\ 0 & 1 & 1 \end{pmatrix} \begin{pmatrix} (x_0 + x_1)y_0 \\ x_1(y_0 + y_1) \\ (x_0 - x_1)y_1 \end{pmatrix} \quad (9)$$

where the sums involving x_i are **pre-computed**.

Data Compression



17

$$\frac{1}{2}(G_4) \rightarrow$$

$$\begin{pmatrix} x_0 & -x_3 & -x_2 & -x_1 \\ x_1 & x_0 & -x_3 & -x_2 \\ x_2 & x_1 & x_0 & -x_3 \\ x_3 & x_2 & x_1 & x_0 \end{pmatrix} \begin{pmatrix} y_0 \\ y_1 \\ y_2 \\ y_3 \end{pmatrix} = \begin{pmatrix} X_0 & -X_1 \\ X_1 & X_0 \end{pmatrix} \begin{pmatrix} Y_0 \\ Y_1 \end{pmatrix}$$

where

$$X_0 = \begin{pmatrix} x_0 & -x_3 \\ x_1 & x_0 \end{pmatrix}, \quad X_1 = \begin{pmatrix} x_2 & x_1 \\ x_3 & x_2 \end{pmatrix}$$

$$Y_0 = \begin{pmatrix} y_0 \\ y_1 \end{pmatrix}, \quad Y_1 = \begin{pmatrix} y_2 \\ y_3 \end{pmatrix}$$

We can use the recipe of (9) but replace each product with a matrix-vector product and each sum with a vector sum.

Data Compression



18

The matrix-vector product are all of the form

$$\begin{pmatrix} x_0 & x_1 \\ x_2 & x_0 \end{pmatrix} \begin{pmatrix} y_0 \\ y_1 \end{pmatrix} = \begin{pmatrix} 1 & -1 & 0 \\ 1 & 0 & 1 \end{pmatrix} \begin{pmatrix} x_0(y_0 + y_1) \\ (x_0 - x_1)y_1 \\ (x_2 - x_0)y_0 \end{pmatrix} \quad (10)$$

which can be done with 3 additions and 3 multiplications (the sum involving the x_j are pre-computed).

→ $\frac{1}{2} G_4$ can be computed with

$3 \times 3 = 9$ multiplications and

$3 \times 3 + 3 \times 3 = 18$ additions.

Data Compression



19

Thus, with this implementation, the product of C_8 can be done with 14 multiplications and 35 additions.

An attractive feature of this algorithm is that each Computation path contains only one multiplication. That is, the computation never involves products of factors which are themselves sum of products. This is significant when one is concerned about bit requirements for accuracy of computation.

Data Compression



20

Alternately, the product of $\frac{1}{2} G_4$ with a vector can be done using the following identity :

$$G_4 = \frac{1}{2} D_4^{-1} H_{4,1} \begin{pmatrix} 1 & & & \\ & \boxed{G_1} & & \\ & & r(4) & \\ & & & G_2 \end{pmatrix} H_{4,2} \quad (11)$$

where

$$D_4 = \begin{bmatrix} r(5) & & & \\ & r(1) & & \\ & & r(3) & \\ & & & r(7) \end{bmatrix}$$

$$H_{4,1} = \begin{pmatrix} 1 & 1 & -1 & 0 \\ -1 & 1 & 0 & 1 \\ -1 & -1 & -1 & 0 \\ 1 & -1 & 0 & 1 \end{pmatrix}$$

and

$$H_{4,2} = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & 0 & -1 \\ 0 & 1 & -1 & 0 \end{pmatrix}$$

Data Compression



21

→ the product by $\frac{1}{2} G_4$ can be done using 3 adds (multiplication by $H_{4,2}$), followed by one multiplication by $\frac{1}{4}$, one by $\frac{1}{4} r(4)$, and one by a rotator (multiplication by $\frac{1}{4} (1 \oplus G_1 \oplus G_4)$), followed by 6 more additions (multi. by $H_{4,1}$, followed by 4 mults. (multip. By D_4^{-1}).

→ $\frac{1}{2} (G_4)$ needs 8 mults. & 12 adds.

→ C_8 needs 13 mults. & 29 adds.

Observe that (11) yields a procedure for transforming the product by G_4 , which can be thought of as the “Core” half of the 8-point DCT computation, into essentially a 4-point DCT followed by multiplication by a “diagonal matrix times something which is essentially a 2-point DCT matrix.

Data Compression



22

Namely,

$$G_2 = \frac{1}{2} \begin{pmatrix} r(6) & \\ & r(2) \end{pmatrix}^{-1} \begin{pmatrix} 1 & 1 \\ -1 & 1 \end{pmatrix} \begin{pmatrix} 1 & \\ & G_1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ -1 & 1 \end{pmatrix} \quad (12)$$

Eqn.(12) gives an alternate method for computing the product by G_2 with 3 adds and 3 multis., but these are nested.

In general, G_2^k can be factored to a diagonal matrix times a matrix which is essentially the core of C_2^{K-1} , thereby yielding a recursive algorithm for the DCT on 2^m -point.

Data Compression



23

The 2-D DCT on 8x8 points

Computation of the 8x8 2-D DCT involves the product of the matrix $C_8 \otimes C_8$ with a 64-point vector.

$$C_8 = P_8 K_8 B$$

$$\rightarrow C_8 \otimes C_8 = (P_8 \otimes P_8)(K_8 \otimes K_8)(B \otimes B) \quad (13)$$

Also,

$$K_8 \otimes K_8 = \frac{1}{4} \oplus G_j \otimes G_k \quad (14)$$

where \oplus : the matrix direct sum

j, k run through the values 1, 1, 2, 4 in lexicographic order.

Eqn.(13) suggests the following algorithm for computing $C_8 \otimes C_8$

Data Compression



24

- (i) Compute the product by $B \otimes B$ using, say the row-column method, with $2 \times 8 \times 14 = 224$ adds.
- (ii) Compute separately the product by $G_j \otimes G_k$
- (iii) Finish with a signed-permutation defined by $P_8 \otimes P_8$.
(The factor $\frac{1}{4}$ can either be computed at the end with shifts, or, preferably, incorporated into the product by the $G_j \otimes G_k$)

Question :

Can the products by $G_j \otimes G_k$ be done much more efficiently than by the row-column method when both j and k are greater than or equal to 2 ?

Data Compression



25

Let consider the simplest case, $G_1 \otimes G_2$, in considerable detail.

the product of a 2-vector by G_2 needs 3 mult & 3 adds.

→ the product of a 4-vector by $G_2 \otimes G_2$ can be done in “row-column” fashion using 4 products of 2-vectors by G_2 , hence with 12 mults & 12 adds.

We can improve upon this, by using the following trigonometric identity :


$$2 \cos \theta_1 \cos \theta_2 = \cos(\theta_1 + \theta_2) + \cos(\theta_1 - \theta_2)$$

or $2 r(a)r(b) = r(a+b) + r(a-b)$ (15)

Data Compression




26





$$\begin{aligned}
 G_2 \otimes G_2 &= \begin{pmatrix} r(6) & r(2) \\ -r(2) & r(6) \end{pmatrix} \otimes \begin{pmatrix} r(6) & r(2) \\ -r(2) & r(6) \end{pmatrix} \\
 &= \begin{pmatrix} r(6)r(6) & r(6)r(2) & r(2)r(6) & r(2)r(2) \\ -r(6)r(2) & r(6)r(6) & -r(2)r(2) & r(2)r(6) \\ -r(2)r(6) & -r(2)r(2) & r(6)r(6) & r(6)r(2) \\ r(2)r(2) & -r(2)r(6) & -r(6)r(2) & r(6)r(6) \end{pmatrix} \\
 &= \frac{1}{2} \begin{pmatrix} r(0)-r(4) & r(4) & r(4) & r(0)+r(4) \\ -r(4) & r(0)-r(4) & -r(0)-r(4) & r(4) \\ -r(4) & -r(0)-r(4) & r(0)-r(4) & r(4) \\ r(0)+r(4) & -r(4) & -r(4) & r(0)-r(4) \end{pmatrix} \\
 &\quad (r^2(2)+r^2(6)=1) \\
 &= \frac{1}{2} \begin{pmatrix} 1 & 0 & 0 & 1 \\ 0 & 1 & -1 & 0 \\ 0 & -1 & 1 & 0 \\ 1 & 0 & 0 & 1 \end{pmatrix} + \frac{1}{2} \begin{pmatrix} -r(4) & r(4) & r(4) & r(4) \\ -r(4) & -r(4) & -r(4) & r(4) \\ -r(4) & -r(4) & -r(4) & r(4) \\ r(4) & -r(4) & -r(4) & -r(4) \end{pmatrix}
 \end{aligned}$$

Data Compression



27

- 
- Multiplying a vector by the first summand of the last expression above can be done with 2 adds (and/or subtractions) and 2 multiplications by $\frac{1}{2}$.
 - Multiplying a vector by the second summand can be done with 4 adds and 2 mults by $r(4)/2$.
 - These could then be combined with 4 adds.
- multiplying a vector by $G_2 \otimes G_2$ can be done with 10 adds, 2 mults, and 2 mults. by $\frac{1}{2}$.
- { as compared to 12 mults & 12 adds
in the direct row-column approach }
- Data Compression
- 

28

By the work of Feig and Winograd ([IE³ trans. SP-40. pp.2174-2193](#)), one obtains,

$$(G_2 \otimes G_2) = \begin{pmatrix} 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & -1 \\ -1 & 0 & 1 & 0 \end{pmatrix} \begin{pmatrix} \frac{-r(4)}{2} & \frac{r(4)}{2} & 0 & 0 \\ \frac{-r(4)}{2} & \frac{-r(4)}{2} & 0 & 0 \\ 0 & 0 & \frac{1}{2} & 0 \\ 0 & 0 & 0 & \frac{1}{2} \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & -1 \\ 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & -1 & 0 \end{pmatrix}$$

→ the product of a 4 vector by $G_2 \otimes G_2$ needs 2 mults., 10 adds, and 2 shifts.

Data Compression



29

$(G_2 \otimes G_4)$ will be changed to

$$D_{2,4} \stackrel{\text{def}}{=} \tilde{\rho}_4(V_2)(G_2 \otimes G_4)\tilde{\rho}_4(V_2)^{-1}$$

$$= \begin{bmatrix} -r(5) & -r(1) & r(3) & r(7) \\ -r(7) & -r(5) & -r(1) & r(3) \\ -r(3) & -r(7) & -r(5) & -r(1) \\ r(1) & -r(3) & -r(7) & -r(5) \end{bmatrix} \begin{bmatrix} r(1) & r(3) & r(7) & r(5) \\ -r(5) & r(1) & r(3) & r(7) \\ r(7) & -r(5) & r(1) & r(3) \\ -r(3) & -r(7) & -r(5) & -r(1) \end{bmatrix} \quad (16)$$

Data Compression



30

$(G_4 \otimes G_4)$ will be changed to

$$D_{4,4} \stackrel{\text{def}}{=} \tilde{\rho}(V_4)(G_4 \otimes G_4)\tilde{\rho}_4^{-1}(V_4) \\ = 2 \begin{pmatrix} H_1 & & & \\ & H_2 & & \\ & & H_3 & \\ & & & H_4 \end{pmatrix} \quad (17)$$

where $\tilde{\rho}_4$ is an **isomorphic mapping** and V_p is the **Vandermonde matrix**.

Data Compression



31

$$H_1 = \begin{pmatrix} 0 & -r(2) & 0 & r(6) \\ -r(6) & 0 & -r(2) & 0 \\ 0 & -r(6) & 0 & -r(2) \\ r(2) & 0 & -r(6) & 0 \end{pmatrix}$$

$$H_2 = \begin{pmatrix} 0 & r(4) & 0 & r(4) \\ -r(4) & 0 & r(4) & 0 \\ 0 & -r(4) & 0 & r(4) \\ -r(4) & 0 & -r(4) & 0 \end{pmatrix}$$

$$H_3 = \begin{pmatrix} -r(6) & 0 & r(2) & 0 \\ 0 & -r(6) & 0 & r(2) \\ -r(2) & 0 & -r(6) & 0 \\ 0 & -r(2) & 0 & -r(6) \end{pmatrix}$$

and $H_4 = I_4$

Data Compression



32

(16) \rightarrow the product by $G_2 \otimes G_4$ is equivalent to 2 products by G_4

(17) \rightarrow the product by $G_4 \otimes G_4$ is equivalent to a direct sum of 4 products by G_2 and 4 products by $r(4)$.

$$G_4 \otimes G_2 = P_s (G_2 \otimes G_4) P_s^{-1}$$

\rightarrow algorithmically equivalent

where P_s : perfect-shuffle permutation

$$G_2 \otimes G_2 = (2\tilde{\rho}_2(v_2))^{-1} \left(\frac{1}{2} D_{2,2} \right) \tilde{\rho}_2(v_2)$$

$$G_2 \otimes G_4 = (2\tilde{\rho}_4(v_2))^{-1} \left(\frac{1}{2} D_{2,4} \right) \tilde{\rho}_4(v_2)$$

$$G_4 \otimes G_4 = (4\tilde{\rho}_4(v_4))^{-1} \left(\frac{1}{4} D_{4,4} \right) \tilde{\rho}_4(v_4)$$

Data Compression



33

where

$$v_2 = \begin{pmatrix} 1 & i \\ 1 & -i \end{pmatrix} = \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ 0 & i \end{pmatrix}$$

$$v_4 = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 1 & 0 & 0 \\ 1 & -1 & 0 & 0 \\ 0 & 0 & 1 & 1 \\ 0 & 0 & 1 & -1 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & i \end{pmatrix}$$

$$\begin{pmatrix} 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & -1 & 0 \\ 0 & 1 & 0 & -1 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & w & 0 & 0 \\ 0 & 0 & w^2 & 0 \\ 0 & 0 & 0 & w^3 \end{pmatrix}$$

$$w = \exp\left(-j \frac{2\pi}{8}\right)$$

Data Compression



34

Altogether, the algorithm just described for the 8×8-point DCT will require 94 multiplications and 454 additions.

No. Times	Operator	Mults	Adds	Shifts	Total Mults	Total adds	Total shifts
4	$G_1 \otimes G_1$	0	0	1	0	0	4
4	$\sqrt{2}G_2$	3	3	0	12	12	0
4	$\sqrt{2}G_4$	8	12	0	32	48	0
1	$G_2 \otimes G_2$	2	10	2	2	10	2
2	$G_2 \otimes G_4$	16	40	0	32	80	0
1	$G_4 \otimes G_4$	16	80	0	16	80	0
	Pre-additions					224	
total					94	454	6


Data Compression



35

The Scaled DCT

In most applications, the DCT is followed by **scaling** and **quantization**.



Data Compression



36

Because of the scaling, we can instead of computing the DCT itself, compute rather a **scaled DCT**.

consider for example :

$$C_8 = P_8 D_8 R_{8,1} M_8 R_{8,2} \quad (18)$$

P_8 : the signed-permutation matrix

D_8 : the 8×8 diagonal matrix with elements :

$r(0), \frac{1}{2} r(6), \frac{1}{2} r(2), \frac{1}{2} r(5), \frac{1}{2} r(1), \frac{1}{2} r(3), \frac{1}{2} r(7)$

$$R_{8,1} = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & -1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 1 & -1 & 0 \\ 0 & 0 & 0 & 0 & -1 & 1 & 0 & 1 \\ 0 & 0 & 0 & 0 & -1 & -1 & -1 & 0 \\ 0 & 0 & 0 & 0 & 1 & -1 & 0 & 1 \end{bmatrix}$$

$(1 \ 1) \ -1 \ 0$
 $-(1 \ -1) \ 0 \ 1$
 $-(1 \ 1) \ -1 \ 0$
 $(1 \ -1) \ 1$

$1+1+6$
 $= 8 \text{ adds}$

Data Compression



37

$$M_8 = \begin{bmatrix} 1 & & & & & & & \\ & 1 & & & & & & \\ & & 1 & & & & & \\ & & & r(4) & & & & \\ & & & & r(4) & & & \\ & & & & & r(6) & r(2) & \\ & & & & & -r(2) & r(6) & \end{bmatrix}$$

$1+1+3=5 \text{ mults.}$
 3 adds

and

$$R_{8,2} = \tilde{B}_1 \tilde{B}_2 \tilde{B}_3 \rightarrow 4 \text{ adds}$$

8 adds

$$\tilde{B}_1 = \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ -1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & -1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 0 & -1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 1 & 0 & -1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 1 \end{bmatrix}$$


6 adds

Data Compression



38

Eqn.(18) suggests that we can compute the scaled DCT on 8 points by first computing the product by $R_{8,1} M_8 R_{8,2}$ and then **incorporating the factors $P_8 D_8$ into the scaling.**



→ Thus we can compute the scaled-DCT on 8-points with 5 mults. and 29 adds.

Data Compression



39

2-D scaled-DCT :

$$(P_8 D_8 R_{8,1} M_8 R_{8,2}) \otimes (P_8 D_8 R_{8,1} M_8 R_{8,2}) \\ = ((P_8 D_8) \otimes (P_8 D_8)) ((R_{8,1} M_8 R_{8,2}) \otimes (R_{8,1} M_8 R_{8,2}))$$

We can compute the 2-D scaled DCT on 8×8 points by first computing a product by

$$(R_{8,1} M_8 R_{8,2}) \otimes (R_{8,1} M_8 R_{8,2})$$

and then incorporating the product by

$$(P_8 D_8) \otimes (P_8 D_8)$$

into scaling. This again is so because

$$(P_8 D_8) \otimes (P_8 D_8) = (P_8 \otimes P_8) (D_8 \otimes D_8)$$

is a product of a diagonal matrix followed by a signed-permutation matrix.

Data Compression



40

$$(R_{8,1} M_8 R_{8,2}) \otimes (R_{8,1} M_8 R_{8,2})$$

$$= (R_{8,1} \otimes R_{8,1}) (M_8 \otimes M_8) (R_{8,2} \otimes R_{8,2})$$

$$R_{8,1} \otimes R_{8,1} : \text{post additions} = 2 \times 8 \times 8 = 128$$

$$R_{8,2} \otimes R_{8,2} : \text{pre-additions} = 2 \times 8 \times 18 = 288$$

(by row-column scheme)

The core of the 8×8 scaled DCT is the computation of the product by $M_8 \otimes M_8$, which can be done by using
(not in row-column fashion)

Data Compression



41

No. Times	Operator	Mults	Adds	Shifts	Total Mults	Total adds	Total shifts
16	1	0	0	0	0	0	0
16	G_1	1	0	0	16	0	0
8	G_2	3	3	0	24	24	0
4	$\sqrt{2}G_2$	3	3	0	12	12	0
4	$G_1 \otimes G_1$	0	0	1	0	0	4
1	$G_2 \otimes G_2$	2	10	2	2	10	2
Pro-additions						288	
Pre-additions						128	
total					54	462	6

Data Compression



42


Inverse DCT

C_8 is orthogonal, $C_8^{-1} = C_8^t$
 $C_8^{-1} = B^t K_8^t P_8^t$
 and $K_8^t = G_1 \oplus G_1 \oplus G_2^t \oplus G_4^t$

DCT v.s. DFT

DFT : K-point

$$F(u) = \sum_{x=0}^{K-1} S(x) W_K^{ux} \quad , \quad W_K = \exp\left(-j \frac{2\pi}{K}\right)$$

Data Compression 

43

Extend an N-point sequence $s(x)$, $x=0,1,\dots,N-1$,
 by defining another N points with symmetry about the
 point $(2N-1)/2$, i.e.,


$$s(x) = S(2N-x-1) \quad , \quad x=N, N+1, \dots, 2N-1 \quad (19)$$

Consider the 2N-point DFT of $s(x)$, $x=0,1,\dots,2N-1$

$$F'(u) = \sum_{x=0}^{N-1} S(x) W_{2N}^{ux} + \sum_{x=N}^{2N-1} S(2N-x-1) W_{2N}^{ux}$$

let $k=2N-x-1$, $x=N, N+1, \dots, 2N-1$

$$\begin{aligned} F'(u) &= \sum_{x=0}^{N-1} S(x) W_{2N}^{ux} + \sum_{k=0}^{N-1} S(k) W_{2N}^{u[2N-(k+1)]} \\ &= \sum_{x=0}^{N-1} S(x) W_{2N}^{ux} + \sum_{k=0}^{N-1} S(k) W_{2N}^{-u(k+1)} \end{aligned}$$

Data Compression 

44

replacing the index k by x and multiplying by $\frac{1}{2}W_{2N}^{\frac{u}{2}}$

$$\rightarrow \frac{1}{2}F(u)W_{2N}^{\frac{u}{2}} = \sum_{x=0}^{N-1} S(x) \cos\left[\frac{\pi(2x+1)u}{2N}\right] \quad (20)$$


→ The first N DFT coeffs., when multiplied by a complex scaling factor, give the N-point DCT coeffs.

Notice that, the right-hand side of Eqn.(20) is real, the left-hand side must also be real.

Denoting the real and imaginary part F(u) by A(u) and B(u) respectively,

$$F(u)W_{2N}^{\frac{u}{2}} = (A_u + jB_u) \cdot \left(\cos\left(\frac{\pi u}{2N}\right) - j \sin\left(\frac{\pi u}{2N}\right) \right) \quad (21)$$

Expanding the above equation into separate real and imaginary parts and setting the imaginary part to zero (the DCT is real),



Data Compression

45

we get :


$$B_u = A_u \frac{\sin\left(\frac{\pi u}{2N}\right)}{\cos\left(\frac{\pi u}{2N}\right)}$$

When this is substituted back into eqn.(21), it gives :

$$\begin{aligned} F(u)W_{2N}^{\frac{u}{2}} &= A_u \sec\left(\frac{\pi u}{2N}\right) \\ &= R_e(F(u)) \sec\left(\frac{\pi u}{2N}\right) \\ &\Rightarrow \sum_{x=0}^{N-1} S(x) \cos\left[\frac{\pi u(2x+1)}{2N}\right] \\ &= R_e[F(u)] \cdot \sec\left(\frac{\pi u}{2N}\right) \end{aligned}$$

→ The DCT coeffs. can be obtained by a simple N-point scaling of the real part of the DFT coeffs.

2N-point




Data Compression

46

The relationship between DFT and DCT, i.e. eqn.(20), explains why DCTs outperform DFTs in terms of energy compaction :

$$DCT_N \{x(n)\} = W_{2N}^{\frac{k}{2}} DFT_{2N} \{x_2(n)\}$$

where $x_2(n) = \{x(n), x(2N-1-n)\}$



Data Compression

