

Heavy Duty Sled Design for Rough Terrain Deployment

MLS3200 MINE SPEC SERIES

SLED MOUNTED LIGHTING TOWER

AUSTRALIAN DESIGNED & ENGINEERED

★ MDG15 ★ MDG41 ★ ELV 24VDC ★ AUSTRALIAN DESIGNED & ENGINEERED ★ 12 MONTH WARRANTY

665,600 lm	208 lm/W	60,000 hrs	11.2 m	10 × 320 W	5,830 kg	277 L	325 hrs
TOTAL LUMENS	LUMENS/WATT	LAMP LIFE	MAST HEIGHT	LED CONFIG	TARE WEIGHT	FUEL CAPACITY	RUNTIME

TECHNICAL SPECIFICATIONS

Dimensional & Physical		Electrical & Lighting	
DIMENSIONS (W×L×H)	2,500 × 5,800 × 3,200 mm	LIGHT TYPE	LED
WEIGHT (TARE)	5,830 kg	LED CONFIGURATION	10 × 320 W
SLED BASE	530mm Heavy Wall I Beams	INSTALLED WATTAGE	3,200 W
WEAR PACKAGE	20mm BIS80 Wear Packages to Bottom	TOTAL LUMENS	665,600 lm
DECK	6mm Heavy Duty Checker Plate	LUMENS PER WATT	208 lm/W
ACCESS STEPS	MDG15 Compliant, Max 400mm Step height	LAMP LIFE	60,000 hours
HANDRAILS	MDG15 Compliant All 4 Sides (Painted Yellow)	CONTROLLER	Smartgen ALC700
REFLECTIVE TAPE	50mm Yellow Sides, Red Front/Rear	SYSTEM VOLTAGE	ELV 24 VDC
TOW CHAIN	16mm Twin leg with Large Tow Ring	THERMAL CONTROL	Automatic Thermal Control
WIND RATING	100 km/h	COATING	Military/Aero Grade Titanium Based
PAINT PROCESS	3-Stage, E-coated & Baked 180°C	SOLDERING PROCESS	Military/Aero Grade
MATERIAL	Steel skid, Body 316L Stainless Steel	PCB	Copper PCB
FIRE EXTINGUISHER	2 x 9kg Dry Chemical Powder	ELECTRICAL CONTROL	Failsafe Light Switch PCB, Smart Brightness (No PWM)
Engine & Fuel		AUTO START/STOP	Standard
ENGINE	Kubota Z482-E, 2 Cylinder, 1650 RPM	LOW FUEL BEACON	Automatic Email @10%
ASPIRATION	Natural	MAST & STRUCTURE	
TIER	Tier IV — Australian Compliant	MAST TYPE	Hydraulic w/ Safety Valves
FUEL CAPACITY	277 L	MAST HEIGHT	11.2 m
FUEL CONSUMPTION	0.85 L/hr	ROTATION	340°
RUNTIME	325 Hours	HYDRAULIC MOTOR	2.2 kW, 12 V, Fan Cooled
FILL POINT	2 Inch Cam Lock (Wiggins Optional)	HYDRAULIC MANIFOLD	12 Volt 4 Station with Test Port
FILTERING	10 Micron on Return Circuit	BURST PROTECTION	MDG41 with Burst Sleeve
ENGINE PROTECTION	Twin Filtered Engine Oil, 2 Stage Air Filter	PIPES	CNC Stainless Bent Pipe
SERVICE INTERVAL	500 hours	SAFETY VALVES	Double Pilot Check on All Cylinders
Electrical System			
BATTERY	24 VDC		
GENERATOR	Brushless, 24 VDC		
Standards & Compliance			
STANDARDS	MDG15, MDG41		
WARRANTY	12 months / 1,500 hours		
Options			
WIGGINS QUICK FILL	Optional Fill Point		
CUSTOM FINISH	Custom Paint / Branding		
GPS MONITORING	Remote Tracking Available		
LONG RANGE FUEL TANK	325 L		