



German-Engineered Premium Architectural & Industrial LED Lighting

# DARK LIGHT

DLA (ARCHITECTURAL) • DLI (INDUSTRIAL)

IP67 • 160 lm/W • 3 YEAR WARRANTY

★ FULL CUT-OFF ASYMMETRIC OPTIC ★ MODULAR REFLECTOR ★ 5 CUTOFF ANGLES ★ CRI >80 ★ 3 YEAR WARRANTY

|                                   |                                         |                             |                                   |                                    |                                |
|-----------------------------------|-----------------------------------------|-----------------------------|-----------------------------------|------------------------------------|--------------------------------|
| <b>320-1,800 W</b><br>POWER RANGE | <b>51,000-288,000 lm</b><br>LUMEN RANGE | <b>160 lm/W</b><br>EFFICACY | <b>IP67</b><br>INGRESS PROTECTION | <b>196,000 hrs</b><br>SERVICE LIFE | <b>8 CCT</b><br>COLOUR OPTIONS |
|-----------------------------------|-----------------------------------------|-----------------------------|-----------------------------------|------------------------------------|--------------------------------|

## TECHNICAL SPECIFICATIONS

| ELECTRICAL        |                                                               |
|-------------------|---------------------------------------------------------------|
| WATTAGE RANGE     | 320W - 1,800W                                                 |
| LUMEN OUTPUT      | 51,000 - 288,000 lm                                           |
| LUMINOUS EFFICACY | Up to 160 lm/W                                                |
| INPUT VOLTAGE     | 100-277 VAC / 50-60 Hz                                        |
| CCT OPTIONS       | 1800K / 2200K / 2700K / 3000K / 4000K / 5000K / 5700K / 6500K |
| COLOUR RENDERING  | CRI >80                                                       |
| DRIVER OPTIONS    | Integral / Remote / Tray-Mounted                              |
| POWER FACTOR      | >0.95                                                         |
| DUAL COLOUR       | Available on request                                          |
| OPTICAL SYSTEM    |                                                               |
| OPTIC TYPE        | Full Cut-Off Asymmetric                                       |
| CUTOFF ANGLES     | 5 Angles: 63°-75°                                             |
| REFLECTOR SYSTEM  | Modular Reflector System                                      |
| DISTRIBUTION      | Type III / Type V                                             |
| GLARE CONTROL     | Full Cut-Off / Glare-Free                                     |

| MECHANICAL               |                              |
|--------------------------|------------------------------|
| CONSTRUCTION (DLA)       | Rounded Wedge, Architectural |
| CONSTRUCTION (DLI)       | Marine Grade Aluminium, IP67 |
| FINISH                   | High-Durability Powder Coat  |
| LENS                     | Toughened Safety Glass       |
| MOUNTING                 | Surface / Pole / Bracket     |
| ENVIRONMENTAL & LIFETIME |                              |
| INGRESS PROTECTION       | IP67 (Industrial)            |
| SERVICE LIFE             | Up to 196,000 hours          |
| AMBIENT TEMPERATURE      | -40°C to +85°C               |
| SURGE PROTECTION         | 10 kV / 10 kA                |
| CORROSION RESISTANCE     | Marine Grade (C5-M)          |
| WARRANTY                 | 3 Years                      |

| KEY FEATURES                                     |                                                   |
|--------------------------------------------------|---------------------------------------------------|
| ▶ Full cut-off asymmetric optic — zero uplight   | ▶ 5 adjustable cutoff angles (63°-75°)            |
| ▶ Modular reflector system for precise control   | ▶ 8 CCT options + dual colour on request          |
| ▶ Multiple driver options (integral/remote/tray) | ▶ DLA: Architectural wedge / DLI: IP67 Industrial |

| MODEL VARIANT MATRIX |         |            |           |             |           |
|----------------------|---------|------------|-----------|-------------|-----------|
| Model                | Wattage | Lumens     | Series    | CCT Options | IP Rating |
| DL1-320              | 320 W   | 51,000 lm  | DLA / DLI | 8 Options   | IP65/IP67 |
| DL1-400              | 400 W   | 64,000 lm  | DLA / DLI | 8 Options   | IP65/IP67 |
| DL1-600              | 600 W   | 96,000 lm  | DLA / DLI | 8 Options   | IP65/IP67 |
| DL2-800              | 800 W   | 128,000 lm | DLI       | 8 Options   | IP67      |
| DL2-1200             | 1,200 W | 192,000 lm | DLI       | 8 Options   | IP67      |
| DL3-1800             | 1,800 W | 288,000 lm | DLI       | 8 Options   | IP67      |