

Remotely Deploying, Visualizing and Controlling a Robot Swarm with ROS and Cloudmesh

MATTHEW LAWSON¹ AND GREGOR VON LASZEWSKI^{1,*}

¹ School of Informatics and Computing, Bloomington, IN 47408, U.S.A.

* Corresponding authors: laszewski@gmail.com

Project: S17-IO-3010, May 7, 2017

Working with robot swarms is one important research area of robotics. To educate the next generation experts we are in the need to simulate large such swarms as the cost to deploy them as real hardware may be prohibitive to a university with limited budget. Hence, we explore the the feasibility of simulating such swarms while harnessing remotely-located distributed computing environments to conduct such simulations. We are especially interested to reuse clouds to simulate large-scale robot swarms. For this reason we created a proof-of-concept that creates a two-robot swarm on multiple clouds we have access to. The important point is the the deployment is done automated and can be executed by non cloud experts so the environment is accessible and usable not only by advanced PhD students, but by freshmen and potentially even STEM students. The robots behaviour are streamed as a visual simulation the remote user. We demonstrate that users can start up the behavior of a robot through a single command allowing us to benchmark the activity streams of the swarm in tehe cloud. The project uses opensource software and utilizes Open Source Robotics Foundation (OSRF) to define, create and control the virtual robots with *Robot Operating System*. *Gazebo* provides the visualization of the simulation. To simplify the interaction with various clouds we use *cloudmesh*.

Keywords: Cloud, I524, ROS, Gazebo, Robot, Swarm

Report: <https://github.com/cloudmesh/sp17-i524/tree/master/project/S17-IO-3010/report/report.pdf>

Code: <https://github.com/cloudmesh/cloudmesh.ros>

1. INTRODUCTION

With the evolution of robotics and its increased influence in society we anticipate the need to deal with robot swarms. Thus, we need to educate the next generation of scientists by offering abilities to simulate a multitude and diverse set of robot swarms. Simulation allows safe interaction with the swarm while conducting actions and observing responses to its environment prior to real-world deployment to mitigates operational risk. Furthermore it allows to simulate such environments in a cost effective way that goes beyond the capabilities that are provided by a single workstation. The question we ask, would it be possible to simulate 10th of thousands of robots on a cloud environment?

However, deployment of an interconnected swarm of virtual robots in a cloud imposes additional requirements to the scientist researching such swarms. Thus we try to also evaluate if it is possible to bring down the barrier of managing such a *virtual swarm* not only for an individual researcher but for potential inclusion in class settings on the freshmen and the STEM level. Although cloud environments are available today accessing and configuring multiple computers presents a time and resource challenge in contrast to a single-host setup. In addition,

network security measures, such as ssh keys and port access, impede ROS' intra-cluster communication capabilities. These aspects are typically out of reach for such entry level educational communities. In order to address the unique requirements of a networked, remotely-located swarm, we create a multi-platform system to automate the creation and deployment of the virtual swarm with the help of cloudmesh [?].

2. VIRTUAL ROBOT SWARM COMPONENTS

2.1. Robot Operating System (ROS)

The Open Source Robotics Foundation's middleware product *Robot Operating System*, or ROS, provides a framework for writing operating systems for robots. ROS offers "a collection of tools, libraries, and conventions [meant to] simplify the task of creating complex and robust robot behavior across a wide variety of robotic platforms" [2]. The Open Source Robotics Foundation, hereinafter OSRF or the Foundation, attempts to meet the aforementioned objective by implementing ROS as a modular system. That is, ROS offers a core set of features, such as inter-process communication, that work with or without pre-existing, self-contained components for other tasks.




Fig. 2. Deployment Workflow for the Virtual Robot Swarm Project

2.6. Robots and Worlds

A ROS robot may be extremely simple, such as the pre-built talker and listener robots supplied in the ROS distribution, or as complex as the roboticist desires. If users desire to visualize the robot, s/he must define his / her ROS robot in *Universal Robot Description Format*. A ROS robot's specifications reside in a series of files with *xacro* extensions, referred to as URDF files. These files, which borrow XML's syntax structure, can include specifications for the basic shapes of the robot and its appendages (if applicable), e.g., rectangular box, cylinder, etc. with attached wheels, various kinds of joints, such as ones that rotate around an axis or extend along an axis, types and numbers of sensors, number of joints in an appendage, colors of the robot(s), etc., etc. In addition, any file in the robot description stack may reference an external file to complete the description of the robot. This capability allows the user to re-use code by incorporating previously-completed robot features into a new robot. Finally, simulations include a world file to provide the setting, or environment, in which the robot simulation occurs. As with the URDF files, the world file can be simple, like the *empty_world* file included in the ROS distribution or extremely complex.

Finally, a simulation package will include one or more *launch* files. These files coordinate the disparate aspects of the entire simulation package in a manner similar to that of Ansible's playbook file. According to the OSRF, best practices for robot simulation dictate that the main launch file consist of little more than calls to other launch files in the package [14]. Continuing with the playbook analogy, the launch files called from the main launch file would correspond to the roles defined in Ansible. This functionality significantly increases ROS' usability since managing even relatively straightforward robots, simulated or real, can prove unwieldy. For instance, this project, a proof-of-concept project, utilizes a *.world* file, four URDF files and four launch files in addition to the pre-compiled talker and listener robots.

This project uses two straightforward differential drive robots sourced from an online tutorial entitled *Simulating Robot Models in ROS (part 1)* [15]

3. VIRTUAL ROBOT SWARM PROJECT IMPLEMENTATION

3.1. VR Swarm task

Although the swarm accomplishes the seemingly-trivial task of driving in circles, the real accomplishment rests in proving the feasibility of automating the deployment of multiple controllable virtual robots on a remote cluster of computers and then visualizing them on a local computer.

3.2. Deployment

Achieving the aforementioned task requires coordinating a modestly-complex mix of shell commands, cloudmesh commands, Ansible commands and ROS / Gazebo commands. A shell script provides the automation for the shell, cloudmesh and ROS commands, while Ansible's *playbook* functionality handles the Ansible-focused portion. Only the initial step, retrieving and sourcing the shell script that begins the deployment process, requires user intervention. However, if the user wants to listen to the talker robot (*talker.py* and *listener.py*), s/he needs to follow the steps described in the README file.




Fig. 3. Example of a Complex Simulated Robot




Fig. 4. An Example of Two Simpler Robots

wget...begin - Retrieve the Initialization Bash Script Deployment begins when the user retrieves the initialization file, named *begin*, from the project's Github repository. The user then starts the execution sequence by sourcing the file with the command

```
> ./begin
```

from the directory where the *begin* bash script resides.

begin bash script The bash script calls three *cloudmesh_client* commands:

1. > *cm cluster define* -n *rosA1* -c 3
2. > *cm cluster allocate*
3. > *cm cluster cross_ssh*

These scripts create and prepare the three-node cluster named *rosA1*. We then use two additional *Cloudmesh* commands:

1. > *cm cluster nodes*
2. > *cm vm ip show*

to capture the public and private ip addresses of the cluster as well as the host names.

The ip addresses and names are written to separate files for distinct purposes. The host names and private ip addresses are used to create a file to append to each cluster node's *known_hosts* file. The private ip addresses also end up in a different file that serves as the basis for a custom Ansible inventory file.

The private ip addresses, termed static ips by Chameleon, must be used because ROS nodes communicate by binding to any available port. That is, ROS does not specify the port beforehand, and it does not consider whether or not the firewall blocks the port for security purposes. As a result, intra-cluster communication requires access to every port, i.e., the firewall cannot close any port on any computer running ROS when that computer needs to communicate with another computer in the cluster. Obviously, this presents a major security concern, especially on shared resources. Refer to the *Common Pitfalls* section below for the workaround used with this project.

As its penultimate step, the *begin* script places all the necessary files for the demonstration on the correct cluster nodes. The ROS robot files and the Ansible files go onto the main node, while the script places a copy of the *known_hosts* addendum onto each cluster node. In addition, the script uses the *wget* command to copy the bash script for the next step in the process onto the main node.

The final lines of the file initiate the next step in the process and perform a few administrative duties.

beginAgain bash script This script handles the software installation and initialization of the robots. It first establishes the veracity of the main node and the other nodes by connecting to each one in turn via ssh connection. If these steps do not occur before Ansible runs, the software installations never occur because Ansible hangs mid-process. Ansible installs all the necessary software on each cluster node. It installs Linux's *tree* package because the author prefers to use it to view directory structures; the ROS package; the *roshash* package; the *roinstall* package; and, the *catkin_tools* package. Ansible also creates a new *known_hosts* file for each computer node.

Upon completing the installation, the file's instructions initialize the robot workspace. The *catkin_tools* package accomplishes this on behalf of ROS. *catkin_tools* represents an evolution of ROS' built-in *catkin* family of commands. Initializing the robot workspace essentially involves the addition of numerous hidden helper files, which assist in building the robot package. Creating

the robot package, referred to as *building* the package, involves a series of automated *CMake* commands.

With the robot package built, the script copies another script from github. This small script starts ROS' *talker* robot, a simple robot included as part of ROS' tutorial packages. It relies upon Linux's *byobu* program to set up usable working environment if the user chooses to start the listener robot on the third cluster node.

Finally, execution of the last few lines of the script occurs. These lines start ROS, start the two robots, create a simulated world for the robots and then issue a command for the robots to drive in circles. Gazebo's simulation of the robots and their world come back through the ssh connection to the end user so s/he can see the simulation in real time.

talkListen bash script The *talkListen* script sets up a multiplexed terminal environment on the second node and starts ROS' *talker* robot, which ROS' maintainers include as a pre-built package with the distribution. It relies upon Linux's *byobu* terminal multiplexing program. Using a series of `> byobu -tmux ...` commands, it creates a terminal screen with three panels. ROS's *rosmaster* program starts in panel 1, while the *talker* program/robot/node starts in Panel 2. The final panel, panel 0, connects to the third node in the cluster in anticipation of the user starting the listener program (also included in the ROS distribution).

3.3. Common Pitfalls

Intra-Node Communication In order to maintain security and enable intra-cluster communication, two of the three computer nodes must have their public ip addresses removed, i.e., disassociated, using Chameleon's browser-based graphical user interface (GUI), Horizon. Then, and only then, the ports can be opened by applying the *ros* security group to the two nodes in question (the private nodes). Since the third node, the main node, still has a public-facing ip address, the other two nodes can be accessed via an ssh connection (*ssh'ing*) to the main node and then *ssh'ing* to one of the private nodes.

Deployment Problems Even if a script or a user completes each step correctly to set up a controllable virtual swarm on remotely-located resources, problems still occur that cause deployment failures. Usually, the issues can be resolved with manual intervention, so the deployment can be completed.

Adding the ROS Repository Key The deployment often goes awry during the Ansible script to retrieve the repository key for the ROS repo. When the key retrieval failed, the ROS software installation would also fail. Obviously, if the main node lacks ROS, the simulation will not launch either. As a workaround, the script adds the repository to each machine with the *deb [trusted=yes] ...* syntax. Using this method obviates the need for the repo key. Although it works, applying it to repos in general creates unnecessary risks. Therefore, it should be used sparingly.

Starting the Robot Simulation Receiving an error while starting the simulation occurred much more frequently during the development process than the key repo problem. ROS prints error messages in red to the console, so they stand out. The most common error: `[gazebo_gui-3] process has died`. Sometimes, an almost identical error occurs, `[gazebo-2] process has died`, while other times the launch program cannot find parts of the robot model. The latter error consists of one or both of the following: `Error [parser.cc:581] Unable to find uri[model://sun .` Unlike the

previously-described error, this one requires manual intervention. The user needs to enter the following commands at the terminal prompt:

1. `> killall roscore`
2. `> killall rosmaster`
3. `> killall gzclient`
4. `> killall gzserver`
5. `> source ~/.bashrc`
6. `> ./beginAgain`

Somewhat maddeningly, this process often needs to be completed twice before the simulation will start successfully. If the simulation still will not start, refer to the instructions in the *Initializing the Swarm* section.

3.4. Initializing the Swarm Manually

If needed the user can manually start the simulation with the commands listed below. You will need three terminals for the three commands, so ssh into the main node three times from three separate consoles or use *byobu* to split the terminal into three panes. The command

```
> roslaunch mybot_gazebo mybot_world.launch
```

starts the simulation. Entering

```
rostopic pub /robot1/cmd_vel geometry_msgs/Twist '{linear: {x: 0.2, y: 0.0, z: 0.0}, angular: {x: 0.0, y: 0.0, z: 0.1}}'
```

in a free terminal will command the first robot to begin turning in a circle. Likewise,

```
rostopic pub /robot1/cmd_vel geometry_msgs/Twist '{linear: {x: 0.2, y: 0.0, z: 0.0}, angular: {x: 0.0, y: 0.0, z: 0.1}}'
```

moves the second robot. Alternatively, one can delete the cluster and run the deployment script again.

4. VR SWARM PROJECT CONCLUSIONS

TBD; present the data collected in some visualization format; discuss why this project advances robotics forward by utilizing distributed computing;

5. SUPPLEMENTAL MATERIAL

REFERENCES

- [1] H. Boyer, "Open Source Robotics Foundation And The Robotics Fast Track," web page, nov 2015, accessed 19-mar-2017. [Online]. Available: <https://www.osrfoundation.org/wordpress2/wp-content/uploads/2015/11/rft-boyer.pdf>
- [2] Open Source Robotics Foundation, "About ROS," Web page, mar 2017, accessed 16-mar-2017. [Online]. Available: <http://www.ros.org/about-ros/>
- [3] National Instruments, "A Layered Approach to Designing Robot Software," Web page, mar 2017, accessed 18-mar-2017. [Online]. Available: <http://www.ni.com/white-paper/13929/en/>
- [4] Open Source Robotics Foundation, "Beginner: Overview: What is Gazebo?" Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: http://gazebosim.org/tutorials?cat=guided_b&tut=guided_b1
- [5] Open Dynamics Engine, "Open Dynamics Engine Wiki," Web page, feb 2017, accessed 30-apr-2017. [Online]. Available: https://www.ode-wiki.org/wiki/index.php?title=Main_Page
- [6] Real-Time Physics Simulation, "Bullet Physics Library: Real-Time Physic Simulation," Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: <http://bulletphysics.org/wordpress/>
- [7] P. E. Michael Sherman, "Simbody: Multibody Physics API," Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: <https://simtk.org/projects/simbody/>

```

cc@eunosm3-367 (192.168.0.214) - byobu
File Edit Tabs Help

* Management: https://landscape.canonical.com
* Support: https://ubuntu.com/advantage

Get cloud support with Ubuntu Advantage Cloud Guest:
http://www.ubuntu.com/business/services/cloud

53 packages can be updated.
27 updates are security updates.

Last login: Sat May 6 04:41:16 2017 from 192.168.0.215
export ROS_MASTER_URI=http://192.168.0.214:11311
cc@eunosm3-368:~$ export ROS_MASTER_URI=http://192.168.0.214:11311
cc@eunosm3-368:~$

PARAMETERS
* /roscistro: kinetic
* /rosversion: 1.12.7
NODES
auto-starting new master
process[master]: started with pid [28662]
ROS_MASTER_URI=http://eunosm3-367:11311/

setting /run_id to a709fb18-3216-11e7-ac43-fa163ec
96acc
process[rosout-1]: started with pid [28751]
started core service [/rosout]

[INFO] [1494046003.522244]: hello world 1494046003.
52
[INFO] [1494046003.622244]: hello world 1494046003.
62
[INFO] [1494046003.722242]: hello world 1494046003.
72
[INFO] [1494046003.822246]: hello world 1494046003.
82
[INFO] [1494046003.922193]: hello world 1494046003.
92
[INFO] [1494046004.022249]: hello world 1494046004.
02
[INFO] [1494046004.122244]: hello world 1494046004.
12

u[1A] 16.04 0:ssh* 53!! 85m 0.00 4x2.36Hz 7.867% 2017-05-06 04:46:43

```

Fig. 5. The Multiplexed Talk-Listen Terminal

- [8] Georgia Tech and Carnegie Mellon University, "DART: Dynamic Animation and Robotics Toolkit," Web page, mar 2017, accessed 30-apr-2017. [Online]. Available: <http://dartsim.github.io>
- [9] Torus Knot Software Ltd, "OGRE3D," Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: <http://www.ogre3d.org>
- [10] Torus Knot Software Ltd, "OGRE: About," Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: <http://www.ogre3d.org/about>
- [11] Open Source Robotics Foundation, "gazebo-ros-pkgs: Package Summary," Web page, aug 2016, accessed 30-apr-2017. [Online]. Available: <http://wiki.ros.org/gazebo-ros-pkgs>
- [12] Red Hat, Inc., "redhat," Web page, apr 2017, accessed 30-04-2017. [Online]. Available: <https://www.redhat.com/en>
- [13] G. Laszewski, von, "Cloudmesh Client Toolkit," Web page, apr 2017, accessed 30-apr-2017. [Online]. Available: <http://cloudmesh.github.io/client/>
- [14] Open Source Robotics Foundation, "Roslaunch tips for large projects," Web page, nov 2012, accessed 05-may-2017. [Online]. Available: <https://goo.gl/3xBx0t>
- [15] moorerobots.com, "Simulating Robot Models with ROS (part 1)," Web page, sep 2016, accessed 15-apr-2017. [Online]. Available: <http://moorerobots.com/blog/post/1>

AUTHOR BIOGRAPHIES

Matthew Lawson received his BSBA, Finance in 1999 from the University of Tennessee, Knoxville. His research interests include data analysis, visualization and behavioral finance.

Matthew Lawson. Designed the project in collaboration w/ Gregor von Laszewski, researched the material and implemented the project. Slept far too little.

Gregor von Laszewski. Provided invaluable insights at key points during the process.