Vis.	Time(sec)	Last Device	At Device
	0.557	--	Switch0(1)
	0.558	Switch0(1)	PC2(1)
	0.558	Switch0(1)	PC1(1)
	0.558	Switch0(1)	Switch0
	0.559	Switch0	PC2
	0.559	Switch0	PC1
	0.559	Switch0	PC0
	0.984	--	Switch0(1)
	0.985	Switch0(1)	Switch0
	0.985	--	Switch0(1)
	0.986	Switch0(1)	Switch0
	1.554	--	Switch0(1)
	1.555	Switch0(1)	Laptop1(1)
	1.555	Switch0(1)	Laptop2(1)
	1.555	Switch0(1)	Switch0
	1.556	Switch0	Laptop0
	1.556	Switch0	Laptop1
	1.556	Switch0	Laptop2
	2.001	--	Switch0(1)
	2.002	Switch0(1)	Switch0

Physical   Config   CLI   Attributes

IOS Command Line Interface

```
Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#int gig0/1
Switch(config-if)#switchport mode trunk
Switch(config-if)#switchport trunk allowed vlan 2?
WORD
Switch(config-if)#switchport trunk allowed vlan 2,3
Switch(config-if)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show vlan

VLAN Name                             Status    Ports
---- -------------------------------- --------- -------------------------------
1    default                          active    Fa0/5, Fa0/6, Fa0/7, Fa0/8
                                                Fa0/9, Fa0/10, Fa0/11, Fa0/12
                                                Fa0/13, Fa0/14, Fa0/15, Fa0/16
                                                Fa0/17, Fa0/18, Fa0/19, Fa0/20
                                                Fa0/21, Fa0/22, Fa0/23, Fa0/24
                                                Gig0/1
2    programmer                       active    Fa0/1, Fa0/2
3    buhg                             active    Fa0/3, Fa0/4
4    director                         active
1002 fddi-default                     active
1003 token-ring-default               active
1004 fddinet-default                  active
1005 trnet-default                    active


VLAN Type  SAID       MTU   Parent RingNo BridgeNo Stp  BrdgMode Trans1 Trans2
---- ----- ---------- ----- ------ ------ -------- ---- -------- ------ ------
```