

# **ICPC Workshop 1**

## Graph Theory

**Isaiah Iliffe and Angus Ritossa**

# Table of contents

## **1 Problem: Internet**

- Statement
- Solution

## **2 Problem: Two Colouring**

- Statement
- Solution

## **3 Problem: Cards**

- Statement
- Solution

## **4 Lab: work on vjudge set**

# Internet: Statement

There are  $N$  houses in a town, labelled from 1 to  $N$ .

$M$  specified pairs of houses have a cable between them.

Which houses are connected by some sequence of cables to house 1?

# Internet: Statement

There are  $N$  houses in a town, labelled from 1 to  $N$ .

$M$  specified pairs of houses have a cable between them.

Which houses are connected by some sequence of cables to house 1?

## Sample Input

```
9 8
1 2
1 5
2 5
5 4
4 3
2 3
4 6
7 8
```

# Internet: Statement

There are  $N$  houses in a town, labelled from 1 to  $N$ .

$M$  specified pairs of houses have a cable between them.

Which houses are connected by some sequence of cables to house 1?

## Sample Input

9 8  
1 2  
1 5  
2 5  
5 4  
4 3  
2 3  
4 6  
7 8

## Sample Output

1  
2  
3  
4  
5  
6

## Constraints

$N, M \leq 200000$

# Internet: Statement

There are  $N$  houses in a town, labelled from 1 to  $N$ .

$M$  specified pairs of houses have a cable between them.

Which houses are connected by some sequence of cables to house 1?

## Sample Input

```
9 8
1 2
1 5
2 5
5 4
4 3
2 3
4 6
7 8
```


## Sample Output

```
1
2
3
4
5
6
```

## Constraints

$N, M \leq 200000$

## Diagram



# Representing graphs

- A graph is an abstraction of the town, as simply a set of objects in which some pairs of the objects are in some sense “related”

# Representing graphs

- A graph is an abstraction of the town, as simply a set of objects in which some pairs of the objects are in some sense “related”
- Houses correspond to **nodes** and cables correspond to **edges**
- How can we represent a graph mathematically? Computationally?



# Representing graphs

- A graph is an abstraction of the town, as simply a set of objects in which some pairs of the objects are in some sense “related”
- Houses correspond to **nodes** and cables correspond to **edges**
- How can we represent a graph mathematically? Computationally?
- Adjacency list
  - For each node, store a list (vector in C++) of adjacent nodes
  - Implementation: see code

# Depth-first search


- To “process” a node, just “process” each of its neighbours
- But never “process” a node more than once
- Implementation: see code

## Theorem (Fundamental Theorem of DFS)

*A DFS initiated at a node  $u$  will process a node  $v$  exactly when there exists a path between  $u$  and  $v$ .*

- So our problem can be solved by running a DFS from node 1, then checking which nodes have been processed. We'll come back to how exactly to code a solution up and submit it.

# DFS Walkthrough



# Two Colouring: Statement

You are given a graph with  $N$  nodes and  $M$  edges.

# Two Colouring: Statement

You are given a graph with  $N$  nodes and  $M$  edges.

Can you colour each node either black or white, such that any two connected nodes are of different colour?

# Two Colouring: Statement

You are given a graph with  $N$  nodes and  $M$  edges.

Can you colour each node either black or white, such that any two connected nodes are of different colour? (In other words, is the graph bipartite?)

If yes, output a possible allocation of colours for each node.


# Two Colouring: Statement

You are given a graph with  $N$  nodes and  $M$  edges.

Can you colour each node either black or white, such that any two connected nodes are of different colour? (In other words, is the graph bipartite?)

If yes, output a possible allocation of colours for each node.

## Example



# Two Colouring: Solution

- Modify the DFS algorithm so each node gets a colour, and all nodes seen so far satisfy the different colour criterion



# Two Colouring: Solution

- Modify the DFS algorithm so each node gets a colour, and all nodes seen so far satisfy the different colour criterion
- If there is ever a contradiction in what colour a node should be, say NO

# Two Colouring: Solution

- Modify the DFS algorithm so each node gets a colour, and all nodes seen so far satisfy the different colour criterion
- If there is ever a contradiction in what colour a node should be, say NO
- Otherwise, output the final colour of each node.

# Two Colouring: Solution

- Modify the DFS algorithm so each node gets a colour, and all nodes seen so far satisfy the different colour criterion
- If there is ever a contradiction in what colour a node should be, say NO
- Otherwise, output the final colour of each node.
- What if not everything is connected, though?

# Two Colouring: Solution

- Modify the DFS algorithm so each node gets a colour, and all nodes seen so far satisfy the different colour criterion
- If there is ever a contradiction in what colour a node should be, say NO
- Otherwise, output the final colour of each node.
- What if not everything is connected, though?
- Implementation: see code

# Cards: Statement

There are  $N$  cards.

The  $i$ -th card has the colour  $a[i]$  on one side, and the colour  $b[i]$  on the other side.

What is the maximum number of colours you can see at once?

# Cards: Statement

There are  $N$  cards.

The  $i$ -th card has the colour  $a[i]$  on one side, and the colour  $b[i]$  on the other side.

What is the maximum number of colours you can see at once?

## Sample Input

4

1 2

1 3

4 2

2 3

## Sample Output

4

## Constraints

$N, M \leq 200000$

# Cards: Statement

There are  $N$  cards.

The  $i$ -th card has the colour  $a[i]$  on one side, and the colour  $b[i]$  on the other side.

What is the maximum number of colours you can see at once?

## Sample Input

4

1 2

1 3

4 2

2 3

## Sample Output

4

## Constraints

$N, M \leq 200000$

## Thinking time

# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?



# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?
- Observations after trying stuff on paper
  - Each component (set of nodes reached by one DFS) can be dealt with independently

# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?
- Observations after trying stuff on paper
  - Each component (set of nodes reached by one DFS) can be dealt with independently
  - If there are no cycles in a component, we can activate every node but one. Why?

# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?
- Observations after trying stuff on paper
  - Each component (set of nodes reached by one DFS) can be dealt with independently
  - If there are no cycles in a component, we can activate every node but one. Why?
  - If there is a cycle, it allows us to activate everything. Why?

# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?
- Observations after trying stuff on paper
  - Each component (set of nodes reached by one DFS) can be dealt with independently
  - If there are no cycles in a component, we can activate every node but one. Why?
  - If there is a cycle, it allows us to activate everything. Why?
- So our problem can be solved by finding each component (using DFS), and for each component, determining whether or not there is a cycle (within our DFS, or otherwise).

# Cards: Solution

- Reframe in terms of a graph
  - You are given a graph
  - You must choose a node at one end of each edge to be activated
  - What is the maximum number of distinct activated nodes?
- Observations after trying stuff on paper
  - Each component (set of nodes reached by one DFS) can be dealt with independently
  - If there are no cycles in a component, we can activate every node but one. Why?
  - If there is a cycle, it allows us to activate everything. Why?
- So our problem can be solved by finding each component (using DFS), and for each component, determining whether or not there is a cycle (within our DFS, or otherwise).
- Implementation

# Lab

- Join the vjudge group: <https://vjudge.net/group/unswicpc>
- Go to the contest for this workshop
- If you need help, or don't know what to do, message me or Angus
- **A: A+B** — solve this first if you haven't used vjudge before
- **B: Internet** — implement the first problem from today
- **C: Cards** — implement the third problem from today
- **D: Paradox** — second problem from today (two colouring), but a bit harder
- **E: Maze** and **F: Graph** — harder problems
- Angus will go over Graph at 1:40