


1 | 2








-NOTE-


- 1. This product is enable to mount both USB-IF Recommended PCB pattern botton of soldering terminals
- 2. Coplanarity: The dimension between flat tool and when connector put on the flat tool like PCB Signal Contact ter' solder tail: Max 0.08 mm Metal tab : Max 0.1mm
- 3. Product numbering: 10103592 - 0001 LF











Material

Thermoplastic

Coppper alloy

Sustainess steel

Sustainess steel

1 | 2

Part Name

Housing

Plate

Shield

Contact Ter

2

3



DETAIL "A"

Remarks

Finish

Black

Au over Ni

Sn over Ni

RECOMMENDED PCB Pattern

(Tolerance: ± 0.05)

CUSTOMER

COPY

	Α	T10-0002 J.H		J.H	1/7	/10	linea	r 🗌	E XX.		± 0.25		projection		title										
									.XX	(X ±	0.1	0	4	7 -	1						D/D		·		
							angle	es	0° ±2°					$\oplus \circlearrowleft$		MICRO-USB B-TYPE REVERSE									
						dr	JASC	ASON HSU		1/7	1/7/10		ММ		product family USB							code			
							engr	gr JASON HSU		1/7	/10			-	size	dwg no						TWN			
							chr	GARY HSIEH			1/7/10		scale			Δ4	10103592						sheet		
							appd	JOSE	DSEPH HSIA		1/7/10		NA		M44	10103392						1 of 1			
	sheet		revisi	ion	Α																				В
	inde	index		sheet																					D
3 cage code													4												

strictly reserved. Reproduction on issue to third parties in any tever is not permitted without written authority from the proprietor, of FCI. Copyright FCI.

ACAD

dr

date

PDM: Rev:A

tolerances unless

otherwise specified

 $.X \pm 0.38$

STATUS: Released Printed: Jun 02, 2010 -

www.fciconnect.com

mat'l. code

Itr ecn no