Programs and courses

👤 Damon Anthony Toumbourou   2 ▾

🏠   Online Tests   **Review Test Submission: Online Quiz 5 (based on lectures 9 and 10)**

Review Test Submission: Online Quiz 5 (based on lectures 9 and 10)

User	Damon Anthony Toumbourou
Course	Web Database Applications
Test	Online Quiz 5 (based on lectures 9 and 10)
Started	04/10/17 21:43
Submitted	04/10/17 21:47
Due Date	08/10/17 00:00
Status	Completed
Attempt Score	9 out of 20 points
Time Elapsed	3 minutes out of 1 hour
Results Displayed	All Answers, Correct Answers

Question 1

1 out of 1 points

While using react router, one must wrap the main app inside _____ tags.

Answers:
1. BrowserRoutes
✅ 2. BrowserRouter
3. BrowserRoute
4. BrowserRoute

Question 2

0 out of 1 points

In order to pass data from one sibling to another, one must use _____.

Answers:
✅ 1. props, callback and state
2. props
3. callback and state
4. state

Question 3

1 out of 1 points

The following command will install the react router packages and update the package.json file

Answers: 1. npm install react-router react-router-dom

2. npm install react-router react-router-dom -- g

✅ 3. npm install react-router react-router-dom -- save

4. npm install react-router react-router-dom --file= package.json

Question 4

0 out of 1 points

In react, form components are known as _____ components.

Answers: 1. input

✅ 2. controlled

3. uncontrolled

4. mixed

Question 5

1 out of 1 points

Using a local MongoDB instance with React involves writing code using _____ stack.

Answers: 1. MEAN

✅ 2. MERN

3. MEN

4. MEDIAN

Question 6

1 out of 1 points

MongoDb is a _____ database.

Answers: 1. RDBMS

2. semi-RDBMS

✅ 3. document-oriented

4. OORDBMS

Question 7

1 out of 1 points

_____ is Google's cloud hosted database.

Answers: ✅ 1. Firebase

2. Parse

3. Bluemix

4. Stormpath

Question 8

0 out of 1 points

Bootstrap comes in-built with PhpStorm's React project template.

Answers: 1. TRUE

✅ 2. FALSE

Question 9

0 out of 1 points

In react router, the _____ element will iterate over its children elements (the routes) and only render the first one that matches the current pathname.

Answers: 1. switcher

2. iterator

3. enumerator

✅ 4. switch

Question 10

0 out of 1 points

To write an uncontrolled component, instead of writing an event handler for every state update, you can use _____ keyword to get form values from the DOM.

Answers: 1. reference

✅ 2. ref

3. valueof

4. uncontrolled

Question 11

0 out of 1 points

In Google's cloud database- Firebase, the data is saved in _____ format.

Answers: 1. json

2. text

✅ 3. xml

4. byte

Question 12

0 out of 1 points

React _____ pattern makes use of *dispatchers* and *stores*.

Answers: 1. MVC

2. Redact

3. MVVC

✅ 4. Flux

Question 13

1 out of 1 points

While using React with a non-react library, it is best to use _____ component(s).

Answers: ✅ 1. uncontrolled

2. mixed

3. controlled

4. input

Question 14

1 out of 1 points

While transferring data from parent to child component, use _____.

Answers: 1. ref

✅ 2. props

3. callbacks and state

4. state

Question 15

0 out of 1 points

In a react web application, _____ can be used to implement animation for a stateless (*simple*) component.

Answers: 1. CSS webkit

2. Animation 3d library

✅ 3. CSS3 transitions

4. HTML5 animations

Question 16

0 out of 1 points

_____ is loosely based on Flux.

Answers:
1. MVC

2. MVVC

3. Redact

✅ 4. Redux

Question 17

0 out of 1 points

With a controlled component, every state change will have an associated handler function.

Is the above statement TRUE of FALSE?

Answers:
✅ 1. TRUE

2. FALSE

Question 18

1 out of 1 points

_____ is a collection of navigational components that compose declaratively with your application

Answers:
1. nav path

✅ 2. react router

3. router-react

4. router

Question 19

0 out of 1 points

_____ can be used to implement animation with a component that undergoes change in state.

Answers:
1. CSS transitions

2. HTML5 animations

3. Webkit library

✅ 4. ReactTransitionGroup

Question 20   1 out of 1 points

While transferring data from a child to parent component, use _____.

Answers: ✓ 1. callbacks and state

2. state

3. props

4. ref

Wednesday, 4 October 2017 21:47:09 o'clock AEDT

← **OK**