


Code Generation

TEACHING ASSISTANT: DAVID TRABISH

Code Generation



MIPS Architecture

- MIPS has 32 registers:
 - t0, ..., t9
 - general purpose
 - a0, a1, a2, a3
 - arguments (in some compilers)
 - v0, v1
 - return value, system calls
 - sp, fp
 - stack pointer, frame pointer
 - ra
 - return address

MIPS Architecture

- Labels

```
data_label_1: .word 17
```

```
data_label_2: .asciiz "abc"
```

```
code_label:
```

```
li $t0, 3
```

```
...
```

MIPS Architecture

- Basic assignments

```
li $t0, 3  
move $t1, $t2
```

MIPS Architecture

- Arithmetic instructions operate on registers and constants:
 - add, sub, mul, div, and, or, xor, ...

```
add $t2, $t0, $t1  
mul $t3, t1, 7
```

MIPS Architecture

- Read from memory:

```
lw $t0, 4($t1)
```

```
lw $t0, label
```

```
lw $t0, label+4
```

```
lw $t0, label+8($t1)
```

MIPS Architecture

- Write to memory:

```
sw $t0,2($t1)
```

```
sw $t0,label
```

```
sw $t0,label+4
```

```
sw $t0,label+8($t1)
```


MIPS Architecture

- Branches and Jumps:

```
beq $t1, $t2, label  
bne $t1, 7, label  
j label  
jal label  
jalr $t1
```

MIPS Architecture

- System calls:
 - Syscall number passed via v0
 - Arguments are passed via a0, a1, a2, a3
- For example, calling **PrintInt(3)**:

```
li $v0, 1
li $a0, 3
syscall
```

SPIM

```
.data  
g_foo: .word 17  
g_str: .asciiz "hello"  
...
```

} global data

```
.text  
{ li $v0, 1  
  lw $a0, g_foo  
  syscall  
{ li $v0, 4  
  la $a0, g_str  
  syscall
```

} code

SPIM

```
.data
g_foo: .word 17
g_str: .asciiz "hello"
...
```

} global data


```
PrintInt(17) {
PrintStr("hello") {
    .text
    li $v0, 1
    lw $a0, g_foo
    syscall
    li $v0, 4
    la $a0, g_str
    syscall
}
```

} code

SPIM

- Running SPIM:
 - `spim -f input_file`
- Interactive debugging:
 - `xspim`
- Tutorials:
 - <https://courses.cs.washington.edu/courses/cse410/08sp/notes/spim/SpimTutorial.pdf>
 - https://web.stanford.edu/class/cs143/materials/SPIM_Manual.pdf

Stack




Stack

```
int f(int x, int y) {  
    int z = x + y;  
    return z;  
}  
int g() {  
    int x = f(10, 20)  
}
```

```
f:  
subu $sp, $sp, 4  
sw $ra, 0($sp)  
subu $sp, $sp, 4  
sw $fp, 0($sp)  
move $fp, $sp  
subu $sp, $sp, 16  
lw $t0, 8($fp)  
lw $t1, 12($fp)  
add $t2, $t0, $t1  
sw $t2, -4($fp)  
lw $v0, -4($fp)  
move $sp, $fp  
lw $fp, 0($sp)  
lw $ra, 4($sp)  
addu $sp, $sp, 8  
jr $ra
```

```
g:  
...  
li $t0, 20  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
li $t0, 10  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
jal f  
addu $sp, $sp, 8  
move $t0, $v0  
...
```

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```



Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack



f:

subu \$sp, \$sp, 4

sw \$ra, 0(\$sp)

subu \$sp, \$sp, 4

sw \$fp, 0(\$sp)

move \$fp, \$sp

subu \$sp, \$sp, 16

lw \$t0, 8(\$fp)

lw \$t1, 12(\$fp)

add \$t2, \$t0, \$t1

sw \$t2, -4(\$fp)

lw \$v0, -4(\$fp)

move \$sp, \$fp

lw \$fp, 0(\$sp)

lw \$ra, 4(\$sp)

addu \$sp, \$sp, 8

jr \$ra

g:

...

li \$t0, 20

subu \$sp, \$sp, 4

sw \$t0, 0(\$sp)

li \$t0, 10

subu \$sp, \$sp, 4

sw \$t0, 0(\$sp)


jal f

addu \$sp, \$sp, 8

move \$t0, \$v0

...

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack



prologue


```
f:
    subu $sp, $sp, 4
    sw $ra, 0($sp)
    subu $sp, $sp, 4
    sw $fp, 0($sp)
    move $fp, $sp
    subu $sp, $sp, 16
    lw $t0, 8($fp)
    lw $t1, 12($fp)
    add $t2, $t0, $t1
    sw $t2, -4($fp)
    lw $v0, -4($fp)
    move $sp, $fp
    lw $fp, 0($sp)
    lw $ra, 4($sp)
    addu $sp, $sp, 8
    jr $ra
```

```
g:
    ...
    li $t0, 20
    subu $sp, $sp, 4
    sw $t0, 0($sp)
    li $t0, 10
    subu $sp, $sp, 4
    sw $t0, 0($sp)
    jal f
    addu $sp, $sp, 8
    move $t0, $v0
    ...
```

sp →

← fp


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



```
f:
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

```
g:
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack



f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
```


move \$sp, \$fp

```
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack



f:


```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
```

jr \$ra

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```


Stack



f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
```


epilogue {

```
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:

```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Stack



f:


```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
subu $sp, $sp, 16
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -4($fp)
lw $v0, -4($fp)
move $sp, $fp
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

g:


```
...
li $t0, 20
subu $sp, $sp, 4
sw $t0, 0($sp)
li $t0, 10
subu $sp, $sp, 4
sw $t0, 0($sp)
jal f
addu $sp, $sp, 8
move $t0, $v0
...
```

Register Backup

- Called functions may modify registers
- Backup at the **prologue**
- Restore at the **epilogue**



Register Backup: Prologue




f:

```
subu $sp, $sp, 4
sw $ra, 0($sp)
subu $sp, $sp, 4
sw $fp, 0($sp)
move $fp, $sp
```

backup {

```
subu $sp, $sp, 4
sw $t0, 0($sp)
...
subu $sp, $sp, 4
sw $t9, 0($sp)
subu $sp, $sp, 16
```

Register Backup: Epilogue




```
f:
...

move $sp, $fp
lw $t0, -4($sp)
...
lw $t9, -40($sp)
lw $fp, 0($sp)
lw $ra, 4($sp)
addu $sp, $sp, 8
jr $ra
```

restore {

Register Backup




```
f:
...
lw $t0, 8($fp)
lw $t1, 12($fp)
add $t2, $t0, $t1
sw $t2, -44($fp)
lw $v0, -44($fp)
...
```

Translating IR to MIPS

- Our IR is likely to use too many registers
- Assume for now, that the number of IR registers is reduced
 - Every **IR register** mapped to a **CPU register** (t0, ... t9)
- We will see later how to compute this **register allocation**

Translating IR to MIPS


- Translate global variable initializations
- Translate the IR instructions for each function
 - Implement a translation function for each IR instruction
 - If the translation requires additional registers:
 - Use registers s0, s1, ...



Translating IR

- Assignments (constant)

`t1 = c`




`li $t1, c`

Translating IR

- Assignments (read from memory)
- For local variables and parameters:


t1 = x



lw \$t1, off(\$fp)

Translating IR


- Assignments (read from memory)
- For local variables and parameters:



Translating IR

- Assignments (write to memory)
- For local variables and parameters:

x = t1




sw \$t1, off(\$fp)

Translating IR

- Global initializations (integers)

```
int g_1 = 7;
```




```
.data:  
g_1: .word 7
```

Translating IR

- Assignments (read from memory)
- For global variables:

`t1 = g_var`




```
g_var: .word 17
...
lw $t1, g_var
```

Translating IR

- Assignments (write to memory)
- For global variables:

`g_var = t1`




```
g_var: .word 17
...
sw $t1, g_var
```


Translating IR

- Arithmetic operation

```
t0 = add t1, t2
```




```
add $t0, $t1, $t2
```

Translating IR

- Arithmetic operation

`t0 = add t1, t2`




```
add $t0, $t1, $t2
ble $t0, max, end
li $t0, max
end:
# more checks...
```

Translating IR

- Branch

```
beq t1, t2, label
```




```
beq $t1, $t2, label
```

Translating IR

- Function call

```
t0 = call f(t1, t2)
```




```
subu $sp, $sp, 4  
sw $t2, 0($sp)  
subu $sp, $sp, 4  
sw $t1, 0($sp)  
jal f  
addu $sp, $sp, 8  
move $t0, $v0
```

Translating IR

- Return (in a function f)
- Store result in **v0** and jump to f's **epilogue label** (f_epilogue)

return t1



```
move $v0, $t1  
j f_epilogue
```

Translating IR

```
int g = 70;  
int f(int x) {  
    int z = x;  
    if (z) {  
        z = g  
    }  
    return z;  
}
```

```
f:  
t1 = x  
z = t1  
t2 = z  
beq t2, 0, end  
t3 = g  
z = t3  
end:  
t4 = z  
return t4
```

Translating IR

```
.data  
g: .word 70
```

```
int g = 70;  
int f(int x) {  
    int z = x;  
    if (z) {  
        z = g  
    }  
    return z;  
}
```

```
f:  
t1 = x  
z = t1  
t2 = z  
beq t2, 0, end  
t3 = g  
z = t3  
end:  
t4 = z  
return t4
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
```


Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw t2, -44($fp)
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
sw $t3, -44($fp)
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
sw $t3, -44($fp)
end:
```


Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g;
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
sw $t3, -44($fp)
end:
lw $t4, -44($fp)
```

Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g;
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
sw $t3, -44($fp)
end:
lw $t4, -44($fp)
move $v0, $t4
j f_epilogue
```


Translating IR

```
int g = 70;
int f(int x) {
    int z = x;
    if (z) {
        z = g
    }
    return z;
}
```

```
f:
t1 = x
z = t1
t2 = z
beq t2, 0, end
t3 = g
z = t3
end:
t4 = z
return t4
```

```
.data
g: .word 70
.text
f:
# prologue here
...
lw $t1, 8($fp)
sw $t1, -44($fp)
lw $t2, -44($fp)
beq $t2, 0, end
lw $t3, g
sw $t3, -44($fp)
end:
lw $t4, -44($fp)
move $v0, $t4
j f_epilogue
f_epilogue:
# epilogue here
...
```


Calling *main*



Strings

- We use null terminated strings
- Every character is one byte


```
string s1 = "1234";  
string s2 = "a";  
...  
...
```



Strings

- Constant assignment

`t0 = "1234"`



`la $t0, str_const`



goes to **code section**

.data

`str_const: .asciiz "1234"`



must be defined in **data section**

Strings

- Global variable initialization

```
string z := "1234";
```

```
.data  
z_str: .asciiz "1234"  
z: .word z_str
```

Strings

- Assume that *s1* and *s2* are strings

```
if (s1 == s2) {  
    ...  
}
```

```
t1 = s1;  
t2 = s2;  
t3 = str_eq t1, t2  
beq t3, 0, label  
...
```


Strings

- Inline string comparison

```
t1 = s1;  
t2 = s2;  
t3 = str_eq t1, t2  
beq t3, 0, label  
...
```

```
li $t3, 1 // result  
move $s0, $t1  
move $s1, $t2  
str_eq_loop:  
lb $s2, 0($s0)  
lb $s3, 0($s1)  
bne $s2, $s3, neq_label  
beq $s2, 0, str_eq_end  
addu $s0, $s0, 1  
addu $s1, $s1, 1  
j str_eq_loop  
neq_label:  
li $t3, 0  
str_eq_end:
```

Strings


- Alternatively, create a function `str_eq`

```
t1 = s1;  
t2 = s2;  
t3 = str_eq t1, t2  
beq t3, 0, label  
...
```

```
subu $sp, $sp, 4  
sw $t2, 0($sp)  
subu $sp, $sp, 4  
sw $t1, 0($sp)  
jal str_eq  
addu $sp, $sp, 8  
move $t3, $v0
```

Arrays

- Each cell is 4 bytes (*int* or *pointer*)
- First cell is the **size** of the array
- The rest of the cells contain **data**



Arrays

- Creating arrays

```
t0 = new_array t1
```

```
li $v0, 9  
move $a0, $t1  
add $a0, $a0, 1  
mul $a0, $a0, 4  
syscall  
move $t0, $v0  
sw $t1, 0($t0)
```

Arrays

- Array access

```
t0 = array_access t1, t2
```

```
move $s0, $t2  
add $s0, $s0, 1  
mul $s0, $s0, 4  
addu $s0, $t1, $s0  
lw $t0, 0($s0)
```

Arrays

- Checking access violation


```
t0 = array_access t1, t2
```

```
bltz $t2, abort
lw $s0, 0($t1)
bge $t2, $s0, abort
move $s0, $t2
add $s0, $s0, 1
mul $s0, $s0, 4
addu $s0, $t1, $s0
lw $t0, 0($s0)
...
abort:
li $v0, 10
syscall
```

Classes

Class Layout



```
class A {  
    int x;  
    string y;  
    int f() { ...  
    int g() { ...  
}
```



Class Layout

```
class A {  
    int x;  
    string y;  
    int f() { ...  
    int g() { ...  
}
```


```
class B extends A {  
    int z;  
    int f() { ...  
    int h() { ...  
}
```



B's layout

Creating Objects

```
class A {  
    int f1 = c;  
    ...  
    int m1() { ...  
    ...  
}  
  
A a = new A;
```



Creating Objects

```
class A {  
    int f1 = c;  
    ...  
    int m1() { ...  
    ...  
}
```



```
A a = new A;
```

```
t0 = new_class A  
a = t0
```

IR

Creating Objects



```
t0 = new_class A
```



virtual table

Creating Objects

```
t0 = new_class A
```




virtual table

```
.data  
vt_A:  
    .word m1  
    .word m2  
    ...
```

Creating Objects

```
t0 = new_class A
```





```
.data  
vt_A:  
    .word m1  
    .word m2  
    ...
```

```
li $v0, 9  
li $a0, size-of-A  
syscall  
move $t0, $v0
```

Creating Objects

```
t0 = new_class A
```





virtual table

```
.data  
vt_A:  
    .word m1  
    .word m2  
    ...
```

```
li $v0, 9  
li $a0, size-of-A  
syscall  
move $t0, $v0  
la $s0, vt_A  
sw $s0, 0($t0)
```

Creating Objects

```
t0 = new_class A
```



virtual table

```
.data  
vt_A:  
    .word m1  
    .word m2  
    ...
```


```
li $v0, 9  
li $a0, size-of-A  
syscall  
move $t0, $v0  
la $s0, vt_A  
sw $s0, 0($t0)  
li $s0, c  
sw $s0, 4($t0)  
...
```


Field Access

```
t0 = field_access t1, f
```

```
lw $t0, off($t1)
```

use annotated AST




t1

Field Access

```
t0 = field_access t1, f
```

```
beq $t1, 0, abort  
lw $t0, off($t1)  
...  
abort:  
li $v0, 10  
syscall
```




t1

Field Access

```
field_set t0, f, t1
```



```
beq $t0, 0, abort  
sw $t1, off($t0)  
...  
abort:  
li $v0, 10  
syscall
```



t1

Method Calls

```
t2 = virtual_call t0, m, t1
```





virtual table

Method Calls

```
t2 = virtual_call t0, m, t1
```

```
subu $sp, $sp, 4  
sw $t1, 0($sp)
```




virtual table

Method Calls



```
t2 = virtual_call t0, m, t1
```

```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)
```



Method Calls

```
t2 = virtual_call t0, m, t1
```





virtual table

```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
lw $s0, 0($t0)
```

Method Calls

```
t2 = virtual_call t0, m, t1
```




virtual table

```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
lw $s0, 0($t0)  
lw $s1, off($s0)
```

use annotated AST

Method Calls

```
t2 = virtual_call t0, m, t1
```




virtual table

```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
lw $s0, 0($t0)  
lw $s1, off($s0)  
jalr $s1
```

Method Calls


```
t2 = virtual_call t0, m, t1
```



```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
lw $s0, 0($t0)  
lw $s1, off($s0)  
jalr $s1  
addu $sp, $sp, 8
```

Method Calls

```
t2 = virtual_call t0, m, t1
```



```
subu $sp, $sp, 4  
sw $t1, 0($sp)  
subu $sp, $sp, 4  
sw $t0, 0($sp)  
lw $s0, 0($t0)  
lw $s1, off($s0)  
jalr $s1  
addu $sp, $sp, 8  
move $t2, $v0
```

Method Calls

```
class A {  
    void m1(int x) {}  
    void m2(int x) {}  
}  
class B extends A {  
    void m2(int x) {}  
}
```

```
B b = new B;  
z = b.m2(7)
```

```
t0 = new_class B  
b = t0  
t1 = b  
t2 = 7  
t3 = virtual_call t1, m2, t2  
z = t3
```

IR

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

.data

vt_B:

.word A_m1

.word B_m2

} data section

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
```

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
sw $t0, off_b($fp)
```

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
sw $t0, off_b($fp)
lw $t1, off_b($fp)
```


Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
sw $t0, off_b($fp)
lw $t1, off_b($fp)
li $t2, 7
```

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
sw $t0, off_b($fp)
lw $t1, off_b($fp)
li $t2, 7
subu $sp, $sp, 4
sw $t2, 0($sp)
subu $sp, $sp, 4
sw $t1, 0($sp)
lw $s0, 0($t1)
lw $s1, 4($s0)
jalr $s1
addu $sp, $sp, 8
move $t3, $v0
```

Method Calls

```
t0 = new_class B
b = t0
t1 = b
t2 = 7
t3 = virtual_call t1, m2, t2
z = t3
```

```
.data
vt_B:
.word A_m1
.word B_m2
```

} data section

```
li $v0, 9
li $a0, 4
syscall
move $t0, $v0
la $s0, vt_B
sw $s0, 0($t0)
sw $t0, off_b($fp)
lw $t1, off_b($fp)
li $t2, 7
subu $sp, $sp, 4
sw $t2, 0($sp)
subu $sp, $sp, 4
sw $t1, 0($sp)
lw $s0, 0($t1)
lw $s1, 4($s0)
jalr $s1
addu $sp, $sp, 8
move $t3, $v0
sw $t3, off_z($fp)
```