



北京大学

本科生毕业论文

题目： 三维模型最优二维视图生成方法研究
Synthesizing best 2D views of 3D models

姓 名： 黄道吉
学 号： 1600017857
院 系： 元培学院
本科专业： 计算机科学与技术
指导老师： 连宙辉

二〇二〇 年 五 月

摘要

生成三维模型的最优视图任务要求给定一个三维模型，我们能够选取出合适的视角，并且在这个视角下渲染出具有真实性的图片。随着三维建模方法的不断完善，三维模型的使用在近几年正变的越来越广泛。大规模三维模型数据库的出现更加便捷了有关三维模型的研究的进展。而三维模型不同于二维图片的特性使得它需要经过渲染才能显示在屏幕上。生成符合人类感知的三维模型的最优视图，将大大方便三维模型库的检索。近年来神经网络在二维视图生成工作的进展飞速，这也使得借助神经网络来生成三维模型的最优视图成为可能，尤其是生成对抗网络和变分自编码器在条件生成和非条件生成领域取得了很好的效果。本文回顾了以往在这个方向上研究者的工作，包括最优视角选择和新视角生成的算法，并提出了新的生成三维模型视图的方法。我们的方法首先能够根据一张导引图片提供的材质信息来渲染给定的三维模型在某一个视角下的视图，也能够通过在隐空间中采样来无条件的生成多样的三维模型的视图。定性和定量的实验结果表明，我们的新算法能够产生更加准确、更具真实性的三维模型图像，也在选择视角方面相对其他算法有自己的优势。最后，我们总结了本文的成果并展望了未来的工作。

关键词: 最优视图 图像生成

Abstract

forem

Key Words:

全文目录

摘要 1

Abstract 2

全文目录 3

第一章 引言 4

 1. 研究背景 4

参考文献 5

本科期间的主要工作和成果 7

致谢 8

第一章 引言

1. 研究背景

三维模型是图形学和计算机视觉方向的研究重点。近年来,三维模型的应用变得越来越广泛,从游戏界和工业界的 CAD 模型,到前沿领域的自动驾驶,使用三维模型正大大便利着业界。RGB-D 传感器的应用也使得产生三维模型更加容易。在学术界,三维模型也有着广泛的应用:三维模型的分割 ([1,2])、重建 ([3,4]),以及利用三维模型强化对图片的理解 ([5])。这些因素都催生了大规模三维模型库的产生和广泛使用(如 Shapenet [6], Pascal3D+ [7], ModelNet [8])。

在如此多的精力投入利用数据集解决问题的同时,相对少的精力投入到利用数据驱动的方法方便数据集的可视化和检索上。不同于二维图片便于观看、容易生成缩略图,三维模型在不同视角下会有不同的姿态,并且需要材质信息才能渲染出一张图片。这使得检索三维模型的数据库是一件费事的工作。ShapeNet 数据集 [6] 将每一个类别的模型对齐到同一个朝向,并在固定的方向渲染了 8 张缩略图,ModelNet 数据集 [8] 只提供了三维模型,这些方法并不能提供一个便捷的检索三维模型的方案。现有的处理三维模型的软件(如 MeshLab [9]),提供用户一个拖拽视角的界面,让用户寻找最好的视角。如果能设计出生成最优视图的算法,将会便利检索三维模型数据库。

我们认为生成三维模型的最优视图至少包括两个部分,一个部分是选定最优的视角,另一部分是在这个选定的视角下渲染出带有材质的二位视图。第一个部分以往工作主要从图形学入手,通过在三维模型的顶点或是在二维视图上定义信息(熵),取熵最大的视角作为最优视角。渲染材质的工作则集中利用了基于神经网络的生成模型,将材质生成问题定义为有条件的图片到图片翻译的问题。我们借鉴了这两方面方法的核心思想,并提出了新的生成三维模型最优视图的算法。

参考文献

- [1] Xiaobai Chen, Aleksey Golovinskiy, and Thomas A. Funkhouser. A benchmark for 3d mesh segmentation. In *SIGGRAPH 2009*, 2009.
- [2] Abhijit Kundu, Yin Li, Frank Dellaert, Fuxin Li, and James M. Rehg. Joint semantic segmentation and 3d reconstruction from monocular video. In *ECCV*, 2014.
- [3] Christopher Bongsoo Choy, Danfei Xu, JunYoung Gwak, Kevin Chen, and Silvio Savarese. 3d-r2n2: A unified approach for single and multi-view 3d object reconstruction. *ArXiv*, abs/1604.00449, 2016.
- [4] Priyanka Mandikal, L. NavaneetK., Mayank Agarwal, and Venkatesh Babu Radhakrishnan. 3d-lmnet: Latent embedding matching for accurate and diverse 3d point cloud reconstruction from a single image. In *BMVC*, 2018.
- [5] Christopher Bongsoo Choy, Michael Stark, Sam Corbett-Davies, and Silvio Savarese. Enriching object detection with 2d-3d registration and continuous view-point estimation. *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2512–2520, 2015.
- [6] Angel X. Chang, Thomas A. Funkhouser, Leonidas J. Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. Shapenet: An information-rich 3d model repository. *ArXiv*, abs/1512.03012, 2015.
- [7] Yu Xiang, Roozbeh Mottaghi, and Silvio Savarese. Beyond pascal: A benchmark for 3d object detection in the wild. *IEEE Winter Conference on Applications of Computer Vision*, pages 75–82, 2014.
- [8] Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1912–1920, 2014.

- [9] Paolo Cignoni, Marco Callieri, Massimiliano Corsini, Matteo Dellepiane, Fabio Ganovelli, and Guido Ranzuglia. Meshlab: an open-source mesh processing tool. In *Eurographics Italian Chapter Conference*, 2008.

本科期间的主要工作和成果

本科期间参加的主要科研项目
本研基金

1. 国家创新训练计划. 基金类型. 连宙辉. 2018-2019

致谢

感谢