

Package ‘ohicore’

December 8, 2013

Version 0.1

Date 2013-09-25

Title Ocean Health Index calculation package

Author Ben Best, Steve Hastings, Darren Hardy

Maintainer Ben Best <bbest@nceas.ucsb.edu>

Depends R (>= 2.14.0),plyr,reshape2,RJSONIO

Description A collection of functions for generically calculating the Ocean Health Index scores as well as individual goals and sub-goals.

License MIT

Collate

‘CalculatePressuresComponent.R’ ‘CalculateResilienceComponent.R’ ‘CalculateStatusComponent.R’ ‘CalculateSubgoal.R’

LazyData TRUE

R topics documented:

CalculatePressures	2
CalculatePressuresComponent	3
CalculatePressuresMatrix	3
CalculatePressuresScore	5
CalculateResilience	8
CalculateResilienceComponent	9
CalculateResilienceScore	9
CalculateStatusComponent	11
CalculateSubgoal	12
CheckLayers	12
Conf	14
Conf_write	15
Halpern2012.	15
Halpern2012.AO	15
Halpern2012.BD.HAB	16
Halpern2012.BD.SPP	16
Halpern2012.CP	17
Halpern2012.CS	17

Halpern2012.CW	18
Halpern2012.FP	18
Halpern2012.FP.FIS	19
Halpern2012.FP.MAR	19
Halpern2012.ICO	20
Halpern2012.LE	20
Halpern2012.LE.ECO	21
Halpern2012.LE.LIV	21
Halpern2012.LSP	22
Halpern2012.NP	22
Halpern2012.SP	23
Halpern2012.TR	23
Layers	24
layers.Global2012.Nature2012ftp	25
layers.Global2012.www2013	25
layers.Global2013.www2013	25
Scores	26
scores.Global2012.www2013	26
scores.Global2013.www2013	27
ScoreScaling	27
SelectLayersData	28
SpatialSchemes	29
TransformSpatialScheme	29
Index	30

CalculatePressures	<i>Calculate the pressures score for each (sub)goal.</i>
--------------------	--

Description

Calculate the pressures score for each (sub)goal.

Usage

CalculatePressures(layers, conf, gamma, debug = F)

Arguments

- | | |
|--------|---|
| layers | object Layers |
| conf | object Conf |
| gamma | (optional) if not specified defaults to 0.5 |

Value

data.frame containing columns 'region_id' and per subgoal pressures score

CalculatePressuresComponent

Calculate the pressures component of each (sub)goal.

Description

Calculate the pressures component of each (sub)goal.

Usage

```
CalculatePressuresComponent(eco.pressures,
  social.pressures, c.name = "category",
  s.name = "region", gamma = 0.5)
```

Arguments

eco.pressures	data.frame containing columns 'region', 'category', 'weight', and 'value'
social.pressures	data.frame containing columns 'region', and 'value'
gamma	(optional) if not specified defaults to 0.5

Value

data.frame containing columns 'region', 'p_E', 'p_S', and 'p_x'

CalculatePressuresMatrix

Calculate Pressures Matrix

Description

The pressures matrix model function computes a pressures weighting matrix based on regional attributes per category.

Usage

```
CalculatePressuresMatrix(alpha, beta, calc = "avg")
```

Arguments

alpha	the weighting matrix of the form [category x pressure]. Each rank weight must be an integer between 0 and 3 inclusive, or NA.
beta	the aggregation matrix of the form [region_id x category] to collapse across each category.
calc	type of calculation, whether avg (default), mean (diff't from avg?) or presence (results in 1 or 0).

Details

Given:

- g is the goal or subgoal (e.g., AO, CW, LIV, ECO, ...),
- i is the region (e.g., 1, 2, 3, ...),
- j is the pressures layer or stressor (e.g., cc_acid, fp_art_lb, etc.).
- k is the category (e.g., habitat, sector, product, etc.)

There may be a component k for a given goal g such that $p_w(g, i, j, k)$ and $w(g, i, j, k)$.

$$p_w(g, i, j, k) = w(g, i, j, k) * p(i, j)$$

In these cases where there is a component k for goal g , there's an additional aggregation or formula to calculate $w(g, i, j)$ based on the core rank weight $\alpha(g, j, k)$ from the original pressures matrix (as written in Halpern et al. (2012)) and some region-specific data for each category k $\beta(i, k)$.

This function CalculatePressuresMatrix will aggregate a category-specific weighting matrix $\alpha(g, j, k)$ [category x pressure] using region-specific data $\beta(g, i, k)$ into a [region_id x pressure] matrix $w(g, i, j)$ used in CalculatePressuresScore, such that:

$$w(g, i, j) = \frac{\sum_k \alpha(g, j, k) * \beta(g, i, k)}{\sum_k \beta(g, i, k)}$$

1. For the CP, CS goals, the weight depends on the extent A of habitat k in region i :

$$\beta(i, k) = A(i, k)$$

2. For the HAB goal, the weight depends on the presence of habitat k (i.e., if $A(i, k) > 0$) in region i :

$$\beta(i, k) = hasHabitat(i, k)$$

3. For the LIV and ECO goals, the weight depends on the presence of sector k if data available for region i and sector k :

$$\beta(i, k) = hasSector(i, k)$$

4. For the NP goal, the weight depends on the peak dollar value of each product k across all years (see w_p from SI Equation S27) if data available for region i and product k :

$$\beta(i, k) = w_p(i, k)$$

Value

Returns a weight matrix w [region_id x pressure] suitable for CalculatePressuresScore.

See Also

[CalculatePressuresScore](#)

CalculatePressuresScore

Calculate Pressures Score

Description

The pressures score is calculated for each region given a weighting matrix for a goal and the individual pressures values.

Usage

```
CalculatePressuresScore(p, w, GAMMA = 0.5, browse = F,
  pressures_categories = list(environmental = c("po", "hd", "fp", "sp", "cc"), social = "ss"))
```

Arguments

p the pressures value matrix [region_id x pressure]. Each score must be a real number between 0 and 1 inclusive, or NA. The pressure names must be of the form *category_pressure* where *category* is one of the categories listed in `ohi.pressure.category`. Use `ss` to denote the social category.

```
pressure region_id cc_acid cc_sst cc_uv
fp_art_hb 1 0.879 0.360 0.764 NA 2 0.579 0.396 0.531 NA 3
0.926 0.235 0.769 NA 4 0.914 0.554 0.795 NA 5 0.860 0.609
0.802 0.001 6 0.871 0.325 0.788 0.001 7 0.846 0.410 0.677
0.000 8 0.806 0.671 0.752 NA 9 0.844 0.595 0.678 NA 10
0.860 0.575 0.781 0.109
```

w the weighting matrix of the form [region_id x pressure]. Each rank weight must be a real number between 0 and 3 inclusive, or NA.

```
pressure
region_id cc_acid cc_sst cc_uv fp_art_hb 1 2 1 0.6 NA 2 2
1 0.5 NA 3 2 1 2.1 NA 4 2 1 3.0 NA 5 2 1 2.8 1 6 2 1 2.2
1 7 2 1 1.3 1 8 2 1 1.7 NA 9 2 1 3.0 NA 10 2 1 1.2 1
```

GAMMA Multiplier used to combine environmental and social pressures.

Details

Each pressure layer $p(i, j)$ is either environmental or social, belongs to a pressures category $K \in \{cc, fp, hd, po, sp, ss\}$, and has a value (0..1) for each region i and pressures layer j . Each goal has a weight matrix w that has a rank weight between 0 and 3 inclusive, or NoData, for each region i and each pressure layer j on a per goal g basis.

The pressures scores calculations go through 5 steps, using a complex weighting scheme that varies across goals, subgoals, pressures categories, and regions:

- g is the goal or subgoal (e.g., AO, CW, LIV, ECO, ...),
- i is the region (e.g., 1, 2, 3, ...),
- j is the pressures layer or stressor (e.g., cc_acid, fp_art_lb, etc.).

Calculations

1. Apply weights for each goal g , region i , and pressure layer j : Each weighted pressure $p_w(g, i, j)$ is the pressure layer value $p(i, j)$ per region i and pressure layer j multiplied by the rank weight $w(g, i, j)$ for that goal g , region i , and pressure layer j . If the $w(g, i, j)$ is NoData or 0, the weighted pressure $p_w(g, i, j)$ is NoData.

$$p_w(g, i, j) = w(g, i, j) * p(i, j)$$

2. Category-level aggregation: The pressures category score p_K is the sum of all p_w within each category, then rescaled to 0..1 using a linear scale range transformation (from 0..3 to 0..1). Any score p_K greater than 1 is capped to 1:

$$p_K(g, i) = \frac{\min(\sum_{j \in K} p_w(g, i, j), 3)}{3}$$

3. Environmental aggregation: The environmental pressures score $p_E(g, i)$ is the weighted sum of $p_K(g, i)$, where each weight is the maximum weight in the pressure category K , and then divided by the sum of the maximum weights:

$$w_{K, max}(g, i) = \max(\{\forall_j \in K | w(g, i, j)\})$$

$$p_E(g, i) = \frac{\sum_K w_{K, max}(g, i) p_K(g, i)}{\sum_K w_{K, max}(g, i)}$$

4. Social aggregation: The social pressures score $p_S(g, i)$ is the mean of the *unweighted* social pressure scores $p(i, j)$:

$$p_S(g, i) = \frac{\sum_{j \in S} p(i, j)}{N}$$

5. Gamma combination: The pressures score $p_X(g, i)$:

$$p_X(g, i) = \gamma p_E(g, i) + (1 - \gamma) p_S(g, i)$$

Value

Returns a named vector with the pressures score for each named region.

See Also

[CalculatePressuresMatrix](#)

Examples

```
## Not run:
> conf$config$pressures_categories
$environmental
[1] "po" "hd" "fp" "sp" "cc"

$social
[1] "ss"
> p
      pressure
region_id fp_art_hb fp_art_lb fp_com_hb fp_com_lb hd_intertidal
1         0.122     0.25     0.35     0.395     0.954
```

2	0.096	0.94	0.85	0.252	0.649
3	0.858	0.46	0.84	0.097	0.425
4	0.814	0.63	0.60	0.672	0.659
5	0.247	0.51	0.58	0.941	0.046
6	0.853	0.34	0.15	0.370	0.385
7	0.601	0.31	0.39	0.873	0.064
8	0.355	0.89	0.74	0.159	0.273
9	0.289	0.94	0.52	0.743	0.094
10	0.887	0.89	0.87	0.660	0.746

pressure

region_id	hd_subtidal_hb	hd_subtidal_sb	po_chemicals	po_nutrients
1	0.535	0.651	0.042	0.931
2	0.454	0.069	0.234	0.025
3	0.297	0.428	0.970	0.679
4	0.953	0.485	0.063	0.565
5	0.963	0.045	0.552	0.828
6	0.598	0.213	0.907	0.220
7	0.476	0.641	0.980	0.214
8	0.285	0.858	0.447	0.793
9	0.591	0.702	0.719	0.472
10	0.072	0.431	0.685	0.102

pressure

region_id	sp_alien	sp_genetic	ss_wgi
1	0.979	0.761	0.181
2	0.345	0.091	0.631
3	0.223	0.986	0.646
4	0.035	0.078	0.559
5	0.992	0.643	0.432
6	0.963	0.416	0.221
7	0.752	0.627	0.257
8	0.100	0.245	0.333
9	0.316	0.373	0.347
10	0.283	0.224	0.031

> w

pressure

region_id	fp_art_hb	fp_art_lb	fp_com_hb	fp_com_lb	hd_intertidal
1	2	1	0.92	1	1
2	2	1	0.48	1	1
3	2	1	2.81	1	1
4	2	1	1.19	1	1
5	2	1	2.82	1	1
6	2	1	1.07	1	1
7	2	1	1.48	1	1
8	2	1	0.46	1	1
9	2	1	0.56	1	1
10	2	1	0.90	1	1

pressure

region_id	hd_subtidal_hb	hd_subtidal_sb	po_chemicals	po_nutrients
1	2	2	1.00	1
2	2	2	0.79	1
3	2	2	0.37	1
4	2	2	0.91	1
5	2	2	1.06	1
6	2	2	0.72	1
7	2	2	0.49	1
8	2	2	1.18	1
9	2	2	0.18	1

```

      10      2      2      0.28      1
      pressure
region_id sp_alien sp_genetic ss_wgi
      1      1      1      1
      2      1      1      1
      3      1      1      1
      4      1      1      1
      5      1      1      1
      6      1      1      1
      7      1      1      1
      8      1      1      1
      9      1      1      1
     10      1      1      1
> p_x <- CalculatePressuresScore(p, w)
> p_x
      1      2      3      4      5      6      7      8      9     10
0.40 0.53 0.68 0.63 0.60 0.43 0.48 0.47 0.50 0.30
> data.frame(region_id=names(p_x), pressure=p_x)
      region_id pressure
1             1      0.40
2             2      0.53
3             3      0.68
4             4      0.63
5             5      0.60
6             6      0.43
7             7      0.48
8             8      0.47
9             9      0.50
10            10      0.30
>
>

## End(Not run)
```

CalculateResilience	<i>Calculate the resilience score for each (sub)goal.</i>
---------------------	---

Description

Calculate the resilience score for each (sub)goal.

Usage

CalculateResilience(layers, conf, debug = FALSE)

Arguments

layers object [Layers](#)
conf object [Conf](#)

Value

data.frame containing columns 'region_id' and per subgoal resilience score

CalculateResilienceComponent

Calculate the Resilience component of each (sub)goal.

Description

Calculate the Resilience component of each (sub)goal.

Usage

```
CalculateResilienceComponent(goal.specific.regulations,
  ecological.integrity, social.integrity,
  c.name = "category", s.name = "region", gamma = 0.5)
```

Arguments

goal.specific.regulations	(data.frame) contains columns 'region', 'weight', and 'value'
gamma	(numeric) represents the weighting between ecological and social aspects of resilience, defaults to 0.5 (equal weights)

Value

(data.frame)

CalculateResilienceScore

Calculate Resilience Score

Description

The resilience model function computes a resilience score for each region given a weighting matrix for a goal and the individual resilience values.

Usage

```
CalculateResilienceScore(r, t, w = NA, gamma = 0.5,
  resilience_categories = c("environmental", "regulatory", "social"))
```

Arguments

r	the resilience value matrix [region_id x layer]. Each score must be a real number between 0 and 1 inclusive, or NA.
t	the typing vector t[layer] where values are from resilience_categories.
w	the weighting matrix of the form [region_id x layer]. Each rank weight must be a real number >= 0, or NA for even weighting.
w.layers	the weighting vector of the form [layer]. Each rank weight must be a real number >= 0, or NA for even weighting.
gamma	the gamma constant for $r_{i,x}$ calculation.
b	a boolean value matrix [region_id x layer] which is TRUE if the given region_id should include layer, and FALSE otherwise.

Details

To calculate Resilience for each goal g and region i ($r(g, i)$) we assess three types of resilience measures j : ecological integrity ($Y_E(g, i)$), goal-specific regulations aimed at addressing ecological pressures ($G(g, i)$), and social integrity ($Y_S(g, i)$). The first two measures address ecological resilience while the third addresses social resilience. When all three aspects are relevant to a goal, Resilience is calculated for each goal g and each region i :

$$r(g, i) = \gamma * \left(\frac{Y_E(g, i) + G(g, i)}{2} \right) + (1 - \gamma) * Y_S(g, i)$$

where each goal g is comprised of several resilience layers j where w_j is a configuration-time weight to aggregate across resilience categories:

$$G(g, i) = \frac{\sum_{j \in g} w_j G(i, j)}{\sum_{j \in g} w_j}$$

$$Y_E(g, i) = \frac{\sum_{j \in g} Y_E(i, j)}{N}$$

$$Y_S(g, i) = \frac{\sum_{j \in g} Y_S(i, j)}{N}$$

Value

`ohi.model.resilience` returns resilience score for each region. `ohi.model.resilience.matrix` returns a weighting matrix suitable for `ohi.model.resilience`.

Examples

```
## Not run:
> conf$config$resilience_categories
[1] "environmental" "regulatory"      "social"
> b
      layer
region_id fishing-v1 habitat-combo species-diversity-3nm wgi-all
  104      TRUE      TRUE      TRUE      TRUE
  105      TRUE      TRUE      TRUE      TRUE
  106      TRUE      TRUE      TRUE      TRUE
  107      TRUE      TRUE      TRUE      TRUE
  108      TRUE      TRUE      TRUE      TRUE
  109      TRUE      TRUE      TRUE      TRUE
  110      TRUE      TRUE      TRUE      TRUE
  111      TRUE      TRUE      TRUE      TRUE
  112      TRUE      TRUE      TRUE      TRUE
  113      TRUE      TRUE      TRUE      TRUE
  114      TRUE      TRUE      TRUE      TRUE
> w
      fishing-v1 habitat-combo species-diversity-3nm wgi-all
      2          2          1
      wgi-all
      1
> w <- -ohi.model.resilience.matrix(b, w)
> w
      layer
region_id fishing-v1 habitat-combo species-diversity-3nm wgi-all
```

```

104      2      2      1      1
105      2      2      1      1
106      2      2      1      1
107      2      2      1      1
108      2      2      1      1
109      2      2      1      1
110      2      2      1      1
111      2      2      1      1
112      2      2      1      1
113      2      2      1      1
114      2      2      1      1

> r
      layer
region_id fishing-v1 habitat-combo species-diversity-3nm wgi-all
104      0.4870      0.4495      0.8679 0.4385
105      0.5162      0.5905      0.8748 0.2460
106      0.4811      0.4051      0.8852 0.6465
107      0.3618      0.2583      0.8260 0.8007
108      0.5322      0.4703      0.9318 0.5579
109      0.5053      0.4703      0.9313 0.5579
110      0.6491      0.5690      0.9239 0.5703
111      0.3629      0.1562      0.9230 0.6375
112      0.5670      0.5000      0.9273 0.5718
113      0.3807      0.2530      0.9339 0.4484
114      0.6508      0.5690      0.9275 0.5703

> t
      fishing-v1      habitat-combo species-diversity-3nm
      "regulatory"      "regulatory"      "environmental"
      wgi-all
      "social"

> ohi.model.resilience(r, t, w)
104 105 106 107 108 109 110 111 112 113
0.5533 0.4800 0.6553 0.6844 0.6372 0.6337 0.6684 0.6144 0.6511 0.5369
114
0.6695

## End(Not run)

```

CalculateStatusComponent

Compute a single subgoal.

Description

Compute a single subgoal.

Usage

```
CalculateStatusComponent(DATA, fun, trend.Years = 5,
  c.name = "year", s.name = "region")
```

Arguments

DATA	data.frame containing columns 'region', 'value', and (optionally) 'w'
fun	(optional) function for calculating the subgoal value, if not specified it will default to a weighted average
w	(optional) numeric vector describing the

Value

stuff

CalculateSubgoal	<i>Compute a single subgoal.</i>
------------------	----------------------------------

Description

Compute a single subgoal.

Usage

```
CalculateSubgoal(current.data, eco.pressures,
  social.pressures, gs.regulations, social.integrity,
  eco.integrity, fun = stats::weighted.mean,
  trend.Years = 5)
```

Arguments

DATA	data.frame containing columns 'region', 'value', and (optionally) 'w'
fun	(optional) function for calculating the subgoal value, if not specified it will default to a weighted average
w	(optional) numeric vector describing the

Value

stuff

CheckLayers	<i>Check Layers</i>
-------------	---------------------

Description

Check all the input layers as defined by layers.csv and update required fields

Usage

```
CheckLayers(layers.csv, layers.dir, flds_id, verbose = T,
  msg.indent = " ")
```

Arguments

<code>layers.csv</code>	full path to the layers.csv file.
<code>layers.dir</code>	full path to the directory containing the layers files.
<code>flds_id</code>	character vector of unique identifiers, typically spatial, eg c('region_id', 'country_id', 'saup_id'), described in your <code>Conf\$layers_id_fields</code> .
<code>if</code>	True (default), extra diagnostics are output

Details

The `CheckLayers()` function iterates through all the layers in `layers.csv` and updates the following field names:

- *fld_id_num* - numeric unique identifier
- *fld_id_chr* - character unique identifier
- *fld_category* - category
- *fld_year* - year
- *fld_val_num* - numeric value
- *fld_val_chr* - character value

Additional diagnostic fields are updated:

- *file_exists* - input filename exists
- *val_min* - minimum value, if numeric
- *val_max* - maximum value, if numeric
- *val_0to1* - TRUE if value ranges between 0 and 1
- *flds_unused* - unused fields from input file when guessing prescribed field names (aboves)
- *flds_missing* - fields expected, as given by Layers units, and not found
- *rows_duplicated* - given the combination of all row-identifying fields (and excluding value fields), the number of rows which are duplicates
- *num_ids_unique* - number of unique ids, as provided by just the unique instances of the *fld_id*

Value

warning messages

Examples

```
## Not run:
  CheckLayers(layers.csv, layers.dir, c('rgn_id','cntry_key','saup_id'))

## End(Not run)
```

Conf	<i>Conf reference class.</i>
------	------------------------------

Description

Conf reference class.

Usage

```
Conf(...)
```

Arguments

`dir` path to directory containing necessary files

Details

To create this object, `Conf(dir)`. The `dir` is expected to have the following files:

- *config.R*
- *functions.R*
- *goals.csv*
- *pressures_matrix.csv*
- *resilience_matrix.csv*
- *resilienceweights.csv*

See also [Conf_write\(\)](#) to write the configuration back to disk.

Value

object reference class of `Config` containing:

- *config*
- *functions*
- *goals*
- *pressures_matrix*
- *resilience_matrix*
- *resilienceweights*

Conf_write	<i>Write the Conf to disk</i>
------------	-------------------------------

Description

Write the Conf to disk

Arguments

dir	path to directory where the Conf files should be output
-----	---

Details

Use this function to write the configuration to disk, like so `conf$write(dir)`. This is useful for modifying and then reloading with `Conf(dir)`.

Halpern2012.	<i>Calculate Biodiversity.</i>
--------------	--------------------------------

Description

Calculate Biodiversity.

Usage

```
Halpern2012.(A, G, w, Cc, Cr, ...)
```

Arguments

placeholder	placeholder
-------------	-------------

Value

1

Halpern2012.A0	<i>Calculate Artisanal Fishing Opportunities.</i>
----------------	---

Description

Calculate Artisanal Fishing Opportunities.

Usage

```
Halpern2012.A0(Sao, Oao, PPPpcGDP, ...)
```

Arguments

placeholder	placeholder Sao
placeholder	placeholder Oao
placeholder	placeholder PPPpcGDP

Value

1

Halpern2012.BD.HAB	<i>Calculate Habitats subgoal of Biodiversity.</i>
--------------------	--

Description

Calculate Habitats subgoal of Biodiversity.

Usage

Halpern2012.BD.HAB(Cc, Cr, ...)

Arguments

placeholder	placeholder
-------------	-------------

Value

1

Halpern2012.BD.SPP	<i>Calculate Species subgoal of Biodiversity.</i>
--------------------	---

Description

Calculate Species subgoal of Biodiversity.

Usage

Halpern2012.BD.SPP(A, G, w, ...)

Arguments

placeholder	placeholder
-------------	-------------

Value

1

Halpern2012.CP	<i>Calculate Coastal Protection</i>
----------------	-------------------------------------

Description

Calculate Coastal Protection

Usage

Halpern2012.CP(Cc, Cr, w, A, ...)

Arguments

placeholder	placeholder Cc current 'condition' of habitat k
placeholder	placeholder Cr reference 'condition' of habitat k
placeholder	placeholder A amount of area covered by habitat k
placeholder	placeholder w rank weight of habitat protective ability

Value

1

Halpern2012.CS	<i>Calculate Carbon Storage</i>
----------------	---------------------------------

Description

Calculate Carbon Storage

Usage

Halpern2012.CS(Cc, Cr, A, ...)

Arguments

placeholder	placeholder Cc current 'condition' of habitat k
placeholder	placeholder Cr reference 'condition' of habitat k
placeholder	placeholder A amount of area covered by habitat k

Value

1

Halpern2012.CW	<i>Calculate Clean Waters.</i>
----------------	--------------------------------

Description

Calculate Clean Waters.

Usage

Halpern2012.CW(a, u, l, d, ...)

Arguments

placeholder	placeholder a number of coastal people without access to sanitation rescaled to global maximum
placeholder	placeholder u l - (nutrient input)
placeholder	placeholder l l - (chemical input)
placeholder	placeholder d l - (marine debris input)

Value

1

Halpern2012.FP	<i>Calculate Food Provision.</i>
----------------	----------------------------------

Description

Calculate Food Provision.

Usage

Halpern2012.FP(w, dBt, mMSY, Bt, Tc, k, Smk, Ac, Yk, ...)

Arguments

placeholder	placeholder k each mariculture species
placeholder	placeholder Smk sustainability score for each species k
placeholder	placeholder Ac area of coastal waters (3nm strip)
placeholder	placeholder Yl yield of each species k

Value

1

Halpern2012.FP.FIS	<i>Calculate Fisheries subgoal of Food Provision.</i>
--------------------	---

Description

Calculate Fisheries subgoal of Food Provision.

Usage

Halpern2012.FP.FIS(mMSY, Bt, Tc, ...)

Arguments

placeholder	placeholder dBt absolute difference between landed biomass and mMSY
placeholder	placeholder mMSY multi-species maximum sustainable yield
placeholder	placeholder Tc taxonomic report quiality correction factor
placeholder	placeholder Bt wild-caught fishing yield

Value

1

Halpern2012.FP.MAR	<i>Calculate Mariculture subgoal of Food Provision.</i>
--------------------	---

Description

Calculate Mariculture subgoal of Food Provision.

Usage

Halpern2012.FP.MAR(k, Smk, Ac, Yk, ...)

Arguments

placeholder	placeholder k each mariculture species
placeholder	placeholder Smk sustainability score for each species k
placeholder	placeholder Ac area of coastal waters (3nm strip)
placeholder	placeholder Yl yield of each species k

Value

1

Halpern2012.IC0	<i>Calculate Iconic Species subgoal of Sense of Place.</i>
-----------------	--

Description

Calculate Iconic Species subgoal of Sense of Place.

Usage

Halpern2012.IC0(S, w, ...)

Arguments

placeholder	placeholder S number of assessed species in each category
placeholder	placeholder w status weight assigned per threat category

Value

1

Halpern2012.LE	<i>Calculate Coastal Livelihoods and Economies.</i>
----------------	---

Description

Calculate Coastal Livelihoods and Economies.

Usage

Halpern2012.LE(jc, jr, gc, gr, ec, er, ...)

Arguments

placeholder	placeholder jc total adjusted jobs per sector at current time
placeholder	placeholder jr total adjusted jobs per sector at reference time
placeholder	placeholder gc average PPP-adjusted per-capita annual wages per sector in current region
placeholder	placeholder gr average PPP-adjusted per-capita annual wages per sector in reference region
placeholder	placeholder ec total adjusted revenue generated per sector at current time
placeholder	placeholder er total adjusted revenue generated per sector at reference time

Value

1

Halpern2012.LE.ECO	<i>Calculate Economies subgoal of Coastal Livelihoods and Economies.</i>
--------------------	--

Description

Calculate Economies subgoal of Coastal Livelihoods and Economies.

Usage

Halpern2012.LE.ECO(ec, er, ...)

Arguments

placeholder	placeholder ec total adjusted revenue generated per sector at current time
placeholder	placeholder er total adjusted revenue generated per sector at reference time

Value

1

Halpern2012.LE.LIV	<i>Calculate Livelihoods subgoal of Coastal Livelihoods and Economies.</i>
--------------------	--

Description

Calculate Livelihoods subgoal of Coastal Livelihoods and Economies.

Usage

Halpern2012.LE.LIV(jc, jr, gc, gr, ...)

Arguments

placeholder	placeholder jc total adjusted jobs per sector at current time
placeholder	placeholder jr total adjusted jobs per sector at reference time
placeholder	placeholder gc average PPP-adjusted per-capita annual wages per sector in current region
placeholder	placeholder gr average PPP-adjusted per-capita annual wages per sector in reference region

Value

1

Halpern2012.LSP	<i>Calculate Lasting Special Places subgoal of Sense of Place.</i>
-----------------	--

Description

Calculate Lasting Special Places subgoal of Sense of Place.

Usage

Halpern2012.LSP(CMPA, tCMPA, CP, tCP, ...)

Arguments

placeholder	placeholder CMPA coastal marine protected area
placeholder	placeholder tCMPA total coastal marine area
placeholder	placeholder CP coastline protected
placeholder	placeholder tCP total coastline

Value

1

Halpern2012.NP	<i>Calculate Natural Products. (Needs work)</i>
----------------	---

Description

Calculate Natural Products. (Needs work)

Usage

Halpern2012.NP(N, wp, Hp, E, R, Nv, Nk, w, ...)

Arguments

placeholder	placeholder N number of products that have ever been harvested
placeholder	placeholder wp proportional peak dollar value of each product relative to the total peak dollar value of all products
placeholder	placeholder Hp harvest of a product relative to its buffered peak reference point
placeholder	placeholder E exposure term
placeholder	placeholder R risk term
placeholder	placeholder Nv 1 or 2, depending on whether or not a viability term is used
placeholder	placeholder Nk number of species in each k category of exploitation
placeholder	placeholder w weight assigned to each k category of exploitation status

Value

1

Halpern2012.SP	<i>Calculate Sense of Place.</i>
----------------	----------------------------------

Description

Calculate Sense of Place.

Usage

Halpern2012.SP(S, w, CMPA, tCMPA, CP, tCP, ...)

Arguments

placeholder	placeholder S number of assessed species in each category
placeholder	placeholder w status weight assigned per threat category
placeholder	placeholder CMPA coastal marine protected area
placeholder	placeholder tCMPA total coastal marine area
placeholder	placeholder CP coastline protected
placeholder	placeholder tCP total coastline

Value

1

Halpern2012.TR	<i>Calculate Tourism and Recreation.</i>
----------------	--

Description

Calculate Tourism and Recreation.

Usage

Halpern2012.TR(D, t, V, S, ...)

Arguments

placeholder	placeholder D number of tourist-days
placeholder	placeholder t most recent year
placeholder	placeholder V total region population size
placeholder	placeholder S sustainability factor

Value

1

Layers	<i>Layers reference class.</i>
--------	--------------------------------

Description

Layers reference class.

Usage

```
Layers(...)
```

Arguments

<code>layers.csv</code>	path to comma-seperated value file with row of metadata per layer
<code>layers.dir</code>	path of directory containing individual layer files

Details

To instantiate this object, `Layers(layers.csv, layers.dir)` is used. The `layers.csv` is expected to have the following columns:

- *layer* - unique identifier (no spaces or special characters)
- *targets* - the pipe and space (' | ') delimited list of targets (goal name, 'Pressures' or 'Resilience') to feed this data layer
- *title* - full title of the variable
- *description* detailed description
- *citation* - reference for documentation
- *units* - indicating units and required column name in the layer csv file
- *filename* - the csv data file for the layer

The `layers.dir` directory should contain all the csv filenames listed in the `layers.csv` file.

Value

object (non-instantiated) reference class of Layers containing

- *meta* - metadata data frame of original layers.csv
- *data* - named list of data frames, one per layer
- *targets* - named list of character vector indicating a layer's targets, goal (status, trend) or dimension (pressures, resilience)

layers.Global2012.Nature2012ftp

Layers accompanying Nature 2012 publication on the FTP site for Global 2012 analysis.

Description

These layers get used to calculate the Ocean Health Index.

Format

a [Layers](#) object

References

<http://ohi-science.org>

layers.Global2012.www2013

Layers used for the 2013 web launch applied to Global 2012 analysis.

Description

These layers get used to calculate the Ocean Health Index.

Format

a [Layers](#) object

References

<http://ohi-science.org>

layers.Global2013.www2013

Layers used for the 2013 web launch applied to Global 2013 analysis.

Description

These layers get used to calculate the Ocean Health Index.

Format

a [Layers](#) object

References

<http://ohi-science.org>

Scores	<i>Scores reference class.</i>
--------	--------------------------------

Description

Scores reference class.

Usage

```
Scores(...)
```

Arguments

scores.csv path to comma-seperated results file, long style

Details

To instantiate this object, Scores(results.csv) is used. The results.csv is expected to have the following columns:

- *region_id* - unique numeric region identifier, reserving 0 as the region_id for the area-weighted average of the entire study area
- *goal* - the goal code or Index
- *dimension* - the dimension code, one of: status, trend, pressures, resilience, future, score
- *score* - the numeric score: 0-100 for all dimensions, except trend (-1 to 1)

To get the wide view (many columns, with one row per region and columns having combination of goal and dimension), use something like: reshape2::dcast(.self\$long, region_id ~ goal + dimension, value.var='score').

Value

object reference class of Layers containing

- *data* - long view (many rows) of score results with columns: region_id, goal, dimension, score

scores.Global2012.www2013

Scores resulting from the 2013 web launch applied to Global 2012 analysis.

Description

These scores are the results of the Ocean Health Index.

Format

a [Scores](#) object

References

<http://ohi-science.org>

scores.Global2013.www2013

Scores resulting from the 2013 web launch applied to Global 2013 analysis.

Description

These scores are the results of the Ocean Health Index.

Format

a [Scores](#) object

References

<http://ohi-science.org>

ScoreScaling

Score Scaling Functions

Description

Scoring functions

Usage

```
score.rescale(x, xlim = NULL, method = "linear", ...)
```

Arguments

x	A numeric vector of data.
xlim	The scoring range. If null, derives range from data.
p	A percentage buffer to add to the maximum value.
method	Only 'linear' is supported.
...	Arguments for min, max, pmin, pmax.

Value

Returns scores.

See Also

min, max, pmin, pmax

Examples

```
score.max(c(0.5, 1, 2))
score.max(c(0.5, 1, 2), p=0.25)
score.rescale(c(0.5, 1, 2))
score.clamp(c(-0.5, 1, 2))
score.clamp(c(-0.5, 1, 2), xlim=c(-1, 1))
```

SelectLayersData	Select Layers to Data
------------------	-----------------------

Description

Select Layers to Data

Usage

```
SelectLayersData(object, targets = NULL, layers = NULL,
  cast = TRUE, narrow = FALSE,
  expand.time.invariant = FALSE)
```

Arguments

object	instance of Layers class
targets	specifies the targets of layers to be selected, defaulting to <code>c('regions')</code>
layers	specifies the layers to be selected. If given as a named character vector, then layers get renamed with new names as values, and old names as names per <code>plyr::rename</code>
narrow	narrow the resulting data frame to just the fields containing data (as described by <i>flds</i> in the default wide result) #
expand.time.invariant	for layers without a year column, populate the same value throughout all years where available in other layer(s) #
cast	whether to cast the resulting dataset, or leave it melted, defaults to TRUE

Details

If neither targets or layers are specified then all layers are returned. If targets and layers are specified, then the union of the two sets of layers are returned, with any renamed layers renamed.

Value

data.frame with the merged data of selected layers having the following fields:

- *layer* - layer name, possibly renamed
- *layer0* - original layer name, if fed a named character vector to layers
- *id_num* - numeric id
- *id_chr* - character id
- *id_name* - fieldname of id
- *category* - category
- *category_name* - fieldname of character
- *year* - year
- *val_num* - numeric value
- *val_chr* - character value
- *val_name* - fieldname of value, usually in units as specified in Layers
- *flds* - data fields used for the layer

SpatialSchemes	<i>SpatialSchemes reference class.</i>
----------------	--

Description

SpatialSchemes reference class.

Usage

SpatialSchemes(...)

Value

object (non-instantiated) reference class of SpatialSchemes

TransformSpatialScheme	<i>Transform data</i>
------------------------	-----------------------

Description

Transform data

Usage

TransformSpatialScheme(object, data, target, origin, categories)

Arguments

- | | |
|------------|--|
| object | instance of SpatialSchemes class |
| data | data.frame such as returned from 'SelectLayersData' function |
| target | single spatial scheme to which data should be transformed |
| origin | spatial schemes from which to transform, can be vector |
| categories | layers for which transformation should be done (to be safe, for now this should be all the layers in param data) |

Value

data.frame transformed data

Index

*Topic **datasets**

- layers.Global2012.Nature2012ftp, [25](#)
- layers.Global2012.www2013, [25](#)
- layers.Global2013.www2013, [25](#)
- scores.Global2012.www2013, [26](#)
- scores.Global2013.www2013, [27](#)

*Topic **layers**

- CheckLayers, [12](#)

*Topic **ohi**

- CalculatePressuresMatrix, [3](#)
- CalculatePressuresScore, [5](#)
- CalculateResilienceScore, [9](#)
- ScoreScaling, [27](#)

- CalculatePressures, [2](#)
- CalculatePressuresComponent, [3](#)
- CalculatePressuresMatrix, [3](#), [6](#)
- CalculatePressuresScore, [4](#), [5](#)
- CalculateResilience, [8](#)
- CalculateResilienceComponent, [9](#)
- CalculateResilienceScore, [9](#)
- CalculateStatusComponent, [11](#)
- CalculateSubgoal, [12](#)
- CheckLayers, [12](#)
- Conf, [2](#), [8](#), [13](#), [14](#), [15](#)
- Conf_write, [14](#), [15](#)

- Halpern2012., [15](#)
- Halpern2012.AO, [15](#)
- Halpern2012.BD.HAB, [16](#)
- Halpern2012.BD.SPP, [16](#)
- Halpern2012.CP, [17](#)
- Halpern2012.CS, [17](#)
- Halpern2012.CW, [18](#)
- Halpern2012.FP, [18](#)
- Halpern2012.FP.FIS, [19](#)
- Halpern2012.FP.MAR, [19](#)
- Halpern2012.ICO, [20](#)
- Halpern2012.LE, [20](#)
- Halpern2012.LE.ECO, [21](#)
- Halpern2012.LE.LIV, [21](#)
- Halpern2012.LSP, [22](#)
- Halpern2012.NP, [22](#)

- Halpern2012.SP, [23](#)
- Halpern2012.TR, [23](#)

- Layers, [2](#), [8](#), [24](#), [25](#)
- layers.Global2012.Nature2012ftp, [25](#)
- layers.Global2012.www2013, [25](#)
- layers.Global2013.www2013, [25](#)

- plyr::rename, [28](#)

- resilience_categories
(CalculateResilienceScore), [9](#)

- score.clamp (ScoreScaling), [27](#)
- score.max (ScoreScaling), [27](#)
- score.rescale (ScoreScaling), [27](#)
- Scores, [26](#), [26](#), [27](#)
- scores.Global2012.www2013, [26](#)
- scores.Global2013.www2013, [27](#)
- ScoreScaling, [27](#)
- SelectLayersData, [28](#)
- SpatialSchemes, [29](#)

- TransformSpatialScheme, [29](#)