



University of
BRISTOL



Recurrent neural networks in brains and machines

Seán Froudist-Walsh

Lecturer in Computational Neuroscience

1

1

Why have recurrent connections?

2

2

1

A popular working memory task (n-back)

- We will present a series of letter on the screen, one at a time.
- Whenever the letter on the screen is the same as the previous letter, say 'now'.

3

3



4

2

Feedforward neural networks cannot do this easy task

- But do you fancy a challenge?
- Rewind the video, and now respond any time the letter on the screen is the same as the one shown *three* letters back (e.g. A, B, C, A).

5

5

Intended Learning Outcomes

By the end of this video you will be able to

- explain why recurrent connections can be useful
- describe where most recurrent connections are in the brain
- compare biologically-realistic and trained recurrent neural networks
- design a dynamical model of the whole cortex step-by-step
- write the equation for AI-style recurrent neural networks (RNNs) and leaky RNNs
- formally compare feedforward and recurrent neural networks


6

6

3

What are recurrent connections?

- Recurrent connections are neural pathways that enable information to travel in loops, to be maintained, integrated or to re-enter the system.
- Recurrent connections can be within a brain area (local) or between brain areas (long-range).
- Recurrent connections can be excitatory or inhibitory



Byrne, 2023


<https://nba.uth.tmc.edu/neuroscience/m/s1/introduction.html>

7

7

Where are the recurrent connections in the brain?

- There are many long-distance recurrent loops across brain areas.
- In primates, approximately 2/3 of all possible connections between brain areas do exist (~97% in mice).
- However most connections (~80%) are from within the same brain area (in the cortex)

Markov et al., *Cerebral Cortex*, 2011 Markov et al., *J. Comp. Neurol.*, 2014 Stefanics et al., *Front. Hum. Neurosci*, 2014

8

8

A parallel tradition of biologically-realistic models of brain functions


Chapter 7 - Network Models

- Introduction
- Firing-Rate Models
- Feedforward and Recurrent Networks
- Continuously Labelled Networks
- Feedforward Networks
- Neural Coordinate Transformations
- Recurrent Networks
- Linear Recurrent Networks
- Selective Amplification
- Input Integration
- Continuous Linear Recurrent Networks
- Nonlinear Recurrent Networks
- Noiseless Amplification
- A Recurrent Model of Simple Cells in Primary Visual Cortex
- A Recurrent Model of Complex Cells in Primary Visual Cortex
- Winner-Take-All Input Selection
- Gain Modulation
- Sustained Activity
- Maximum Likelihood and Network Recoding
- Network Stability
- Associative Memory
- Excitatory-Inhibitory Networks
- Homogeneous Excitatory and Inhibitory Populations
- Phase-Plane Methods and Stability Analysis
- The Olfactory Bulb
- Oscillatory Amplification
- Stochastic Networks
- Chapter Summary
- Appendix


IV Dynamics of Cognition

- 16 Competing Populations and Decision Making
- 17 Memory and Attractor Dynamics
- 18 Cortical Field Models for Perception
- 19 Synaptic Plasticity and Learning
- 20 Outlook: Dynamics in Plastic Networks

V1 - vision
prefrontal – working memory



hippocampus - memory




prefrontal/parietal - choice
hippocampus - memory
V1 - vision

9

9

Biologically-realistic models link physiology to behaviour

- Biologically-realistic models can be detailed models of many spiking neurons, or simplified (via mean-field techniques) to firing rate models of populations of cells
- Detailed spiking models can lead to clear experimental predictions.
- Simplified firing rate models allow mathematical analysis and deeper intuitions
- Both have been successful at explaining neural activity and behavior.
- The equations of simplified models can be similar to trained (AI-style) RNNs
- The main difference in implementation is that the parameters are not trained but taken directly from neuroscience experiments, or chosen to represent a hypothesis about how the brain computes
- Currently biologically-realistic models make more directly testable predictions for experiments, but are less capable of high-level functions compared to trained RNNs.



Amit & Brunel, *Cerebral Cortex*, 1997; Wang, *Neuron*, 2002; Wong & Wang, *J. Neurosci.*, 2006

10

10


Quiz – blackboard

- pros and cons of using biologically-realistic models versus trained RNNs to simulate a cognitive task

11

11

Most brain functions emerge from interactions of many areas – a challenge for local RNNs



12

How do we build a dynamical model of the whole cortex?

Step 1/6: building blocks – local circuit models

13

13

Canonical local cortical circuit

“Our view is that the rapid evolutionary expansion of neocortex has been made possible by building an ‘isocortex’ — a structure that uses **repeats of the same basic local circuits throughout a single [cortical] sheet.**”

RJ Douglas and KA Martin (2012)

14

14

A canonical local circuit model

Excitatory and inhibitory populations

At each step in time the firing rate of the Excitatory neurons in area x would drop down towards zero if not for synaptic inputs.

Activity is pushed up by

- positive connections from the Excitatory population to itself
- and long-range inputs from other brain areas y

Activity is pushed down by

- negative inputs from the Inhibitory population

The size of the response to input depends on the slope. Chaudhuri et al., *Neuron*, 2015
w, β , τ set to match Binzegger et al (2009)

The time constant determines how quickly the rate can rise and fall in response to input
Firing rates cannot be negative.


15

How do we build a dynamical model of the whole cortex?


Step 1/6: building blocks – local circuit models

Step 2/6: connect the blocks – anatomical connectivity data


16



17




18




19

19




20

20




21

21




22

22



23




24

How do qualitatively different functions emerge across the cortex?

25

25




Prof. Ghrist


26

26

13



27



28

How do we build a dynamical model of the whole cortex?

Step 1/6: building blocks – local circuit models

Step 2/6: connect the blocks – anatomical connectivity data



Step 3/6: (large-scale 2.0) allow local variation of circuit properties, based on data

Step 4/6: (large-scale 2.0) simulate task stimuli as input & measure activity

29

29

Working memory activity across cortical areas and multiple cell types



Froudist-Walsh et al., *Neuron*, 2021
see also
Mejias & Wang, *eLife*, 2022

30

30

15

How do we build a dynamical model of the whole cortex?

Step 1/6: building blocks – local circuit models

Step 2/6: connect the blocks – anatomical connectivity data

Step 3/6: (large-scale 2.0) allow local variation of circuit properties, based on data

Step 4/6: (large-scale 2.0) simulate task stimuli as input & measure activity


Step 5/6: (large-scale 2.0) validate model against real neural data

31

31

The model captures the persistent activity pattern of > 90 experimental studies

mega-analysis of experimental data - Leavitt et al., *TiCS*, 2017



model simulation - Froudast-Walsh et al., *Neuron*, 2021

32

32


How do we build a dynamical model of the whole cortex?

- Step 1/6: building blocks – local circuit models
- Step 2/6: connect the blocks – anatomical connectivity data
- Step 3/6: (large-scale 2.0) allow local variation of circuit properties, based on data
- Step 4/6: (large-scale 2.0) simulate task stimuli as input & measure activity
- Step 5/6: (large-scale 2.0) validate model against real neural data
- Step 6/6: (large-scale 2.0) make predictions for future experiments

33

33

“Zoom in” to find the cell-type responsible for distractor-resistance

Froudist-Walsh et al., *Neuron*, 2021

34

17

Now you have a dynamical model of the whole cortex and predictions for new experiments

35

35

Quiz - blackboard

What is the sequence of steps for building a whole-cortex model?

36

36

Recurrent neural networks (RNNs) in AI

- The basic ("vanilla") RNN

Elman, *Cog. Sci.*, 1990

37


$$a(t) = f(W_{x \rightarrow a} x(t) + W_{a \rightarrow a} a(t-1) + b_1)$$

$$o(t) = g(W_{a \rightarrow o} a(t) + b_2)$$

The **hidden layer activity** is a **nonlinear function** (e.g. ReLU, sigmoid) of a **weighted sum** of the **inputs** and a **weighted sum** of the **hidden layer activity from one timestep ago** plus a **bias**. The **output layer activity** is a **nonlinear function** of the **hidden layer activity** plus a **bias**.

37

The mathematical equivalence of (some) feedforward and recurrent neural networks




van Bergen & Kriegeskorte, *Curr. Opin. Neurobiol.*, 2020 38

38

19

Leaky RNNs for neuro-AI



Continuous time version (written in papers)

$$\tau \frac{da}{dt} = -a(t-1) + f(W_{x \rightarrow a} x(t) + W_{a \rightarrow a} a(t-1) + b_1)$$

Discrete time version (Euler method - written in code)

$$a(t) = a(t-1) + \frac{\Delta t}{\tau} (-a(t-1) + f(W_{x \rightarrow a} x(t) + W_{a \rightarrow a} a(t-1) + b_1))$$

Δt is the length of the simulation timestep. Logically, shorter timesteps lead to smaller changes in activity between timesteps.

τ is the neuronal time constant, which dictates how rapidly the activity changes in response to inputs/leak.

$$o(t) = g(W_{a \rightarrow o} a(t) + b_2)$$

39

39

Quiz - blackboard

- Comparing feedforward and recurrent neural networks.

40

40

Recap

- Recurrent connections enable neural networks to use and compute on previous information, which contributes to many cognitive functions, including memory and decision-making
- The whole cortex is recurrent, but most recurrent connections are from other neurons within the same brain area.
- Biologically-realistic models make more directly testable predictions for experiments, but are less capable of high-level functions compared to trained RNNs.
- Most brain functions rely on activity across many different brain areas
- Whole cortex models are built up by connecting many local circuits and adjusting parameters across areas according to anatomy
- There is an increase in the time constants of neurons along the cortical (visual and auditory) hierarchy
- RNNs are like feedforward networks, but with inputs from the previous timestep
- Some feedforward and recurrent neural networks are mathematically equivalent
- In neuroscience, leaky RNNs are often used to allow for more biologically-realistic neural dynamics

41

41

Still curious? You can dive in deeper to any of today's topics:


- Most cortical connections are from within the same brain area
 - Markov, Nikola T., P. Misery, Arnaud Falchier, C. Lamy, J. Vezoli, R. Quilodran, M. A. Gariel et al. "Weight consistency specifies regularities of macaque cortical networks." *Cerebral cortex* 21, no. 6 (2011): 1254-1272.
- An early cortex-wide dynamical model
 - Chaudhuri, Rishidev, Kenneth Knoblauch, Marie-Alice Gariel, Henry Kennedy, and Xiao-Jing Wang. "A large-scale circuit mechanism for hierarchical dynamical processing in the primate cortex." *Neuron* 88, no. 2 (2015): 419-431.
- A cortex-wide dynamical model of working memory
 - Froudast-Walsh, Sean, Daniel P. Bliss, Xingyu Ding, Lucija Rapan, Meiqi Niu, Kenneth Knoblauch, Karl Zilles, Henry Kennedy, Nicola Palomero-Gallagher, and Xiao-Jing Wang. "A dopamine gradient controls access to distributed working memory in the large-scale monkey cortex." *Neuron* 109, no. 21 (2021): 3500-3520.
- Comparing feedforward and recurrent neural networks
 - van Bergen, Ruben S., and Niklaus Kriegeskorte. "Going in circles is the way forward: the role of recurrence in visual inference." *Current Opinion in Neurobiology* 65 (2020): 176-193.
- The "vanilla" RNN paper
 - Elman, Jeffrey L. "Finding structure in time." *Cognitive science* 14, no. 2 (1990): 179-211.

42

42

21

Next: training deep neural networks
and comparisons with brains



video: James DiCarlo (MIT)
Yamins et al., PNAS, 2014

43