
DATA 442: Neural Networks & Deep Learning

Dan Runfola – danr@wm.edu

icss.wm.edu/data442/



Some Reminders

- Piazza
 - I - and the TAs - are checking Piazza regularly.
- Lab 1
 - Launches at midnight tonight! See Piazza for the deadline.
 - We'll be covering the content for lab 1 over the next couple of lectures.

CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY

Image Classification



We must pre-specify a set of labels that we want to choose between.
For example:

Car


Building

Person

Bird

CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY
A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE


34	40	34	3	8	30	50	26	16	28	41	6	23	2	24	0
14	37	19	25	6	9	14	17	4	46	20	7	38	6	29	28
4	39	0	29	15	6	50	2	21	10	8	45	150	145	106	46
42	10	15	19	24	18	111	123	118	104	119	122	117	140	138	28
21	35	19	30	14	143	146	147	142	103	109	127	108	148	20	23
30	105	147	102	126	118	108	101	140	131	124	136	47	27	26	38
135	133	137	108	140	144	135	120	118	137	125	43	8	31	45	10
106	142	108	138	137	111	38	36	32	1	19	44	34	4	38	49
122	142	127	131	143	8	47	4	0	31	39	18	46	1	50	25
149	137	122	36	50	19	24	45	16	30	2	47	2	35	29	50
147	115	3	29	10	2	13	1	48	3	45	28	39	14	14	20



CAOE | CENTER FOR ACCELERATING OPERATIONAL EFFICIENCY

A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE


34	40	34	3	8	30	50	26	16	28	41	6	23	2	24	0
14	37	19	25	6	9	14	17	4	46	20	7	38	6	29	28
4	39	0	29	15	6	50	2	21	10	8	45	150	145	106	46
42	10	15	19	24	18	111	123	118	104	119	122	117	140	138	28
21	35	19	30	14	143	146	147	142	103	109	127	108	148	20	23
30	105	147	102	126	118	108	101	140	131	124	136	47	27	26	38
135	133	137	108	140	144	135	120	118	137	125	43	8	31	45	10
106	142	108	138	137	111	38	36	32	1	19	44	34	4	38	49
122	142	127	131	143	8	47	4	0	31	39	18	46	1	50	25
149	137	122	36	50	19	24	45	16	30	2	47	2	35	29	50
147	115	3	29	10	2	13	1	48	3	45	28	39	14	14	20



CAOE | CENTER FOR ACCELERATING OPERATIONAL EFFICIENCY

A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE

34	40	34	3	8	30	50	26	16	28	41	6	23	2	24	0
14	37	19	25	6	9	14	17	4	46	20	7	38	6	29	28
28	6	31	39	0	23	36	34	21	10	8	45	6	29	45	46
71	6	9	44	41	23	36	61	4	104	119	122	117	140	138	28
8	60	45	11	12	165	122	115	142	103	109	127	108	148	100	23
2	94	156	88	174	160	62	59	140	131	124	136	127	150	145	38
183	94	160	101	108	163	135	119	118	137	125	43	8	31	45	10
128	179	74	122	89	140	59	22	32	1	19	44	34	4	38	49
165	100	106	172	110	41	58	11	0	31	39	18	46	1	50	25
154	175	158	76	53	58	61	69	16	30	2	47	2	35	29	50
153	138	43	12	19	40	62	26	48	3	45	28	39	14	14	20



GAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY
DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE

Viewpoint



Lighting



Background



Background




Deformation

CAC
A DEPARTMENT



Deformation




Occlusion



```
letterT = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

**12 Row * 10 Column
Resolution Data**



E | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY

A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE


```
def imageClassifier(letter):  
    # Pick a label based on the data input  
    predictedLabel = "Some Letter"  
  
    return(predictedLabel)  
  
print(imageClassifier(letterT))
```

ING
BY
NCE

32 "1" Values


```
letterT = [0 0 0 0 0 0 0 0 0 0
           0 1 1 1 1 1 1 1 1 0
           0 1 1 1 1 1 1 1 1 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 1 1 0 0 0 0
           0 0 0 0 0 0 0 0 0 0]
```

```
def imageClassifier(letter):
    if(sum(letter) == 32):
        predictedLabel = "T"


    # Pick a label based on the data input

    return(predictedLabel)

print(imageClassifier(letterT))
```



(a)




(b)

```
def imageClassifier(letter):
    #Detect number of line intersections
    #(For the case of "T", this would be 1 intersection)
    intersections = 1


    if(intersections == 1):
        predictedLabel = "T"
    # Pick a label based on the data input

    return(predictedLabel)

print(imageClassifier(letterT))
```



(a)



(b)



JOE
MENT OF HON

Machine Learning & AI



1) Curate / Label a Huge Dataset of Images

```
def train(observedImages, humanLabels):  
    #Teach the model all of the exceptions and rules  
    return imageClassifier
```

2) Train a Classifier

```
def predict(imageClassifier, myNewImage):  
    #Use the classifier  
    return predictedLabel
```

3) Test How Well It Does on Data It's Never Seen

Nearest Neighbor & Imagery

```
def train(observedImages, humanLabels):  
    #Teach the model all of the exceptions and rules  
    return imageClassifier
```

1) Saves All Observations into Memory

```
def predict(imageClassifier, myNewImage):  
    #Use the classifier  
    return predictedLabel
```

2) Compares and Contrasts Input to all Observations to Select Most Similar

ACCELERATING
EFFICIENCY

A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE

Example Training Data


```
letterT = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

```
letterI = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```


CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY
A COMMITMENT TO EXCELLENCE

```
letterI = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

T from Training Data



T to Recognize



T from Training Data

[illegible]

T to Recognize

[illegible]

Nearest Neighbor - L1 Distance

$$L_1(I_1, I_2) = \sum_p |I_{1,p} - I_{2,p}|$$

L_1 = L1 Distance

$$I_i = \text{Image } i$$

p = Index for a given pixel in image

$$I_{i,p} = \text{Value for a given pixel } p \text{ in image } I$$

Sum of Absolute Difference: 10

T from Training Data

T we want to Recognize

$$L_1(I_1, I_2) = \sum_p |I_{1,p} - I_{2,p}|$$

L_1 = L1 Distance

I_i = Image i

p = Index for a given pixel in image

$I_{i,p}$ = Value for a given pixel p in image I

```
import numpy as np
def L1Norm(imageA, imageB):
    print("Total number of black pixels in Image A: " +
          str(np.sum(imageA)))

    print("Total number of black pixels in Image B: " +
          str(np.sum(imageB)))

    pixelWiseDiff = str(np.sum(np.abs(np.asarray(imageA) - np.asarray(imageB))))
    print("Absolute pixelwise difference: " +
          pixelWiseDiff)

    return(pixelWiseDiff)
```

```
L1Norm(letterT, testedT)
```

```
Total number of black pixels in Image A: 32
Total number of black pixels in Image B: 30
Absolute pixelwise difference: 10
```

ERATING
IENCY
CELLENCE

[illegible][illegible]

```
letterI = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
            0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
            0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
            0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
            0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

```
testedT = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,  
           0, 0, 1, 1, 1, 1, 1, 1, 0, 0,  
           0, 0, 1, 1, 1, 1, 1, 1, 0, 0,  
           0, 0, 1, 0, 1, 1, 0, 1, 0, 0,  
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,  
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,  
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,  
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,  
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,  
           0, 0, 0, 1, 1, 1, 1, 0, 0, 0,  
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0,  
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

```
training = {}
training["T"] = letterT
training["l"] = letterl
training["I"] = letterI

predictLetter = testedT
estimates = {}
for l in training:
    distance = L1Norm(training[l], predictLetter)
    estimates[l] = distance

print(estimates)
```

```
{'T': '10', 'l': '14', 'I': '18'}
```


Interlude - Numpy

```
letterT = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 1, 1, 1, 1, 1, 1, 1, 1, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
           0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY

```
letterT = np.asarray(letterT)
print(letterT)
```

SECURITY CENTER OF EXCELLENCE

```
[0 0 0 0 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 0 0 1 1 1 1 1 1 1 0 0 0 0 0 1 1 0
 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0
 1 1 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0
 0 0 0 0 0 0 0 0]
```

A toy nearest neighbor classifier

```
class NearestNeighborSinglePrediction:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        l1Distances = np.sum(np.abs(self.Xtr - X[0]), axis=1)
        minimumDistance = np.argmin(l1Distances)
        Ypred = self.ytr[minimumDistance]

        return Ypred
```

INSTITUTE FOR ACCELERATING
INTEGRATIONAL EFFICIENCY
SECURITY CENTER OF EXCELLENCE

A toy nearest neighbor classifier

```
class NearestNeighborSinglePrediction:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        l1Distances = np.sum(np.abs(self.Xtr - X[0]), axis=1)
        minimumDistance = np.argmin(l1Distances)
        Ypred = self.ytr[minimumDistance]

        return Ypred
```

INSTITUTE FOR ACCELERATING
OPERATIONAL EFFICIENCY
SECURITY CENTER OF EXCELLENCE

A toy nearest neighbor classifier

```
class NearestNeighborSinglePrediction:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        l1Distances = np.sum(np.abs(self.Xtr - X[0]), axis=1)
        minimumDistance = np.argmin(l1Distances)
        Ypred = self.ytr[minimumDistance]

        return Ypred
```

```
trainingX = [letterT, letterI, letterL]
trainingy = np.array(["T", "I", "L"])

nn = NearestNeighborSinglePrediction()
nn.train(X=trainingX, y=trainingy)
estimates = nn.predict(X=[testLetter])

print(estimates)
```

INSTITUTE FOR ACCELERATING
OPERATIONAL EFFICIENCY
SECURITY CENTER OF EXCELLENCE

T

A toy nearest neighbor classifier

```
class NearestNeighborSinglePrediction:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        l1Distances = np.sum(np.abs(self.Xtr - X[0]), axis=1)
        minimumDistance = np.argmin(l1Distances)
        Ypred = self.ytr[minimumDistance]

        return Ypred
```

```
for l in training:
    distance = L1Norm(training[l], predictLetter)
    estimates[l] = distance
```

A toy nearest neighbor classifier

l

=

```
testedL = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 1, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 1, 1, 0, 0,
            0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
            0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

T

=

```
testedT = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
            0, 0, 1, 1, 1, 1, 1, 1, 0, 0,
            0, 0, 1, 1, 1, 1, 1, 1, 0, 0,
            0, 0, 1, 0, 1, 1, 0, 1, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 0, 1, 1, 0, 0, 0, 0,
            0, 0, 0, 1, 1, 1, 1, 0, 0, 0,
            0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
            0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```


A toy nearest neighbor classifier

```
class NearestNeighbor:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        #We'll be doing our test for every input X this time,
        #just in case we want to test multiple
        #cases (As we'll be doing later!)

        #Create an empty list to hold our results
        #Note the dtype tells Numpy if the output (y) estimates
        #should be a float, integer, or string based on the training y.
        Ypred = np.zeros(len(X), dtype=np.dtype(self.ytr.dtype))

        for i in range(0, len(X)):
            l1Distances = np.sum(np.abs(self.Xtr - X[i]), axis=1)
            minimumDistance = np.argmin(l1Distances)
            Ypred[i] = self.ytr[minimumDistance]

        return Ypred
```

```
nn = NearestNeighbor()
nn.train(X=trainingX, y=trainingy)
estimates = nn.predict(X=[testLetter, testLetter2])

print(estimates)
```

['T', '1']

A toy nearest neighbor classifier

```
class NearestNeighbor:
    def __init__(self):
        pass

    def train(self, X, y):
        #For nearest neighbor, we just copy the data for later use.
        self.Xtr = X
        self.ytr = y

    def predict(self, X):
        #We'll be doing our test for every input X this time,
        #just in case we want to test multiple
        #cases (As we'll be doing later!)

        #Create an empty list to hold our results
        #Note the dtype tells Numpy if the output (y) estimates
        #should be a float, integer, or string based on the training y.
        Ypred = np.zeros(len(X), dtype=np.dtype(self.ytr.dtype))

        for i in range(0, len(X)):
            l1Distances = np.sum(np.abs(self.Xtr - X[i]), axis=1)
            minimumDistance = np.argmin(l1Distances)
            Ypred[i] = self.ytr[minimumDistance]

        return Ypred
```

Slow! We have to compare every single case in our training data to every input.

FOR ACCELERATING
AL EFFICIENCY
CENTER OF EXCELLENCE

Example: Nearest Neighbor & CIFAR 10

airplane



automobile



bird



cat



deer



dog




frog



horse



ship



truck



60,000 Images

50,000 Training

10,000 Testing

32 x 32 Pixels


10 Classes (shown to left)

CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY
ID SECURITY CENTER OF EXCELLENCE



K Nearest Neighbors


In this example, we have multiple examples of letters we're using for training. Every red dot is an "A", and every blue dot is a "T". The yellow dot is representative of a hand-written T, that we're trying to identify the letter of.



Pixelwise Difference Between Test Image and Observed Image


K Nearest Neighbors

Most similar letter with a L1 Distance of ~ 10 .



Pixelwise Difference Between Test Image and Observed Image

K=3 Nearest Neighbors



Pixelwise Difference Between Test Image and Observed Image







	N=1	N=2	N=3	N=4	N=5	N=6	N=7	N=8	N=9	N=10
Airplane	0	0	0	0	20%	16%	14%	13%	22%	20%
Car	0	0	0	0	0	0	0	13%	11%	10%
Bird	0	0	0	0	0	0	0	0	0	0
Cat	100%	50%	66%	50%	40%	50%	43%	37%	33%	30%
Deer	0	0	0	0	0	0	0	0	0	0
Dog	0	0	0	0	0	0	0	0	0	0
Frog	0	50%	33%	50%	40%	34%	43%	37%	33%	30%
Horse	0	0	0	0	0	0	0	0	0	0
Ship	0	0	0	0	0	0	0	0	0	10%
Truck	0	0	0	0	0	0	0	0	0	0



KNN - Distance Metric pt 2.

$$L_1(I_1, I_2) = \sum_p |I_{1,p} - I_{2,p}| \quad L_2(I_1, I_2) = \sqrt{\sum_p (I_{1,p} - I_{2,p})^2}$$



KNN - Distance Metric pt 2.

$$L_1(I_1, I_2) = \sum_p |I_{1,p} - I_{2,p}| \quad L_2(I_1, I_2) = \sqrt{\sum_p (I_{1,p} - I_{2,p})^2}$$



Hyperparameters


How do we choose the right K?

How do we choose between L1 and L2?


CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY

Both of these are **hyperparameters** - settings we choose about the algorithm that are not learned from the data.


Choosing Hyperparameters




Choosing Hyperparameters



Choosing Hyperparameters



Cross Validation



KNN

- Great as an example for some basic machine learning terminology.
- Not great for actual use.
 - Operational use very slow (training is fast, prediction is slow).
 - Simple distance metrics can't capture perceptual differences that matter.
 - “Curse of Dimensionality”


A DEPARTMENT OF HOMELAND SECURITY CENTER OF EXCELLENCE

Dimensionality of Images

“Normal Data”

Dimensions: 2

Observation	Height	Weight
A	3ft	10lb
B	4ft	20lb
C	5ft	30lb




Dimensionality of Images

“Normal Data”

Dimensions: 2

Observation	Height	Weight
A	3ft	10lb
B	4ft	20lb
C	5ft	30lb




Dimensionality of Images

“Normal Data”

Dimensions: 2

Observation	Height	Weight	Age
A	3ft	10lb	5
B	4ft	20lb	5
C	5ft	30lb	5



Dimensionality of Images

Image Data

Dimensions: Thousands

Observations: 3

Observation	Pixel 1	Pixel 2	...	Pixel 12000	Pixel 12001
A	10	10		25	85
B	20	20		35	75
C	30	30		65	95

Recap

- We are exploring the topic of image classification, in which we are using a large training set of images that have human-created labels, and we are using this to predict the correct labels for a test set of data.
- KNN is an example of how you can do this, though not a good one. It predicts based on the nearest training example.
- In the case of KNN, the distance metric (L1 vs. L2) and K are the hyperparameters you must choose.
- A validation set and test set allow you to choose appropriate hyperparameters.
- For small datasets, cross-fold validation can improve the robustness of your results.

CAOE | CENTER FOR ACCELERATING
OPERATIONAL EFFICIENCY

Reminders

- Remember to check in on Piazza with any questions!
- Piazza will also have information on the first lab.
- Group study is encouraged, but your submissions should be your own!