Comparison of AdamW and Muon for LoRA Fine-Tuning of Qwen2.5-0.5B

Danil Eremenko

March 2026

Abstract

This report compares AdamW and Muon for LoRA fine-tuning of Qwen2.5-0.5B on a consumer AMD GPU. The experiments use a matched setup with 5,000 training samples from OpenWebText-100k, sequence length 512, batch size 4, and 2 epochs. We evaluate the optimizers by convergence proxy, wall-clock time, peak GPU memory, optimizer-step overhead, and downstream quality on PIQA. In the tuned matched runs, AdamW and Muon reached very similar final training losses, but AdamW was substantially faster while using essentially the same peak memory. PIQA results were nearly identical for the two fine-tuned models and slightly below the unfine-tuned base model, suggesting that short generic-text fine-tuning did not improve a commonsense QA benchmark in this setting.

1 Introduction

Optimizer choice affects both training dynamics and practical efficiency. The task for this project is to compare optimization strategies for Qwen2.5-0.5B LoRA fine-tuning using training time, maximum memory usage, final model quality, and convergence as the main criteria. The required training data source is at least 1% of OpenWebText-100k, and the evaluation benchmark is PIQA. The baseline optimizers required by the task are AdamW and Muon.

The present work focuses on a reproducible base-task comparison between AdamW and Muon on a single AMD Radeon RX 7900 XTX GPU under ROCm.

2 Experimental Setup

2.1 Hardware and software

Experiments were run on an AMD Radeon RX 7900 XTX with ROCm-enabled PyTorch. The training code uses Hugging Face Transformers and PEFT, but the training loop itself is implemented manually.

2.2 Model and adaptation setup

The base model is Qwen2.5-0.5B. LoRA was applied to the `q_proj` and `v_proj` modules with rank $r = 8$, $\alpha = 16$, and dropout 0.1. Only LoRA adapter weights were trainable.

A parameter routing inspection showed that the Muon branch received 96 trainable tensors totaling 540,672 elements, while the auxiliary Adam branch received zero trainable parameters. Therefore, although the code path used a Muon wrapper capable of handling an Adam side branch,

the actual Muon experiments in this report were effectively pure Muon on the trainable LoRA weights.

2.3 Training data and workload

All main experiments used the same workload: 5,000 samples from `Elriggs/openwebtext-100k`, sequence length 512, batch size 4 and 2 epochs.

A learning-rate sweep was performed separately for AdamW and Muon:

- AdamW: 10^{-4}, $3 \cdot 10^{-4}$, 10^{-3}, $3 \cdot 10^{-3}$
- Muon: $3 \cdot 10^{-4}$, 10^{-3}, $3 \cdot 10^{-3}$, 10^{-2}

2.4 Metrics

For each run, the following quantities were recorded: total training time, peak GPU memory, average loss over the last 10 logged points, final logged loss, average per-step time and average optimizer-step time.

For downstream quality, the best tuned AdamW and Muon checkpoints were evaluated on PIQA with `lm-evaluation-harness`. The unfine-tuned base model was also evaluated as a reference point.

3 Results

3.1 Learning-rate sweep

Figure 1 shows the average loss over the last ten logged points across the learning-rate sweep. For both optimizers, the best result was obtained at a learning rate of 10^{-3}. Muon degraded sharply at 10^{-2}, while AdamW was comparatively stable across the tested range.



Figure 1: Average loss over the last 10 logged points as a function of learning rate.

Figure 2 shows that AdamW remained faster than Muon across the sweep. The wall-clock gap is modest at the full-run level but consistent.



Figure 2: Total training time as a function of learning rate.

3.2 Best matched comparison

Table 1 reports the best run for each optimizer under the matched workload. AdamW and Muon reached very similar training losses, with AdamW slightly lower on both the final logged loss and the average over the last ten logged points. The main practical difference is runtime: AdamW finished about 79.5 seconds faster. Peak memory was effectively identical.

Table 1: Best tuned matched runs (5,000 samples, 2 epochs, sequence length 512, batch size 4).

Optimizer	LR	Time (s)	Peak mem (GB)	Final loss	Avg. last 10	Avg. opt. step (s)
AdamW	0.001	319.31	7.546	2.496	2.517	0.0009
Muon	0.001	398.84	7.544	2.503	2.529	0.0293

3.3 PIQA evaluation

PIQA results are shown in Table 2. The unfine-tuned base model achieved the highest PIQA accuracy in this comparison. Both fine-tuned models obtained nearly identical PIQA scores, and both were slightly lower than the base model. This indicates that short generic-text fine-tuning on OpenWebText does not meaningfully improve PIQA in this setup.

Table 2: PIQA evaluation results.

Model	Accuracy
Base Qwen2.5-0.5B	0.7051
AdamW fine-tuned	0.6997
Muon fine-tuned	0.6997

4 Discussion

The PIQA results show that the fine-tuning corpus and evaluation benchmark matter. OpenWeb-Text is a generic web-text corpus, while PIQA is a physical commonsense reasoning benchmark. Under short fine-tuning with only 5,000 text samples, neither optimizer produced a measurable PIQA gain relative to the base model. This suggests that the training objective improved adaptation to the training distribution more than it improved task-specific reasoning ability.

5 Conclusion

For LoRA fine-tuning of Qwen2.5-0.5B on an RX 7900 XTX under a matched 5,000-sample, 2-epoch setup, AdamW and Muon achieved similar training losses, but AdamW was materially faster and used the same amount of peak memory. PIQA evaluation showed no downstream advantage for either fine-tuned model over the base model in this experiment. Therefore, within this specific low-rank adapter training regime, AdamW is the stronger practical baseline.

A natural next step is to test Muon in a denser trainable-parameter regime, such as partial or full-model fine-tuning, or to implement the challenge-mode hybrid split where distinct trainable parameter groups are intentionally assigned to Muon and AdamW.

A Sweep summary

Table 3 lists all runs included in the learning-rate sweep.

Table 3: Learning-rate sweep summary.

Run	LR	Time (s)	Peak mem (GB)	Final loss	Avg. last 10
adamw_lora_lr1e4	0.0001	318.07	7.546	2.515	2.538
adamw_lora_lr3e4	0.0003	318.94	7.546	2.507	2.530
adamw_lora_lr1e3	0.001	319.31	7.546	2.496	2.517
adamw_lora_lr3e3	0.003	318.67	7.546	2.503	2.523
muon_lora_lr3e4	0.0003	398.51	7.544	2.509	2.534
muon_lora_lr1e3	0.001	398.84	7.544	2.503	2.529
muon_lora_lr3e3	0.003	395.45	7.544	2.509	2.532
muon_lora_lr1e2	0.01	398.45	7.544	6.141	6.073