Quick Reference Card

Your cheat sheet for GitHub Copilot CLI commands, syntax, and workflows.

Last updated: 2026-02-02

Three Interaction Modes

Mode	How to Use	Best For
Interactive	`copilot`	Exploration, multi-turn conversations, iteration
Plan	`/plan` or `Shift+Tab`	Complex tasks, reviewing approach before coding
Programmatic	`copilot -p "prompt"`	Automation, scripts, CI/CD pipelines

Essential Slash Commands

Core Commands

Command	Description
`/help`	Show available commands
`/clear`	Clear conversation history
`/model`	Show or switch AI model
`/exit`	End the session
`/plan`	Create implementation plan before coding
`/review`	Run code-review agent on staged/unstaged changes
`/delegate`	Hand off task to Copilot coding agent on GitHub
`/diff`	Review changes made in current directory (experimental)

Session Management

Command	Description
`/session`	Show session info and workspace summary
`/usage`	Display session usage metrics

`/context`	Show context window token usage
`/compact`	Summarize conversation to reduce context
`/share`	Export session as markdown or GitHub gist
`/rename`	Rename the current session
`/resume`	Switch to a different session
`/tasks`	View background subagents and detached shell sessions

Permissions

Command	Description
`/allow-all`	Auto-approve all permission prompts (use with caution)
`/yolo`	Alias for `/allow-all`

Directory Access

Command	Description
`/add-dir <path>`	Add a directory to allowed list
`/list-dirs`	Show all allowed directories
`/cwd` or `/cd`	View or change working directory

Authentication

Command	Description
`/login`	Log in to GitHub Copilot
`/logout`	Log out of GitHub Copilot

Configuration

Command	Description
`/theme`	View or set terminal theme
`/terminal-setup`	Enable multiline input support
`/user`	Manage GitHub accounts
`/feedback`	Submit feedback to GitHub
`/init`	Initialize Copilot instructions for repository
`/experimental`	Toggle experimental features on/off

> 📖 **Official docs**: *CLI command reference*

@ Syntax for Context

File References

```
@filename.js                # Single file
@samples/src/api/users.js   # File with path
@samples/src/               # Entire directory
@samples/src/**/*.js        # Glob pattern
```

Multiple Files

```
> @samples/src/auth/login.js @samples/src/auth/register.js Compare these implementations
> @samples/src/api/ Generate tests for all API endpoints
```

Best Practices

- Start specific, expand if needed
- Use glob patterns for targeted searches
- Combine files for cross-file analysis

Built-in Agents

Agent	How to Invoke	Purpose
Plan	`/plan` or `Shift+Tab`	Step-by-step implementation plans
Code-review	`/review`	Focused review of staged/unstaged changes
Explore	*Automatic*	Codebase analysis (used internally)
Task	*Automatic*	Tests, builds, lints (success = brief summary, failure = full details)

Use `/agent` to browse and select from your custom agents.

📚 Agents Documentation

Custom Agents

Create `AGENTS.md` or `*.agent.md` files:

```
---
name: frontend
description: Frontend specialist with expertise in React and TypeScript
tools: ["read", "edit", "search"]
---

## Frontend Agent

You are a frontend specialist with expertise in React and TypeScript.
```

```
**Focus Areas**:
- Component architecture
- Accessibility (WCAG 2.1 AA)
- Performance optimization
```

> 💡 **Required**: The `description` field in YAML frontmatter is required. Other fields like `name`, `tools`, and `target` are optional. Tool aliases: `read`, `edit`, `search`, `execute`, `web`, `agent`.
>
> 📖 **Official docs**: *Custom agents configuration*

Agents vs Skills

	Agents	Skills
Analogy	Hiring a specialist	Giving a detailed checklist
Invocation	**Manual** (`/agent` or `--agent`)	**Automatic** (prompt matching)
Scope	Broad expertise	Specific task
YAML required	`description`	`name` + `description`

Key insight: Agent = *who* helps you. Skill = *what procedure* they follow.

Skills System

Using Skills

Skills are **automatically triggered** based on your prompt matching the skill's description:

```
> Review this code for security issues
# Your "security-audit" skill activates automatically

> Generate tests for the login function
# Your "generate-tests" skill activates automatically
```

Managing Installed Skills

Command	Purpose
`/skills list`	Show all installed skills
`/skills info <name>`	Get skill details
`/skills add <name>`	Enable a skill
`/skills remove <name>`	Disable a skill
`/skills reload`	Reload after editing

> *Skills trigger automatically when your prompt matches their description - no manual activation needed.*

Creating Skills

Create `~/.copilot/skills/skill-name/SKILL.md` :

```
---
name: my-skill
description: What this skill does and when to use it
---

# My Skill

Instructions for the skill...
```

Required properties: `name` (lowercase, hyphens), `description` . Optional: `license` .

> 📖 **Official docs**: *About Agent Skills*

MCP Servers

Common Servers

Server	Purpose
`github`	Issues, PRs, repositories (included by default)
`filesystem`	Enhanced file operations
`postgres`	Database inspection

Using MCP

```
> Get issue #42 details          # Uses GitHub MCP
> List open PRs                   # Uses GitHub MCP
> Create a PR for this branch     # Uses GitHub MCP
```

> 📖 **Official docs**: *About MCP*

Plugins

Extend GitHub Copilot CLI with community plugins:

Command	Purpose
`/plugin list`	See installed plugins
`/plugin marketplace`	Browse available plugins
`/plugin install <name>`	Install a plugin

Common Workflows

Security Review

```
copilot -p "Review @samples/src/auth/ for security vulnerabilities"
```

Code Review

```
copilot
> /review                        # Review staged changes
> @samples/src/api/users.js Review for security, performance, best practices
```

Test Generation

```
copilot -p "@samples/src/utils/helpers.js Generate Jest tests with edge cases"
```

Debugging

```
copilot
> @samples/buggy-code/js/paymentProcessor.js Users report $10.20 + $5.10 shows as $15.299999
> Debug why this happens
```

Git Commit Message

```
copilot -p "Generate commit message for: $(git diff --staged)"
```

PR Description

```
copilot -p "Generate PR description for: $(git log main..HEAD --oneline)"
```

Model Selection

Model	Best For
`claude-sonnet-4.5`	Default, balanced
`claude-opus-4.5`	Complex architecture decisions
`gpt-5-mini`	Quick tasks (non-premium)
`gpt-4.1`	Routine code generation (non-premium)

```
> /model claude-opus-4.5    # Switch model
> /model                    # See available models
```

Session Persistence

Save and Resume

```
# Save current session
> /rename feature-auth

# Later, resume it
copilot --resume feature-auth

# Or continue last session
copilot --continue
```

CI/CD Integration

Basic Usage

```
copilot -p "Security review of @$file" --silent >> review.md
```

Pre-commit Hook Example

```bash
#!/bin/bash
STAGED=$(git diff --cached --name-only --diff-filter=ACM | grep -E '\.(js|ts)$')
for file in $STAGED; do
  copilot -p "Quick security review of @$file - critical issues only"
done
```

> 📖 **Official docs**: *Use hooks*

Quick Tips

1. **Use `-p` for one-off questions** - Faster than interactive mode
2. **Reference files with `@`** - Gives Copilot full context
3. **Use `/plan` for complex tasks** - Review approach before coding
4. **Switch models for different tasks** - Opus for architecture, mini for routine
5. **Save sessions** - Resume work later with full context
6. **Use `--silent` in scripts** - Cleaner CI/CD output

Keyboard Shortcuts

Shortcut	Action
`Shift+Tab`	Toggle Plan Mode
`Ctrl+C`	Cancel current operation
`Esc`	Cancel current input or exit menus
`Ctrl+L`	Clear the screen
`!command`	Run shell command directly (e.g., `!git status`)

Resources

- GitHub Copilot CLI for Beginners Course Repository
- GitHub Copilot CLI Docs
- MCP Server Registry

Generated from GitHub Copilot CLI for Beginners course materials.