

Markov Chain Monte Carlo Diagnostics

Michael Betancourt

2023-07-01

Table of contents

1	Compilation	2
2	Extraction	3
3	Hamiltonian Monte Carlo Diagnostics	4
3.1	Check Hamiltonian Monte Carlo Diagnostics	4
3.2	Integrator Inverse Metric Elements	9
3.3	Integrator Step Sizes	10
3.4	Numerical Trajectory Lengths	11
3.5	Average Proxy Acceptance Statistic	13
3.6	Divergence-Labeled Pairs Plot	13
4	Expectand Diagnostic Functions	19
4.1	xihat	20
4.2	Frozen Chains	24
4.3	Split Rhat	25
4.4	Integrated Autocorrelation Time	28
4.5	All Expectand Diagnostics	32
4.6	Empirical Autocorrelation Visualization	41
4.7	Chain-Separated Pairs Plot	43
5	Markov Chain Monte Carlo Estimation	45
6	Demonstration	49
	License	75
	Original Computing Environment	76

In this short note I will preview the new suite of Markov chain Monte Carlo analysis tools

that I will be introducing more formally in upcoming writing. These tools largely focus on diagnostics but there are also a few that cover Markov chain Monte Carlo estimation assuming a central limit theorem.

We'll start with diagnostics specific to Hamiltonian Monte Carlo then consider more generic diagnostics that consider each expectand of interest one at a time. Finally we'll look at a way to visualize one-dimensional pushforward distributions using Markov chain Monte Carlo to estimate bin probabilities.

1 Compilation

Unlike `RStan` the `PyStan2` interface does not automatically cache Stan executables for reuse. This function compiles a given Stan program into an executable and then saves the executable as a `.pkl` object for later use.

```
def compile_model(filename, model_name=None, **kwargs):
    """This will automatically cache models.

    See http://pystan.readthedocs.io/en/latest/avoiding\_recompilation.html"""
    from hashlib import md5

    with open(filename) as f:
        model_code = f.read()
        code_hash = md5(model_code.encode('ascii')).hexdigest()
        if model_name is None:
            cache_fn = 'cached-model-{}.pkl'.format(code_hash)
        else:
            cache_fn = 'cached-{}-{}.pkl'.format(model_name, code_hash)
        try:
            sm = pickle.load(open(cache_fn, 'rb'))
        except:
            sm = pystan.StanModel(model_code=model_code)
            with open(cache_fn, 'wb') as f:
                pickle.dump(sm, f)
        else:
            print("Using cached StanModel")
    return sm
```

Rarely these caches can become corrupted, in which case deleting the `.pkl` file and recompiling can be helpful. On some exceptional systems `.pkl` files have proven to be completely unusable; if you encounter persistent errors then you may have to default to standard `PyStan2` instructions.

2 Extraction

The `extract` function in `PyStan` parses the Markov chain output within a `StanFit` object into a usable format. Due to some unfortunate choices in early development, however, the function behaves a bit awkwardly.

By default it permutes the Markov chain iterations and then aggregates them together. This permutation strips the iterations of their autocorrelations, making it impossible to recover accurate estimates of the Markov chain Monte Carlo estimator error.

There is an optional argument that deactivates the permutation, but that also completely changes the output format. In particular it strips the expectands of their names, requiring that users access each expectand by the order in which they appear in the original Stan program.

Finally the `extract` function also ignores all of the Hamiltonian Monte Carlo diagnostic information emitted at each transition. Instead the `get_sampler_params` function recovers this information, albeit it yet another output format.

To facilitate the analysis of Stan output I've included my own custom extract functions that format the Markov chain Monte Carlo output into named lists, with one named element for each expectand or Hamiltonian Monte Carlo diagnostic. The elements themselves are two-dimensional arrays with the first index denoting the individual Markov chains and the second index denoting the iterations within an individual Markov chain.

```
# Extract unpermuted expectand values from a StanFit object and format
# them for convenient access
# @param stan_fit A StanFit object
# @return A dictionary of two-dimensional arrays for each expectand in
#         the StanFit object. The first dimension of each element
#         indexes the Markov chains and the second dimension indexes the
#         sequential states within each Markov chain.
def extract_expectands(stan_fit):
    nom_params = stan_fit.extract(permuted=False, inc_warmup=False)
    params = { name: numpy.transpose(nom_params[:, :, k])
              for k, name in enumerate(stan_fit.flatnames) }
    return params

# Extract Hamiltonian Monte Carlo diagnostics values from a StanFit
# object and format them for convenient access
# @param stan_fit A StanFit object
# @return A dictionary of two-dimensional arrays for each expectand in
#         the StanFit object. The first dimension of each element
#         indexes the Markov chains and the second dimension indexes the
```

```
# sequential states within each Markov chain.
def extract_hmc_diagnostics(stan_fit):
    diagnostic_names = ['divergent__', 'treedepth__', 'n_leapfrog__',
                        'stepsize__', 'energy__', 'accept_stat__' ]

    nom_params = stan_fit.get_sampler_params(inc_warmup=False)
    C = len(nom_params)
    params = { name: numpy.vstack([ nom_params[c][name]
                                    for c in range(C) ])
              for name in diagnostic_names }
    return params
```

If users are able to modify these functions to accept the output from other interfaces to Stan and return the same output format then all of the following functions will be immediately available. That is all except for the `plot_inv_metric` function which does require a separate PyStan-specific function for extracting adaptation information.

3 Hamiltonian Monte Carlo Diagnostics

Hamiltonian Monte Carlo introduces a suite of powerful diagnostics that can identify obstructions to Markov chain Monte Carlo central limit theorems. These diagnostics are not only extremely sensitive but also probe the behavior of the entire Markov chain state instead of the projections of that state through single expectands.

3.1 Check Hamiltonian Monte Carlo Diagnostics

All of our diagnostics are assembled in this single `check_all_hmc_diagnostics` function.

The first diagnostic looks for unstable numerical Hamiltonian trajectories, or divergences. These unstable trajectories are known to obstruct typical central limit theorem conditions. Divergences arise when the target distribution is compressed into a narrow region; this forces the Hamiltonian dynamics to accelerate which makes them more difficult to accurately simulate.

Increasing `adapt_delta` will on average result in a less aggressive step size optimization that in some cases may improve the stability of the numerical integration but at the cost of longer, and hence more expensive, numerical Hamiltonian trajectories. In most cases, however, the only productive way to avoid divergences is to reparameterize the ambient space to decompress these pinches in the target distribution.

Stan's Hamiltonian Monte Carlo sampler expands the length of the numerical Hamiltonian trajectories dynamically to maximize the efficiency of the exploration. That length, however, is capped at $2^{\text{max_treedepth}}$ steps to prevent trajectories from growing without bound.

When numerical Hamiltonian trajectories are long but finite this truncation will limit the computational efficiency. Increasing `max_treedepth` allow the trajectories to expand further. While the resulting trajectories will be more expensive that added cost will be more than made up for by increased computational efficiency.

The energy fraction of missing information, or E-FMI, quantifies how well the Hamiltonian dynamics are able to explore the target distribution. If the E-FMI is too small then even the exact Hamiltonian trajectories will be limited to confined regions of the ambient space and full exploration will be possible only with the momenta resampling between trajectories. In this case the Markov chain exploration devolves into less efficient, diffusive behavior where Markov chain Monte Carlo estimation is fragile at best.

This confinement is caused by certain geometries in the target distribution, most commonly a funnel geometry where some subset of parameters shrink together as another parameter ranges across its typical values. The only way to avoid these problems is to identify the problematic geometry and then find a reparameterization of the ambient space that transforms the geometry into something more pleasant.

Finally the average proxy accept statistic is a summary for Stan's step size adaptation. During warmup the integrator step size is dynamically tuned until this statistic achieves the target value which defaults to 0.801. Because this adaptation is stochastic the realized average during the main sampling phase can often vary between 0.75 and 0.85.

So long as the target distribution is sufficiently well-behaved then the adaptation should always converge to that target, at least for long enough warmup periods. Small averages indicate some obstruction to the adaptation, for example discontinuities in the target distribution or inaccurate gradient evaluations.

```
# Check all Hamiltonian Monte Carlo Diagnostics
# for an ensemble of Markov chains
# @param diagnostics A dictionary of two-dimensional arrays for
#                   each expectand. The first dimension of each
#                   element indexes the Markov chains and the
#                   second dimension indexes the sequential
#                   states within each Markov chain.
# @param adapt_target Target acceptance proxy statistic for step size
#                   adaptation.
# @param max_treedepth The maximum numerical trajectory treedepth
# @param max_width Maximum line width for printing
def check_all_hmc_diagnostics(diagnostics,
```

```

        adapt_target=0.801,
        max_treedepth=10,
        max_width=72):
    """Check all Hamiltonian Monte Carlo Diagnostics for an
        ensemble of Markov chains"""

    if type(diagnostics) is not dict:
        print('Input variable `diagnostics` is not a standard dictionary!')
        return

    no_warning = True
    no_divergence_warning = True
    no_treedepth_warning = True
    no_efmi_warning = True
    no_accept_warning = True

    messages = []

    C = diagnostics['divergent__'].shape[0]
    S = diagnostics['divergent__'].shape[1]

    for c in range(C):
        local_messages = []

        # Check for divergences
        n_div = sum(diagnostics['divergent__'][c])

        if n_div > 0:
            no_warning = False
            no_divergence_warning = False
            local_messages.append(f' Chain {c + 1}: {n_div:.0f} of {S} '
                                  f'transitions ({n_div / S:.2%}) diverged.')

        # Check for tree depth saturation
        n_tds = sum([ td > max_treedepth
                      for td in diagnostics['treedepth__'][0] ])

        if n_tds > 0:
            no_warning = False
            no_treedepth_warning = False
            local_messages.append(f' Chain {c + 1}: {n_tds:.0f} of {S} '
                                  f'transitions ({n_tds / S:.2%}) saturated.')

```

```

        f'transitions ({n_div / S:.2%}) saturated '
        f'the maximum treedepth of {max_treedepth}.'))

# Check the energy fraction of missing information (E-FMI)
energies = diagnostics['energy__'][c]
numer = sum( [ (energies[i] - energies[i - 1])**2
               for i in range(1, len(energies)) ] ) / S
denom = numpy.var(energies)
if numer / denom < 0.2:
    no_warning = False
    no_efmi_warning = False
    local_messages.append(f' Chain {c + 1}: '
                          f'E-FMI = {numer / denom:.3f}.'))

# Check convergence of the stepsize adaptation
ave_accept_proxy = numpy.mean(diagnostics['accept_stat__'][c])
if ave_accept_proxy < 0.9 * adapt_target:
    no_warning = False
    no_accept_warning = False
    local_messages.append(f' Chain {c + 1}: Average proxy acceptance '
                          f'statistic ({ave_accept_proxy:.3f}) is')
    local_messages.append(' smaller than 90% of the '
                          f'target ({adapt_target:.3f}).')

if len(local_messages) > 0:
    messages.append(local_messages)
    messages.append([' '])

if no_warning:
    desc = ('All Hamiltonian Monte Carlo diagnostics are consistent '
            'with accurate Markov chain Monte Carlo.')
    desc = textwrap.wrap(desc, max_width)
    messages.append(desc)
    messages.append([' '])

if not no_divergence_warning:
    desc = ('Divergent Hamiltonian transitions result from '
            'unstable numerical trajectories. These '
            'instabilities are often due to degenerate target '
            'geometry, especially "pinches". If there are '
            'only a small number of divergences then running ')

```

```

        'with adept_delta larger '
        f'than {adapt_target:.3f} may reduce the '
        'instabilities at the cost of more expensive '
        'Hamiltonian transitions.')
    desc = textwrap.wrap(desc, max_width)
    messages.append(desc)
    messages.append([' '])

if not no_treedepth_warning:
    desc = ('Numerical trajectories that saturate the '
            'maximum treedepth have terminated prematurely. '
            f'Increasing max_depth above {max_treedepth} '
            'should result in more expensive, but more '
            'efficient, Hamiltonian transitions.')
    desc = textwrap.wrap(desc, max_width)
    messages.append(desc)
    messages.append([' '])

if not no_efmi_warning:
    desc = ('E-FMI below 0.2 arise when a funnel-like geometry '
            'obstructs how effectively Hamiltonian trajectories '
            'can explore the target distribution.')
    desc = textwrap.wrap(desc, max_width)
    messages.append(desc)
    messages.append([' '])

if not no_accept_warning:
    desc = ('A small average proxy acceptance statistic '
            'indicates that the adaptation of the numerical '
            'integrator step size failed to converge. This is '
            'often due to discontinuous or imprecise '
            'gradients.')
    desc = textwrap.wrap(desc, max_width)
    messages.append(desc)
    messages.append([' '])

print('\n'.join([ '\n'.join(m) for m in messages ]))

```


3.2 Integrator Inverse Metric Elements

Diagnostic failures indicate the presence of problems but only hint at the nature of those problems. In order to resolve the underlying problems we need to investigate them beyond these hints. Fortunately Hamiltonian Monte Carlo provides a wealth of additional information that can assist.

First we can look at the inverse metric adaptation in each of the Markov chains. Inconsistencies in the adapted inverse metric elements across the Markov chains are due to the individual chains encountering different behaviors during warmup.

```
# Plot outcome of inverse metric adaptation
# @params adaptation_info A list containing raw adaptation text for
#                          each Markov chain. The output of RStan and
#                          PyStan's `get_adaptation_info` functions.
# @params B The number of bins for the inverse metric element histograms.
def plot_inv_metric(fit, B=25):
    """Plot outcome of inverse metric adaptation"""
    chain_info = fit.get_adaptation_info()
    C = len(chain_info)

    inv_metric_elems = [None] * C
    for c, raw_info in enumerate(chain_info):
        clean1 = re.sub("# Adaptation terminated\n# Step size = [0-9.]*\n#",
                        "", raw_info)
        clean2 = re.sub("[a-zA-Z]*:\n# ", "", clean1)
        clean3 = re.sub("\n$", "", clean2)
        inv_metric_elems[c] = [float(s) for s in clean3.split(',')]

    min_elem = min([ min(a) for a in inv_metric_elems ])
    max_elem = max([ max(a) for a in inv_metric_elems ])

    delta = (max_elem - min_elem) / B
    min_elem = min_elem - delta
    max_elem = max_elem + delta
    bins = numpy.arange(min_elem, max_elem + delta, delta)
    B = B + 2

    max_y = max([ max(numpy.histogram(a, bins=bins)[0]) for a in inv_metric_elems ])

    idxs = [ idx for idx in range(B) for r in range(2) ]
    xs = [ bins[idx + delta] for idx in range(B) for delta in [0, 1]]
```

```

N_plots = C
N_cols = 2
N_rows = math.ceil(N_plots / N_cols)
f, axarr = plot.subplots(N_rows, N_cols)
k = 0

sampler_params = fit.get_sampler_params(inc_warmup=False)
sci_formatter = matplotlib.ticker.FuncFormatter(lambda x, lim: f'{x:.1e}')

for c in range(C):
    counts = numpy.histogram(inv_metric_elems[c], bins=bins)[0]
    ys = counts[idxs]

    eps = sampler_params[c]['stepsize__'][0]

    idx1 = k // N_cols
    idx2 = k % N_cols
    k += 1

    axarr[idx1, idx2].plot(xs, ys, dark)
    axarr[idx1, idx2].set_title(f'Chain {c + 1}\n(Stepsize = {eps:.3e})')
    axarr[idx1, idx2].set_xlabel("Inverse Metric Elements")
    axarr[idx1, idx2].set_xlim([min_elem, max_elem])
    axarr[idx1, idx2].get_xaxis().set_major_formatter(sci_formatter)
    axarr[idx1, idx2].set_ylabel("")
    axarr[idx1, idx2].get_yaxis().set_visible(False)
    axarr[idx1, idx2].set_ylim([0, 1.05 * max_y])
    axarr[idx1, idx2].spines["top"].set_visible(False)
    axarr[idx1, idx2].spines["left"].set_visible(False)
    axarr[idx1, idx2].spines["right"].set_visible(False)

plot.subplots_adjust(hspace=1.0, wspace=0.25)
plot.show()

```

Note that the adaptation information may be accessed differently in other Stan interfaces, in which case this function would have to be modified accordingly.

3.3 Integrator Step Sizes

The other product of Stan's adaptation is the step size of the numerical integrator used to build the numerical Hamiltonian trajectories. As with the inverse metric elements heterogeneity in

the adapted values across the Markov chains indicates that the Markov chains encountered substantially different behavior during warmup.

```
# Display adapted symplectic integrator step sizes
# @param diagnostics A dictionary of two-dimensional arrays for
#                     each expectand. The first dimension of each
#                     element indexes the Markov chains and the
#                     second dimension indexes the sequential
#                     states within each Markov chain.
def display_stepsizes(diagnostics):
    """Display adapted symplectic integrator step sizes"""
    if type(diagnostics) is not dict:
        print('Input variable `diagnostics` is not a standard dictionary!')
        return

    stepsizes = diagnostics['stepsize__']
    C = stepsizes.shape[0]

    for c in range(C):
        stepsize = stepsizes[c, 1]
        print(f'Chain {c + 1}: Integrator Step Size = {stepsize:.2e}')
```

3.4 Numerical Trajectory Lengths

We can see the consequence of the adapted step sizes by looking at the numerical trajectories generated for each Hamiltonian Markov transition. The longer these trajectories the more degenerate the target distribution, and the more expensive it is to explore.

```
# Display symplectic integrator trajectory lengths
# @param diagnostics A dictionary of two-dimensional arrays for
#                     each expectand. The first dimension of each
#                     element indexes the Markov chains and the
#                     second dimension indexes the sequential
#                     states within each Markov chain.
def plot_num_leapfrog(diagnostics):
    """Display symplectic integrator trajectory lengths"""
    if type(diagnostics) is not dict:
        print('Input variable `diagnostics` is not a standard dictionary!')
        return

    lengths = diagnostics['n_leapfrog__']
```

```

C = lengths.shape[0]

vals_counts = [ numpy.unique(lengths[c], return_counts=True)
                 for c in range(C) ]
max_n = max([ max(a[0]) for a in vals_counts ]).astype(numpy.int64)
max_counts = max([ max(a[1]) for a in vals_counts ])

idxs = [ idx for idx in range(max_n) for r in range(2) ]
xs = [ idx + delta for idx in range(max_n) for delta in [-0.5, 0.5]]

N_plots = C
N_cols = 2
N_rows = math.ceil(N_plots / N_cols)
f, axarr = plot.subplots(N_rows, N_cols)
k = 0

for c in range(C):
    counts = numpy.histogram(lengths[c],
                             bins=numpy.arange(0.5, max_n + 1.5, 1))[0]

    ys = counts[idxs]

    eps = diagnostics['stepsize__'][0][0]

    idx1 = k // N_cols
    idx2 = k % N_cols
    k += 1

    axarr[idx1, idx2].plot(xs, ys, dark)
    axarr[idx1, idx2].set_title(f'Chain {c + 1}\n(Stepsize = {eps:.3e})')
    axarr[idx1, idx2].set_xlabel("Numerical Trajectory Length")
    axarr[idx1, idx2].set_xlim([0.5, max_n + 0.5])
    axarr[idx1, idx2].set_ylabel("")
    axarr[idx1, idx2].get_yaxis().set_visible(False)
    axarr[idx1, idx2].set_ylim([0, 1.1 * max_counts])
    axarr[idx1, idx2].spines["top"].set_visible(False)
    axarr[idx1, idx2].spines["right"].set_visible(False)

plot.subplots_adjust(hspace=1.0, wspace=0.25)
plot.show()

```

3.5 Average Proxy Acceptance Statistic

When the different adaptation outcomes are due to problematic behaviors encountered during warmup then the average proxy acceptance statistics should also vary across the Markov chains.

```
# Display empirical average of the proxy acceptance statistic across
# each Markov chain
# @param diagnostics A dictionary of two-dimensional arrays for
#                    each expectand. The first dimension of each
#                    element indexes the Markov chains and the
#                    second dimension indexes the sequential
#                    states within each Markov chain.
def display_ave_accept_proxy(diagnostics):
    """Display empirical average of the proxy acceptance statistic
    across each Markov chain"""

    if type(diagnostics) is not dict:
        print('Input variable `diagnostics` is not a standard dictionary!')
        return

    proxy_stats = diagnostics['accept_stat__']
    C = proxy_stats.shape[0]

    for c in range(C):
        proxy_stat = numpy.mean(proxy_stats[c,:])
        print( f'Chain {c + 1}: Average proxy acceptance '
              + f'statistic = {proxy_stat:.3f}')
```

3.6 Divergence-Labeled Pairs Plot

One of the most powerful features of divergent transitions is that they not only indicate problematic geometry but also provide some spatial information on the source of that problematic geometry. In particular the states generated from unstable numerical Hamiltonian trajectories will tend to be closer to the problematic geometry than those from stable trajectories.

Consequently if we plot the states from divergent and non-divergent transitions separately then we should see the divergent states concentrate towards the problematic behavior. The high-dimensional states themselves can be visualized with pairs plots.

```

# Plot pairwise scatter plots with non-divergent and divergent
# transitions separated by color
# @param expectand_samples A named list of two-dimensional arrays for
#                           each expectand. The first dimension of each
#                           element indexes the Markov chains and the
#                           second dimension indexes the sequential
#                           states within each Markov chain.
# @param diagnostics A named list of two-dimensional arrays for
#                     each expectand. The first dimension of each
#                     element indexes the Markov chains and the
#                     second dimension indexes the sequential
#                     states within each Markov chain.
# @params transforms Vector of flags configurating which if any
#                    transformation to apply to each named expectand:
#                    0: identity
#                    1: log
#                    2: logit
# @params plot_mode Plotting style configuration:
#                    0: Non-divergent transitions are plotted in
#                       transparent red while divergent transitions are
#                       plotted in transparent green.
#                    1: Non-divergent transitions are plotted in gray
#                       while divergent transitions are plotted in
#                       different shades of teal depending on the
#                       trajectory length. Transitions from shorter
#                       trajectories should cluster somewhat closer to
#                       the neighborhoods with problematic geometries.
# @param max_width Maximum line width for printing
def plot_div_pairs(expectand_samples, diagnostics, transforms,
                   plot_mode=0, max_width=72):
    """Plot pairwise scatter plots with non-divergent and divergent
    transitions separated by color"""
    if type(expectand_samples) is not dict:
        print(('Input variable `expectand_samples` '
              'is not a standard dictionary!'))
        return

    if type(diagnostics) is not dict:
        print('Input variable `diagnostics` is not a standard dictionary!')
        return

```

```

if type(transforms) is not list:
    print('Input variable `transforms` is not a list!')
    return

# Check expectand/transform compatibility
N = len(expectand_samples)
if len(transforms) != N:
    print(('Input variables `expectand_names` and `transforms` '
          'are not the same length!'))
    return

expectand_names = list(expectand_samples.keys())
for n, name in enumerate(expectand_names):
    if transforms[n] < 0 or transforms[n] > 2:
        desc = (f'The transform flag {transforms[n]} for '
                 f'expectand {name} is invalid. '
                 'Defaulting to no tranformation.')
        desc = textwrap.wrap(desc, max_width)
        print('\n'.join(desc))

    if transforms[n] == 1:
        if numpy.amin(expectand_samples[name]) <= 0:
            desc = (f'Log transform requested for expectand {name} '
                    'but expectand values are not strictly positive.')
            desc = textwrap.wrap(desc, max_width)
            print('\n'.join(desc))
            return

    if transforms[n] == 2:
        if (numpy.amin(expectand_samples[name]) <= 0 or
            numpy.amax(expectand_samples[name]) >= 1):
            desc = (f'Logit transform requested for expectand {name} '
                    'but expectand values are not strictly confined '
                    'to the unit interval.')
            desc = textwrap.wrap(desc, max_width)
            print('\n'.join(desc))
            return

if plot_mode < 0 or plot_mode > 1:
    print(f'Invalid `plot mode` value {plot_mode}.')
    return

```

```

# Extract tree-depth information
C = diagnostics['divergent__'].shape[0]
div_nlfs = [ x for c in range(C)
              for x, d in zip(diagnostics['n_leapfrog__'][c],
                              diagnostics['divergent__'][c])
              if d == 1 ]
if len(div_nlfs) > 0:
    max_nlf = max(div_nlfs)
else:
    max_nlf = 0
nom_colors = [light_teal, mid_teal, dark_teal]
cmap = LinearSegmentedColormap.from_list("teals", nom_colors,
                                          N=max_nlf)

# Set plot layout dynamically
N_pairs = math.comb(N, 2)

if N_pairs == 1:
    N_cols = 1
    N_rows = 1
    N_plots = 1
else:
    N_cols = 2
    N_rows = math.ceil(N_pairs / N_cols)

if N_rows <= 3:
    N_plots = 1
else:
    N_plots = math.ceil(N_rows / 3)
    N_rows = 3

# Plot!
k = 0

for n in range(N - 1):
    for m in range(n + 1, N):
        if k == 0:
            f, axarr = plot.subplots(N_rows, N_cols, squeeze=False)

            name_x = expectand_names[n]

```



```

if transforms[n] == 0:
    x_nondiv_samples = [ x for c in range(C) for x, d in
                        zip(expectand_samples[name_x][c],
                            diagnostics['divergent__'][c])
                        if d == 0 ]
    x_div_samples = [ x for c in range(C) for x, d in
                    zip(expectand_samples[name_x][c],
                        diagnostics['divergent__'][c])
                    if d == 1 ]
    x_display_name = name_x
elif transforms[n] == 1:
    x_nondiv_samples = [ math.log(x) for c in range(C) for x, d in
                        zip(expectand_samples[name_x][c],
                            diagnostics['divergent__'][c])
                        if d == 0 ]
    x_div_samples = [ math.log(x) for c in range(C) for x, d in
                    zip(expectand_samples[name_x][c],
                        diagnostics['divergent__'][c])
                    if d == 1 ]
    x_display_name = f'log({name_x})'
elif transforms[n] == 2:
    x_nondiv_samples = [ math.log(x / (1 - x))
                        for c in range(C) for x, d in
                        zip(expectand_samples[name_x][c],
                            diagnostics['divergent__'][c])
                        if d == 0 ]
    x_div_samples = [ math.log(x / (1 - x))
                    for c in range(C) for x, d in
                    zip(expectand_samples[name_x][c],
                        diagnostics['divergent__'][c])
                    if d == 1 ]
    x_display_name = f'logit({name_x})'

xmin = min(numpy.concatenate((x_nondiv_samples, x_div_samples)))
xmax = max(numpy.concatenate((x_nondiv_samples, x_div_samples)))

name_y = expectand_names[m]

if transforms[m] == 0:
    y_nondiv_samples = [ y for c in range(C) for y, d in
                        zip(expectand_samples[name_y][c],

```

```

        diagnostics['divergent__'][c])
        if d == 0 ]
y_div_samples = [ y for c in range(C) for y, d in
        zip(expectand_samples[name_y][c],
        diagnostics['divergent__'][c])
        if d == 1 ]
y_display_name = name_y
elif transforms[m] == 1:
y_nondiv_samples = [ math.log(y) for c in range(C) for y, d in
        zip(expectand_samples[name_y][c],
        diagnostics['divergent__'][c])
        if d == 0 ]
y_div_samples = [ math.log(y) for c in range(C) for y, d in
        zip(expectand_samples[name_y][c],
        diagnostics['divergent__'][c])
        if d == 1 ]
y_display_name = f'log({name_y})'
elif transforms[m] == 2:
y_nondiv_samples = [ math.log(y / (1 - y))
        for c in range(C) for y, d in
        zip(expectand_samples[name_y][c],
        diagnostics['divergent__'][c])
        if d == 0 ]
y_div_samples = [ math.log(y / (1 - y))
        for c in range(C) for y, d in
        zip(expectand_samples[name_y][c],
        diagnostics['divergent__'][c])
        if d == 1 ]
y_display_name = f'logit({name_y})'

ymin = min(numpy.concatenate((y_nondiv_samples, y_div_samples)))
ymax = max(numpy.concatenate((y_nondiv_samples, y_div_samples)))

idx1 = k // N_cols
idx2 = k % N_cols

if plot_mode == 0:
    axarr[idx1, idx2].scatter(x_nondiv_samples, y_nondiv_samples, s=5,
        color=dark_highlight, alpha=0.05)
    axarr[idx1, idx2].scatter(x_div_samples, y_div_samples, s=5,
        color="#00FF00", alpha=0.25)

```

```

elif plot_mode == 1:
    axarr[idx1, idx2].scatter(x_nondiv_samples, y_nondiv_samples,
                              s=5, color="#DDDDDD")
    if len(x_div_samples) > 0:
        axarr[idx1, idx2].scatter(x_div_samples, y_div_samples, s=5,
                                   cmap=cmap, c=div_nlhs)

    axarr[idx1, idx2].set_xlabel(x_display_name)
    axarr[idx1, idx2].set_xlim([xmin, xmax])
    axarr[idx1, idx2].set_ylabel(y_display_name)
    axarr[idx1, idx2].set_ylim([ymin, ymax])
    axarr[idx1, idx2].spines["top"].set_visible(False)
    axarr[idx1, idx2].spines["right"].set_visible(False)

    k += 1
    if k == N_rows * N_cols:
        # Flush current plot
        plot.subplots_adjust(hspace=0.75, wspace=0.75)
        plot.show()
        k = 0

# Turn off any remaining subplots
if k > 0:
    for kk in range(k, N_rows * N_cols):
        idx1 = kk // N_cols
        idx2 = kk % N_cols
        axarr[idx1, idx2].axis('off')
    plot.subplots_adjust(hspace=0.75, wspace=0.75)
    plot.show()

```

4 Expectand Diagnostic Functions

The Hamiltonian Monte Carlo diagnostics exploited the particular structure of the Hamiltonian Markov transition. For a general Markov transition we don't have any particular structure to exploit, and hence limited diagnostic options. In this general setting we have to investigate the behavior of not the entire state but instead particular expectands of interest.

4.1 xihat

A Markov chain Monte Carlo central limit theorem cannot exist for the expectand $f : X \rightarrow \mathbb{R}$ unless both $\mathbb{E}_\pi[f]$ and $\mathbb{E}_\pi[f^2]$ are finite, in which case we say that the expectand is sufficiently integrable. Moreover the smaller the following moments the faster the central limit theorem will kick in.

$\hat{\xi}$ uses the tail behavior of a realized Markov chain to estimate the integrability of an expectand. More specifically $\hat{\xi}$ estimates the shape of a general Pareto density function from non-central values of the expectand.

If the tail behavior were exactly general Pareto then the larger the shape parameter ξ the fewer moments of the distribution will be well-defined. Formally the m th-order moment is well-defined only if

$$m < \frac{1}{\xi}.$$

For example with $\xi = 0.9$ the expectation $\mathbb{E}_\pi[f]$ is finite but $\mathbb{E}_\pi[f^2]$ is not. Similarly for $\xi = 0.4$ the expectations $\mathbb{E}_\pi[f]$ and $\mathbb{E}_\pi[f^2]$ are finite but the third-order moment $\mathbb{E}_\pi[f^3]$ is not.

The estimator $\hat{\xi}$ is constructed from the smallest and largest values of an expectand evaluated across a realized Markov chain, where the smallest and largest values are separated from the central values using a heuristic. Because $\hat{\xi}$ only estimates the tail shape I require a conservative threshold of $\hat{\xi} \geq 0.25$ for the diagnostic warning to be triggered.

If the expectand output is bounded then the lower and upper tail might consist of the same value. In this case the $\hat{\xi}$ estimator is poorly-behaved, but the boundedness also guarantees that moments of all orders exist. To make this diagnostic as robust as possible $\hat{\xi}$ will return -2 in these cases to avoid the diagnostic threshold.

```
# Compute hat{xi}, an estimate for the shape of a generalized Pareto
# distribution from a sample of positive values using the method
# introduced in "A New and Efficient Estimation Method for the
# Generalized Pareto Distribution" by Zhang and Stephens
# https://doi.org/10.1198/tech.2009.08017.
#
# Within the generalized Pareto distribution family all moments up to
# the mth order are finite if and only if
#   xi < 1 / m.
#
# @params fs A one-dimensional array of positive values.
# @return Shape parameter estimate.
def compute_xi_hat(fs):
    """Compute empirical Pareto shape configuration for a positive sample"""
    N = len(fs)
```

```

sorted_fs = sorted(fs)

if sorted_fs[0] == sorted_fs[-1]:
    return -2

if (sorted_fs[0] < 0):
    print("Sequence values must be positive!")
    return NaN

# Estimate 25% quantile
q = sorted_fs[math.floor(0.25 * N + 0.5)]
if q == sorted_fs[0]:
    return -2

# Heuristic Pareto configuration
M = 20 + math.floor(math.sqrt(N))

b_hat_vec = [None] * M
log_w_vec = [None] * M

for m in range(M):
    b_hat_vec[m] = 1 / sorted_fs[-1] \
        + (1 - math.sqrt(M / (m + 0.5))) / (3 * q)
    if b_hat_vec[m] != 0:
        xi_hat = numpy.mean( [ math.log(1 - b_hat_vec[m] * f)
                               for f in sorted_fs ] )
        log_w_vec[m] = N * ( math.log(-b_hat_vec[m] / xi_hat)
                             - xi_hat - 1)
    else:
        log_w_vec[m] = 0

# Remove terms that don't contribute to improve numerical stability
# of average
log_w_vec = [ lw for lw in log_w_vec if lw != 0 ]
b_hat_vec = [ b for b in b_hat_vec if b != 0 ]

max_log_w = max(log_w_vec)
b_hat = sum( [ b * math.exp(lw - max_log_w)
               for b, lw in zip(b_hat_vec, log_w_vec) ] ) /\
    sum( [ math.exp(lw - max_log_w) for lw in log_w_vec ] )

```

```

    return numpy.mean( [ math.log(1 - b_hat * f) for f in sorted_fs ] )

# Compute empirical generalized Pareto shape for upper and lower tails
# for an arbitrary sample of expectand values, ignoring any
# autocorrelation between the values.
# @param fs A one-dimensional array of expectand values.
# @return Left and right shape estimators.
def compute_tail_xi_hats(fs):
    """Compute empirical Pareto shape configuration for upper and lower tails"""
    f_center = numpy.median(fs)

    # Isolate lower and upper tails which can be adequately modeled by a
    # generalized Pareto shape for sufficiently well-behaved distributions
    fs_left = [ math.fabs(f - f_center) for f in fs if f <= f_center ]
    N = len(fs_left)
    M = int(min(0.2 * N, 3 * 3 * math.sqrt(N)))
    fs_left = fs_left[M:N]

    fs_right = [ f - f_center for f in fs if f > f_center ]
    N = len(fs_right)
    M = int(min(0.2 * N, 3 * 3 * math.sqrt(N)))
    fs_right = fs_right[M:N]

    # Default to NaN if left tail is ill-defined
    xi_hat_left = math.nan
    if len(fs_left) > 40:
        xi_hat_left = compute_xi_hat(fs_left)

    # Default to NaN if right tail is ill-defined
    xi_hat_right = math.nan
    if len(fs_right) > 40:
        xi_hat_right = compute_xi_hat(fs_right)

    return [xi_hat_left, xi_hat_right]

# Check upper and lower tail behavior of a given expectand output
# ensemble.
# @param samples A two-dimensional array of scalar Markov chain states
#               with the first dimension indexing the Markov chains and
#               the second dimension indexing the sequential states
#               within each Markov chain.

```

```

# @param max_width Maximum line width for printing
def check_tail_xi_hats(samples, max_width=72):
    """Check empirical Pareto shape configuration for upper and lower
    tails of a given expectand output ensemble"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return

    C = samples.shape[0]
    no_warning = True

    for c in range(C):
        xi_hats = compute_tail_xi_hats(samples[c,:])
        xi_hat_threshold = 0.25
        if math.isnan(xi_hats[0]) and math.isnan(xi_hats[1]):
            no_warning = False
            print(f' Chain {c + 1}: Both left and right tail '
                  'hat{{xi}}s are Nan!\n')
        elif math.isnan(xi_hats[0]):
            no_warning = False
            print(f' Chain {c + 1}: Left tail '
                  'hat{{xi}} is Nan!\n')
        elif math.isnan(xi_hats[1]):
            no_warning = False
            print(f' Chain {c + 1}: Right tail '
                  'hat{{xi}} is Nan!\n')
        elif ( xi_hats[0] >= xi_hat_threshold
              and xi_hats[1] >= xi_hat_threshold):
            no_warning = False
            print(f' Chain {c + 1}: Both left and right tail '
                  f'hat{{xi}}s ({xi_hats[0]:.3f}, '
                  f'{xi_hats[1]:.3f}) exceed '
                  f'{xi_hat_threshold}!\n')
        elif ( xi_hats[0] < xi_hat_threshold
              and xi_hats[1] >= xi_hat_threshold):
            no_warning = False
            print(f' Chain {c + 1}: Ony right tail hat{{xi}} '
                  f'({xi_hats[1]:.3f}) exceeds '
                  f'{xi_hat_threshold}!\n')
        elif ( xi_hats[0] >= xi_hat_threshold
              and xi_hats[1] < xi_hat_threshold):

```

```

no_warning = False
print(f' Chain {c + 1}: Only left tail hat{{{xi}}} '
      f'({xi_hats[0]:.3f}) exceeds '
      f'{xi_hat_threshold}!\n')

if no_warning:
    print('Expectand appears to be sufficiently integrable.\n')
else:
    desc = (' Large tail xi_hats suggest that the expectand might '
            'not be sufficiently integrable.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

```

4.2 Frozen Chains

Another sign of problems is when all evaluations of an expectand are constant. This could be due to the Markov chain being stuck at a single state or just that the pushforward distribution of the expectand concentrates on a single value. We can't distinguish between these possibilities without more information, but we can signal a constant expectand by looking at its empirical variance.

Here we'll use a Welford accumulator to compute the empirical variance of the expectand values in a single sweep.

```

# Compute empirical mean and variance of a given sequence with a single
# pass using Welford accumulators.
# @params A one-dimensional array of expectand values.
# @return The empirical mean and variance.
def welford_summary(fs):
    """Welford accumulator for empirical mean and variance of a
    given sequence"""
    mean = 0
    var = 0

    for n, f in enumerate(fs):
        delta = f - mean
        mean += delta / (n + 1)
        var += delta * (f - mean)

    var /= (len(fs) - 1)

```



```

    return [mean, var]

# Check expectand output ensemble for vanishing empirical variance.
# @param samples A two-dimensional array of scalar Markov chain states
#               with the first dimension indexing the Markov chains and
#               the second dimension indexing the sequential states
#               within each Markov chain.
# @param max_width Maximum line width for printing
def check_variances(samples, max_width=72):
    """Check expectand output ensemble for vanishing empirical variance"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return

    C = samples.shape[0]
    no_warning = True

    for c in range(C):
        var = welford_summary(samples[c,:])[1]
        if var < 1e-10:
            no_warning = True
            print(f' Chain {c + 1}: Expectand is constant!\n')

    if no_warning:
        print('Expectand is varying in all Markov chains.\n')
    else:
        desc = (' If the expectand is not expected (haha) to be '
                'constant then the Markov transitions are misbehaving.')
        desc = textwrap.wrap(desc, max_width)
        desc.append(' ')
        print('\n'.join(desc))

```

4.3 Split Rhat

One of the key features of Markov chain equilibrium is that the distribution of Markov chain realizations is independent of the initialization. In particular the expectand evaluations from any equilibrated Markov chain should be statistically equivalent to any other. Even more the evaluations across any subset of Markov chain states should be equivalent.

The split \hat{R} statistic quantifies the heterogeneity in the expectand evaluations across an ensemble of Markov chains, each of which has been split in half. Mathematically split \hat{R} is similar to

analysis of variance in that compares the empirical variance of the average expectand values in each chain half to the average of the empirical variances in each chain half; the key difference is that split \hat{R} transforms this ratio so that in equilibrium the statistic decays towards 1 from above.

When split \hat{R} is much larger than 1 the expectand evaluations across each Markov chain halves are not consistent with each other. This could be because the Markov chains have not converged to the same typical set or because they have not yet expanded into that typical set.

```
# Split a sequence of expectand values in half to create an initial and
# terminal Markov chains
# @params chain A sequence of expectand values derived from a single
#               Markov chain.
# @return Two subsequences of expectand values.
def split_chain(chain):
    """Split a Markov chain into initial and terminal Markov chains"""
    N = len(chain)
    M = N // 2
    return [ chain[0:M], chain[M:N] ]

# Compute split hat{R} for the expectand values across a Markov chain
# ensemble.
# @param samples A two-dimensional array of scalar Markov chain states
#               with the first dimension indexing the Markov chains and
#               the second dimension indexing the sequential states
#               within each Markov chain.
# @return Split Rhat estimate.
def compute_split_rhat(samples):
    """Compute split hat{R} for an expectand output ensemble across
    a collection of Markov chains"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return

    split_chains = [ c for chain in samples for c in split_chain(chain) ]
    N_chains = len(split_chains)
    N = sum([ len(chain) for chain in split_chains ])

    means = [None] * N_chains
    vars = [None] * N_chains
```

```

for c, chain in enumerate(split_chains):
    summary = welford_summary(chain)
    means[c] = summary[0]
    vars[c] = summary[1]

total_mean = sum(means) / N_chains
W = sum(vars) / N_chains
B = N * sum([ (mean - total_mean)**2 / (N_chains - 1)
              for mean in means ])

rhat = math.nan
if abs(W) > 1e-10:
    rhat = math.sqrt( (N - 1 + B / W) / N )

return rhat

# Compute split hat{R} for all input expectands
# @param expectand_samples A dictionary of two-dimensional arrays for
#                           each expectand. The first dimension of each
#                           element indexes the Markov chains and the
#                           second dimension indexes the sequential
#                           states within each Markov chain.
def compute_split_rhats(expectand_samples):
    """Compute split hat{R} for all expectand output ensembles across
    a collection of Markov chains"""
    if type(expectand_samples) is not dict:
        print(('Input variable `expectand_samples` '
              'is not a standard dictionary!'))
        return

    rhats = []
    for name in expectand_samples:
        samples = expectand_samples[name]
        rhats.append(compute_split_rhat(samples))

    return rhats

# Check split hat{R} across a given expectand output ensemble.
# @param samples A two-dimensional array of scalar Markov chain states
#                with the first dimension indexing the Markov chains and
#                the second dimension indexing the sequential states

```

```

#             within each Markov chain.
# @param max_width Maximum line width for printing
def check_rhat(samples, max_width=72):
    """Check split hat{R} for all expectand output ensembles across
        a collection of Markov chains"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return

    rhat = compute_split_rhat(samples)

    no_warning = True

    if math.isnan(rhat):
        print('All Markov chains appear to be frozen!')
    elif rhat > 1.1:
        print(f'Split hat{{R}} is {rhat:.3f}!')
        no_warning = False

    if no_warning:
        desc = ('Markov chain behavior is consistent with equilibrium.')
        desc = textwrap.wrap(desc, max_width)
        desc.append(' ')
        print('\n'.join(desc))
    else:
        desc = ('Split hat{R} larger than 1.1 suggests that at least one '
                'of the Markov chains has not reached an equilibrium.')
        desc = textwrap.wrap(desc, max_width)
        desc.append(' ')
        print('\n'.join(desc))

```

4.4 Integrated Autocorrelation Time

The information about the target distribution encoded within a Markov chain, and hence the potential precision of Markov chain Monte Carlo estimators, is limited by the autocorrelation of the internal states. Assuming equilibrium we can estimate the stationary autocorrelations between the outputs of a given expectand from the realized Markov chain and then combine them into an estimate of the integrated autocorrelation time $\tau[f]$ which moderates the asymptotic variance of well-behaved Markov chain Monte Carlo estimators.

In practice it's often easier to interpret the effective sample size,

$$\text{ESS}[f] = \frac{N}{\tau[f]},$$

or in practice the empirical effective sample size that we estimate from the realized Markov chains,

$$\text{ESS}\hat{[f]} = \frac{N}{\hat{\tau}[f]}.$$

The effective sample size can be interpreted as how large of an ensemble of exact samples we would need to achieve the same estimator error for the particular expectand of interest.

```
# Compute empirical integrated autocorrelation time for a sequence
# of expectand values, known here as \hat{\tau}.
# @param fs A one-dimensional array of expectand values.
# @return Left and right shape estimators.
def compute_tau_hat(fs):
    """Compute empirical integrated autocorrelation time for a sequence"""
    # Compute empirical autocorrelations
    N = len(fs)
    m, v = welford_summary(fs)
    zs = [ f - m for f in fs ]

    if v < 1e-10:
        return math.inf

    B = 2**math.ceil(math.log2(N)) # Next power of 2 after N
    zs_buff = zs + [0] * (B - N)

    Fs = numpy.fft.fft(zs_buff)
    Ss = numpy.abs(Fs)**2
    Rs = numpy.fft.ifft(Ss)

    acov_buff = numpy.real(Rs)
    rhos = acov_buff[0:N] / acov_buff[0]

    # Drop last lag if (L + 1) is odd so that the lag pairs are complete
    L = N
    if (L + 1) % 2 == 1:
        L = L - 1

    # Number of lag pairs
    P = (L + 1) // 2
```

```

# Construct asymptotic correlation from initial monotone sequence
old_pair_sum = rhos[0] + rhos[1]
for p in range(1, P):
    current_pair_sum = rhos[2 * p] + rhos[2 * p + 1]

    if current_pair_sum < 0:
        rho_sum = sum(rhos[1:(2 * p)])

        if rho_sum <= -0.25:
            rho_sum = -0.25

        asymp_corr = 1.0 + 2 * rho_sum
        return asymp_corr

    if current_pair_sum > old_pair_sum:
        current_pair_sum = old_pair_sum
        rhos[2 * p] = 0.5 * old_pair_sum
        rhos[2 * p + 1] = 0.5 * old_pair_sum

# if p == P:
#     throw some kind of error when autocorrelation
#     sequence doesn't get terminated

old_pair_sum = current_pair_sum

```

Assuming stationarity we can use the empirical effective sample size to estimate the Markov chain Monte Carlo standard error for any well-behaved expectand estimator

$$\hat{f} \approx \mathbb{E}_{\pi}[f].$$

The necessary effective sample size depends on the precision required for a given Markov chain Monte Carlo estimator. This can vary not only from analysis to analysis but also between multiple expectands within a single analysis. That said an effective sample size of 100 is sufficient for most applications and provides a useful rule of thumb.

When Markov chains have not equilibrated the empirical effective sample size will have no relation to the error of Markov chain Monte Carlo estimators. To avoid any confusion we should interpret an empirical effective sample size simply as a quantification of the autocorrelations of a particular expectand within a realized Markov chain. In particular an empirical effective sample size below 100 indicates strong autocorrelation that will complicate Markov chain Monte Carlo estimation in the worst case and reduce estimator precision in the best case.

```

# Compute the maximum empirical effective sample size across the
# Markov chains for the given expectands
# @param expectand_samples A named list of two-dimensional arrays for
#                           each expectand. The first dimension of each
#                           element indexes the Markov chains and the
#                           second dimension indexes the sequential
#                           states within each Markov chain.
def compute_min_eesss(expectand_samples):
    """Compute the minimum empirical integrated autocorrelation time
    across a collection of Markov chains for all expectand output
    ensembles"""
    if type(expectand_samples) is not dict:
        print(('Input variable `expectand_samples` '
              'is not a standard dictionary!'))
        return

    min_eesss = []
    for name in expectand_samples:
        samples = expectand_samples[name]
        C = samples.shape[0]
        S = samples.shape[0]

        eesss = [None] * 4
        for c in range(C):
            tau_hat = compute_tau_hat(samples[c,:])
            eesss[c] = S / tau_hat

        min_eesss.append(min(eesss))

    return min_eesss

# Check the empirical effective sample size (EESS) for all a given
# expectand output ensemble.
# @param samples A two-dimensional array of scalar Markov chain states
#               with the first dimension indexing the Markov chains and
#               the second dimension indexing the sequential states
#               within each Markov chain.
# @param min_eess_per_chain The minimum empirical effective sample size
#               before a warning message is passed.
# @param max_width Maximum line width for printing
def check_eess(samples, min_eess_per_chain=100, max_width=72):

```

```

"""Check the empirical effective sample size for all expectand
output ensembles"""
if len(samples.shape) != 2:
    print('Input variable `samples` is not a two-dimensional array!')
    return

no_warning = True
C = samples.shape[0]
S = samples.shape[1]

for c in range(C):
    tau_hat = compute_tau_hat(samples[c,:])
    eess = S / tau_hat
    if eess < min_eess_per_chain:
        print(f'Chain {c + 1}: The empirical effective sample size '
              f'{eess :.1f} is too small!')
        no_warning = False

if no_warning:
    desc = ('The empirical effective sample size is large enough for '
           'Markov chain Monte Carlo estimation to be reliable '
           'assuming that a central limit theorem holds.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))
else:
    desc = ('If the empirical effective sample size is too small than '
           'Markov chain Monte Carlo estimation may be unreliable '
           'even when a central limit theorem holds.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

```

For example empirical effective sample sizes can provide a useful way to distinguish if some diagnostic failures are due to Markov chains that are just too short or more persistent problems.

4.5 All Expectand Diagnostics

In practice we have no reason not to check all of these diagnostics at once for each expectand of interest.


```

# Check all expectand-specific diagnostics.
# @param expectand_samples A dictionary of two-dimensional arrays for
#                           each expectand. The first dimension of each
#                           element indexes the Markov chains and the
#                           second dimension indexes the sequential
#                           states within each Markov chain.
# @param min_eess_per_chain The minimum empirical effective sample size
#                           before a warning message is passed.
# @param exclude_zvar Binary variable to exclude all expectands with
#                       vanishing empirical variance from other diagnostic
#                       checks.
# @param max_width Maximum line width for printing
def check_all_expectand_diagnostics(expectand_samples,
                                    min_eess_per_chain=100,
                                    exclude_zvar=False,
                                    max_width=72):
    """Check all expectand diagnostics"""
    if type(expectand_samples) is not dict:
        print(('Input variable `expectand_samples` '
              'is not a standard dictionary!'))
        return

    no_xi_hat_warning = True
    no_zvar_warning = True
    no_rhat_warning = True
    no_eess_warning = True

    message = ""

    for name in expectand_samples:
        samples = expectand_samples[name]
        C = samples.shape[0]
        S = samples.shape[1]

        local_warning = False
        local_message = name + ':\n'

        if exclude_zvar:
            # Check zero variance across all Markov chains for exclusion
            any_zvar = False
            for c in range(C):

```

```

    var = welford_summary(samples[c,:])[1]
    if var < 1e-10:
        any_zvar = True

if any_zvar:
    continue

for c in range(C):
    fs = samples[c,:]

    # Check tail xi_hats in each Markov chain
    xi_hats = compute_tail_xi_hats(fs)
    xi_hat_threshold = 0.25
    if math.isnan(xi_hats[0]) and math.isnan(xi_hats[1]):
        no_xi_hat_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: Both left and right tail '
                          'hat{{{xi}}}s are Nan!\n')
    elif math.isnan(xi_hats[0]):
        no_xi_hat_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: Left tail '
                          'hat{{{xi}}} is Nan!\n')
    elif math.isnan(xi_hats[1]):
        no_xi_hat_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: Right tail '
                          'hat{{{xi}}} is Nan!\n')
    if ( xi_hats[0] >= xi_hat_threshold
        and xi_hats[1] >= xi_hat_threshold):
        no_xi_hat_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: Both left and right tail '
                          f'hat{{{xi}}}s ({xi_hats[0]:.3f}, '
                          f'{xi_hats[1]:.3f}) exceed '
                          f'{xi_hat_threshold}!\n')
    elif ( xi_hats[0] < xi_hat_threshold
          and xi_hats[1] >= xi_hat_threshold):
        no_xi_hat_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: Only right tail hat{{{xi}}} '

```

```

        f'({xi_hats[1]:.3f}) exceeds '
        f'{xi_hat_threshold}!\n')
elif (    xi_hats[0] >= xi_hat_threshold
        and xi_hats[1] < xi_hat_threshold):
    no_xi_hat_warning = False
    local_warning = True
    local_message += (f' Chain {c + 1}: Only left tail hat{{xi}} '
                      f'({xi_hats[0]:.3f}) exceeds '
                      f'{xi_hat_threshold}!\n')

# Check empirical variance in each Markov chain
var = welford_summary(fs)[1]
if var < 1e-10:
    no_zvar_warning = False
    local_warning = True
    local_message += (f' Chain {c + 1}: Expectand exhibits '
                      'vanishing empirical variance!\n')

# Check split Rhats across Markov chains
rhat = compute_split_rhat(samples)

if math.isnan(rhat):
    local_message += ' Split hat{R} is ill-defined!\n'
elif rhat > 1.1:
    no_rhat_warning = False
    local_warning = True
    local_message += f' Split hat{{R}} ({rhat:.3f}) exceeds 1.1!\n'

for c in range(C):
    # Check empirical effective sample size
    fs = samples[c,:]

    tau_hat = compute_tau_hat(fs)
    eess = S / tau_hat
    if eess < min_eess_per_chain:
        no_eess_warning = False
        local_warning = True
        local_message += (f' Chain {c + 1}: hat{{ESS}} ({eess:.1f}) '
                          'is smaller than desired '
                          f'({min_eess_per_chain:.0f})!\n')

```

```

    if local_warning:
        message += local_message + '\n'

if (    no_xi_hat_warning and no_zvar_warning
    and no_rhat_warning    and no_eess_warning):
    desc = ('All expectands checked appear to be behaving well enough '
            'for reliable Markov chain Monte Carlo estimation.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))
    return

print(message)

if not no_xi_hat_warning:
    desc = ('Large tail hat{xi}s suggest that the expectand '
            'might not be sufficiently integrable.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

if not no_zvar_warning:
    desc = ('If the expectands are not constant then zero empirical '
            'variance suggests that the Markov transitions may be '
            'misbehaving.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

if not no_rhat_warning:
    desc = ('Split Rhat larger than 1.1 suggests that at least one of '
            'the Markov chains has not reached an equilibrium.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

if not no_eess_warning:
    desc = ('Small empirical effective sample sizes indicate strong '
            'empirical autocorrelations in the realized Markov chains. '
            'If the empirical effective sample size is too '
            'small then Markov chain Monte Carlo estimation ')

```

```

        'may be unreliable even when a central limit '
        'theorem holds.')
```

desc = textwrap.wrap(desc, max_width)

desc.append(' ')

print('\n'.join(desc))

return

That said for particularly problematic fits the output from checking all of the expectands can be overwhelming. In cases where that may be a risk we can summarize the output more compactly.

```

# Summary all expectand-specific diagnostics.
# @param expectand_samples A dictionary of two-dimensional arrays for
#                           each expectand. The first dimension of each
#                           element indexes the Markov chains and the
#                           second dimension indexes the sequential
#                           states within each Markov chain.
# @param min_eess_per_chain The minimum empirical effective sample size
#                           before a warning message is passed.
# @param exclude_zvar Binary variable to exclude all expectands with
#                       vanishing empirical variance from other diagnostic
#                       checks.
# @param max_width Maximum line width for printing
def summarize_expectand_diagnostics(expectand_samples,
                                    min_eess_per_chain=100,
                                    exclude_zvar=False,
                                    max_width=72):
    """Summarize expectand diagnostics"""
    if type(expectand_samples) is not dict:
        print(('Input variable `expectand_samples` '
              'is not a standard dictionary!'))
        return

    failed_names = []
    failed_xi_hat_names = []
    failed_zvar_names = []
    failed_rhat_names = []
    failed_eess_names = []

    for name in expectand_samples:
```

```

samples = expectand_samples[name]
C = samples.shape[0]
S = samples.shape[1]

if exclude_zvar:
    # Check zero variance across all Markov chains for exclusion
    any_zvar = False
    for c in range(C):
        var = welford_summary(samples[c,:])[1]
        if var < 1e-10:
            any_zvar = True
    if any_zvar:
        continue

for c in range(C):
    fs = samples[c,:]

    # Check tail xi_hats in each Markov chain
    xi_hats = compute_tail_xi_hats(fs)
    xi_hat_threshold = 0.25
    if math.isnan(xi_hats[0]) or math.isnan(xi_hats[1]):
        failed_names.append(name)
        failed_xi_hat_names.append(name)
    if xi_hats[0] >= xi_hat_threshold or xi_hats[1] >= xi_hat_threshold:
        failed_names.append(name)
        failed_xi_hat_names.append(name)

    # Check empirical variance in each Markov chain
    var = welford_summary(fs)[1]
    if var < 1e-10:
        failed_names.append(name)
        failed_zvar_names.append(name)

# Check split Rhat across Markov chains
rhat = compute_split_rhat(samples)

if math.isnan(rhat):
    failed_names.append(name)
    failed_rhat_names.append(name)
elif rhat > 1.1:
    failed_names.append(name)

```

```

    failed_rhat_names.append(name)

for c in range(C):
    # Check empirical effective sample size
    tau_hat = compute_tau_hat(samples[c,:])
    eess = S / tau_hat

    if eess < min_eess_per_chain:
        failed_names.append(name)
        failed_eess_names.append(name)

failed_names = list(numpy.unique(failed_names))
if len(failed_names):
    desc = (f'The expectands {"", ".join(failed_names)} '
            'triggered diagnostic warnings.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))
else:
    desc = ('All expectands checked appear to be behaving well enough '
            'for reliable Markov chain Monte Carlo estimation.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

failed_xi_hat_names = list(numpy.unique(failed_xi_hat_names))
if len(failed_xi_hat_names):
    desc = (f'The expectands {"", ".join(failed_xi_hat_names)} '
            'triggered tail hat{xi} warnings.')
    desc = textwrap.wrap(desc, max_width)
    print('\n'.join(desc))

    desc = (' Large tail hat{k}s suggest that the expectand '
            'might not be sufficiently integrable.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

failed_zvar_names = list(numpy.unique(failed_zvar_names))
if len(failed_zvar_names):
    desc = (f'The expectands {"", ".join(failed_zvar_names)} '

```

```

        'triggered zero variance warnings.')
desc = textwrap.wrap(desc, max_width)
print('\n'.join(desc))

desc = ('  If the expectands are not constant then zero empirical'
        '  variance suggests that the Markov'
        '  transitions may be misbehaving.')
desc = textwrap.wrap(desc, max_width)
desc.append(' ')
print('\n'.join(desc))

failed_rhat_names = list(numpy.unique(failed_rhat_names))
if len(failed_rhat_names):
    desc = (f'The expectands {"", ".join(failed_rhat_names)}'
            'triggered hat{R} warnings.')
    desc = textwrap.wrap(desc, max_width)
    print('\n'.join(desc))

    desc = ('  Split Rhat larger than 1.1 suggests that at '
            'least one of the Markov chains has not reached '
            'an equilibrium.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

failed_eess_names = list(numpy.unique(failed_eess_names))
if len(failed_eess_names):
    desc = (f'The expectands {"", ".join(failed_rhat_names)}'
            'triggered hat{ESS} warnings.')
    desc = textwrap.wrap(desc, max_width)
    print('\n'.join(desc))

    desc = ('Small empirical effective sample sizes indicate strong '
            'empirical autocorrelations in the realized Markov chains. '
            'If the empirical effective sample size is too '
            'small then Markov chain Monte Carlo estimation '
            'may be unreliable even when a central limit '
            'theorem holds.')
    desc = textwrap.wrap(desc, max_width)
    desc.append(' ')
    print('\n'.join(desc))

```


4.6 Empirical Autocorrelation Visualization

If we encounter large empirical integrated autocorrelation times, or small estimated effective sample sizes, then we may want to follow up with the empirical autocorrelations themselves. An empirical correlogram provides a useful visualization of these estimates.

```
# Compute empirical autocorrelations for a given Markov chain sequence
# @param fs A one-dimensional array of sequential expectand values.
# @return A one-dimensional array of empirical autocorrelations at each
#         lag up to the length of the sequence.
def compute_rhos(fs):
    """Visualize empirical autocorrelations for a given sequence"""
    # Compute empirical autocorrelations
    N = len(fs)
    m, v = welford_summary(fs)
    zs = [ f - m for f in fs ]

    if v < 1e-10:
        return [1] * N

    B = 2**math.ceil(math.log2(N)) # Next power of 2 after N
    zs_buff = zs + [0] * (B - N)

    Fs = numpy.fft.fft(zs_buff)
    Ss = numpy.abs(Fs)**2
    Rs = numpy.fft.ifft(Ss)

    acov_buff = numpy.real(Rs)
    rhos = acov_buff[0:N] / acov_buff[0]

    # Drop last lag if (L + 1) is odd so that the lag pairs are complete
    L = N
    if (L + 1) % 2 == 1:
        L = L - 1

    # Number of lag pairs
    P = (L + 1) // 2

    # Construct asymptotic correlation from initial monotone sequence
    old_pair_sum = rhos[1] + rhos[2]
    max_L = N
```

```

for p in range(1, P):
    current_pair_sum = rhos[2 * p] + rhos[2 * p + 1]

    if current_pair_sum < 0:
        max_L = 2 * p
        rhos[max_L:N] = [0] * (N - max_L)
        break

    if current_pair_sum > old_pair_sum:
        current_pair_sum = old_pair_sum
        rhos[2 * p] = 0.5 * old_pair_sum
        rhos[2 * p + 1] = 0.5 * old_pair_sum

    # if p == P:
    #     # throw some kind of error when autocorrelation
    #     # sequence doesn't get terminated

    old_pair_sum = current_pair_sum

return rhos

# Plot empirical correlograms for a given expectand across a Markov
# chain ensemble.
# @ax Matplotlib axis object
# @param fs A two-dimensional array of scalar Markov chain states
#           with the first dimension indexing the Markov chains and
#           the second dimension indexing the sequential states
#           within each Markov chain.
# @param max_L Maximum autocorrelation lag
# @param rho_lim Plotting range of autocorrelation values
# @display_name Name of expectand
def plot_empirical_correlogram(ax,
                               fs,
                               max_L,
                               rho_lim=[-0.2, 1.1],
                               name=""):
    """Plot empirical correlograms for the expectand output ensembles in a
    collection of Markov chains"""
    if len(fs.shape) != 2:
        print('Input variable `fs` is not a two-dimensional array!')
    return

```

```

C = fs.shape[0]

idxs = [ idx for idx in range(max_L) for r in range(2) ]
xs = [ idx + delta for idx in range(max_L) for delta in [-0.5, 0.5]]

colors = [dark, dark_highlight, mid, light_highlight]

for c in range(C):
    rhos = compute_rhos(fs[c,:])
    pad_rhos = [ rhos[idx] for idx in idxs ]
    ax.plot(xs, pad_rhos, colors[c % 4], linewidth=2)

ax.axhline(y=0, linewidth=2, color="#DDDDDD")

ax.set_title(name)
ax.set_xlabel("Lag")
ax.set_xlim(-0.5, max_L + 0.5)
ax.set_ylabel("Empirical\nAutocorrelation")
ax.set_ylim(rho_lim[0], rho_lim[1])
ax.spines["top"].set_visible(False)
ax.spines["right"].set_visible(False)

```

4.7 Chain-Separated Pairs Plot

We can also visualize strong autocorrelations by coloring the states of each Markov chain in a continuous gradient. When neighboring states are strongly correlated these colors will appear to vary smoothly across the ambient space. More productive Markov transitions result in a more chaotic spray of colors.

```

# Visualize the projection of a Markov chain ensemble along two
# expectands as a pairs plot. Point colors darken along each Markov
# chain to visualize the autocorrelation.
# @param f1s A two-dimensional array of expectand values with the first
#             dimension indexing the Markov chains and the second
#             dimension indexing the sequential states within each
#             Markov chain.
# @params display_name1 Name of first expectand
# @param f2s A two-dimensional array of expectand values with the first
#             dimension indexing the Markov chains and the second
#             dimension indexing the sequential states within each

```

```

#             Markov chain.
# @params display_name2 Name of second expectand
def plot_chain_sep_pairs(f1s, display_name1,
                        f2s, display_name2):
    """Plot two expectand output ensembles against each other separated by
        Markov chain """
    if len(f1s.shape) != 2:
        print('Input variable `f1s` is not a two-dimensional array!')
        return
    C1 = f1s.shape[0]
    S1 = f1s.shape[1]

    if len(f2s.shape) != 2:
        print('Input variable `f2s` is not a two-dimensional array!')
        return
    C2 = f2s.shape[0]
    S2 = f2s.shape[1]

    if C1 != C2:
        C = min(C1, C2)
        C1 = C
        C2 = C
        print(f'Plotting only {C} Markov chains.')

    if S1 != S2:
        S = min(S1, S2)
        S1 = S
        S2 = S
        print(f'Plotting only {S} samples per Markov chain.')

    colors = ["#DCBCBC", "#C79999", "#B97C7C",
              "#A25050", "#8F2727", "#7C0000"]
    cmap = LinearSegmentedColormap.from_list("reds", colors, N=S1)

    min_x = min(f1s.flatten())
    max_x = max(f1s.flatten())

    min_y = min(f2s.flatten())
    max_y = max(f2s.flatten())

    N_plots = C1

```

```

N_cols = 2
N_rows = math.ceil(N_plots / N_cols)
f, axarr = plot.subplots(N_rows, N_cols)
k = 0

for c in range(C1):
    idx1 = k // N_cols
    idx2 = k % N_cols
    k += 1

    axarr[idx1, idx2].scatter(f1s.flatten(), f2s.flatten(),
                             color="#DDDDDD", s=5, zorder=3)
    axarr[idx1, idx2].scatter(f1s[c,:], f2s[c,:],
                             cmap=cmap, c=range(S1), s=5, zorder=4)

    axarr[idx1, idx2].set_title(f'Chain {c + 1}')
    axarr[idx1, idx2].set_xlabel(display_name1)
    axarr[idx1, idx2].set_xlim([min_x, max_x])
    axarr[idx1, idx2].set_ylabel(display_name2)
    axarr[idx1, idx2].set_ylim([min_y, max_y])
    axarr[idx1, idx2].spines["top"].set_visible(False)
    axarr[idx1, idx2].spines["right"].set_visible(False)

plot.subplots_adjust(hspace=1.0, wspace=0.5)
plot.show()

```

5 Markov Chain Monte Carlo Estimation

If none of the diagnostics indicate an obstruction to a Markov chain Monte Carlo central limit theorem then we can construct expectation value estimates and their standard errors.

```

# Evaluate an expectand at the states of a Markov chain ensemble.
# @param samples A two-dimensional array of scalar Markov chain states
#               with the first dimension indexing the Markov chains and
#               the second dimension indexing the sequential states
#               within each Markov chain.
# @param expectand Scalar function to be applied to the Markov chain
#               states.
# @return A two-dimensional array of expectand values with the

```

```

#         first dimension indexing the Markov chains and the
#         second dimension indexing the sequential states within
#         each Markov chain.
def pushforward_chains(samples, expectand):
    """Evaluate an expectand along a Markov chain"""
    return numpy.vectorize(expectand)(samples)

# Estimate expectand expectation value from a single Markov chain.
# @param fs A one-dimensional array of sequential expectand values.
# @return The Markov chain Monte Carlo estimate, its estimated standard
#         error, and empirical effective sample size.
def mcmc_est(fs):
    """Estimate expectand expectation value from a Markov chain"""
    S = len(fs)
    if S == 1:
        return [fs[0], 0, math.nan]

    summary = welford_summary(fs)

    if summary[1] == 0:
        return [summary[0], 0, math.nan]

    tau_hat = compute_tau_hat(fs)
    eess = S / tau_hat
    return [summary[0], math.sqrt(summary[1] / eess), eess]

# Estimate expectand expectation value from a Markov chain ensemble.
# @param samples A two-dimensional array of expectand values with the
#         first dimension indexing the Markov chains and the
#         second dimension indexing the sequential states within
#         each Markov chain.
# @return The ensemble Markov chain Monte Carlo estimate, its estimated
#         standard error, and empirical effective sample size.
def ensemble_mcmc_est(samples):
    """Estimate expectand expectation value from a collection of
    Markov chains"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return [math.nan, math.nan, math.nan]

    C = samples.shape[0]

```

```

chain_ests = [ mcmc_est(samples[c,:]) for c in range(C) ]

# Total effective sample size
total_ess = sum([ est[2] for est in chain_ests ])

if math.isnan(total_ess):
    m = numpy.mean([ est[0] for est in chain_ests ])
    se = numpy.mean([ est[1] for est in chain_ests ])
    return [m, se, math.nan]

# Ensemble average weighted by effective sample size
mean = sum([ est[0] * est[2] for est in chain_ests ]) / total_ess

# Ensemble variance weighed by effective sample size
# including correction for the fact that individual Markov chain
# variances are defined relative to the individual mean estimators
# and not the ensemble mean estimator
vars = [0] * C

for c in range(C):
    est = chain_ests[c]
    chain_var = est[2] * est[1]**2
    var_update = (est[0] - mean)**2
    vars[c] = est[2] * (var_update + chain_var)
var = sum(vars) / total_ess

return [mean, math.sqrt(var / total_ess), total_ess]

```

In addition to examining the single expectation value of an expectand we can also visualize the entire pushforward distribution of the expectand by estimating the target probabilities in histogram bins.

```

# Visualize pushforward distribution of a given expectand as a
# histogram, using Markov chain Monte Carlo estimators to estimate the
# output bin probabilities. Bin probability estimator error is shown
# in gray.
# @ax Matplotlib axis object
# @param samples A two-dimensional array of expectand values with the
#                 first dimension indexing the Markov chains and the
#                 second dimension indexing the sequential states within
#                 each Markov chain.

```

```

# @param B The number of histogram bins
# @param display_name Expectand name
# @param flim Optional histogram range
# @param baseline Optional baseline value for visual comparison
def plot_expectand_pushforward(ax, samples, B, display_name="f",
                               flim=None, baseline=None):
    """Plot pushforward histogram of a given expectand using Markov chain
    Monte Carlo estimators to estimate the output bin probabilities"""
    if len(samples.shape) != 2:
        print('Input variable `samples` is not a two-dimensional array!')
        return

    if flim is None:
        # Automatically adjust histogram binning to range of outputs
        min_f = min(samples.flatten())
        max_f = max(samples.flatten())

        # Add bounding bins
        delta = (max_f - min_f) / B
        min_f = min_f - delta
        max_f = max_f + delta
        flim = [min_f, max_f]

    bins = numpy.arange(min_f, max_f + delta, delta)
    B = B + 2
    else:
        delta = (flim[1] - flim[0]) / B
        bins = numpy.arange(flim[0], flim[1] + delta, delta)

    mean_p = [0] * B
    delta_p = [0] * B

    for b in range(B):
        def bin_indicator(x):
            return 1.0 if bins[b] <= x and x < bins[b + 1] else 0.0

        indicator_samples = pushforward_chains(samples, bin_indicator)
        est = ensemble_mcmc_est(indicator_samples)

    # Normalize bin probabilities by bin width to allow
    # for direct comparison to probability density functions

```



```

width = bins[b + 1] - bins[b]
mean_p[b] = est[0] / width
delta_p[b] = est[1] / width

idxs = [ idx for idx in range(B) for r in range(2) ]
xs = [ bins[b + o] for b in range(B) for o in range(2) ]

lower_inter = [ max(mean_p[idx] - 2 * delta_p[idx], 0)
                for idx in idxs ]
upper_inter = [ min(mean_p[idx] + 2 * delta_p[idx], 1 / width)
                for idx in idxs ]

min_y = min(lower_inter)
max_y = 1.05 * max(upper_inter)

ax.fill_between(xs, lower_inter, upper_inter,
                facecolor=light, color="#DDDDDD")
ax.plot(xs, [ mean_p[idx] for idx in idxs ], color=dark, linewidth=2)

if baseline is not None:
    ax.axvline(x=baseline, linewidth=4, color="white")
    ax.axvline(x=baseline, linewidth=2, color="black")

ax.set_xlim(flim)
ax.set_xlabel(display_name)
ax.set_ylim([min_y, max_y])
ax.set_ylabel("Estimated Bin\nProbabilities / Bin Width")
ax.get_yaxis().set_visible(False)
ax.spines["top"].set_visible(False)
ax.spines["left"].set_visible(False)
ax.spines["right"].set_visible(False)

```

6 Demonstration

Now let's put all of these analysis tools to use with an `PyStan` fit object.

First we setup our local `Python` environment.

```

import matplotlib
import matplotlib.pyplot as plot

```

```

plot.rcParams['figure.figsize'] = [6, 4]
plot.rcParams['figure.dpi'] = 100
plot.rcParams['font.family'] = "Serif"
from matplotlib.colors import LinearSegmentedColormap

light="#DCBCBC"
light_highlight="#C79999"
mid="#B97C7C"
mid_highlight="#A25050"
dark="#8F2727"
dark_highlight="#7C0000"

import numpy

import pystan

import multiprocessing
multiprocessing.set_start_method("fork")

```

Next we source all of these diagnostics into a local namespace to avoid any conflicts with other functions.

```
import stan_utility_pystan2 as util
```

Then we can simulate some binary data from a logistic regression model.

```

model = util.compile_model('stan_programs/simu_logistic_reg.stan')
simu = model.sampling(iter=1, warmup=0, chains=1, chain_id=[1],
                      refresh=1000, seed=4838282,
                      algorithm="Fixed_param")

X = simu.extract()['X'][0]
y = simu.extract()['y'][0].astype(numpy.int64)

data = dict(M = 3, N = 1000, x0 = [-1, 0, 1], X = X, y = y)

```

We'll try to fit this model not with a constraint-respecting logistic regression model but rather a constraint blaspheming linear probability model. Importantly the resulting posterior density function is discontinuous with configurations $\alpha + \delta X * \beta > 0$ resulting in finite `bernoulli_lpmf` outputs and those with $\alpha + \delta X * \beta \leq 0$ resulting in minus infinite outputs.

Because of this awkward constraint we have to carefully initialize our Markov chains to satisfy the $\alpha + \delta X * \beta > 0$ constraint.

```
import scipy.stats as stats
numpy.random.seed(seed=48383499)

interval_inits = [None] * 4

for c in range(4):
    beta = [0, 0, 0]
    alpha = stats.norm.rvs(0.5, 0.1, size=1)[0]
    interval_inits[c] = dict(alpha = alpha, beta = beta)

model = util.compile_model('stan_programs/bernoulli_linear.stan')
fit = model.sampling(data=data, seed=8438338, warmup=1000, iter=2024,
                    chain_id=[1, 2, 3, 4], refresh=0,
                    init=interval_inits)
```

Stan is able to run to completion, but just how useful are the Markov chains that it generates?

Let's start with the Hamiltonian Monte Carlo diagnostics.

```
diagnostics = util.extract_hmc_diagnostics(fit)
util.check_all_hmc_diagnostics(diagnostics)
```

Chain 1: 1017 of 1024 transitions (99.32%) diverged.

Chain 2: 1009 of 1024 transitions (98.54%) diverged.

Chain 3: 1014 of 1024 transitions (99.02%) diverged.

Chain 3: Average proxy acceptance statistic (0.700) is
smaller than 90% of the target (0.801).

Chain 4: 1016 of 1024 transitions (99.22%) diverged.


Divergent Hamiltonian transitions result from unstable numerical trajectories. These instabilities are often due to degenerate target geometry, especially "pinches". If there are only a small number of divergences then running with `adept_delta` larger than 0.801 may reduce the instabilities at the cost of more expensive Hamiltonian transitions.

A small average proxy acceptance statistic indicates that the adaptation of the numerical integrator step size failed to converge. This is often due to discontinuous or imprecise gradients.

Almost every transition across the four Markov chains resulted in a divergence. This is due to the discontinuity in the linear probability model as the sudden jump from a finite to a negative infinite target density results in unstable numerical trajectories.

We also see the one of the Markov chains wasn't quite able to hit the step size adaptation target. To see why let's dig into the adapted configuration of the Hamiltonian Markov transition.

```
util.plot_inv_metric(fit, 75)
```



The problematic third Markov chain also exhibits the least variation in its inverse metric elements, which in this case is probably an artifact of its warmup phase spending too much time close to a constraint boundary. Inverse metric elements that cannot adapt to each parameter can frustrate numerical integration which can then frustrate the integrator step size adaptation.

The step size in the third Markov chain is slightly larger than the others which explains the lower average proxy acceptance statistic. We can also see that the first Markov chain has a much smaller step size than the other which results in an overly conservative average proxy acceptance statistic.

```
util.display_stepsizes(diagnostics)
```


```
Chain 1: Integrator Step Size = 1.48e-02  
Chain 2: Integrator Step Size = 9.11e-03  
Chain 3: Integrator Step Size = 5.73e-02  
Chain 4: Integrator Step Size = 1.05e-02
```

```
util.display_ave_accept_proxy(diagnostics)
```

```
Chain 1: Average proxy acceptance statistic = 0.840  
Chain 2: Average proxy acceptance statistic = 0.903  
Chain 3: Average proxy acceptance statistic = 0.700  
Chain 4: Average proxy acceptance statistic = 0.883
```

The different inverse metric results in different Hamiltonian dynamics. In this case the dynamics driving the third Markov chain are not able to explore as far as those in the other chains.


```
util.plot_num_leapfrog(diagnostics)
```



Finally because nearly every transition is divergent we can't extract much information from the divergent-labeled pairs plots.

```
samples = util.extract_expectands(fit)

base_samples = { k: samples[k] for k in
                 ['alpha', 'beta[1]', 'beta[2]', 'beta[3]']}
util.plot_div_pairs(base_samples, diagnostics, [0, 0, 0, 0])
```




We can also color the divergent transitions by their numerical trajectory lengths. On average transitions from shorter numerical trajectories should be closer to the problematic behavior than transitions from longer numerical trajectories. Because there are so many divergent transitions here the point colors overlap and it's hard to make too much out, but there *may* be signs of a problematic boundary.

For example plot of **beta[2]** against **beta[1]** is not inconsistent with a boundary defined by

$$\beta_1 + \beta_2 = \text{constant}.$$

```
util.plot_div_pairs(base_samples, diagnostics,
                    [0, 0, 0, 0], plot_mode=1)
```



Having examined the Hamiltonian Monte Carlo diagnostics let's now look through the expectand specific diagnostics. By default we'll look at the parameter projection functions as well as all of the expectands defined in the `generated quantities` block.

Because of the Hamiltonian Monte Carlo diagnostic failures let's start by looking at the expectand diagnostics summary instead of the full details.

```
util.summarize_expectand_diagnostics(samples)
```

The expectands `alpha`, `beta[1]`, `beta[2]`, `beta[3]`, `p[1000]`, `p[100]`, `p[101]`, `p[102]`, `p[103]`, `p[104]`, `p[105]`, `p[106]`, `p[107]`, `p[108]`, `p[109]`, `p[110]`, `p[111]`, `p[112]`, `p[113]`, `p[114]`, `p[115]`, `p[116]`, `p[117]`, `p[118]`, `p[119]`, `p[120]`, `p[121]`, `p[122]`, `p[123]`, `p[124]`, `p[125]`, `p[126]`, `p[127]`, `p[128]`, `p[129]`, `p[130]`, `p[131]`, `p[132]`, `p[133]`, `p[134]`, `p[135]`, `p[136]`, `p[137]`, `p[138]`, `p[139]`, `p[140]`, `p[141]`, `p[142]`, `p[143]`, `p[144]`, `p[145]`, `p[146]`, `p[147]`, `p[148]`, `p[149]`, `p[150]`, `p[151]`, `p[152]`, `p[153]`, `p[154]`, `p[155]`, `p[156]`, `p[157]`, `p[158]`, `p[159]`, `p[160]`, `p[161]`, `p[162]`, `p[163]`, `p[164]`, `p[165]`, `p[166]`, `p[167]`, `p[168]`, `p[169]`, `p[170]`, `p[171]`, `p[172]`, `p[173]`, `p[174]`, `p[175]`, `p[176]`, `p[177]`, `p[178]`, `p[179]`, `p[180]`, `p[181]`, `p[182]`, `p[183]`, `p[184]`, `p[185]`, `p[186]`, `p[187]`, `p[188]`, `p[189]`, `p[190]`,

p[191], p[192], p[193], p[194], p[195], p[196], p[197], p[198], p[199],
p[19], p[1], p[200], p[201], p[202], p[203], p[204], p[205], p[206],
p[207], p[208], p[209], p[20], p[210], p[211], p[212], p[213], p[214],
p[215], p[216], p[217], p[218], p[219], p[21], p[220], p[221], p[222],
p[223], p[224], p[225], p[226], p[227], p[228], p[229], p[22], p[230],
p[231], p[232], p[233], p[234], p[235], p[236], p[237], p[238], p[239],
p[23], p[240], p[241], p[242], p[243], p[244], p[245], p[246], p[247],
p[248], p[249], p[24], p[250], p[251], p[252], p[253], p[254], p[255],
p[256], p[257], p[258], p[259], p[25], p[260], p[261], p[262], p[263],
p[264], p[265], p[266], p[267], p[268], p[269], p[26], p[270], p[271],
p[272], p[273], p[274], p[275], p[276], p[277], p[278], p[279], p[27],
p[280], p[281], p[282], p[283], p[284], p[285], p[286], p[287], p[288],
p[289], p[28], p[290], p[291], p[292], p[293], p[294], p[295], p[296],
p[297], p[298], p[299], p[29], p[2], p[300], p[301], p[302], p[303],
p[304], p[305], p[306], p[307], p[308], p[309], p[30], p[310], p[311],
p[312], p[313], p[314], p[315], p[316], p[317], p[318], p[319], p[31],
p[320], p[321], p[322], p[323], p[324], p[325], p[326], p[327], p[328],
p[329], p[32], p[330], p[331], p[332], p[333], p[334], p[335], p[336],
p[337], p[338], p[339], p[33], p[340], p[341], p[342], p[343], p[344],
p[345], p[346], p[347], p[348], p[349], p[34], p[350], p[351], p[352],
p[353], p[354], p[355], p[356], p[357], p[358], p[359], p[35], p[360],
p[361], p[362], p[363], p[364], p[365], p[366], p[367], p[368], p[369],
p[36], p[370], p[371], p[372], p[373], p[374], p[375], p[376], p[377],
p[378], p[379], p[37], p[380], p[381], p[382], p[383], p[384], p[385],
p[386], p[387], p[388], p[389], p[38], p[390], p[391], p[392], p[393],
p[394], p[395], p[396], p[397], p[398], p[399], p[39], p[3], p[400],
p[401], p[402], p[403], p[404], p[405], p[406], p[407], p[408], p[409],
p[40], p[410], p[411], p[412], p[413], p[414], p[415], p[416], p[417],
p[418], p[419], p[41], p[420], p[421], p[422], p[423], p[424], p[425],
p[426], p[427], p[428], p[429], p[42], p[430], p[431], p[432], p[433],
p[434], p[435], p[436], p[437], p[438], p[439], p[43], p[440], p[441],
p[442], p[443], p[444], p[445], p[446], p[447], p[448], p[449], p[44],
p[450], p[451], p[452], p[453], p[454], p[455], p[456], p[457], p[458],
p[459], p[45], p[460], p[461], p[462], p[463], p[464], p[465], p[466],
p[467], p[468], p[469], p[46], p[470], p[471], p[472], p[473], p[474],
p[475], p[476], p[477], p[478], p[479], p[47], p[480], p[481], p[482],
p[483], p[484], p[485], p[486], p[487], p[488], p[489], p[48], p[490],
p[491], p[492], p[493], p[494], p[495], p[496], p[497], p[498], p[499],
p[49], p[4], p[500], p[501], p[502], p[503], p[504], p[505], p[506],
p[507], p[508], p[509], p[50], p[510], p[511], p[512], p[513], p[514],
p[515], p[516], p[517], p[518], p[519], p[51], p[520], p[521], p[522],
p[523], p[524], p[525], p[526], p[527], p[528], p[529], p[52], p[530],
p[531], p[532], p[533], p[534], p[535], p[536], p[537], p[538], p[539],

p[53], p[540], p[541], p[542], p[543], p[544], p[545], p[546], p[547],
p[548], p[549], p[54], p[550], p[551], p[552], p[553], p[554], p[555],
p[556], p[557], p[558], p[559], p[55], p[560], p[561], p[562], p[563],
p[564], p[565], p[566], p[567], p[568], p[569], p[56], p[570], p[571],
p[572], p[573], p[574], p[575], p[576], p[577], p[578], p[579], p[57],
p[580], p[581], p[582], p[583], p[584], p[585], p[586], p[587], p[588],
p[589], p[58], p[590], p[591], p[592], p[593], p[594], p[595], p[596],
p[597], p[598], p[599], p[59], p[5], p[600], p[601], p[602], p[603],
p[604], p[605], p[606], p[607], p[608], p[609], p[60], p[610], p[611],
p[612], p[613], p[614], p[615], p[616], p[617], p[618], p[619], p[61],
p[620], p[621], p[622], p[623], p[624], p[625], p[626], p[627], p[628],
p[629], p[62], p[630], p[631], p[632], p[633], p[634], p[635], p[636],
p[637], p[638], p[639], p[63], p[640], p[641], p[642], p[643], p[644],
p[645], p[646], p[647], p[648], p[649], p[64], p[650], p[651], p[652],
p[653], p[654], p[655], p[656], p[657], p[658], p[659], p[65], p[660],
p[661], p[662], p[663], p[664], p[665], p[666], p[667], p[668], p[669],
p[66], p[670], p[671], p[672], p[673], p[674], p[675], p[676], p[677],
p[678], p[679], p[67], p[680], p[681], p[682], p[683], p[684], p[685],
p[686], p[687], p[688], p[689], p[68], p[690], p[691], p[692], p[693],
p[694], p[695], p[696], p[697], p[698], p[699], p[69], p[6], p[700],
p[701], p[702], p[703], p[704], p[705], p[706], p[707], p[708], p[709],
p[70], p[710], p[711], p[712], p[713], p[714], p[715], p[716], p[717],
p[718], p[719], p[71], p[720], p[721], p[722], p[723], p[724], p[725],
p[726], p[727], p[728], p[729], p[72], p[730], p[731], p[732], p[733],
p[734], p[735], p[736], p[737], p[738], p[739], p[73], p[740], p[741],
p[742], p[743], p[744], p[745], p[746], p[747], p[748], p[749], p[74],
p[750], p[751], p[752], p[753], p[754], p[755], p[756], p[757], p[758],
p[759], p[75], p[760], p[761], p[762], p[763], p[764], p[765], p[766],
p[767], p[768], p[769], p[76], p[770], p[771], p[772], p[773], p[774],
p[775], p[776], p[777], p[778], p[779], p[77], p[780], p[781], p[782],
p[783], p[784], p[785], p[786], p[787], p[788], p[789], p[78], p[790],
p[791], p[792], p[793], p[794], p[795], p[796], p[797], p[798], p[799],
p[79], p[7], p[800], p[801], p[802], p[803], p[804], p[805], p[806],
p[807], p[808], p[809], p[80], p[810], p[811], p[812], p[813], p[814],
p[815], p[816], p[817], p[818], p[819], p[81], p[820], p[821], p[822],
p[823], p[824], p[825], p[826], p[827], p[828], p[829], p[82], p[830],
p[831], p[832], p[833], p[834], p[835], p[836], p[837], p[838], p[839],
p[83], p[840], p[841], p[842], p[843], p[844], p[845], p[846], p[847],
p[848], p[849], p[84], p[850], p[851], p[852], p[853], p[854], p[855],
p[856], p[857], p[858], p[859], p[85], p[860], p[861], p[862], p[863],
p[864], p[865], p[866], p[867], p[868], p[869], p[86], p[870], p[871],
p[872], p[873], p[874], p[875], p[876], p[877], p[878], p[879], p[87],
p[880], p[881], p[882], p[883], p[884], p[885], p[886], p[887], p[888],

p[889], p[88], p[890], p[891], p[892], p[893], p[894], p[895], p[896],
p[897], p[898], p[899], p[89], p[8], p[900], p[901], p[902], p[903],
p[904], p[905], p[906], p[907], p[908], p[909], p[90], p[910], p[911],
p[912], p[913], p[914], p[915], p[916], p[917], p[918], p[919], p[91],
p[920], p[921], p[922], p[923], p[924], p[925], p[926], p[927], p[928],
p[929], p[92], p[930], p[931], p[932], p[933], p[934], p[935], p[936],
p[937], p[938], p[939], p[93], p[940], p[941], p[942], p[943], p[944],
p[945], p[946], p[947], p[948], p[949], p[94], p[950], p[951], p[952],
p[953], p[954], p[955], p[956], p[957], p[958], p[959], p[95], p[960],
p[961], p[962], p[963], p[964], p[965], p[966], p[967], p[968], p[969],
p[96], p[970], p[971], p[972], p[973], p[974], p[975], p[976], p[977],
p[978], p[979], p[97], p[980], p[981], p[982], p[983], p[984], p[985],
p[986], p[987], p[988], p[989], p[98], p[990], p[991], p[992], p[993],
p[994], p[995], p[996], p[997], p[998], p[999], p[99], p[9],
y_pred[100], y_pred[101], y_pred[106], y_pred[108], y_pred[10],
y_pred[114], y_pred[116], y_pred[121], y_pred[122], y_pred[123],
y_pred[124], y_pred[126], y_pred[127], y_pred[130], y_pred[131],
y_pred[132], y_pred[133], y_pred[134], y_pred[137], y_pred[138],
y_pred[144], y_pred[145], y_pred[149], y_pred[151], y_pred[153],
y_pred[154], y_pred[155], y_pred[156], y_pred[157], y_pred[15],
y_pred[160], y_pred[161], y_pred[163], y_pred[164], y_pred[165],
y_pred[166], y_pred[167], y_pred[171], y_pred[173], y_pred[176],
y_pred[179], y_pred[17], y_pred[181], y_pred[182], y_pred[183],
y_pred[184], y_pred[186], y_pred[187], y_pred[189], y_pred[18],
y_pred[191], y_pred[194], y_pred[195], y_pred[197], y_pred[1],
y_pred[200], y_pred[201], y_pred[202], y_pred[204], y_pred[205],
y_pred[206], y_pred[207], y_pred[210], y_pred[211], y_pred[214],
y_pred[216], y_pred[217], y_pred[219], y_pred[225], y_pred[226],
y_pred[227], y_pred[228], y_pred[233], y_pred[236], y_pred[239],
y_pred[240], y_pred[241], y_pred[243], y_pred[244], y_pred[246],
y_pred[249], y_pred[24], y_pred[250], y_pred[251], y_pred[252],
y_pred[253], y_pred[255], y_pred[256], y_pred[257], y_pred[258],
y_pred[260], y_pred[261], y_pred[265], y_pred[266], y_pred[267],
y_pred[268], y_pred[26], y_pred[270], y_pred[272], y_pred[27],
y_pred[281], y_pred[282], y_pred[283], y_pred[284], y_pred[286],
y_pred[287], y_pred[289], y_pred[290], y_pred[291], y_pred[293],
y_pred[294], y_pred[296], y_pred[297], y_pred[298], y_pred[29],
y_pred[2], y_pred[300], y_pred[301], y_pred[303], y_pred[304],
y_pred[308], y_pred[309], y_pred[30], y_pred[310], y_pred[315],
y_pred[316], y_pred[318], y_pred[319], y_pred[31], y_pred[324],
y_pred[325], y_pred[326], y_pred[328], y_pred[32], y_pred[330],
y_pred[332], y_pred[335], y_pred[336], y_pred[338], y_pred[339],
y_pred[341], y_pred[342], y_pred[344], y_pred[345], y_pred[347],

y_pred[348], y_pred[349], y_pred[352], y_pred[353], y_pred[356],
y_pred[359], y_pred[35], y_pred[364], y_pred[365], y_pred[366],
y_pred[367], y_pred[371], y_pred[372], y_pred[373], y_pred[376],
y_pred[378], y_pred[379], y_pred[381], y_pred[382], y_pred[384],
y_pred[386], y_pred[387], y_pred[388], y_pred[391], y_pred[392],
y_pred[393], y_pred[395], y_pred[397], y_pred[398], y_pred[399],
y_pred[3], y_pred[400], y_pred[401], y_pred[403], y_pred[404],
y_pred[405], y_pred[40], y_pred[410], y_pred[413], y_pred[414],
y_pred[415], y_pred[417], y_pred[418], y_pred[41], y_pred[422],
y_pred[423], y_pred[427], y_pred[430], y_pred[435], y_pred[436],
y_pred[437], y_pred[439], y_pred[43], y_pred[440], y_pred[441],
y_pred[447], y_pred[449], y_pred[451], y_pred[452], y_pred[454],
y_pred[456], y_pred[457], y_pred[459], y_pred[45], y_pred[460],
y_pred[462], y_pred[463], y_pred[464], y_pred[468], y_pred[469],
y_pred[473], y_pred[474], y_pred[475], y_pred[476], y_pred[477],
y_pred[479], y_pred[47], y_pred[480], y_pred[481], y_pred[482],
y_pred[484], y_pred[485], y_pred[487], y_pred[488], y_pred[489],
y_pred[490], y_pred[491], y_pred[492], y_pred[494], y_pred[495],
y_pred[496], y_pred[498], y_pred[500], y_pred[503], y_pred[504],
y_pred[506], y_pred[508], y_pred[509], y_pred[50], y_pred[510],
y_pred[511], y_pred[513], y_pred[517], y_pred[518], y_pred[51],
y_pred[521], y_pred[522], y_pred[523], y_pred[524], y_pred[52],
y_pred[530], y_pred[531], y_pred[536], y_pred[537], y_pred[539],
y_pred[53], y_pred[540], y_pred[543], y_pred[544], y_pred[545],
y_pred[547], y_pred[551], y_pred[553], y_pred[554], y_pred[555],
y_pred[559], y_pred[55], y_pred[562], y_pred[564], y_pred[565],
y_pred[56], y_pred[570], y_pred[571], y_pred[573], y_pred[575],
y_pred[576], y_pred[577], y_pred[578], y_pred[579], y_pred[57],
y_pred[584], y_pred[586], y_pred[58], y_pred[590], y_pred[592],
y_pred[593], y_pred[595], y_pred[597], y_pred[598], y_pred[599],
y_pred[59], y_pred[601], y_pred[604], y_pred[606], y_pred[608],
y_pred[609], y_pred[60], y_pred[611], y_pred[612], y_pred[613],
y_pred[614], y_pred[617], y_pred[622], y_pred[624], y_pred[629],
y_pred[62], y_pred[630], y_pred[632], y_pred[634], y_pred[635],
y_pred[636], y_pred[637], y_pred[640], y_pred[646], y_pred[647],
y_pred[648], y_pred[64], y_pred[651], y_pred[657], y_pred[65],
y_pred[661], y_pred[668], y_pred[66], y_pred[670], y_pred[671],
y_pred[672], y_pred[675], y_pred[678], y_pred[679], y_pred[67],
y_pred[680], y_pred[684], y_pred[686], y_pred[689], y_pred[68],
y_pred[690], y_pred[691], y_pred[692], y_pred[694], y_pred[696],
y_pred[698], y_pred[699], y_pred[700], y_pred[701], y_pred[703],
y_pred[704], y_pred[710], y_pred[713], y_pred[714], y_pred[715],
y_pred[716], y_pred[71], y_pred[722], y_pred[726], y_pred[728],

y_pred[729], y_pred[730], y_pred[733], y_pred[735], y_pred[736],
y_pred[737], y_pred[73], y_pred[742], y_pred[743], y_pred[744],
y_pred[745], y_pred[747], y_pred[74], y_pred[754], y_pred[755],
y_pred[757], y_pred[758], y_pred[760], y_pred[763], y_pred[764],
y_pred[767], y_pred[770], y_pred[771], y_pred[772], y_pred[775],
y_pred[776], y_pred[778], y_pred[779], y_pred[780], y_pred[781],
y_pred[784], y_pred[785], y_pred[792], y_pred[794], y_pred[798],
y_pred[799], y_pred[79], y_pred[7], y_pred[801], y_pred[805],
y_pred[807], y_pred[808], y_pred[80], y_pred[812], y_pred[814],
y_pred[815], y_pred[816], y_pred[817], y_pred[818], y_pred[81],
y_pred[821], y_pred[822], y_pred[823], y_pred[824], y_pred[825],
y_pred[826], y_pred[827], y_pred[828], y_pred[830], y_pred[832],
y_pred[834], y_pred[836], y_pred[840], y_pred[843], y_pred[844],
y_pred[84], y_pred[853], y_pred[855], y_pred[857], y_pred[859],
y_pred[85], y_pred[860], y_pred[862], y_pred[863], y_pred[864],
y_pred[867], y_pred[868], y_pred[869], y_pred[870], y_pred[874],
y_pred[876], y_pred[882], y_pred[886], y_pred[887], y_pred[889],
y_pred[891], y_pred[892], y_pred[894], y_pred[898], y_pred[899],
y_pred[89], y_pred[8], y_pred[900], y_pred[905], y_pred[911],
y_pred[912], y_pred[915], y_pred[916], y_pred[917], y_pred[918],
y_pred[919], y_pred[91], y_pred[921], y_pred[927], y_pred[928],
y_pred[930], y_pred[933], y_pred[934], y_pred[936], y_pred[937],
y_pred[938], y_pred[941], y_pred[942], y_pred[944], y_pred[947],
y_pred[949], y_pred[94], y_pred[952], y_pred[953], y_pred[954],
y_pred[957], y_pred[958], y_pred[960], y_pred[962], y_pred[963],
y_pred[967], y_pred[970], y_pred[971], y_pred[972], y_pred[974],
y_pred[975], y_pred[976], y_pred[977], y_pred[979], y_pred[97],
y_pred[981], y_pred[982], y_pred[986], y_pred[987], y_pred[991],
y_pred[992], y_pred[994], y_pred[995], y_pred[996], y_pred[997],
y_pred[99], y_pred[9] triggered diagnostic warnings.

The expectands y_pred[100], y_pred[101], y_pred[106], y_pred[108],
y_pred[10], y_pred[114], y_pred[116], y_pred[121], y_pred[122],
y_pred[123], y_pred[124], y_pred[126], y_pred[127], y_pred[130],
y_pred[131], y_pred[132], y_pred[133], y_pred[134], y_pred[137],
y_pred[138], y_pred[144], y_pred[145], y_pred[149], y_pred[151],
y_pred[153], y_pred[154], y_pred[155], y_pred[156], y_pred[157],
y_pred[15], y_pred[160], y_pred[161], y_pred[163], y_pred[164],
y_pred[165], y_pred[166], y_pred[167], y_pred[171], y_pred[173],
y_pred[176], y_pred[179], y_pred[17], y_pred[181], y_pred[182],
y_pred[183], y_pred[184], y_pred[186], y_pred[187], y_pred[189],
y_pred[18], y_pred[191], y_pred[194], y_pred[195], y_pred[197],
y_pred[1], y_pred[200], y_pred[201], y_pred[202], y_pred[204],

y_pred[205], y_pred[206], y_pred[207], y_pred[210], y_pred[211],
y_pred[214], y_pred[216], y_pred[217], y_pred[219], y_pred[225],
y_pred[226], y_pred[227], y_pred[228], y_pred[233], y_pred[236],
y_pred[239], y_pred[240], y_pred[241], y_pred[243], y_pred[244],
y_pred[246], y_pred[249], y_pred[24], y_pred[250], y_pred[251],
y_pred[252], y_pred[253], y_pred[255], y_pred[256], y_pred[257],
y_pred[258], y_pred[260], y_pred[261], y_pred[265], y_pred[266],
y_pred[267], y_pred[268], y_pred[26], y_pred[270], y_pred[272],
y_pred[27], y_pred[281], y_pred[282], y_pred[283], y_pred[284],
y_pred[286], y_pred[287], y_pred[289], y_pred[290], y_pred[291],
y_pred[293], y_pred[294], y_pred[296], y_pred[297], y_pred[298],
y_pred[29], y_pred[2], y_pred[300], y_pred[301], y_pred[303],
y_pred[304], y_pred[308], y_pred[309], y_pred[30], y_pred[310],
y_pred[315], y_pred[316], y_pred[318], y_pred[319], y_pred[31],
y_pred[324], y_pred[325], y_pred[326], y_pred[328], y_pred[32],
y_pred[330], y_pred[332], y_pred[335], y_pred[336], y_pred[338],
y_pred[339], y_pred[341], y_pred[342], y_pred[344], y_pred[345],
y_pred[347], y_pred[348], y_pred[349], y_pred[352], y_pred[353],
y_pred[356], y_pred[359], y_pred[35], y_pred[364], y_pred[365],
y_pred[366], y_pred[367], y_pred[371], y_pred[372], y_pred[373],
y_pred[376], y_pred[378], y_pred[379], y_pred[381], y_pred[382],
y_pred[384], y_pred[386], y_pred[387], y_pred[388], y_pred[391],
y_pred[392], y_pred[393], y_pred[395], y_pred[397], y_pred[398],
y_pred[399], y_pred[3], y_pred[400], y_pred[401], y_pred[403],
y_pred[404], y_pred[405], y_pred[40], y_pred[410], y_pred[413],
y_pred[414], y_pred[415], y_pred[417], y_pred[418], y_pred[41],
y_pred[422], y_pred[423], y_pred[427], y_pred[430], y_pred[435],
y_pred[436], y_pred[437], y_pred[439], y_pred[43], y_pred[440],
y_pred[441], y_pred[447], y_pred[449], y_pred[451], y_pred[452],
y_pred[454], y_pred[456], y_pred[457], y_pred[459], y_pred[45],
y_pred[460], y_pred[462], y_pred[463], y_pred[464], y_pred[468],
y_pred[469], y_pred[473], y_pred[474], y_pred[475], y_pred[476],
y_pred[477], y_pred[479], y_pred[47], y_pred[480], y_pred[481],
y_pred[482], y_pred[484], y_pred[485], y_pred[487], y_pred[488],
y_pred[489], y_pred[490], y_pred[491], y_pred[492], y_pred[494],
y_pred[495], y_pred[496], y_pred[498], y_pred[500], y_pred[503],
y_pred[504], y_pred[506], y_pred[508], y_pred[509], y_pred[50],
y_pred[510], y_pred[511], y_pred[513], y_pred[517], y_pred[518],
y_pred[51], y_pred[521], y_pred[522], y_pred[523], y_pred[524],
y_pred[52], y_pred[530], y_pred[531], y_pred[536], y_pred[537],
y_pred[539], y_pred[53], y_pred[540], y_pred[543], y_pred[544],
y_pred[545], y_pred[547], y_pred[551], y_pred[553], y_pred[554],
y_pred[555], y_pred[559], y_pred[55], y_pred[562], y_pred[564],

y_pred[565], y_pred[56], y_pred[570], y_pred[571], y_pred[573],
y_pred[575], y_pred[576], y_pred[577], y_pred[578], y_pred[579],
y_pred[57], y_pred[584], y_pred[586], y_pred[58], y_pred[590],
y_pred[592], y_pred[593], y_pred[595], y_pred[597], y_pred[598],
y_pred[599], y_pred[59], y_pred[601], y_pred[604], y_pred[606],
y_pred[608], y_pred[609], y_pred[60], y_pred[611], y_pred[612],
y_pred[613], y_pred[614], y_pred[617], y_pred[622], y_pred[624],
y_pred[629], y_pred[62], y_pred[630], y_pred[632], y_pred[634],
y_pred[635], y_pred[636], y_pred[637], y_pred[640], y_pred[646],
y_pred[647], y_pred[648], y_pred[64], y_pred[651], y_pred[657],
y_pred[65], y_pred[661], y_pred[668], y_pred[66], y_pred[670],
y_pred[671], y_pred[672], y_pred[675], y_pred[678], y_pred[679],
y_pred[67], y_pred[680], y_pred[684], y_pred[686], y_pred[689],
y_pred[68], y_pred[690], y_pred[691], y_pred[692], y_pred[694],
y_pred[696], y_pred[698], y_pred[699], y_pred[700], y_pred[701],
y_pred[703], y_pred[704], y_pred[710], y_pred[713], y_pred[714],
y_pred[715], y_pred[716], y_pred[71], y_pred[722], y_pred[726],
y_pred[728], y_pred[729], y_pred[730], y_pred[733], y_pred[735],
y_pred[736], y_pred[737], y_pred[73], y_pred[742], y_pred[743],
y_pred[744], y_pred[745], y_pred[747], y_pred[74], y_pred[754],
y_pred[755], y_pred[757], y_pred[758], y_pred[760], y_pred[763],
y_pred[764], y_pred[767], y_pred[770], y_pred[771], y_pred[772],
y_pred[775], y_pred[776], y_pred[778], y_pred[779], y_pred[780],
y_pred[781], y_pred[784], y_pred[785], y_pred[792], y_pred[794],
y_pred[798], y_pred[799], y_pred[79], y_pred[7], y_pred[801],
y_pred[805], y_pred[807], y_pred[808], y_pred[80], y_pred[812],
y_pred[814], y_pred[815], y_pred[816], y_pred[817], y_pred[818],
y_pred[81], y_pred[821], y_pred[822], y_pred[823], y_pred[824],
y_pred[825], y_pred[826], y_pred[827], y_pred[828], y_pred[830],
y_pred[832], y_pred[834], y_pred[836], y_pred[840], y_pred[843],
y_pred[844], y_pred[84], y_pred[853], y_pred[855], y_pred[857],
y_pred[859], y_pred[85], y_pred[860], y_pred[862], y_pred[863],
y_pred[864], y_pred[867], y_pred[868], y_pred[869], y_pred[870],
y_pred[874], y_pred[876], y_pred[882], y_pred[886], y_pred[887],
y_pred[889], y_pred[891], y_pred[892], y_pred[894], y_pred[898],
y_pred[899], y_pred[89], y_pred[8], y_pred[900], y_pred[905],
y_pred[911], y_pred[912], y_pred[915], y_pred[916], y_pred[917],
y_pred[918], y_pred[919], y_pred[91], y_pred[921], y_pred[927],
y_pred[928], y_pred[930], y_pred[933], y_pred[934], y_pred[936],
y_pred[937], y_pred[938], y_pred[941], y_pred[942], y_pred[944],
y_pred[947], y_pred[949], y_pred[94], y_pred[952], y_pred[953],
y_pred[954], y_pred[957], y_pred[958], y_pred[960], y_pred[962],
y_pred[963], y_pred[967], y_pred[970], y_pred[971], y_pred[972],

y_pred[974], y_pred[975], y_pred[976], y_pred[977], y_pred[979],
y_pred[97], y_pred[981], y_pred[982], y_pred[986], y_pred[987],
y_pred[991], y_pred[992], y_pred[994], y_pred[995], y_pred[996],
y_pred[997], y_pred[99], y_pred[9] triggered tail hat{xi} warnings.

Large tail hat{k}s suggest that the expectand might not be
sufficiently integrable.

The expectands alpha, beta[1], beta[2], beta[3], p[1000], p[100],
p[101], p[102], p[103], p[104], p[105], p[106], p[107], p[108], p[109],
p[110], p[111], p[112], p[113], p[114], p[115], p[116], p[117],
p[118], p[119], p[120], p[121], p[122], p[123], p[124], p[125],
p[126], p[127], p[128], p[129], p[130], p[131], p[132], p[133],
p[134], p[135], p[136], p[137], p[138], p[139], p[140], p[141],
p[142], p[143], p[144], p[145], p[146], p[147], p[148], p[149], p[150],
p[151], p[152], p[153], p[154], p[155], p[156], p[157], p[158],
p[159], p[160], p[161], p[162], p[163], p[164], p[165], p[166],
p[167], p[168], p[169], p[170], p[171], p[172], p[173], p[174],
p[175], p[176], p[177], p[178], p[179], p[180], p[181], p[182],
p[183], p[184], p[185], p[186], p[187], p[188], p[189], p[190],
p[191], p[192], p[193], p[194], p[195], p[196], p[197], p[198], p[199],
p[200], p[201], p[202], p[203], p[204], p[205], p[206],
p[207], p[208], p[209], p[210], p[211], p[212], p[213], p[214],
p[215], p[216], p[217], p[218], p[219], p[220], p[221], p[222],
p[223], p[224], p[225], p[226], p[227], p[228], p[229], p[230],
p[231], p[232], p[233], p[234], p[235], p[236], p[237], p[238], p[239],
p[240], p[241], p[242], p[243], p[244], p[245], p[246], p[247],
p[248], p[249], p[250], p[251], p[252], p[253], p[254], p[255],
p[256], p[257], p[258], p[259], p[260], p[261], p[262], p[263],
p[264], p[265], p[266], p[267], p[268], p[269], p[270], p[271],
p[272], p[273], p[274], p[275], p[276], p[277], p[278], p[279], p[280],
p[281], p[282], p[283], p[284], p[285], p[286], p[287], p[288],
p[289], p[290], p[291], p[292], p[293], p[294], p[295], p[296],
p[297], p[298], p[299], p[300], p[301], p[302], p[303],
p[304], p[305], p[306], p[307], p[308], p[309], p[310], p[311],
p[312], p[313], p[314], p[315], p[316], p[317], p[318], p[319], p[320],
p[321], p[322], p[323], p[324], p[325], p[326], p[327], p[328],
p[329], p[330], p[331], p[332], p[333], p[334], p[335], p[336],
p[337], p[338], p[339], p[340], p[341], p[342], p[343], p[344],
p[345], p[346], p[347], p[348], p[349], p[350], p[351], p[352],
p[353], p[354], p[355], p[356], p[357], p[358], p[359], p[360],
p[361], p[362], p[363], p[364], p[365], p[366], p[367], p[368], p[369],
p[370], p[371], p[372], p[373], p[374], p[375], p[376], p[377],
p[378], p[379], p[380], p[381], p[382], p[383], p[384], p[385],

p[386], p[387], p[388], p[389], p[38], p[390], p[391], p[392], p[393],
p[394], p[395], p[396], p[397], p[398], p[399], p[39], p[3], p[400],
p[401], p[402], p[403], p[404], p[405], p[406], p[407], p[408], p[409],
p[40], p[410], p[411], p[412], p[413], p[414], p[415], p[416], p[417],
p[418], p[419], p[41], p[420], p[421], p[422], p[423], p[424], p[425],
p[426], p[427], p[428], p[429], p[42], p[430], p[431], p[432], p[433],
p[434], p[435], p[436], p[437], p[438], p[439], p[43], p[440], p[441],
p[442], p[443], p[444], p[445], p[446], p[447], p[448], p[449], p[44],
p[450], p[451], p[452], p[453], p[454], p[455], p[456], p[457], p[458],
p[459], p[45], p[460], p[461], p[462], p[463], p[464], p[465], p[466],
p[467], p[468], p[469], p[46], p[470], p[471], p[472], p[473], p[474],
p[475], p[476], p[477], p[478], p[479], p[47], p[480], p[481], p[482],
p[483], p[484], p[485], p[486], p[487], p[488], p[489], p[48], p[490],
p[491], p[492], p[493], p[494], p[495], p[496], p[497], p[498], p[499],
p[49], p[4], p[500], p[501], p[502], p[503], p[504], p[505], p[506],
p[507], p[508], p[509], p[50], p[510], p[511], p[512], p[513], p[514],
p[515], p[516], p[517], p[518], p[519], p[51], p[520], p[521], p[522],
p[523], p[524], p[525], p[526], p[527], p[528], p[529], p[52], p[530],
p[531], p[532], p[533], p[534], p[535], p[536], p[537], p[538], p[539],
p[53], p[540], p[541], p[542], p[543], p[544], p[545], p[546], p[547],
p[548], p[549], p[54], p[550], p[551], p[552], p[553], p[554], p[555],
p[556], p[557], p[558], p[559], p[55], p[560], p[561], p[562], p[563],
p[564], p[565], p[566], p[567], p[568], p[569], p[56], p[570], p[571],
p[572], p[573], p[574], p[575], p[576], p[577], p[578], p[579], p[57],
p[580], p[581], p[582], p[583], p[584], p[585], p[586], p[587], p[588],
p[589], p[58], p[590], p[591], p[592], p[593], p[594], p[595], p[596],
p[597], p[598], p[599], p[59], p[5], p[600], p[601], p[602], p[603],
p[604], p[605], p[606], p[607], p[608], p[609], p[60], p[610], p[611],
p[612], p[613], p[614], p[615], p[616], p[617], p[618], p[619], p[61],
p[620], p[621], p[622], p[623], p[624], p[625], p[626], p[627], p[628],
p[629], p[62], p[630], p[631], p[632], p[633], p[634], p[635], p[636],
p[637], p[638], p[639], p[63], p[640], p[641], p[642], p[643], p[644],
p[645], p[646], p[647], p[648], p[649], p[64], p[650], p[651], p[652],
p[653], p[654], p[655], p[656], p[657], p[658], p[659], p[65], p[660],
p[661], p[662], p[663], p[664], p[665], p[666], p[667], p[668], p[669],
p[66], p[670], p[671], p[672], p[673], p[674], p[675], p[676], p[677],
p[678], p[679], p[67], p[680], p[681], p[682], p[683], p[684], p[685],
p[686], p[687], p[688], p[689], p[68], p[690], p[691], p[692], p[693],
p[694], p[695], p[696], p[697], p[698], p[699], p[69], p[6], p[700],
p[701], p[702], p[703], p[704], p[705], p[706], p[707], p[708], p[709],
p[70], p[710], p[711], p[712], p[713], p[714], p[715], p[716], p[717],
p[718], p[719], p[71], p[720], p[721], p[722], p[723], p[724], p[725],
p[726], p[727], p[728], p[729], p[72], p[730], p[731], p[732], p[733],

p[734], p[735], p[736], p[737], p[738], p[739], p[73], p[740], p[741],
 p[742], p[743], p[744], p[745], p[746], p[747], p[748], p[749], p[74],
 p[750], p[751], p[752], p[753], p[754], p[755], p[756], p[757], p[758],
 p[759], p[75], p[760], p[761], p[762], p[763], p[764], p[765], p[766],
 p[767], p[768], p[769], p[76], p[770], p[771], p[772], p[773], p[774],
 p[775], p[776], p[777], p[778], p[779], p[77], p[780], p[781], p[782],
 p[783], p[784], p[785], p[786], p[787], p[788], p[789], p[78], p[790],
 p[791], p[792], p[793], p[794], p[795], p[796], p[797], p[798], p[799],
 p[79], p[7], p[800], p[801], p[802], p[803], p[804], p[805], p[806],
 p[807], p[808], p[809], p[80], p[810], p[811], p[812], p[813], p[814],
 p[815], p[816], p[817], p[818], p[819], p[81], p[820], p[821], p[822],
 p[823], p[824], p[825], p[826], p[827], p[828], p[829], p[82], p[830],
 p[831], p[832], p[833], p[834], p[835], p[836], p[837], p[838], p[839],
 p[83], p[840], p[841], p[842], p[843], p[844], p[845], p[846], p[847],
 p[848], p[849], p[84], p[850], p[851], p[852], p[853], p[854], p[855],
 p[856], p[857], p[858], p[859], p[85], p[860], p[861], p[862], p[863],
 p[864], p[865], p[866], p[867], p[868], p[86], p[870], p[871], p[872],
 p[873], p[874], p[875], p[876], p[877], p[878], p[879], p[87], p[880],
 p[881], p[882], p[883], p[884], p[885], p[886], p[887], p[888], p[889],
 p[88], p[890], p[891], p[892], p[893], p[894], p[895], p[896], p[897],
 p[898], p[899], p[89], p[8], p[900], p[901], p[902], p[904], p[905],
 p[906], p[907], p[908], p[909], p[90], p[910], p[911], p[912], p[913],
 p[914], p[915], p[916], p[917], p[918], p[919], p[91], p[920], p[921],
 p[922], p[923], p[924], p[925], p[926], p[927], p[928], p[929], p[92],
 p[930], p[931], p[932], p[933], p[934], p[935], p[936], p[937], p[938],
 p[939], p[93], p[940], p[941], p[942], p[943], p[944], p[945], p[946],
 p[947], p[948], p[949], p[94], p[950], p[951], p[952], p[953], p[954],
 p[955], p[956], p[957], p[958], p[959], p[95], p[960], p[961], p[962],
 p[963], p[964], p[965], p[966], p[967], p[968], p[969], p[96], p[970],
 p[971], p[972], p[973], p[974], p[975], p[976], p[977], p[978], p[979],
 p[97], p[980], p[981], p[982], p[983], p[984], p[985], p[986], p[987],
 p[988], p[989], p[98], p[990], p[991], p[992], p[993], p[994], p[995],
 p[996], p[997], p[998], p[999], p[99], p[9] triggered \hat{R} warnings.

Split Rhat larger than 1.1 suggests that at least one of the Markov chains has not reached an equilibrium.

The expectands alpha, beta[1], beta[2], beta[3], p[1000], p[100],
 p[101], p[102], p[103], p[104], p[105], p[106], p[107], p[108], p[109],
 p[10], p[110], p[111], p[112], p[113], p[114], p[115], p[116], p[117],
 p[118], p[119], p[11], p[120], p[121], p[122], p[123], p[124], p[125],
 p[126], p[127], p[128], p[129], p[12], p[130], p[131], p[132], p[133],
 p[134], p[135], p[136], p[137], p[138], p[139], p[13], p[140], p[141],
 p[142], p[143], p[144], p[145], p[146], p[147], p[148], p[149], p[14],

p[150], p[151], p[152], p[153], p[154], p[155], p[156], p[157], p[158],
p[159], p[160], p[161], p[162], p[163], p[164], p[165], p[166],
p[167], p[168], p[169], p[170], p[171], p[172], p[173], p[174],
p[175], p[176], p[177], p[178], p[179], p[180], p[181], p[182],
p[183], p[184], p[185], p[186], p[187], p[188], p[189], p[190],
p[191], p[192], p[193], p[194], p[195], p[196], p[197], p[198], p[199],
p[200], p[201], p[202], p[203], p[204], p[205], p[206],
p[207], p[208], p[209], p[210], p[211], p[212], p[213], p[214],
p[215], p[216], p[217], p[218], p[219], p[220], p[221], p[222],
p[223], p[224], p[225], p[226], p[227], p[228], p[229], p[230],
p[231], p[232], p[233], p[234], p[235], p[236], p[237], p[238], p[239],
p[240], p[241], p[242], p[243], p[244], p[245], p[246], p[247],
p[248], p[249], p[250], p[251], p[252], p[253], p[254], p[255],
p[256], p[257], p[258], p[259], p[260], p[261], p[262], p[263],
p[264], p[265], p[266], p[267], p[268], p[269], p[270], p[271],
p[272], p[273], p[274], p[275], p[276], p[277], p[278], p[279], p[280],
p[281], p[282], p[283], p[284], p[285], p[286], p[287], p[288],
p[289], p[290], p[291], p[292], p[293], p[294], p[295], p[296],
p[297], p[298], p[299], p[300], p[301], p[302], p[303],
p[304], p[305], p[306], p[307], p[308], p[309], p[310], p[311],
p[312], p[313], p[314], p[315], p[316], p[317], p[318], p[319], p[320],
p[321], p[322], p[323], p[324], p[325], p[326], p[327], p[328],
p[329], p[330], p[331], p[332], p[333], p[334], p[335], p[336],
p[337], p[338], p[339], p[340], p[341], p[342], p[343], p[344],
p[345], p[346], p[347], p[348], p[349], p[350], p[351], p[352],
p[353], p[354], p[355], p[356], p[357], p[358], p[359], p[360],
p[361], p[362], p[363], p[364], p[365], p[366], p[367], p[368], p[369],
p[370], p[371], p[372], p[373], p[374], p[375], p[376], p[377],
p[378], p[379], p[380], p[381], p[382], p[383], p[384], p[385],
p[386], p[387], p[388], p[389], p[390], p[391], p[392], p[393],
p[394], p[395], p[396], p[397], p[398], p[399], p[400],
p[401], p[402], p[403], p[404], p[405], p[406], p[407], p[408], p[409],
p[410], p[411], p[412], p[413], p[414], p[415], p[416], p[417],
p[418], p[419], p[420], p[421], p[422], p[423], p[424], p[425],
p[426], p[427], p[428], p[429], p[430], p[431], p[432], p[433],
p[434], p[435], p[436], p[437], p[438], p[439], p[440], p[441],
p[442], p[443], p[444], p[445], p[446], p[447], p[448], p[449], p[450],
p[451], p[452], p[453], p[454], p[455], p[456], p[457], p[458],
p[459], p[460], p[461], p[462], p[463], p[464], p[465], p[466],
p[467], p[468], p[469], p[470], p[471], p[472], p[473], p[474],
p[475], p[476], p[477], p[478], p[479], p[480], p[481], p[482],
p[483], p[484], p[485], p[486], p[487], p[488], p[489], p[490],
p[491], p[492], p[493], p[494], p[495], p[496], p[497], p[498], p[499],

p[49], p[4], p[500], p[501], p[502], p[503], p[504], p[505], p[506],
 p[507], p[508], p[509], p[50], p[510], p[511], p[512], p[513], p[514],
 p[515], p[516], p[517], p[518], p[519], p[51], p[520], p[521], p[522],
 p[523], p[524], p[525], p[526], p[527], p[528], p[529], p[52], p[530],
 p[531], p[532], p[533], p[534], p[535], p[536], p[537], p[538], p[539],
 p[53], p[540], p[541], p[542], p[543], p[544], p[545], p[546], p[547],
 p[548], p[549], p[54], p[550], p[551], p[552], p[553], p[554], p[555],
 p[556], p[557], p[558], p[559], p[55], p[560], p[561], p[562], p[563],
 p[564], p[565], p[566], p[567], p[568], p[569], p[56], p[570], p[571],
 p[572], p[573], p[574], p[575], p[576], p[577], p[578], p[579], p[57],
 p[580], p[581], p[582], p[583], p[584], p[585], p[586], p[587], p[588],
 p[589], p[58], p[590], p[591], p[592], p[593], p[594], p[595], p[596],
 p[597], p[598], p[599], p[59], p[5], p[600], p[601], p[602], p[603],
 p[604], p[605], p[606], p[607], p[608], p[609], p[60], p[610], p[611],
 p[612], p[613], p[614], p[615], p[616], p[617], p[618], p[619], p[61],
 p[620], p[621], p[622], p[623], p[624], p[625], p[626], p[627], p[628],
 p[629], p[62], p[630], p[631], p[632], p[633], p[634], p[635], p[636],
 p[637], p[638], p[639], p[63], p[640], p[641], p[642], p[643], p[644],
 p[645], p[646], p[647], p[648], p[649], p[64], p[650], p[651], p[652],
 p[653], p[654], p[655], p[656], p[657], p[658], p[659], p[65], p[660],
 p[661], p[662], p[663], p[664], p[665], p[666], p[667], p[668], p[669],
 p[66], p[670], p[671], p[672], p[673], p[674], p[675], p[676], p[677],
 p[678], p[679], p[67], p[680], p[681], p[682], p[683], p[684], p[685],
 p[686], p[687], p[688], p[689], p[68], p[690], p[691], p[692], p[693],
 p[694], p[695], p[696], p[697], p[698], p[699], p[69], p[6], p[700],
 p[701], p[702], p[703], p[704], p[705], p[706], p[707], p[708], p[709],
 p[70], p[710], p[711], p[712], p[713], p[714], p[715], p[716], p[717],
 p[718], p[719], p[71], p[720], p[721], p[722], p[723], p[724], p[725],
 p[726], p[727], p[728], p[729], p[72], p[730], p[731], p[732], p[733],
 p[734], p[735], p[736], p[737], p[738], p[739], p[73], p[740], p[741],
 p[742], p[743], p[744], p[745], p[746], p[747], p[748], p[749], p[74],
 p[750], p[751], p[752], p[753], p[754], p[755], p[756], p[757], p[758],
 p[759], p[75], p[760], p[761], p[762], p[763], p[764], p[765], p[766],
 p[767], p[768], p[769], p[76], p[770], p[771], p[772], p[773], p[774],
 p[775], p[776], p[777], p[778], p[779], p[77], p[780], p[781], p[782],
 p[783], p[784], p[785], p[786], p[787], p[788], p[789], p[78], p[790],
 p[791], p[792], p[793], p[794], p[795], p[796], p[797], p[798], p[799],
 p[79], p[7], p[800], p[801], p[802], p[803], p[804], p[805], p[806],
 p[807], p[808], p[809], p[80], p[810], p[811], p[812], p[813], p[814],
 p[815], p[816], p[817], p[818], p[819], p[81], p[820], p[821], p[822],
 p[823], p[824], p[825], p[826], p[827], p[828], p[829], p[82], p[830],
 p[831], p[832], p[833], p[834], p[835], p[836], p[837], p[838], p[839],
 p[83], p[840], p[841], p[842], p[843], p[844], p[845], p[846], p[847],

p[848], p[849], p[84], p[850], p[851], p[852], p[853], p[854], p[855], p[856], p[857], p[858], p[859], p[85], p[860], p[861], p[862], p[863], p[864], p[865], p[866], p[867], p[868], p[86], p[870], p[871], p[872], p[873], p[874], p[875], p[876], p[877], p[878], p[879], p[87], p[880], p[881], p[882], p[883], p[884], p[885], p[886], p[887], p[888], p[889], p[88], p[890], p[891], p[892], p[893], p[894], p[895], p[896], p[897], p[898], p[899], p[89], p[8], p[900], p[901], p[902], p[904], p[905], p[906], p[907], p[908], p[909], p[90], p[910], p[911], p[912], p[913], p[914], p[915], p[916], p[917], p[918], p[919], p[91], p[920], p[921], p[922], p[923], p[924], p[925], p[926], p[927], p[928], p[929], p[92], p[930], p[931], p[932], p[933], p[934], p[935], p[936], p[937], p[938], p[939], p[93], p[940], p[941], p[942], p[943], p[944], p[945], p[946], p[947], p[948], p[949], p[94], p[950], p[951], p[952], p[953], p[954], p[955], p[956], p[957], p[958], p[959], p[95], p[960], p[961], p[962], p[963], p[964], p[965], p[966], p[967], p[968], p[969], p[96], p[970], p[971], p[972], p[973], p[974], p[975], p[976], p[977], p[978], p[979], p[97], p[980], p[981], p[982], p[983], p[984], p[985], p[986], p[987], p[988], p[989], p[98], p[990], p[991], p[992], p[993], p[994], p[995], p[996], p[997], p[998], p[999], p[99], p[9] triggered hat{ESS} warnings. Small empirical effective sample sizes indicate strong empirical autocorrelations in the realized Markov chains. If the empirical effective sample size is too small then Markov chain Monte Carlo estimation may be unreliable even when a central limit theorem holds.

That is a lot of diagnostic failures. To avoid overwhelming ourselves with too many detailed diagnostic messages let's focus on the four parameter expectands.

```
base_samples = { k: samples[k] for k in
                  ['alpha', 'beta[1]', 'beta[2]', 'beta[3]']}
util.check_all_expectand_diagnostics(base_samples)
```

alpha:

```
Split hat{R} (1.246) exceeds 1.1!
Chain 1: hat{ESS} (7.3) is smaller than desired (100)!
Chain 2: hat{ESS} (5.0) is smaller than desired (100)!
Chain 3: hat{ESS} (3.9) is smaller than desired (100)!
Chain 4: hat{ESS} (4.9) is smaller than desired (100)!
```

beta[1]:

```
Split hat{R} (2.010) exceeds 1.1!
```

```
Chain 1: hat{ESS} (7.1) is smaller than desired (100)!
Chain 2: hat{ESS} (6.4) is smaller than desired (100)!
Chain 3: hat{ESS} (9.0) is smaller than desired (100)!
Chain 4: hat{ESS} (4.9) is smaller than desired (100)!
```

```
beta[2]:
```

```
Split hat{R} (1.409) exceeds 1.1!
Chain 1: hat{ESS} (4.8) is smaller than desired (100)!
Chain 2: hat{ESS} (9.5) is smaller than desired (100)!
Chain 3: hat{ESS} (10.9) is smaller than desired (100)!
Chain 4: hat{ESS} (22.6) is smaller than desired (100)!
```

```
beta[3]:
```

```
Split hat{R} (1.628) exceeds 1.1!
Chain 1: hat{ESS} (10.1) is smaller than desired (100)!
Chain 2: hat{ESS} (4.0) is smaller than desired (100)!
Chain 3: hat{ESS} (3.5) is smaller than desired (100)!
Chain 4: hat{ESS} (8.9) is smaller than desired (100)!
```

Split \hat{R} larger than 1.1 suggests that at least one of the Markov chains has not reached an equilibrium.

Small empirical effective sample sizes indicate strong empirical autocorrelations in the realized Markov chains. If the empirical effective sample size is too small then Markov chain Monte Carlo estimation may be unreliable even when a central limit theorem holds.

All four parameter expectands exhibit split \hat{R} warnings and low empirical effective sample size warnings. The question is whether or not the split \hat{R} warnings indicate quasistationarity or just insufficient exploration.

Motivated by the small effective sample size estimates let's look at the empirical correlograms for each parameter expectand.

```
unpermuted_samples = fit.extract(permuted=False)

f, axarr = plot.subplots(2, 2)


util.plot_empirical_correlogram(axarr[0, 0], samples['alpha'],
                                300, [-0.05, 1.05], 'alpha')
```

```

util.plot_empirical_correlogram(axarr[0, 1], samples['beta[1]'],
                               300, [-0.05, 1.05], 'beta[1]')
util.plot_empirical_correlogram(axarr[1, 0], samples['beta[2]'],
                               300, [-0.05, 1.05], 'beta[2]')
util.plot_empirical_correlogram(axarr[1, 1], samples['beta[3]'],
                               300, [-0.05, 1.05], 'beta[3]')

plot.subplots_adjust(wspace=0.5, hspace=0.75)
plot.show()


```



Regardless of whether or not these Markov chains are stationary they are extremely autocorrelated. Even assuming stationarity we wouldn't start to forget the beginning of each Markov chain until we've worked through a quarter of the total length, leaving only about four independent samples across each chain.

This is consistent with the constraint violations breaking the coherent, gradient-driven exploration of Hamiltonian Monte Carlo so that the Markov chains devolve into diffuse random walks. Indeed looking at the chain-separated pairs plots we see the spatial color continuity characteristic of a random walk.

```
util.plot_chain_sep_pairs(samples['alpha'], 'alpha',
                           samples['beta[1]'], 'beta[1]')
```




To more quantitatively blame the large split \hat{R} s on these strong autocorrelations we can plot the split \hat{R} from each expectand against the corresponding empirical effective sample size. Specifically for each expectand we plot split \hat{R} against we use the smallest empirical effective sample size of the four Markov chains.

```
rhats = util.compute_split_rhats(samples)
min_eesss = util.compute_min_eesss(samples)

plot.scatter(rhats, min_eesss, color=dark, s=10)
plot.gca().set_xlim([0.95, 2])
plot.gca().set_xlabel("Split Rhat")
plot.gca().set_ylim([0, 5])
plot.gca().set_ylabel("Empirical Effective\nSample Size")
plot.gca().spines["top"].set_visible(False)
plot.gca().spines["right"].set_visible(False)
```



```
plot.show()
```



Every expectand with a large split \hat{R} s also exhibits a particularly small minimum empirical effective sample size, confirming that the latter are due to our Markov chains not containing enough information.

If we are sloppy, ignore these diagnostics, and assume that all of our Markov chain Monte Carlo estimators are accurate then we are quickly misled about the actual behavior of the posterior distribution. One way to guard against this sloppiness is to always accompany a Markov chain Monte Carlo estimator with an estimated error. Even if that error is inaccurate it can sometimes communicate underlying problems.

For example let's look at a pushforward histogram for each parameter with light red bands visualizing the standard error around the bin probability estimates in dark red.

```
f, axarr = plot.subplots(2, 2)


util.plot_expectand_pushforward(axarr[0, 0], samples['alpha'],
                               25, display_name='alpha')
util.plot_expectand_pushforward(axarr[0, 1], samples['beta[1]'],
                               25, display_name='beta[1]')
```

```

util.plot_expectand_pushforward(axarr[1, 0], samples['beta[2]'],
                               25, display_name='beta[2]')
util.plot_expectand_pushforward(axarr[1, 1], samples['beta[3]'],
                               25, display_name='beta[3]')

plot.subplots_adjust(wspace=0.1, hspace=0.5)
plot.show()

```



If we look at the central estimates alone we might convince ourselves of all kinds of interesting structure. For example potential multi-modality in α and $\beta[2]$ and platykurticity in $\beta[1]$ and $\beta[3]$. These structures, however, are all within the scope of the relatively large standard error bands which suggests that they are all consistent with estimator noise.

Reducing the number of bins decreases the relative standard errors but at the same time many of the visual artifacts recede.

```

f, axarr = plot.subplots(2, 2)

util.plot_expectand_pushforward(axarr[0, 0], samples['alpha'],
                               10, display_name='alpha')
util.plot_expectand_pushforward(axarr[0, 1], samples['beta[1]'],


```

```

10, display_name='beta[1]')
util.plot_expectand_pushforward(axarr[1, 0], samples['beta[2]'],
10, display_name='beta[2]')
util.plot_expectand_pushforward(axarr[1, 1], samples['beta[3]'],
10, display_name='beta[3]')

plot.subplots_adjust(wspace=0.1, hspace=0.5)
plot.show()

```



When the bin indicator functions enjoy Markov chain Monte Carlo central limit theorems these standard error bands allow us to discriminate between meaningful structure and accidental artifacts regardless of the histogram binning. Even if central limit theorems don't hold the error bands provide one more way that we can potentially diagnose untrustworthy computation.

License

The code in this case study is copyrighted by Michael Betancourt and licensed under the new BSD (3-clause) license:

<https://opensource.org/licenses/BSD-3-Clause>

The text and figures in this case study are copyrighted by Michael Betancourt and licensed under the CC BY-NC 4.0 license:

<https://creativecommons.org/licenses/by-nc/4.0/>

Original Computing Environment

```
from watermark import watermark
print(watermark())
```

Last updated: 2023-07-10T12:20:35.754133-04:00

Python implementation: CPython

Python version : 3.9.6

IPython version : 8.3.0

Compiler : Clang 12.0.0 (clang-1200.0.32.29)

OS : Darwin

Release : 19.6.0

Machine : x86_64

Processor : i386

CPU cores : 16

Architecture: 64bit

```
print(watermark(packages="matplotlib,numpy,pystan"))
```

matplotlib: 3.5.2

numpy : 1.22.3

pystan : 2.19.1.1

Stan Program 1 `simu_logistic_reg.stan`

```
transformed data {
  int<lower=0> M = 3;           // Number of covariates
  int<lower=0> N = 1000;       // Number of observations

  vector[M] x0 = [-1, 0, 1]'; // Covariate baseline
  vector[M] z0 = [-3, 1, 2]'; // Latent functional behavior baseline
  real gamma0 = -2.6;          // True intercept
  vector[M] gamma1 = [0.2, -2.0, 0.33]'; // True slopes
  matrix[M, M] gamma2 = [ [+0.40, -0.05, -0.20],
                           [-0.05, -1.00, -0.05],
                           [-0.20, -0.05, +0.50] ];
}

generated quantities {
  matrix[N, M] X; // Covariate design matrix
  real y[N];      // Variates

  for (n in 1:N) {
    real x2 = -5;
    while (x2 < x0[2] - 4 || x2 > x0[2] + 4)
      x2 = normal_rng(x0[2], 2);

    X[n, 2] = x2;
    X[n, 1] = normal_rng(x0[1] + 1.0 * cos(1.5 * (X[n, 2] - x0[2])), 0.3);
    X[n, 3] = normal_rng(x0[3] + 0.76 * (X[n, 1] - x0[1]), 0.5);

    y[n] = bernoulli_logit_rng( gamma0
                                + (X[n] - z0') * gamma1
                                + (X[n] - z0') * gamma2 * (X[n] - z0')));
  }
}
```
