

עבודה 3.2 – סביבות פיתוח באינטרנט

מגישים: נמרוד חייט 318403581 דנה אליהו 307976837

ID	Method name	HTTP Method	Parameters	Returns	Explanation
1	private/login/	POST	{ , "" : "username" "password" : "" }	Token	Login cannot pass in GET (not safe)
2	private/forgotPassword	POST	{ , "" : "username" , "" : "qid" , "" : "answer" }	Password password : "pa" {"ssword	forgotPassword cannot pass in GET (not safe) because we get and receive sensitive information
3	private/register	POST	{ "username": "", "password": "", "firstName": "", "lastName": "", "country": "", "city": "", "email": "", "question1": "", "answer1": "", "question2": "", "answer2": "", "interests": ["category1", "category2"] }	error/[]	register cannot pass in GET (not safe)
4	view/getFavoriteAttractions	GET	token	return all favorite attractions attraction[]	Using GET because there is no information to deliver to the server or any wish to change the information
5	view/getLastAttractions	GET	token	Return last two attractions	Using GET because there is no information to deliver to the server or any wish to change the information
6	view/getCategories	GET	token	return all categories category[]	Using GET because there is no information to deliver to the server or any wish to change the information
7	view/getAttractionsByCategory	GET	category, token	return all attractions of a category attraction[]	Using GET because there is no sensitive information to deliver and we wish to update the views attribute in the attraction.

8	view/getRand/ omPopularAttr actions	GET	token	return 3 random attractions with rating 4 or higher attraction[]	Using GET because there is no information to deliver to the server or any wish to change the information
9	view/getAttrac/ tionsByName	GET	token,attractionN ame	return all attractions that have the input name within the attraction name attraction[]	Using GET because there is no sensitive information to deliver and we wish to update the views attribute in the attraction.
10	view/getMostP/ opularAttractio nForUser	GET	token	return 4 most popular attractions by categories the user chose based on what other recommended. attraction[]	Using GET because there is no sensitive information to deliver and we wish to update the views attribute in the attraction.
11	view/viewAttr/ ction	PUT	token, attractionName	Return the exact attraction with all its details.	Using PUT because there is no sensitive information to deliver and we wish to update the views attribute in the attraction.
12	/update/update MyAttractionSo rt	PUT	token, attractionArray,ra nkArray for example: /update/updateMyAttractio nSort/attraction1,attraction 2,attraction3/3,1,2	[]	Using PUT because there is no sensitive information to deliver and we wish to update the order of the favorites list
13	update/addRa/ ting	POST	{ "token": "", "rating": "", "review": "", "date": "", "attractionName" : "" }		using POST because we create a new resource of rating and a review

על החתום,

המתכנת מר נמרוד חייט

מנהלת הפרוייקט גברת דנה אליהו

