## **Support document**

No. 25096558 (Last updated 25.01.2023)



CCF Pricing Head Office CCF LTD TEAM VALLEY TRADING ESTATE KINGSWAY (FORMER DEL MONTE SIT NEWCASTLE Tyne and Wear NE11 0JH

10086973

**Mandale Homes** 

A/c No.

Mandale Construction

Mandale House / STOCKTON-ON-TEES TS18 2RD

Project Start Date January 2023

Project End Date 31.12.2023

Agreement Start Date January 2023

All Support is calculated against our current price list, with the duration based on the start and end dates shown above. All service premiums will be at standard terms unless otherwise shown.

Support number MUST be quoted when placing orders with Knauf Customer Services for support showing additional discounts off invoice & when claiming credits for support on proof of delivery.

Please check project support document and in the case of any query, please contact Customer Administrator at the Sittingbourne office.

Product Description	Off Invoice discount (for directs)	Pence of Support (for ex yard)	Unit of Measure
UK: Std Wallboard			
12.5 Wallboard 1200	Std. Terms	0.28	M2
15 Wallboard 1200	Std. Terms	0.34	M2
UK: Vapour Panel			
12.5 Vapour Panel 1200	Std. Terms	0.39	M2
15 Vapour Panel 1200	Std. Terms	0.47	M2
UK: Soundshield/Plus			
12.5 Soundshield Plus 1200	61.920%	0.90	M2
15 Soundshield Plus 1200	61.910%	1.09	M2
UK: Moisture Panel			
12.5 Moisture Panel 1200	Std. Terms	0.20	M2
15.0 Moisture Panel 1200	Std. Terms	0.25	M2
UK: Performance Plus			
12.5 Performance Plus 1200	57.860%	0.90	M2
15.0 Performance Plus 1200	57.870%	1.09	M2
UK: Fire Panel			
12.5 Fire Panel 1200	Std. Terms	0.42	M2
15 Fire Panel 1200	Std. Terms	0.52	M2
UK: Coreboard			
19 Core Board 600	Std. Terms	0.62	M2
UK: Jointing Mats			
Fill and Finish 30 Premium 10 kg	Std. Terms	Nil	PC
Fill and Finish 60 Premium 10 kg	Std. Terms	Nil	PC
Joint Filler Premium 10 kg	Std. Terms	Nil	PC
Joint Filler Premium 20 kg	Std. Terms	Nil	PC
Joint Cement Premium	Std. Terms	Nil	PC
UK: Drywall Acc			
Joint Tape	Std. Terms	Nil	PAC

## **Support document**

No. 25096558 (Last updated 25.01.2023)



			_
Product Description	Off Invoice discount (for directs)	Pence of Support (for ex yard)	Unit of Measure
Fibre Tape 90 m	Std. Terms	0.11	PC
Joint Tape	Std. Terms	Nil	PAC
UK: Bonding Compound			
Bonding Compound 25 kg	Std. Terms	Nil	PC
UK: C Stud & U Chnl			
50mm C Stud 0.55g	Std. Terms	0.14	M
60mm C Stud 0.55g	Std. Terms	0.20	M
70mm C Stud 0.55g	Std. Terms	0.18	M
92mm C Stud 0.55g	46.780%	0.25	M
146mm C Stud 0.55g	46.760%	0.35	M
70mm C Stud 0.7g	46.730%	0.38	M
92mm C Stud 0.7g	Std. Terms	0.42	M
146mm C Stud 0.7g	Std. Terms	0.50	М
50mm Acoustic C Stud 0.6g	Std. Terms	0.23	М
70mm Acoustic C Stud 0.6g	46.790%	0.33	M
MW Stud	Std. Terms	0.49	M
52 U Channel 0.55g	46.850%	0.15	М
62 U Channel 0.55g	Std. Terms	0.17	M
72 U Channel 0.55g	46.800%	0.17	M
94 U Channel 0.55g	46.780%	0.22	M
148 U Channel 0.55g	46.830%	0.28	M
52 DF U Channel 0.6g	46.780%	0.28	M
72 DF U Channel 0.6g	Std. Terms	0.30	M
52 DF U Channel 0.7g	46.750%	0.44	M
62 DF U Channel 0.7g	Std. Terms	0.46	M
72 DF U Channel 0.7g	Std. Terms	0.47	M
94 DF U Channel 0.7g	Std. Terms	0.55	M
148 DF U Channel 0.7g	46.740%	0.64	М
UW Runner 100/40/06 4000	46.780%	0.38	М
UK: I Stud			
50mm I Stud 0.55g	46.800%	0.36	М
60mm I Stud 0.55g	46.780%	0.35	M
60mm I Stud 0.7g	Std. Terms	0.41	M
70mm I Stud 0.7g	46.730%	0.48	M
92mm I Stud 0.9g	46.770%	0.54	M
146mm I Stud 0.9g	46.760%	0.83	M
Staggered Stud Clip 60 mm	46.740%	4.07	PAC
Staggered Stud Clip 92 mm	46.750%	6.31	PAC
UK: Metal Acc			
Resilient Bar	Std. Terms	0.20	M

Sales Representative Jonathan Kirk Jonathan.Kirk@knauf.com +44 (7771) 806014





## What is it?

Knauf Deflection Head Fire Seal is used at the deflection head detail of drywall partition systems to provide an effective fire and acoustic barrier. Maximum deflection allowance 25mm downward.

Designed for indoor use in dry conditions.

For more information, contact Technical Service:

Tel: 0800 030 4135
Email: technical@knauf.co.uk
www.knauf.co.uk



## What are the benefits?

- Simplification of build
   Eliminates the need for cut fillets, mastics and sealants.
- Time saving Improved productivity from faster installation.
- Improved quality assurance Simple solution — visible result.
- Waste reduction
   Offcuts can be used on next section of track. Easy disposal of any residual product through normal waste channels.
- Improved Health and Safety
   Elimination of dust when cutting fillets.
   Reduction of weight to be
   lifted overhead during installation.

Build for the world we live in