Support document

No. 25094965 (Last updated 04.01.2023)



CCF Pricing Head Office
CCF LTD
TEAM VALLEY TRADING ESTATE
KINGSWAY (FORMER DEL MONTE SIT
NEWCASTLE
Tyne and Wear NE11 0JH

10086973

Commercial Interiors Building Contractor

4 Hollies Court / Cannock WS11 1BD

Project Start Date January 2023

Project End Date 31.12.2023

Agreement Start Date January 2023

Commercial interiors stockton

A/c No.

All Support is calculated against our current price list, with the duration based on the start and end dates shown above. All service premiums will be at standard terms unless otherwise shown.

Support number MUST be quoted when placing orders with Knauf Customer Services for support showing additional discounts off invoice & when claiming credits for support on proof of delivery.

Please check project support document and in the case of any query, please contact Customer Administrator at the Sittingbourne office.

Product Description	Off Invoice discount (for directs)	Pence of Support (for ex yard)	Unit of Measure
UK: Std Wallboard			
12.5 Wallboard 1200	Std. Terms	0.04	M2
12.5 Wallboard 900	Std. Terms	0.01	M2
9.5 Wallboard 1200	Std. Terms	0.00	M2
9.5 Wallboard 900	Std. Terms	0.01	M2
15 Wallboard 1200	Std. Terms	0.05	M2
15 Wallboard 900	Std. Terms	0.01	M2
UK: Plank			
19 Plank 600	Std. Terms	Nil	M2
UK: Vapour Panel			
12.5 Vapour Panel 900	Std. Terms	Nil	M2
12.5 Vapour Panel 1200	Std. Terms	Nil	M2
15 Vapour Panel 1200	Std. Terms	Nil	M2
UK: Soundshield/Plus			
12.5 Soundshield Plus 1200	Std. Terms	0.53	M2
15 Soundshield Plus 1200	Std. Terms	0.64	M2
12.5 Sound Panel 1200	Std. Terms	0.29	M2
UK: Moisture Panel			
12.5 Moisture Panel 1200	Std. Terms	0.20	M2
15.0 Moisture Panel 1200	Std. Terms	0.25	M2
UK: Performance Plus			
12.5 Performance Plus 1200	Std. Terms	0.65	M2
15.0 Performance Plus 1200	Std. Terms	0.78	M2
UK: Fire Panel			
12.5 Fire Panel 900	Std. Terms	Nil	M2
12.5 Fire Panel 1200	Std. Terms	Nil	M2
15 Fire Panel 1200	Std. Terms	Nil	M2
UK: Laminates			

Support document

No. 25094965 (Last updated 04.01.2023)



Product Description	Off Invoice discount (for directs)	Pence of Support (for ex yard)	Unit of Measure
XPS Laminate Plus 55	Std. Terms	Nil	M2
UK: Jointing Mats			
Fill and Finish 60 Premium 10 kg	Std. Terms	Nil	PC
Fill and Finish 30 Premium 10 kg	Std. Terms	Nil	PC
Joint Filler Premium 10 kg	Std. Terms	Nil	PC
Joint Filler Premium 20 kg	Std. Terms	Nil	PC
Joint Cement Premium	Std. Terms	Nil	PC
UK: Drywall Acc			
Joint Tape	Std. Terms	Nil	PC
UK: Bonding Compound	0.1.	N. 171	50
Bonding Compound 25 kg	Std. Terms	Nil	PC
UK: Drywall Fixings	0.1.	.	540
Drywall Screws 25 mm	Std. Terms	Nil	PAC
Drywall Screws 32 mm	Std. Terms	Nil	PAC
Drywall Screws 38 mm	Std. Terms	Nil	PAC
Drywall Screws 42 mm	Std. Terms	Nil	PAC
Drywall Screws 50 mm	Std. Terms	Nil	PAC
Drywall Screws 60 mm	Std. Terms	Nil	PAC
Drywall Screws 75 mm	Std. Terms	Nil	PAC
Collated Drywall Screws 25mm	Std. Terms	Nil	PAC
Collated Drywall Screws 35mm	Std. Terms	Nil	PAC
Collated Drywall Screws 45mm	Std. Terms	Nil	PAC
Jackpoint Screws 25 mm	Std. Terms	Nil	PAC
Jackpoint Screws 35 mm	Std. Terms	Nil	PAC
Jackpoint Screws 42 mm	Std. Terms	Nil	PAC
Jackpoint Screws 55 mm	Std. Terms	Nil	PAC
Drywall Wood Screws 38 mm	Std. Terms	Nil	PAC
Drywall Wood Screws 42 mm	Std. Terms	Nil	PAC
Wafer-Head Self Tapping 14mm	Std. Terms	Nil	PAC
Wafer-Head Jackpoint Screw	Std. Terms	Nil	PAC
Nailable Plug 6/35 mm	Std. Terms	Nil	PAC
Nailable Plug 8/80 mm	Std. Terms	Nil	PAC
Nailable Plug 8/100 mm	Std. Terms	Nil	PAC

Sales Representative Jonathan Kirk Jonathan.Kirk@knauf.com +44 (7771) 806014





What is it?

Knauf Deflection Head Fire Seal is used at the deflection head detail of drywall partition systems to provide an effective fire and acoustic barrier. Maximum deflection allowance 25mm downward.

Designed for indoor use in dry conditions.

For more information, contact Technical Service:

Tel: 0800 030 4135
Email: technical@knauf.co.uk
www.knauf.co.uk



What are the benefits?

- Simplification of build
 Eliminates the need for cut fillets, mastics and sealants.
- Time saving Improved productivity from faster installation.
- Improved quality assurance Simple solution — visible result.
- Waste reduction
 Offcuts can be used on next section of track. Easy disposal of any residual product through normal waste channels.
- Improved Health and Safety
 Elimination of dust when cutting fillets.
 Reduction of weight to be
 lifted overhead during installation.

Build for the world we live in