

BNS Warehouse System

Public Stock API - Integration Guide

This document describes the read-only API BNS Distribution makes available to customers and integration partners who need to check current available stock programmatically. It is versioned alongside the warehouse system itself - new endpoints will be added here as they go live.

Document version: 1.0 | Last updated: 2026-08-13

Authentication

Every request to the public API must include a valid API key in the **X-API-Key** request header. Keys are issued by BNS Distribution from the internal "API Access" screen - contact your BNS account contact to request one.

```
X-API-Key: bns_your_key_here
```

Requests without a valid, active key receive a 401 Unauthorized response:

```
{
  "timestamp": "2026-08-13T09:15:00",
  "status": 401,
  "error": "Unauthorized",
  "message": "Missing or invalid API key. Include a valid key in the X-API-Key header."
}
```

Keep your API key confidential. If a key is compromised, ask BNS Distribution to revoke it and issue a new one - revoked keys stop working immediately.

Base URL

All endpoints in this document are relative to your BNS Warehouse instance's base URL, for example:

```
https://your-bns-instance.example.com/api/public
```

Endpoints

GET /api/public/stock

Returns current available stock for every active product. "Available" means physically in the warehouse and not quarantined, allocated, dispatched, or returned-pending-inspection - it is calculated live at request time.

Example request

```
curl https://your-bns-instance.example.com/api/public/stock \
-H "X-API-Key: bns_your_key_here"
```

Example response (200 OK)

```
[
  {
    "sku": "GWN7802P",
    "name": "GWN7802P Wireless Access Point",
    "availableQuantity": 12
  },
  {
    "sku": "GRP2615",
    "name": "GRP2615 IP Phone",
    "availableQuantity": 4
  }
]
```

```
}  
]
```

GET /api/public/stock/{sku}

Returns current available stock for a single product by SKU. The SKU match is case-insensitive.

Example request

```
curl https://your-bns-instance.example.com/api/public/stock/GWN7802P \  
-H "X-API-Key: bns_your_key_here"
```

Example response (200 OK)

```
{  
  "sku": "GWN7802P",  
  "name": "GWN7802P Wireless Access Point",  
  "availableQuantity": 12  
}
```

If the SKU doesn't exist, this returns a 404:

```
{  
  "timestamp": "2026-08-13T09:15:00",  
  "status": 404,  
  "error": "Not Found",  
  "message": "No product found for SKU GWN7802P"  
}
```

Response Fields

Field	Type	Description
sku	string	The product's SKU / part number
name	string	Human-readable product name
availableQuantity	integer	Units currently available to sell, right now

Errors

All error responses use a consistent shape: **timestamp**, **status**, **error**, and a human-readable **message**. HTTP status codes follow standard conventions - 401 for authentication problems, 404 for a SKU that doesn't exist, and 500 for anything unexpected on our side.

Changelog

Version	Date	Change
---------	------	--------

1.0	2026-08-13	Initial release: GET /api/public/stock and GET /api/public/stock/{sku}
-----	------------	--

More endpoints (order status, RMA lookup, etc.) will be added to this document as they're built.