

BNS Warehouse System

Support Tickets API - Integration Guide

This document describes the API BNS Distribution makes available to a call-transcription or CRM-import partner so a finished call can open a support ticket - or add to one that already exists - without anyone typing it in by hand. It is versioned alongside the warehouse system itself, and shares its authentication scheme with the existing Public Stock API.

Document version: 1.0 | Last updated: 2026-09-23

Authentication

Every request to the public API must include a valid API key in the **X-API-Key** request header. Keys are issued by BNS Distribution from the internal "API Access" screen - contact your BNS account contact to request one. The same key works for both the Support Tickets API and the existing Stock API.

X-API-Key: bns_your_key_here

Requests without a valid, active key receive a 401 Unauthorized response:

```
{
  "timestamp": "2026-09-23T09:15:00",
  "status": 401,
  "error": "Unauthorized",
  "message": "Missing or invalid API key. Include a valid key in the X-API-Key header."
}
```

Keep your API key confidential. If a key is compromised, ask BNS Distribution to revoke it and issue a new one - revoked keys stop working immediately.

Base URL

All endpoints in this document are relative to your BNS Warehouse instance's base URL, for example:

`https://your-bns-instance.example.com/api/public`

Endpoints

POST /api/public/tickets

Opens a new support ticket. Use this once, at the end of a call, to create the ticket and (optionally) log its first timeline entry in a single request.

Request body

```
{
  "title": "Shipment hasn't arrived",
```

```

"callerName": "Jane Smith",
"phone": "07700900000",
"email": "jane@example.com",
"companyId": null,
"orderNumber": "SO-10019",
"talkTimeMinutes": 8,
"note": "Full call summary or transcript goes here.",
"author": "Call Transcript"
}

```

Fields

Field	Required	Description
title	Yes	Short ticket title/subject.
callerName	No	Name of the person who called or emailed.
phone	No	Caller's phone number.
email	No	Caller's email address.
companyId	No	BNS internal company ID, if already known. Usually left out - see orderNumber below.
orderNumber	No	The order's own display number (e.g. "SO-10019"), not an internal ID. When given, the ticket is linked to that order and its company automatically - the most common way tickets get linked.
talkTimeMinutes	No	Call duration in minutes. Defaults to 0 if left out.
note	No	Becomes the ticket's first timeline entry when present (e.g. a call summary or full transcript).
author	No	Attributes the note above to whoever/whatever supplied it. Defaults to "Call Transcript" if left out.

Example response (201 Created)

```

{
  "id": 42,
  "ticketNumber": "TKT-10042",
  "title": "Shipment hasn't arrived",
  "callerName": "Jane Smith",
  "phone": "07700900000",
  "email": "jane@example.com",
  "companyId": 7,
  "companyName": "Example Networks Ltd",
  "orderId": 519,
  "orderNumber": "SO-10019",
  "status": "IN_PROGRESS",
  "talkTimeMinutes": 8,
  "createdAt": "2026-09-23T14:02:11",
  "updatedAt": null,
  "entries": [

```

```
{
  "id": 101,
  "author": "Call Transcript",
  "note": "Full call summary or transcript goes here.",
  "createdAt": "2026-09-23T14:02:11"
}
]
```

If **orderNumber** is given but doesn't match any order, this returns a 400 Bad Request rather than silently creating an unlinked ticket.

```
{
  "timestamp": "2026-09-23T14:02:11",
  "status": 400,
  "error": "Bad Request",
  "message": "No order found with number SO-10019"
}
```

POST /api/public/tickets/{ticketNumber}/entries

Adds a new timeline entry to a ticket that already exists - use this if a caller rings back about the same issue and the ticket should be added to rather than duplicated. **{ticketNumber}** is the ticket's own display number (e.g. TKT-10042).

Request body

```
{
  "note": "Follow-up call - customer confirms the item was located.",
  "author": "Call Transcript"
}
```

Example response (201 Created)

```
{
  "id": 108,
  "author": "Call Transcript",
  "note": "Follow-up call - customer confirms the item was located.",
  "createdAt": "2026-09-23T16:40:02"
}
```

If the ticket number doesn't exist, this returns a 404:

```
{
  "timestamp": "2026-09-23T16:40:02",
  "status": 404,
  "error": "Not Found",
  "message": "Ticket TKT-99999 not found"
}
```

Errors

All error responses use a consistent shape: timestamp, status, error, and a human-readable message.

HTTP status codes follow standard conventions - 401 for authentication problems, 400 for a request that

can't be fulfilled as given (e.g. an unrecognised order number), 404 for a ticket number that doesn't exist, and 500 for anything unexpected on our side.

Changelog

Version	Date	Change
1.0	2026-09-23	Initial release: POST /api/public/tickets and POST /api/public/tickets/{ticketNumber}/entries

Read-only ticket lookups (e.g. checking a ticket's current status) will be added to this document if/when that's needed - today this API is write-only, covering the create-a-ticket workflow the call-transcription integration needs.