

Deploying and Managing Kubernetes Pods



David Clinton

Data Analyst | Linux System Administrator

bootstrap-it.com | linkedin.com/in/dbclinton





Updating a Running Pod



Scaling Pods Using Deployments



Adding Scheduling and Security to Kubernetes Pods

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
      capabilities:
        drop:
          - ALL
        add:
          - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
resources:
  requests:
    memory: "64Mi"
    cpu: "250m"
  limits:
    memory: "128Mi"
    cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```

A Deployment Definition:

```
spec:
  securityContext:
    fsGroup: 2000
  containers:
    - name: secure-container
      image: nginx:1.21
      ports:
        - containerPort: 80
      securityContext:
        runAsUser: 1000
        runAsGroup: 3000
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities:
          drop:
            - ALL
          add:
            - NET_BIND_SERVICE
      resources:
        requests:
          memory: "64Mi"
          cpu: "250m"
        limits:
          memory: "128Mi"
          cpu: "500m"
```