NATIONAL ECONOMICS UNIVERSITY
COLLEGE OF TECHNOLOGY

———- * ———-



MID-TERM ASSIGNMENT

COURSE: Data Analysis with Python

TOPIC: CLUSTERING EMPLOYEES BY WORK BEHAVIOUR AND SATISFACTION – HR ANALYTICS CASE STUDY

Academic advisor: Mr. Tran Duc Minh

Class: AI67C

Members	Student ID
Dang Hoang Minh Tu	11258574
Tran Nguyen Khoi	11253986
Nguyen Hong Nhat	11256438

2026–2027

Abstract

This report applies unsupervised learning to the *HR Analytics Case Study* dataset, which describes about 4,410 employees of a company through demographic, job, survey and attendance (swipe-in/swipe-out) records.

The goal is to discover naturally occurring employee segments without using any pre-defined label. We integrate the relational files, clean and engineer features (including average daily working hours derived from attendance logs), and compare three clustering algorithms — K-Means, Hierarchical (Ward) clustering and DBSCAN — using the Silhouette score, the Elbow method, Davies–Bouldin and Calinski–Harabasz indices.

The resulting segments are profiled and cross-checked against the `Attrition` column (used only for external validation) to derive practical HR recommendations.

Contents

1 Introduction **1**

1.1 Problem Definition 1

1.2 Dataset 1

1.3 Methodology 1

1.4 Source Code 2

2 Initial Data Inspection **2**

2.1 Dataset Overview 2

2.2 Column Consistency 3

2.3 Relationships Between Files 3

2.4 File Encoding 4

2.5 Data Types 4

2.6 Missing Values 4

2.6.1 General Dataset 4

2.6.2 Employee Dataset 5

2.6.3 Manager Dataset 5

2.6.4 Attendance Datasets 5

2.7 Duplicate Records 5

2.8 Initial Data Quality Assessment 5

3 Data Cleaning **6**

3.1 Merging the Tables 6

3.2 Removing Duplicates . . . 6
3.3 Handling Missing Values . . . 6
3.3.1 General and Employee datasets . . . 7
3.4 Processing Attendance Data . . . 8
3.5 Standardizing Data Types . . . 9
3.6 Summary of Data Cleaning . . . 10

4 Exploratory Data Analysis and Feature Selection 10
4.1 Distribution Analysis . . . 10
4.1.1 Age, income, tenure, distance and working hours . . . 10
4.1.2 Satisfaction and engagement surveys . . . 12
4.2 Correlation Analysis . . . 12
4.3 Outlier Detection . . . 14
4.4 Hypothesis Tests: Leavers vs. Stayers . . . 14
4.5 Feature Selection . . . 16
4.6 Feature Preprocessing for Clustering . . . 17
4.6.1 Encoding . . . 17
4.6.2 Log transformation . . . 17
4.6.3 Feature scaling . . . 18
4.7 Dimensionality Reduction . . . 18
4.7.1 PCA . . . 18
4.7.2 PCA and t-SNE in 2D . . . 19
4.8 Summary of EDA and Feature Selection . . . 20

5 Clustering Models 20
5.1 Evaluation Criteria . . . 21
5.2 K-Means . . . 21
5.3 Hierarchical Clustering (Ward) . . . 23
5.4 DBSCAN . . . 24
5.5 Model Comparison and Selected Model . . . 25
5.6 Summary and Limitations . . . 26

6 Model Evaluation 26
6.1 Comparison with Baselines . . . 26
6.2 Stability . . . 27

6.3 Sensitivity to the Feature Groups 28
6.4 Choice of k: $k = 3$ vs. $k = 5$ 28
6.5 Effect of Replicated Records 29

7 Cluster Profiling and External Validation 30
7.1 Cluster Profiles 30
7.2 External Validation with Attrition 31
7.3 Agreement between K-Means and Ward 33

8 Conclusion 33

1 Introduction

1.1 Problem Definition

Employee turnover is costly: every employee who leaves has to be replaced, recruited and trained again, and experience is lost with them. Human Resources (HR) departments therefore want to know *which kinds of employees* exist in the organisation and which of them need attention. The company in this case study has no such grouping; it only has raw records about each employee.

This project uses **unsupervised learning (clustering)** to discover naturally occurring groups of employees with similar career, workload, satisfaction and commute characteristics. No label is given to the algorithms: the goal is not to predict a known outcome, but to find structure that HR can act on. The recorded `Attrition` (whether the employee left the company) is deliberately *not* used for clustering; it is kept aside to check afterwards whether the discovered groups are meaningful.

Research questions.

1. Which employee characteristics carry enough structure to separate groups of employees?
2. Which clustering algorithm (K-Means, Hierarchical clustering, DBSCAN) and how many clusters give the best and most reliable segmentation?
3. How can the segments be described, and do they differ in attrition?
4. What practical actions can HR derive from the segments?

1.2 Dataset

The *HR Analytics Case Study* dataset from Kaggle describes 4,410 employees of one company in five files: general information (demographics, job, pay and career history), an employee satisfaction survey, a manager rating, and swipe-in and swipe-out times for every working day of 2015. Section 2 describes the files in detail.

1.3 Methodology

The analysis follows the steps recommended for the project:

1. **Data inspection** – consistency, keys, encoding, data types, missing values and duplicates of the five files (Section 2).

2. **Loading, integration and cleaning** – merging on `EmployeeID`, imputation, type conversion and conversion of the attendance logs into working-hour and absence features (Section 3).

3. **Exploratory data analysis and feature selection** – distributions, outliers, correlations, hypothesis tests, and preparation of 13 features (Section 4).

4. **Clustering** – K-Means, Ward hierarchical clustering and DBSCAN (Section 5).

5. **Evaluation** – Elbow method, Silhouette, Davies–Bouldin and Calinski–Harabasz indices, baselines, stability, sensitivity and the effect of replicated records (Section 6).

6. **Profiling and external validation** with `Attrition` (Section 7), followed by conclusions and recommendations (Section 8).

1.4 Source Code

All steps are implemented in a single Jupyter notebook, `HR-Analytics-Case-Study-Clustering.ipynb`, which runs from beginning to end and produces every table and figure of this report. The notebook, data and report sources are available in the public GitHub repository:

`https://github.com/DangHoangMinhTu/Project-3---Clustering-HR-Analytics-Case-Study`

2 Initial Data Inspection

Before data preprocessing, an initial inspection was conducted to understand the structure and quality of all five datasets. The inspection focused on the consistency of the files, the relationships between them, file encoding, data types, missing values, and duplicate records.

2.1 Dataset Overview

The HR Analytics dataset consists of five relational files: `general`, `employee`, `manager`, `in_time`, and `out_time`. Each file contains 4,410 records.

Table 1 summarizes the basic information of the five datasets.

Table 1: Overview of the five datasets

Criteria	General	Employee	Manager	In-time	Out-time
Records	4,410	4,410	4,410	4,410	4,410
Attributes	24	4	3	262	262
Missing values	28	83	0	109080	109080
Duplicate records	0	0	0	0	0

Across the five files, there are 555 attributes in total. However, the 22,050 records represent the sum of records across files, not the number of unique employees, since the same employees are represented in multiple relational files.

2.2 Column Consistency

The five files describe different information, so they cannot be concatenated; they must be merged later. Consistency was therefore checked in two ways. First, the numbers of rows and columns were compared (Table 1): every file has 4,410 rows, while the number of columns differs by file (24, 4, 3, 262 and 262). Second, the column names of `in_time` and `out_time`, which have the same structure (one column per calendar day), were compared. They contain the same 262 column names in the same order, so the two files can be processed in parallel when computing working hours. No column name other than `EmployeeID` is shared between the other files, so no naming conflict (e.g. `_x`, `_y` suffixes) will appear after merging.

2.3 Relationships Between Files

The common column of the five files is `EmployeeID`. In `in_time` and `out_time` this column is stored in an unnamed first column (`Unnamed: 0`) and is renamed to `EmployeeID`. Table 2 shows the key checks.

Table 2: Primary key / foreign key check on `EmployeeID`

File	Null keys	Duplicate keys	IDs not in General	General IDs missing
General	0	0	0	0
Employee	0	0	0	0
Manager	0	0	0	0
In-time	0	0	0	0
Out-time	0	0	0	0

`EmployeeID` is the **primary key** of the `general` dataset (unique and non-null) and the **foreign key** in the other four files, so the relationship is one-to-one. A test merge of `general`, `employee` and `manager` on `EmployeeID` returned 4,410 rows, i.e. no record was lost or duplicated.

2.4 File Encoding

The encoding of each CSV file was tested by decoding the raw bytes. All five files were successfully decoded as UTF-8 (no BOM, no decoding error), so no special encoding argument is needed when calling `pd.read_csv()` and no font or character errors are expected.

2.5 Data Types

The data types of each dataset were examined using the `info()` method.

Table 3: Distribution of data types across datasets

Dataset	int64	float64	str	Total attributes
General	14	2	8	24
Employee	1	3	0	4
Manager	3	0	0	3
In-time	1	12	249	262
Out-time	1	12	249	262
Total	**20**	**29**	**506**	**555**

The `general` dataset contains demographic and job-related information. The `employee` dataset provides employee satisfaction and work-life balance information, while the `manager` dataset contains job involvement and performance ratings.

The `in_time` and `out_time` datasets each contain 262 attributes, including 249 string attributes, 12 floating-point attributes, and 1 integer attribute. These two files contain attendance-related records and will be examined further during feature engineering.

2.6 Missing Values

Missing values were identified in the `general` and `employee` datasets.

2.6.1 General Dataset

The `general` dataset contains 28 missing values across two attributes.

Table 4: Missing values in the General dataset

Attribute	Missing values	Percentage
NumCompaniesWorked	19	0.43%
TotalWorkingYears	9	0.20%
Total	**28**	**0.63%**

2.6.2 Employee Dataset

The `employee` dataset contains 83 missing values across three attributes.

Table 5: Missing values in the Employee dataset

Attribute	Missing values	Percentage
EnvironmentSatisfaction	25	0.57%
JobSatisfaction	20	0.45%
WorkLifeBalance	38	0.86%
Total	**83**	**1.88%**

2.6.3 Manager Dataset

The `manager` dataset contains three attributes (`EmployeeID`, `JobInvolvement` and `PerformanceRating`). All 4,410 records are non-null, so no missing values were detected in this file.

2.6.4 Attendance Datasets

The `in_time` and `out_time` datasets each contain 262 attributes and 4,410 records. Each file has 109,080 missing cells (9.5% of the $4{,}410 \times 261$ date cells), and the two files have their missing cells in exactly the same positions. These cells are not random gaps: a cell is empty when the employee did not swipe on that day (public holiday, leave or absence). They are therefore not imputed but converted into attendance features during cleaning (Section 3.4).

2.7 Duplicate Records

Duplicate records were checked in all five datasets. The results showed that no duplicate records were detected in any of the files.

2.8 Initial Data Quality Assessment

Based on the initial inspection, the following observations were identified:

- All five datasets contain 4,410 records each, with a total of 555 attributes.
- The datasets contain numerical and string data types, requiring appropriate preprocessing techniques.
- The `general` dataset contains 28 missing values, while the `employee` dataset contains 83 missing values.
- The `manager` dataset contains no missing values.

- The attendance datasets contain 109,080 missing cells each, which represent days without a swipe rather than data errors.
- No duplicate records were detected in the five datasets.
- `EmployeeID` links all files (primary key in `general`, foreign key elsewhere), and the files can be read with UTF-8 encoding.

These findings provide an overview of the data structure and initial data quality. The next step is to examine the attendance records, handle missing values, and prepare suitable features for clustering.

3 Data Cleaning

The inspection in the previous section showed missing values in the `general`, `employee`, `in_time` and `out_time` files, no duplicate records, and attendance dates stored as strings. This section describes how each problem was handled to obtain the final table `df_clean`. The pipeline is implemented in the accompanying notebook.

3.1 Merging the Tables

The `general`, `employee` and `manager` files were joined on `EmployeeID` with `validate="one_to_one"`, which raises an error if any key is repeated. The merged table keeps all 4,410 employees and contains 28 columns. The two attendance files are processed separately (Section 3.4) and joined at the end.

3.2 Removing Duplicates

Duplicates were checked again after merging, because joins can silently multiply rows. Two criteria were used: fully identical rows and repeated `EmployeeID`. Both checks returned 0, so no record was removed and the table keeps 4,410 employees.

A third check compared the rows of `general` *without* the identifier. Here 2,912 rows (66%) are identical to another row in every column except `EmployeeID`: the file contains only 1,498 distinct profiles, most of them three times. The copies have different survey answers and attendance logs, so they are not plain duplicates and were kept. Their effect on the models is analysed in Section 6.5.

3.3 Handling Missing Values

Missing values were not treated in the same way everywhere. The decision depends on *why* a value is missing.

Table 6: Missing-value handling strategy

Dataset	Attribute	Missing	Strategy
General	NumCompaniesWorked	19	Median imputation
General	TotalWorkingYears	9	Median imputation
Employee	EnvironmentSatisfaction	25	Mode imputation
Employee	JobSatisfaction	20	Mode imputation
Employee	WorkLifeBalance	38	Mode imputation
Manager	—	0	No action
In/Out-time	all date columns	109,080 each	Not imputed: interpreted as absence and converted to features

3.3.1 General and Employee datasets

The General and Employee datasets contain 28 (0.63%) and 83 (1.88%) missing values, respectively. Because these counts are small, all rows were retained instead of being deleted, so that the other attributes of the affected employees are not lost. The missing values were imputed with a statistic chosen according to the nature of each variable.

Count variables: median. `NumCompaniesWorked` and `TotalWorkingYears` are non-negative counts. Figure 1 shows that both are right-skewed (skewness 1.12 and 1.03): most employees have low values, while a small number have very high ones (up to 40 years of experience and up to 9 previous companies) that form a long upper tail. These extreme values pull the mean above the median (11.28 vs. 10 years; 2.69 vs. 2 companies), so the mean no longer describes a typical employee, and for an integer count it also produces non-integer values. The median is not affected by the tail, so it was used.




Figure 1: Distribution of `TotalWorkingYears` and `NumCompaniesWorked` (box: interquartile range, orange line: median, circles: outliers beyond 1.5×IQR).

Ordinal survey scores: mode. `EnvironmentSatisfaction`, `JobSatisfaction` and `WorkLifeBalance` are ordinal scores from 1 to 4. Figure 2 shows that their means (2.72, 2.73 and 2.76) fall between two levels and do not correspond to any valid answer. The

mode (3, 4 and 3) is the level chosen most often, is always a valid score, and keeps the discrete nature of the variable, so it was used instead of the mean.




Figure 2: Distribution of the three survey scores, with mean (dashed) and mode (solid).

3.4 Processing Attendance Data

Each of `in_time` and `out_time` has 261 date columns and 109,080 missing cells. These are *not* random gaps. A cell is empty when the employee did not swipe on that day, that is, on a public holiday, on leave or when absent. Filling them with a mean or median would invent working hours that never happened. The cells were therefore handled in five steps:

Step 1. Convert to datetime. All 261 date columns were parsed with `pd.to_datetime`.

Step 2. Remove non-working days. Days on which no employee has a swipe-in and swipe-out are public holidays or closed days and carry no information. 12 such columns (the float columns in Table 3) were dropped. They account for $12 \times 4{,}410 = 52{,}920$ of the missing cells in each file, and the remaining $109{,}080 - 52{,}920 = 56{,}160$ cells are individual absences. The number of working days is therefore $N_{\text{work}} = 249$.

Step 3. Validate records. A day is valid only if both swipe-in and swipe-out exist and the duration lies in $(0, 24]$ hours. The check found 0 days with only one of the two swipes and 0 days with an invalid duration, so no record had to be discarded.

Step 4. Aggregate per employee. The remaining missing days are skipped (not filled) when computing the features below.

Step 5. Join. The three features are merged into the main table on `EmployeeID` (one-to-one).

$$h_{i,d} = t_{i,d}^{\text{out}} - t_{i,d}^{\text{in}} \quad \text{(hours, valid days only)}, \tag{1}$$

$$\text{AvgWorkHours}_i = \frac{1}{|D_i|} \sum_{d \in D_i} h_{i,d}, \tag{2}$$

$$\text{AbsentDays}_i = N_{\text{work}} - |D_i|, \qquad \text{AbsentRate}_i = \frac{\text{AbsentDays}_i}{N_{\text{work}}}, \tag{3}$$

where D_i is the set of valid days of employee i. Every employee has at least one valid day, so no median fallback was needed for these features.

Table 7: Summary of the engineered attendance features

Feature	**Mean**	**Std**	**Min**	**Median**	**Max**
AvgWorkHours	7.70	1.34	5.95	7.41	11.03
AbsentDays	12.74	5.50	1	13	24
AbsentRate	0.051	0.022	0.004	0.052	0.096

After this step the dataset contains **no missing values** (Table 9).

3.5 Standardizing Data Types

Table 8: Data type conversions

Attributes	**Before**	**After**	**Reason**
261 date columns of in/out-time	string	datetime	Needed to compute working hours
Survey scores, `NumCompaniesWorked`, `TotalWorkingYears`	float64	int64	Imputed values are whole numbers
`BusinessTravel`, `Department`, `EducationField`, `Gender`, `JobRole`, `MaritalStatus`	string	category	Memory and correct encoding
`Attrition`	string (Yes/No)	int64 (1/0)	External validation only

Three constant attributes (`EmployeeCount`, `Over18`, `StandardHours`) have a single value for all employees. They cannot separate clusters and were dropped.

A logical consistency check compared `YearsAtCompany` with `TotalWorkingYears`. Two employees (0.05%) have more years at the company than total working years (IDs 24 and 4410). Both had a missing `TotalWorkingYears` that was filled with the median (10 years), so the conflict comes from the imputation, not from the raw data. The effect is negligible and these records were kept unchanged.

3.6 Summary of Data Cleaning

Table 9: Dataset before and after cleaning

Criteria	Before	After
Employees (rows)	4,410	4,410
Missing values (general + survey)	111	0
Missing values (attendance, per file)	109,080	0 (converted to features)
Duplicate records	0	0
Constant attributes	3	0
Attributes (final table)	555 (5 files)	29

The 29 attributes of `df_clean` are: 21 attributes of `general` (24 minus 3 constant ones), 3 survey scores from `employee`, 2 ratings (`JobInvolvement`, `PerformanceRating`) from `manager`, and 3 attendance features. The cleaned table has one row per employee and is ready for exploratory data analysis and feature selection.

The complete code of every step is in the accompanying notebook (see the GitHub repository in Section 1).

4 Exploratory Data Analysis and Feature Selection

This section examines the cleaned table `df_clean`, selects the variables used for clustering, and prepares them (encoding, scaling, dimensionality reduction). No target variable exists in clustering, so the EDA looks for the distributions and relationships that decide which fields can separate groups of employees. `Attrition` is not used here; it is kept for the external validation of the clusters.

4.1 Distribution Analysis

4.1.1 Age, income, tenure, distance and working hours

Table 10 and Figure 3 describe the main numeric variables.

Table 10: Summary statistics of the main numeric variables

Variable	Mean	Std	Min	Median	Max	Skew
Age	36.92	9.13	18	36	60	0.41
MonthlyIncome	65,029	47,069	10,090	49,190	199,990	1.37
TotalWorkingYears	11.28	7.77	0	10	40	1.12
YearsAtCompany	7.01	6.13	0	5	40	1.76
DistanceFromHome	9.19	8.11	1	7	29	0.96
AvgWorkHours	7.70	1.34	5.95	7.41	11.03	0.86




Figure 3: Distribution of the main numeric variables with mean (dashed) and median (solid).

- **Age** is almost symmetric (skew 0.41) and ranges from 18 to 60, so no transformation is needed.
- **MonthlyIncome** is right-skewed (skew 1.37): the mean (65,029) is well above the median (49,190), and a few employees earn close to 200,000.
- **TotalWorkingYears** and **YearsAtCompany** are also right-skewed (1.12 and 1.76). Half of the employees have been at the company for 5 years or less, while a small group reaches 40 years.
- **DistanceFromHome** is slightly right-skewed (0.96); half of the employees live within 7 km, the maximum is 29 km.
- **AvgWorkHours** (from the attendance logs) has a mean of 7.70 hours and a range of 5.95–11.03 hours. About 18% of employees (813) average more than 9 hours per day, which is the overload signal sought for clustering.

The box plots in Figure 4 show the same upper tails as outlier points. These values are real (senior staff, very long careers) and are exactly the groups clustering should detect, so they are *not removed*; the skew is reduced by a log transformation instead (Section 4.6).




Figure 4: Box plots of the main numeric variables.

4.1.2 Satisfaction and engagement surveys




Figure 5: Share of employees at each score (1–4) of the four survey variables.

Figure 5 shows two different patterns. `EnvironmentSatisfaction` and `JobSatisfaction` are spread over all four levels: about 39% of employees give a low score (1–2) and about 61% a high score (3–4), so a clearly dissatisfied group exists. `WorkLifeBalance` and `JobInvolvement` are concentrated at level 3 (61.2% and 59.0%), and only 5.4% and 5.6% of employees choose level 1. These two variables separate groups less strongly, but their extreme levels point to small and potentially at-risk segments.

4.2 Correlation Analysis

Spearman correlation was used because many variables are ordinal or skewed. Figure 6 shows the matrix and Table 11 lists the pairs with $|\rho| \geq 0.5$.




Figure 6: Spearman correlation matrix of the numeric variables.

Table 11: Strongly correlated pairs ($|\rho| \geq 0.5$)

Variable 1	**Variable 2**	**Spearman ρ**
AbsentDays	AbsentRate	1.00
YearsAtCompany	YearsWithCurrManager	0.84
Age	TotalWorkingYears	0.66
PercentSalaryHike	PerformanceRating	0.63
TotalWorkingYears	YearsAtCompany	0.59
YearsAtCompany	YearsSinceLastPromotion	0.52

Three observations drive the feature selection:

1. The strongly correlated pairs are redundant measurements of the same idea (tenure, age, absence). Keeping both variables would count that idea twice in a distance-based model.

2. Outside these pairs the variables are almost uncorrelated. For example `MonthlyIncome` is unrelated to `JobLevel` ($\rho = 0.05$) and to tenure, and `AvgWorkHours` is unrelated to the satisfaction scores ($|\rho| \leq 0.05$). Income therefore acts as an independent dimension, and a single "senior and well paid" axis should not be expected.

3. The only noticeable relation of `AvgWorkHours` is with `AbsentRate` ($\rho = -0.23$): employees who work longer days are absent less often.

4.3 Outlier Detection

Outliers were counted with the interquartile-range rule: a value is an outlier if it lies below $Q_1 - 1.5\,\mathrm{IQR}$ or above $Q_3 + 1.5\,\mathrm{IQR}$, where $\mathrm{IQR} = Q_3 - Q_1$. Table 12 lists every variable with outliers and the decision taken.

Table 12: Outliers by the IQR rule and handling decision

Variable	**Outliers**	**%**	**Decision**
TrainingTimesLastYear	714	16.2	Keep; discrete 0–6, not a clustering feature
PerformanceRating	678	15.4	Keep; only values 3 and 4, the rule flags all 4s
MonthlyIncome	342	7.8	Keep; real high salaries, reduced by $\log(1+x)$
YearsSinceLastPromotion	321	7.3	Keep; stagnation is a profile of interest, $\log(1+x)$
YearsAtCompany	312	7.1	Keep; long tenure is real, $\log(1+x)$
StockOptionLevel	255	5.8	Keep; discrete 0–3, not a clustering feature
TotalWorkingYears	189	4.3	Keep; $\log(1+x)$
NumCompaniesWorked	156	3.5	Keep; not a clustering feature
YearsWithCurrManager	42	1.0	Keep; not a clustering feature
AvgWorkHours	38	0.9	Keep; long hours are the overtime profile of interest

None of the flagged values is impossible (no negative tenure, no working day longer than 24 hours), so no outlier is a data error. They are real but extreme employees: senior staff with high pay or long tenure, and people who work long days. Deleting them would remove exactly the profiles HR is interested in, so all of them were **kept**. Instead, the skewed clustering features are log-transformed (Section 4.6) so that the extremes do not dominate the distances. For discrete variables such as `PerformanceRating` the IQR rule flags a whole category, which is not an outlier in a meaningful sense.

4.4 Hypothesis Tests: Leavers vs. Stayers

Before clustering, each variable was tested for a difference between employees who left and those who stayed. The null hypothesis H_0 is that the variable has the same distribution in both groups. The Mann–Whitney U test was used for numeric and ordinal variables, because it does not assume normality, and the chi-square test of independence for categorical variables. `Attrition` is used here only to understand the data.

Table 13: Tests of difference between leavers and stayers ($\alpha = 0.05$)

Variable	Test	Median (left)	Median (stayed)	p-value
TotalWorkingYears	Mann–Whitney	7.0	10.0	2.4×10^{-39}
AvgWorkHours	Mann–Whitney	8.19	7.31	8.0×10^{-37}
YearsAtCompany	Mann–Whitney	3.0	6.0	1.2×10^{-36}
YearsWithCurrManager	Mann–Whitney	2.0	3.0	2.5×10^{-31}
MaritalStatus	Chi-square	–	–	8.5×10^{-31}
Age	Mann–Whitney	32	36	6.0×10^{-30}
BusinessTravel	Chi-square	–	–	1.8×10^{-16}
JobSatisfaction	Mann–Whitney	3	3	6.4×10^{-12}
EnvironmentSatisfaction	Mann–Whitney	3	3	3.0×10^{-10}
Department	Chi-square	–	–	4.8×10^{-7}
WorkLifeBalance	Mann–Whitney	3	3	7.8×10^{-4}
AbsentRate	Mann–Whitney	0.048	0.052	6.5×10^{-3}
NumCompaniesWorked	Mann–Whitney	1	2	0.058
MonthlyIncome	Mann–Whitney	49,080	49,300	0.107
Gender	Chi-square	–	–	0.245
JobInvolvement	Mann–Whitney	3	3	0.463
JobLevel	Mann–Whitney	2	2	0.842
DistanceFromHome	Mann–Whitney	7	7	0.926

Selected variables. Above the line: significant at $\alpha = 0.05$; below: not significant. The full table is in the notebook.

- The strongest differences concern **tenure**: leavers are younger and have fewer working years, fewer years at the company and fewer years with their manager.
- **Working hours** are just as important: leavers work about 8.2 hours per day against 7.3 for stayers.
- The three **satisfaction** scores, business travel, marital status and department also differ significantly (for the ordinal scores the medians are equal, but the distributions are shifted).
- **Income, job level, job involvement, distance from home and gender do not differ** ($p > 0.05$).
- These results support using tenure, workload and satisfaction as clustering features. Distance from home is not linked to attrition but is kept to describe the commute dimension.
- Caveat: many records are replicated in this dataset (Section 6.5), so the effective sample is about 1,500 rather than 4,410 and the p-values are optimistic. The large effects remain significant either way.

4.5 Feature Selection

The features were chosen to describe the three kinds of segments targeted by the project: senior and well-paid staff, newcomers and employees at burnout risk, and employees with heavy workload but low satisfaction. Table 14 lists the 13 selected features by group. The choice is also supported by the hypothesis tests of Section 4.4: tenure, workload and satisfaction differ between leavers and stayers.

The four satisfaction scores need a remark. They are kept because describing satisfaction is part of the project goal, but they are almost uncorrelated with every other feature, so they may add little *group structure*. This is tested in the sensitivity analysis (Section 6.3): removing them barely changes the clusters.

Table 14: Selected clustering features

Group	**Features**	**Purpose**
Seniority & pay	MonthlyIncome, JobLevel, TotalWorkingYears, YearsAtCompany, YearsSinceLastPromotion	Senior vs. new staff, stagnation
Workload & attendance	AvgWorkHours, AbsentRate	Overload and absence
Satisfaction & engagement	EnvironmentSatisfaction, JobSatisfaction, WorkLifeBalance, JobInvolvement	Well-being, engagement
Commute & travel	DistanceFromHome, BusinessTravel	Extra load outside working hours

Table 15: Variables not used as clustering input

Variable	**Reason**
EmployeeID, Attrition	Identifier; Attrition is kept for external validation
AbsentDays	Duplicate of AbsentRate ($\rho = 1.00$)
YearsWithCurrManager	Redundant with YearsAtCompany ($\rho = 0.84$)
Age	Redundant with TotalWorkingYears ($\rho = 0.66$)
PerformanceRating	Only two values (3: 84.6%, 4: 15.4%) and tied to PercentSalaryHike
PercentSalaryHike	Tied to PerformanceRating ($\rho = 0.63$), unrelated to the goal
Education, NumCompaniesWorked, StockOptionLevel, TrainingTimesLastYear	Not linked to the workload, satisfaction or seniority goals
Department, JobRole, EducationField, MaritalStatus, Gender	Nominal; used to profile the clusters after clustering

4.6 Feature Preprocessing for Clustering

4.6.1 Encoding

- **Ordinal encoding.** `BusinessTravel` has a natural order and was mapped to Non-Travel = 0, Travel_Rarely = 1, Travel_Frequently = 2.
- **One-hot encoding.** The five nominal variables (Department, JobRole, EducationField, MaritalStatus, Gender) have no order and were one-hot encoded into 23 binary columns. They are *not* part of the clustering input: they would make up 23 of the 36 columns and dominate the distances, and they lower the silhouette score (Table 17). They are kept to profile the clusters.
- The survey scores and `JobLevel` are already ordered integers and are used as they are.

4.6.2 Log transformation

Continuous variables with skewness above 1 were transformed with $x' = \log(1 + x)$ (Figure 7). The transformation keeps every employee, pulls in the long upper tail, and is safe for the value 0.

Table 16: Skewness before and after the $\log(1 + x)$ transformation

Variable	Before	After
MonthlyIncome	1.37	0.29
TotalWorkingYears	1.12	−0.62
YearsAtCompany	1.76	−0.21
YearsSinceLastPromotion	1.98	0.72




Figure 7: Skewed variables before (top) and after (bottom) the $\log(1+x)$ transformation.

4.6.3 Feature scaling

`StandardScaler` was applied, $z = (x - \mu)/\sigma$, so every feature has mean 0 and variance 1. Without scaling, `MonthlyIncome` (standard deviation 47,069) is thousands of times larger than the other variables (for example 8.11 for `DistanceFromHome`) and decides almost all of the distance. Table 17 confirms the effect. All partitions are scored in the same scaled space: K-Means fitted on the unscaled data reaches at most 0.066, because it only cuts `MonthlyIncome` into bands. (Measured in its own raw space the same partition reaches 0.708 for $k = 2$, but that value only reflects the dominance of income and is not comparable.) Adding one-hot nominal variables does not change the result.

Table 17: K-Means silhouette score by number of clusters k for three preprocessing choices (all scored in the scaled 13-feature space)


Input	$k = 2$	$k = 3$	$k = 4$	$k = 5$	$k = 6$
Raw features (no scaling)	0.066	0.026	0.014	0.010	0.003
Log + StandardScaler (13 features)	0.103	0.082	0.078	0.082	0.080
Scaled + one-hot nominal (36 columns)	0.103	0.081	0.078	0.082	0.080

`StandardScaler` was preferred over `MinMaxScaler` because the data still contains tail values after the log transformation, and min–max scaling would squeeze most employees into a narrow range.

4.7 Dimensionality Reduction

4.7.1 PCA

PCA was fitted on the 13 scaled features. Figure 8 shows that the first two components explain only 15.8% and 9.8% of the variance (25.6% together), and 11 of the 13 components are needed to reach 90%. The information is therefore spread over many directions, and PCA would remove very little. For this reason PCA is used **for visualisation only**, and the clustering algorithms run on the 13 scaled features.



(a) Explained variance (b) Loadings of PC1–PC3

Figure 8: PCA of the scaled features.

The loadings give each component a clear meaning:

- **PC1 (15.8%) – tenure**: `YearsAtCompany` (0.62), `TotalWorkingYears` (0.56) and `YearsSinceLastPromotion` (0.54).
- **PC2 (9.8%) – workload**: `AvgWorkHours` (0.69) against `AbsentRate` (−0.66).
- **PC3 – pay and travel**: `MonthlyIncome` (0.68), `JobLevel` (0.38), `BusinessTravel` (−0.48) and `DistanceFromHome` (−0.34).

4.7.2 PCA and t-SNE in 2D

Figure 9 projects the employees onto two dimensions with PCA and t-SNE (perplexity 30, `random_state=42`), coloured by `AvgWorkHours`. The colour is only a visual aid and is not used by the models.




Figure 9: PCA (left) and t-SNE (right) projections of the scaled features, coloured by `AvgWorkHours`.

In the PCA view, working hours increase smoothly along PC2, which matches the loadings above. There is no empty gap between groups: the employees form one continuous cloud. The t-SNE view shows the same picture, with only a few local concentrations of long working hours and no clearly separated islands. t-SNE is used for drawing only; it does not preserve global distances, so it is not used as clustering input.

4.8 Summary of EDA and Feature Selection

- 13 features in four groups (seniority and pay, workload and attendance, satisfaction and engagement, commute and travel) were selected; redundant, constant-like and nominal variables were set aside.
- The input matrix `X` (4,410 × 13) is log-transformed where skewed and standardised; nominal variables are one-hot encoded for profiling only.
- The features are weakly correlated and the 2D projections show one continuous cloud. Clusters with low-to-moderate separation should therefore be expected: the silhouette score of the scaled data is about 0.08–0.10. A low score here reflects the data, not an error, and the clusters will be judged together with the other indices and their business meaning.
- In the next phase K-Means, Hierarchical (Ward) clustering and DBSCAN are run on `X`, and PCA/t-SNE are used to draw the resulting clusters.

5 Clustering Models

Three algorithms were applied to the matrix `X` of 4,410 employees × 13 scaled features (Section 4.6): K-Means, Hierarchical clustering with Ward linkage, and DBSCAN. All

results use the same input and `random_state=42`.

5.1 Evaluation Criteria

Because no label exists, the clusterings are judged with internal indices. For employee i, let $a(i)$ be the mean distance to the other members of its cluster and $b(i)$ the mean distance to the nearest other cluster.

$$s(i) = \frac{b(i) - a(i)}{\max\{a(i), b(i)\}}, \qquad \text{Silhouette} = \frac{1}{n}\sum_{i=1}^{n} s(i) \in [-1, 1], \tag{4}$$

$$\text{WCSS} = \sum_{j=1}^{k} \sum_{x \in C_j} \|x - \mu_j\|^2 \quad \text{(inertia)}. \tag{5}$$

- **Silhouette** (higher is better): cohesion against separation.
- **Davies–Bouldin** (lower is better): average similarity between each cluster and its most similar cluster.
- **Calinski–Harabasz** (higher is better): ratio of between-cluster to within-cluster dispersion. It tends to fall as k grows, so it is read together with the other indices.
- **Elbow (WCSS)**: the k after which the decrease of inertia slows down.
- **Stability**: mean Adjusted Rand Index (ARI) between K-Means models fitted on 10 random 80% subsamples, each labelling all employees. A value near 1 means the same partition is found again.

5.2 K-Means

K-Means was run for $k = 2, \ldots, 10$ with 20 random initialisations per k. Table 18 and Figure 10 show the indices.

Table 18: K-Means model selection

k	Inertia	Drop (%)	Silhouette	Davies–B.	Calinski–H.	Stability
2	51,465	–	**0.103**	2.716	**502.3**	**0.947**
3	48,751	5.3	0.081	3.046	387.8	0.851
4	46,659	4.3	0.078	2.848	335.9	0.623
5	44,709	4.2	0.082	2.666	310.9	0.816
6	43,145	3.5	0.080	2.570	289.6	0.704
7	41,837	3.0	0.075	2.458	271.8	0.787
8	40,806	2.5	0.078	2.338	254.6	0.683
9	39,982	2.0	0.074	**2.251**	238.7	0.602
10	39,298	1.7	0.066	2.413	224.3	0.562




Figure 10: Elbow curve, silhouette score and stability of K-Means for $k = 2, \ldots, 10$. The dashed line marks the chosen $k = 5$.

Reading the indices.

- **Elbow.** The inertia falls smoothly (the drop shrinks from 5.3% to 1.7% per extra cluster) and there is no sharp bend. The elbow method alone therefore does not give a clear k, which is typical of data without well-separated groups.
- **Silhouette.** The global maximum is at $k = 2$ (0.103), followed by a plateau of 0.075–0.082 for $k = 3, \ldots, 8$ with a local peak at $k = 5$ (0.082).
- $k = 2$ **is too coarse.** The two clusters differ almost only in tenure (mean z-scores of `YearsSinceLastPromotion`, `YearsAtCompany` and `TotalWorkingYears` are $-0.53/+1.09$, $-0.48/+0.98$ and $-0.36/+0.74$ in the two clusters, while all other features stay within ± 0.1). This corresponds to the first principal component found in the PCA and cannot represent the workload, commute and satisfaction profiles targeted by the project.
- **Choice.** Restricting the search to $k \geq 3$, $\mathbf{k = 5}$ has the highest silhouette (0.0819 against 0.0814 for $k = 3$), the lowest Davies–Bouldin value among $k = 3, 4, 5$ (2.666), and a high stability (ARI 0.82). $k = 4$ and $k = 6$ are clearly less stable (0.62 and 0.70). The margin between $k = 3$ and $k = 5$ is small; $k = 5$ was kept because it gives finer segments, and $k = 3$ remains a valid coarser alternative (stability 0.85).

Silhouette plot. Figure 11 shows the silhouette of every employee for $k = 5$. The five clusters have sizes 949, 556, 1,469, 740 and 696. The mean silhouette is 0.082 and only 3.2% of employees have a negative value, so few employees are clearly assigned to the wrong cluster; but most values are small (below 0.2), meaning that the clusters touch each other rather than being isolated.




Figure 11: Silhouette plot of K-Means with $k = 5$.

5.3 Hierarchical Clustering (Ward)

Agglomerative clustering with Ward linkage (minimum increase of within-cluster variance, Euclidean distance) was applied to the same matrix. Figure 12 shows the dendrogram of the last 30 merges and the merge distance as a function of the number of clusters.




Figure 12: Ward dendrogram (left) and merge distance by number of clusters (right). The dashed line is the cut for $k = 5$.

The merge distance decreases gradually: 88.0 for $k = 2$, 67.1 for $k = 3$, 60.1 for $k = 4$, 56.0 for $k = 5$ and 51.2 for $k = 6$. There is no large jump that would indicate a natural cut, so the dendrogram confirms that the data has a continuous rather than a clearly layered structure. Cutting at five clusters (the choice made for K-Means) gives sizes 989, 451, 434, 1,576 and 960.

Table 19: Ward model selection

k	Silhouette	Davies–B.	Calinski–H.
2	0.073	2.976	319.3
3	0.062	3.378	263.5
4	0.045	3.543	235.8
5	0.047	3.240	218.6
6	0.048	3.060	204.6
7	0.047	2.976	192.6
8	0.044	2.989	184.6
9	0.043	2.861	177.7
10	0.038	2.711	169.5

For every k Ward has a lower silhouette than K-Means (Table 19 against Table 18). The two $k = 5$ partitions agree only partly (ARI $= 0.344$), so Ward does not simply reproduce the K-Means segments.

5.4 DBSCAN

DBSCAN finds dense regions and labels the remaining points as noise. It was used mainly to detect employees with unusual behaviour. With 13 features, `min_samples` was set to $2 \times 13 = 26$. Figure 13 shows the sorted distance of each employee to its 26-th nearest neighbour, which guides the choice of `eps`.




Figure 13: k-distance plot ($k = 26$). The dashed line marks $\varepsilon = 3.0$.

Table 20: DBSCAN sensitivity to ε (`min_samples` $= 26$)

ε	Clusters	Noise points	Noise (%)
2.6	1	927	21.0
2.8	1	348	7.9
3.0	**1**	**105**	**2.4**
3.2	1	33	0.7
3.4	1	4	0.1

For every tested ε DBSCAN returns **one single cluster** plus noise (Table 20). The employees therefore form one connected dense region and no density-separated groups exist, which agrees with the dendrogram and the 2D projections. Because of this, DBSCAN cannot be used to segment the workforce and silhouette-type indices are not defined for it. It is used as an anomaly detector: $\varepsilon = 3.0$ marks 105 employees (2.4%) as noise, a share small enough to be reviewed individually.




Figure 14: The 105 DBSCAN anomalies on the t-SNE map (left) and their mean z-score per feature (right).

Figure 14 shows what these employees have in common: they are high-level, long-hour employees with poor work-life balance. Compared with the average employee they have a higher `JobLevel` (+0.94), higher `AvgWorkHours` (+0.87), higher `MonthlyIncome` (+0.69) and longer commute (+0.65), and a much lower `WorkLifeBalance` (−0.87), shorter tenure and lower `JobInvolvement` (−0.48). As an external check, their attrition rate is **36.2%**, against 15.6% for the other employees, so the anomalies flag a group at real risk of leaving even though `Attrition` was never used by the algorithm.

5.5 Model Comparison and Selected Model

Table 21: Comparison of the algorithms at $k = 5$

Model	Silhouette	Davies–B.	Calinski–H.	Result
K-Means ($k = 5$)	**0.082**	**2.666**	**310.9**	5 segments
Ward ($k = 5$)	0.047	3.240	218.6	5 segments
DBSCAN ($\varepsilon = 3.0$)	–	–	–	1 cluster + 105 anomalies

K-Means is better than Ward on all three indices, and DBSCAN finds no segmentation. **K-Means with $k = 5$ is therefore selected** to segment the employees, and DBSCAN is kept as a complementary anomaly detector. Figure 15 shows the K-Means clusters on the PCA and t-SNE maps. The clusters are neighbouring regions of one continuous cloud, not separate islands, as expected from the low silhouette.




Figure 15: K-Means clusters ($k = 5$) on the PCA (left) and t-SNE (right) maps.

5.6 Summary and Limitations

- K-Means with $k = 5$ is the selected model (silhouette 0.082, Davies–Bouldin 2.666, stability ARI 0.82); $k = 3$ is a close, more stable alternative.
- All indices are low in absolute terms (silhouette below 0.11 for every model and k). The data has weak group structure: the features are almost uncorrelated and the points form one continuous cloud. The clusters should be read as *soft segments* along the main dimensions (tenure, workload, commute), not as natural, isolated groups.
- The indices alone cannot prove that $k = 5$ is the true number of groups; the segments must be judged by their meaning and by external validation, which is done in Sections 6 and 7 by evaluating, profiling and comparing their attrition rates.
- DBSCAN highlights 105 high-level, long-hour employees with poor work-life balance and a 36.2% attrition rate.

6 Model Evaluation

The previous section selected K-Means with $k = 5$ using internal indices. This section checks whether that choice holds up from four further angles: (i) comparison with baselines, (ii) stability, (iii) sensitivity to the feature groups, and (iv) external validation against `Attrition` (Section 7).

6.1 Comparison with Baselines

Two baselines were built. A model that cannot beat them has found nothing useful:

- **Random labels**: every employee is assigned to one of five groups at random (mean over 20 draws).
- **Unscaled K-Means**: K-Means ($k = 5$) fitted on the raw features, without log transform or scaling.

All partitions are scored in the same scaled 13-feature space, so the values are directly comparable.

Table 22: Internal validity of the models against the baselines ($k = 5$)

Model	Clusters	Silhouette ↑	Davies–B. ↓	Calinski–H. ↑
Baseline: random labels	5	−0.007	52.40	1.0
Baseline: K-Means, unscaled	5	0.010	9.61	86.7
K-Means	5	**0.082**	**2.67**	**310.9**
Ward	5	0.047	3.24	218.6
DBSCAN ($\varepsilon = 3.0$)	1	–	–	–

- K-Means and Ward both clearly beat the **random baseline** (silhouette ≈ 0, Calinski–Harabasz ≈ 1). The partitions capture real, if weak, structure.
- The **unscaled** K-Means only cuts `MonthlyIncome` into bands: its between-cluster spread is 1.31 standard deviations for income and at most 0.10 for any other feature. In the scaled space this partition is barely better than random (silhouette 0.010). Scaling is therefore essential, and the high silhouette of the raw data in Section 4.6 is an artefact of measuring it in an income-dominated space.
- **K-Means is better than Ward on all three indices**. DBSCAN returns one cluster and cannot be scored.

6.2 Stability

Table 23: Stability of K-Means with $k = 5$ (Adjusted Rand Index)

Test	Mean ARI	Min ARI
20 bootstrap samples vs. final model (`n_init=10`)	0.801	0.496
20 random seeds, single initialisation (`n_init=1`)	0.525	0.287
10 subsamples of 80%, pairwise (Table 18)	0.816	–

With a single initialisation, K-Means often stops in a different local optimum (mean ARI 0.53), so many initialisations are needed; the final model uses 20. With 10 initialisations the partition is reproduced reasonably on bootstrap samples (mean ARI 0.80, consistent with the 0.82 obtained on subsamples), but the worst resample only reaches 0.50. The main segments are stable; the borders between neighbouring clusters are soft, so individual assignments near a border should not be over-interpreted.

6.3 Sensitivity to the Feature Groups

Each of the four feature groups (Table 14) was removed in turn and K-Means ($k = 5$) was refitted. A high ARI with the final model means the group hardly influences the segmentation; a low ARI means the group drives it.

Table 24: K-Means ($k = 5$) after removing one feature group

Removed group	**Features left**	**Silhouette**	**ARI vs. final model**
Seniority & pay	8	0.121	0.267
Workload & attendance	11	0.097	0.519
Satisfaction & engagement	9	0.125	**0.895**
Commute & travel	11	0.094	0.507
None (final model)	13	0.082	1.000

Removing *seniority & pay*, *workload* or *commute* changes the partition substantially (ARI 0.27–0.52): these three groups **drive** the segmentation. Removing the four *satisfaction* scores leaves the partition almost unchanged (ARI 0.90) and raises the silhouette. The survey scores add noise rather than structure, which matches the EDA (they are uncorrelated with every other variable). They are kept in the model because the project aims to describe satisfaction, but no segment should be expected to be defined by satisfaction alone.

6.4 Choice of k: $k = 3$ vs. $k = 5$

Model selection (Table 18) kept $k = 5$ but noted $k = 3$ as a close, slightly more stable alternative. Table 25 compares the two on all criteria, including the link with attrition.

Table 25: K-Means with $k = 3$ and $k = 5$

Criterion	$\boldsymbol{k = 3}$	$\boldsymbol{k = 5}$
Silhouette ↑	0.081	0.082
Davies–Bouldin ↓	3.046	**2.666**
Calinski–Harabasz ↑	**387.8**	310.9
Stability (ARI, 80% subsamples)	**0.851**	0.816
Cramér's V with Attrition ↑	0.159	**0.255**
Attrition range across clusters	11.4%–25.2%	**8.6%–37.1%**
Cluster sizes	1,852 / 1,280 / 1,278	1,469 / 949 / 740 / 696 / 556

The internal indices are almost tied: $k = 3$ is slightly better on Calinski–Harabasz (which always favours small k) and stability, $k = 5$ is clearly better on Davies–Bouldin. The decisive difference is external: $k = 3$ only splits employees by tenure, so attrition varies only between 11% and 25%, whereas $k = 5$ also isolates the overtime and long-commute groups and separates attrition much more sharply (8.6% to 37.1%, Cramér's V 0.26 instead

of 0.16). Since the indices do not prefer either option, the better external validity and the more actionable segments justify $k = 5$.

6.5 Effect of Replicated Records

As noted in Section 3, the 4,410 employees come from only 1,498 distinct `general` profiles: 4,326 employees belong to a profile that appears three times, 56 to a profile that appears twice and 28 are unique. Copies always share the same `Attrition` value, but have different survey answers and attendance logs. The Kaggle file was evidently built by replicating a smaller HR table.

In the 13-feature clustering space the copies sit close together: for 92.2% of employees the nearest neighbour is a copy of themselves, and the median distance between copies (1.09) is about 4.5 times smaller than between two random employees (4.93). Table 26 shows what happens when only one copy per profile is kept.

Table 26: DBSCAN noise share on all employees and on one copy per profile (`min_samples` = 26)

ε	Noise, all 4,410 (%)	Noise, 1,498 profiles (%)	Clusters (profiles)
2.6	21.0	48.8	1
2.8	7.9	26.2	1
3.0	2.4	10.1	1
3.2	0.7	3.3	1

- **DBSCAN.** Every point automatically has two very close neighbours, so the local density is artificially high. With one copy per profile the same ε marks 2–5 times more employees as noise (10.1% instead of 2.4% at $\varepsilon = 3.0$). The ε chosen on the full data is therefore optimistic. DBSCAN still finds a single cluster: the replication does not create a group structure, it only hides sparse regions.
- **K-Means.** On one copy per profile the silhouette barely changes (0.076 vs. 0.082), but the partition is only partly reproduced (ARI 0.51 with the final model), consistent with soft cluster borders.
- **Statistical tests.** The effective sample is about 1,500 independent profiles, so the p-values of the hypothesis tests and of the chi-square test with attrition are smaller than they should be. Because the effects are large, the conclusions do not change.
- The records were kept, because each copy carries its own survey and attendance information.

7 Cluster Profiling and External Validation

7.1 Cluster Profiles

Table 27 gives the mean of the main variables in each K-Means cluster, and Figure 16 the standardised means of all features. `Age` and `NumCompaniesWorked` were not used for clustering and serve as an additional check. The names were assigned with explicit rules (fewest working years → Newcomers; then longest time since promotion, longest working hours, longest commute; the remaining cluster is the Steady core).

Table 27: Profile of the five K-Means segments (means)

	Newcomers	**Overtime workers**	**Long commuters**	**Stagnant veterans**	**Steady core**
Employees	556	740	696	949	1,469
Share of workforce	12.6%	16.8%	15.8%	21.5%	33.3%
TotalWorkingYears	2.5	11.3	9.8	17.9	11.0
YearsAtCompany	1.3	6.1	5.6	14.4	5.6
YearsSinceLastPromotion	0.4	1.4	1.1	7.0	0.7
AvgWorkHours	7.67	**9.74**	7.35	7.42	7.03
AbsentRate (%)	4.9	3.7	5.3	5.2	5.8
DistanceFromHome (km)	6.3	7.9	**22.9**	8.2	5.1
MonthlyIncome	67,016	59,727	61,692	71,797	64,158
EnvironmentSatisfaction	2.95	2.92	2.72	2.69	2.57
JobSatisfaction	2.74	2.90	2.68	2.71	2.69
WorkLifeBalance	2.80	2.63	2.80	2.83	2.76
Age*	29.5	37.8	36.3	41.0	37.0
Attrition rate*	**37.1%**	**23.4%**	13.1%	12.0%	8.6%

* not used for clustering.




Figure 16: Standardised cluster means (z-score against the company mean). Left of the vertical line: clustering features; right: variables not used for clustering.

- **Newcomers (12.6%)**: about 2.5 years of total experience and 1.3 years at the company, 29 years old, 46% single (company: 32%).

- **Overtime workers (16.8%)**: 9.7 working hours per day (z = +1.52) and the fewest absences. Their job and environment satisfaction is not lower than average; only work-life balance is slightly lower (z = −0.20).
- **Long commuters (15.8%)**: about 23 km from home (z = +1.69), otherwise close to the company average.
- **Stagnant veterans (21.5%)**: 14 years at the company and *seven years since the last promotion* (z = +1.48), the highest income.
- **Steady core (33.3%)**: the shortest working days (7.0 hours), closest to the office (5.1 km), recently promoted.

Department and marital-status mixes are almost identical across segments, except the high share of single employees among the newcomers.

7.2 External Validation with Attrition

`Attrition` was never given to the algorithms. If the segments differ clearly in attrition, this is independent evidence that they are meaningful. The association was measured with a chi-square test of independence and Cramér's $V = \sqrt{\chi^2/(n(\min(r,c)-1))}$.

Table 28: Association between cluster labels and `Attrition`

Partition	χ^2	p-value	Cramér's V
K-Means ($k = 5$)	**286.2**	1.0×10^{-60}	**0.255**
Ward ($k = 5$)	107.0	3.2×10^{-22}	0.156
DBSCAN anomaly vs. rest	30.5	3.3×10^{-8}	0.083
Random labels	1.0	0.91	0.015




Figure 17: Attrition rate per K-Means segment. Dashed line: company average (16.1%).

Table 29: Concentration of leavers per segment

Segment	Leavers	Attrition	Share of workforce	Share of leavers	Lift
Newcomers	206	37.1%	12.6%	29.0%	**2.30**
Overtime workers	173	23.4%	16.8%	24.3%	**1.45**
Long commuters	91	13.1%	15.8%	12.8%	0.81
Stagnant veterans	114	12.0%	21.5%	16.0%	0.75
Steady core	127	8.6%	33.3%	17.9%	0.54

- The K-Means segments are strongly associated with attrition ($p \approx 10^{-60}$, Cramér's $V = 0.26$), while random labels show no association ($p = 0.91$). K-Means also separates attrition better than Ward ($V = 0.16$), which agrees with the internal indices.
- **Newcomers** and **overtime workers** make up 29% of the workforce but 53% of all leavers. Their attrition rates are 2.3 and 1.45 times the company average.
- The overtime group is a burnout signal that a satisfaction survey would miss: these employees do not report lower job satisfaction.
- The steady core is the most stable segment (8.6%).

Cluster × Attrition matrix. A clustering model does not predict a label, so a classic confusion matrix cannot be computed. Its closest equivalent is the contingency matrix between the clusters and the true `Attrition` value (Figure 18). Reading row by row, 206 of the 556 newcomers left (37.1%), but only 127 of the 1,469 employees of the steady core (8.6%). Two segments, newcomers and overtime workers, contain 379 of the 711 leavers. A partition unrelated to attrition would show about 16% in every row, as the random baseline does.




Figure 18: Contingency matrix between K-Means segments and `Attrition`: counts (left) and percentages within each segment (right).

7.3 Agreement between K-Means and Ward




Figure 19: Number of employees in each combination of K-Means segment and Ward cluster ($k = 5$).

Figure 19 shows where the two algorithms agree. The cores of most segments coincide: 74.6% of the stagnant veterans, 73.5% of the steady core and 69.8% of the newcomers fall into a single Ward cluster. The algorithms disagree in two places. Ward puts the newcomers and most long commuters into the *same* cluster, so it does not separate distance from low tenure, and it spreads the overtime workers over several clusters (only 48.1% in the best match). This explains the moderate ARI of 0.34: both methods find the main structure but draw different borders in a continuous cloud. The K-Means partition is preferred because it separates attrition better (Cramér's V 0.26 vs. 0.16).

8 Conclusion

Summary. Five relational files describing 4,410 employees were merged and cleaned, and the attendance logs were converted into working-hour and absence features. Thirteen features covering seniority and pay, workload, satisfaction and commute were log-transformed where skewed, standardised and clustered with K-Means, Ward hierarchical clustering and DBSCAN.

Best model. **K-Means with** $k = 5$ is the best model. It is better than Ward on all internal indices, clearly beats the random and unscaled baselines, is reasonably stable under bootstrap resampling (ARI 0.80) and separates attrition better than Ward. DBSCAN finds no segmentation in this continuous data but is useful as an anomaly detector: 2.4% of employees, mostly high-level staff with long working hours and poor work-life balance, with 36% attrition.

Practical implications. The segmentation tells HR *where* to act first and *what kind* of action fits each group. Table 30 summarises the evidence and the recommended actions.

Table 30: Recommended HR actions by segment

Segment	What the data shows	Recommended actions
Newcomers (12.6%)	About 2.5 years of experience and 1.3 years at the company; 37% leave, 2.3 times the average. They are 13% of the staff but 29% of all leavers.	Structured onboarding with a named mentor; check-in meetings after 3, 6 and 12 months; a visible path to the first promotion within two years; exit interviews to learn why they leave.
Overtime workers (16.8%)	About 9.7 hours per day, two hours more than average, and the fewest absences; 23% leave, 1.45 times the average. Their satisfaction scores are *not* lower, so a survey would not reveal them.	Monthly report of working hours per team; an alert when an employee exceeds about 9 hours per day for several weeks; redistribute work or hire; compensatory time off.
Stagnant veterans (21.5%)	About 14 years at the company and 7 years without promotion; the highest income; 12% leave.	Career conversations; specialist tracks that do not require a management position; job rotation; a mentoring role for newcomers.
Long commuters (15.8%)	About 23 km from home, otherwise average; 13% leave.	Not a priority today; flexible hours or partial remote work and a transport allowance can prevent fatigue.
Steady core (33.3%)	About 7 hours per day, close to the office, recently promoted; 9% leave.	Keep current conditions; use as the reference group when evaluating HR policies.

How to use the segmentation in practice.

1. Assign every current and new employee to a segment with the fitted scaler and K-Means model.
2. Concentrate the retention budget on the two high-risk segments. They hold 53% of all leavers but only 29% of the workforce, so the same effort reaches almost twice as many potential leavers as an untargeted programme.
3. Review the 105 DBSCAN anomalies one by one: they combine long hours, poor work-life balance and a 36% attrition rate.
4. Repeat the clustering every year to see whether employees move out of the high-risk segments after the actions above.

Limitations.

- The cluster structure is weak (silhouette 0.08): the segments are soft regions of one continuous cloud, and employees near a border could belong to a neighbouring segment.

- The satisfaction scores add no structure (removing them barely changes the partition), so the segmentation cannot identify satisfaction-based groups.
- The dataset is semi-synthetic: the 4,410 employees come from only 1,498 distinct profiles (Section 6.5), which inflates the density used by DBSCAN and makes p-values optimistic; several attributes behave like independent random values; attendance covers only 2015; and K-Means assumes roughly spherical clusters of similar size.

Future work. Gaussian Mixture Models (soft membership) or K-Prototypes (numeric and categorical features together) could be tested; the segments should be validated on real HR data; and they can be combined with a supervised attrition model to target retention actions at individual employees.

List of Figures

1 Distribution of `TotalWorkingYears` and `NumCompaniesWorked` (box: interquartile range, orange line: median, circles: outliers beyond 1.5×IQR). . 7

2 Distribution of the three survey scores, with mean (dashed) and mode (solid). 8

3 Distribution of the main numeric variables with mean (dashed) and median (solid). 11

4 Box plots of the main numeric variables. 11

5 Share of employees at each score (1–4) of the four survey variables. 12

6 Spearman correlation matrix of the numeric variables. 13

7 Skewed variables before (top) and after (bottom) the $\log(1 + x)$ transformation. 17

8 PCA of the scaled features. 19

9 PCA (left) and t-SNE (right) projections of the scaled features, coloured by `AvgWorkHours`. 20

10 Elbow curve, silhouette score and stability of K-Means for $k = 2, \ldots, 10$. The dashed line marks the chosen $k = 5$. 22

11 Silhouette plot of K-Means with $k = 5$. 23

12 Ward dendrogram (left) and merge distance by number of clusters (right). The dashed line is the cut for $k = 5$. 23

13 k-distance plot ($k = 26$). The dashed line marks $\varepsilon = 3.0$. 24

14 The 105 DBSCAN anomalies on the t-SNE map (left) and their mean z-score per feature (right). 25

15 K-Means clusters ($k = 5$) on the PCA (left) and t-SNE (right) maps. . . . 26

16 Standardised cluster means (z-score against the company mean). Left of the vertical line: clustering features; right: variables not used for clustering. 30

17 Attrition rate per K-Means segment. Dashed line: company average (16.1%). 31

18 Contingency matrix between K-Means segments and `Attrition`: counts (left) and percentages within each segment (right). 32

19 Number of employees in each combination of K-Means segment and Ward cluster ($k = 5$). 33

List of Tables

1 Overview of the five datasets 3

2 Primary key / foreign key check on `EmployeeID` 3

3 Distribution of data types across datasets 4
4 Missing values in the General dataset 4
5 Missing values in the Employee dataset 5
6 Missing-value handling strategy 7
7 Summary of the engineered attendance features 9
8 Data type conversions 9
9 Dataset before and after cleaning 10
10 Summary statistics of the main numeric variables 10
11 Strongly correlated pairs ($|\rho| \geq 0.5$) 13
12 Outliers by the IQR rule and handling decision 14
13 Tests of difference between leavers and stayers ($\alpha = 0.05$) 15
14 Selected clustering features 16
15 Variables not used as clustering input 16
16 Skewness before and after the $\log(1 + x)$ transformation 17
17 K-Means silhouette score by number of clusters k for three preprocessing choices (all scored in the scaled 13-feature space) 18
18 K-Means model selection 21
19 Ward model selection 24
20 DBSCAN sensitivity to ε (`min_samples` = 26) 24
21 Comparison of the algorithms at $k = 5$ 25
22 Internal validity of the models against the baselines ($k = 5$) 27
23 Stability of K-Means with $k = 5$ (Adjusted Rand Index) 27
24 K-Means ($k = 5$) after removing one feature group 28
25 K-Means with $k = 3$ and $k = 5$ 28
26 DBSCAN noise share on all employees and on one copy per profile (`min_samples` = 26) 29
27 Profile of the five K-Means segments (means) 30
28 Association between cluster labels and `Attrition` 31
29 Concentration of leavers per segment 32
30 Recommended HR actions by segment 34