



UNIVERSITÀ  
DEGLI STUDI  
FIRENZE

SCUOLA DI INGEGNERIA  
Corso di Laurea Magistrale in Ingegneria  
Informatica

# Illuminant maps analysis for image splicing detection

Lorenzo Cioni

ANNO ACCADEMICO 2015/2016

# Introduction

---

This method is based on *T. Carvalho, V. Schetinger et al.* works presented in [1] and [2].

**Main goal:** finding image inconsistencies based on **illuminant estimation** in order to determine if an image has been **tampered** or not.



# Illuminant Maps estimation

---

For the Illuminant Maps estimation, two different techniques are used:

1. A *statistical-based* approach using **Generalized Grayworld Estimate (GGE)** algorithm.
2. A *physics-based* approach using **Inverse-Intensity Chromaticity (IIC)** method.



## 2.1 Generalized Greyworld Estimate (GGE)

---

**Generalized Greyworld Estimate** is proposed in [2] as a combination of the *Grey-World* and *Grey-Edge methods* aimed to evaluate **color constancy**.

The main premise behind it is that in a normal well color balanced photo, the **average** of all the colors is a neutral gray. Therefore, it assumes that the *Minkowski norm* of the derivative of the reflectance in a scene is **achromatic**.

$$k\mathbf{e}^{n,p,\sigma} = \left( \int \left| \frac{\vartheta^n \mathbf{f}^\sigma(\mathbf{x})}{\vartheta \mathbf{x}^n} \right|^p d\mathbf{x} \right)^{\frac{1}{p}} \quad (1)$$

where  $\mathbf{x}$  denotes a pixel coordinate,  $k$  is a scale factor,  $|\cdot|$  is the absolute value operator,  $\vartheta$  the partial differential operator,  $\mathbf{f}^\sigma$  is the observed intensities at position  $\mathbf{x}$ , smoothed by a Gaussian kernel  $\sigma$ ,  $p$  is the *Minkowski norm*, and  $n$  is the derivative order.

## Generalized Greyworld Estimate (GGE)

---

The illuminant estimation of (1) is a framework for low-level based illuminant estimation based on three variables:

1. The order  $n$  of the image structure.
2. The Minkowski norm  $p$  which determines the relative weights of the multiple measurements from which the final illuminant color is estimated.
3. The scale of the local measurements as denoted by  $\sigma$ .

### Advantages:

- the Minkowski norm of RGB values or derivatives can be computed *extremely fast*
- the method does not require an image database taken under a **known light source**

## Inverse-Intensity Chromaticity (IIC)

Extension of the **dichromatic reflectance model**, which states that *the amount of light reflected from a point,  $\mathbf{x}$ , of a dielectric, non-uniform material is a linear combination of diffuse reflection and specular reflection.*

Given an image taken with a **RGB camera**, the response  $I_c(\mathbf{x})$  for each color filter  $c \in \{R, G, B\}$  is

$$I_c(\mathbf{x}) = m_d(\mathbf{x})B_c(\mathbf{x}) + m_s(\mathbf{x})G_c(\mathbf{x})$$

where  $m_d$  and  $m_s$  are geometric parameters of **diffuse and specular reflection**.

Let  $\Delta_c(\mathbf{x})$  and  $\Gamma_c(\mathbf{x})$  be the diffuse and **specular chromaticity**:


$$\Delta_c(\mathbf{x}) = \frac{B_c(\mathbf{x})}{\sum_{i \in \{R, G, B\}} B_i(\mathbf{x})} \text{ and } \Gamma_c(\mathbf{x}) = \frac{G_c(\mathbf{x})}{\sum_{i \in \{R, G, B\}} G_i(\mathbf{x})}$$

## Inverse-Intensity Chromaticity (IIC)

In this model, the intensity  $I_c(\mathbf{x})$  and the chromaticity  $\sigma_c(\mathbf{x})$  of a color channel  $c \in \{R, G, B\}$  at pixel position  $\mathbf{x}$  are related by

$$\sigma_c(\mathbf{x}) = p_c(\mathbf{x}) \frac{1}{\sum_{i \in \{R, G, B\}} I_i(\mathbf{x})} + \Gamma_c(\mathbf{x}) \quad (2)$$

where  $p_c(\mathbf{x}) = w_d(\mathbf{x}) \sum_i B_i(\mathbf{x})(\Delta_c(\mathbf{x}) - \Gamma_c(\mathbf{x}))$



The *domain* of the line is determined by  $\frac{1}{\sum_i I_i(\mathbf{x})}$  and the *range* is given by  $0 \leq \sigma_c \leq 1$ . Domain and range together form the **inverse-intensity chromaticity (IIC) space**.

## Riferimenti bibliografici

---

- [1] T. Carvalho, et al. *Illuminant-Based Transformed Spaces for Image Forensics*. IEEE Transactions on Information Forensics and Security 11.4 (2016): 720-733.
- [2] V. Schetinger et al. *Exploring Statistical Differences Between Illuminant Estimation Methods for Exposing Digital Forgeries*; 2016.
- [3] J. van de Weijer, Th. Gevers, A. Gijsenij, Edge-Based Color Constancy, IEEE Trans. Image Processing, accepted 2007.
- [4] C. Riess and E. Angelopoulou. 2010. *Scene illumination as an indicator of image manipulation*. In *Proceedings of the 12th international conference on Information hiding*, Berlin, Heidelberg, 66-80.