

MAJOR TECHNICAL SPECIFICATIONS

Item				U.S.A.			
Body Type				Sedan			
Vehicle Grade				LE		XLE	SE
Model Code				ACV40L-A(C)EMNKA	ACV40L-A(C)EANKA	ACV40L-A(C)EAGKA	ACV40L-CEMSKA
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4805 (189.2)	4805 (189.2)	4805 (189.2)	4805 (189.2)
		Width	mm (in.)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
		Height	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1465 (57.7)
	Wheel Base		mm (in.)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
	Tread	Front	mm (in.)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
		Rear	mm (in.)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
	Effective Head Room	Front	mm (in.)	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2
		Rear	mm (in.)	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2
	Effective Leg Room	Front	mm (in.)	1059 (41.7)	1059 (41.7)	1059 (41.7)	1059 (41.7)
		Rear	mm (in.)	974 (38.3)	974 (38.3)	974 (38.3)	974 (38.3)
	Shoulder Room	Front	mm (in.)	1469 (57.8)	1469 (57.8)	1469 (57.8)	1469 (57.8)
		Rear	mm (in.)	1446 (56.9)	1446 (56.9)	1446 (56.9)	1446 (56.9)
	Overhang	Front	mm (in.)	945 (37.2)	945 (37.2)	945 (37.2)	945 (37.2)
		Rear	mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	Min. Running Ground Clearance		mm (in.)	140 (5.5)	140 (5.5)	140 (5.5)	135 (5.3)
	Angle of Approach		degrees	14.1	14.1	14.1	12.8
	Angle of Departure		degrees	15.3	15.3	15.3	14.9
Curb Weight	Front	kg (lb)	870 (1918), 875 (1929)*3	890 (1962), 895 (1973)*3	900 (1984), 905 (1995)*3	890 (1962)	
	Rear	kg (lb)	600 (1323), 605 (1334)*3	600 (1323), 605 (1334)*3	615 (1356), 625 (1378)*3	600 (1323)	
	Total	kg (lb)	1470 (3241), 1480 (3263)*3	1490 (3285), 1500 (3307)*3	1515 (3340), 1530 (3373)*3	1490 (3285)	
Gross Vehicle Weight (MLVW*1)	Front	kg (lb)	976 (2152), 981 (2162)*3	997 (2197), 1003 (2212)*3	1010 (2227), 1015 (2237)*3	1003 (2212)	
	Rear	kg (lb)	931 (2053), 938 (2068)*3	929 (2048), 936 (2063)*3	945 (2083), 952 (2098)*3	943 (2078)	
	Total	kg (lb)	1907 (4205), 1919 (4230)*3	1925 (4245), 1939 (4275)*3	1955 (4310), 1966 (4335)*3	1946 (4290)	
Fuel Tank Capacity		ℓ (US.gal, Imp.gal)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	
Luggage Capacity (SAE)		m³ (cu.ft.)	0.425 (15.0)	0.425 (15.0)	0.411 (14.5)	0.411 (14.5)	
Performance	Max. Speed		km/h (mph)	210 (130)	205 (127)	205 (127)	210 (130)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Acceleration	0 to 60 mph	sec.	9.1	9.3	9.3	9.1
		0 to 400 m	sec.	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	54 (34)	54 (34)	54 (34)	54 (34)
		2nd Gear	km/h (mph)	95 (59)	98 (61)	98 (61)	95 (59)
		3rd Gear	km/h (mph)	146 (91)	152 (94)	152 (94)	146 (91)
		4th Gear	km/h (mph)	200 (124)	—	—	200 (124)
		5th Gear	km/h (mph)	—	—	—	—
	Turning Diameter (Outside Front)	Wall to Wall	m (ft)	11.8 (38.7)	11.8 (38.7)	11.8 (38.7)	11.8 (38.7)
		Curb to Curb	m (ft)	11.0 (36.1)	11.0 (36.1)	11.0 (36.1)	11.0 (36.1)
Engine	Engine Type		2AZ-FE				2AZ-FE
	Valve Mechanism		16-valve, DOHC with VVT-i				16-valve, DOHC with VVT-i
	Bore x Stroke		mm (in.)	88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	88.5 x 96.0 (3.48 x 3.78)	
	Displacement		cm³ (cu.in.)	2362 (144.1)	2362 (144.1)	2362 (144.1)	
	Compression Ratio		9.8 : 1	9.8 : 1	9.8 : 1	9.8 : 1	
	Carburetor Type		SFI	SFI	SFI	SFI	
	Octane Rating		87 or more	87 or more	87 or more	87 or more	
	Max. Output (SAE-NET) kW / rpm (HP@rpm)		118 / 6000 (158 @ 6000), 116 / 6000 (155 @ 6000)*4	118 / 6000 (158 @ 6000), 116 / 6000 (155 @ 6000)*4	118 / 6000 (158 @ 6000), 116 / 6000 (155 @ 6000)*4	118 / 6000 (158 @ 6000), 116 / 6000 (155 @ 6000)*4	
Max. Torque (SAE-NET) N·m / rpm (ft-lbf@rpm)		218 / 4000 (161 @ 4000), 214 / 4000 (158 @ 4000)*4	218 / 4000 (161 @ 4000), 214 / 4000 (158 @ 4000)*4	218 / 4000 (161 @ 4000), 214 / 4000 (158 @ 4000)*4	218 / 4000 (161 @ 4000), 214 / 4000 (158 @ 4000)*4		
Engine Electrical	Battery Capacity (5HR) Voltage & Amp. hr.		12-55	12-55	12-55	12-55	
	Alternator Output		Watts	1200	1200	1200	
	Starter Output		kW	1.7	1.7	1.7	
Chassis	Clutch Type		Dry, Single				Dry, Single
	Transaxle Type		E351	U250E	U250E	E351	
	Gear Ratio	In First	3.538	3.943*5	3.943*5	3.538	
		In Second	2.045	2.197*5	2.197*5	2.045	
		In Third	1.333	1.413*5	1.413*5	1.333	
		In Fourth	0.972	0.975*5	0.975*5	0.972	
		In Fifth	0.731	0.703*5	0.703*5	0.731	
		In Sixth	—	—	—	-	
	In Reverse	3.583	3.145*5	3.145*5	3.583		
		3.944	3.391	3.391	3.944		
	Differential Gear Ratio		3.944	3.391	3.391	3.944	
	Brake Type	Front	Ventilated Disc				Ventilated Disc
		Rear	Solid Disc				Solid Disc
	Parking Brake Type		Duo-servo				Duo-servo
	Brake Booster Type and Size		Single,10"				Single,10"
Proportioning Valve Type		—				—	
Suspension Type	Front	MacPherson Strut				MacPherson Strut	
	Rear	MacPherson Strut				MacPherson Strut	
Stabilizer Bar	Front	Standard				Standard	
	Rear	Standard				Standard	
Steering Gear Type		Rack & Pinion				Rack & Pinion	
Power Steering Type		Hydraulic Type				Hydraulic Type	

*1: Maximum Loaded Vehicle Mass *2: With sliding roof *3: TMMK production models *4: Models for California package *5: Counter gear ratio included

U.S.A.				
Sedan				
	SE	LE	XLE	SE
	ACV40L-CEASKA	GSV40L-A(C)ETNKA	GSV40L-A(C)ETGKA	GSV40L-CETSKA
5	4805 (189.2)	4805 (189.2)	4805 (189.2)	4805 (189.2)
	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
	1465 (57.7)	1470 (57.9)	1470 (57.9)	1465 (57.7)
	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
10	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2	986 (38.8), 962 (37.9)*2
	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2	959 (37.8), 950 (37.4)*2
	1059 (41.7)	1059 (41.7)	1059 (41.7)	1059 (41.7)
	974 (38.3)	974 (38.3)	974 (38.3)	974 (38.3)
15	1469 (57.8)	1469 (57.8)	1469 (57.8)	1469 (57.8)
	1446 (56.9)	1446 (56.9)	1446 (56.9)	1446 (56.9)
	945 (37.2)	945 (37.2)	945 (37.2)	945 (37.2)
	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
	135 (5.3)	135 (5.3)	135 (5.3)	130 (5.1)
20	12.8	14.1	14.1	12.8
	14.9	15.3	15.3	14.9
	900 (1984)	960 (2116), 965 (2127)*3	965 (2127), 970 (2138)*3	965 (2127)
	610 (1345)	600 (1323), 605 (1334)*3	620 (1367), 625 (1378)*3	615 (1356)
	1520 (3351)	1560 (3439), 1570 (3461)*3	1585 (3494), 1595 (3516)*3	1580 (3483)
25	1017 (2242)	1062 (2342), 1069 (2357)*3	1069 (2357), 1076 (2372)*3	1078 (2377)
	949 (2093)	931 (2053), 936 (2063)*3	947 (2088), 952 (2098)*3	956 (2108)
	1966 (4335)	1994 (4395), 2005 (4420)*3	2016 (4445), 2028 (4470)*3	2034 (4485)
	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)
	0.411 (14.5)	0.425 (15.0)	0.411 (14.5)	0.411 (14.5)
30	210 (130)	230 (143)	230 (143)	230 (143)
	—	—	—	—
	9.3	6.8	6.8	6.8
	—	—	—	—
	54 (34)	60 (37)	60 (37)	60 (37)
35	98 (61)	104 (65)	104 (65)	104 (65)
	152 (94)	139 (86)	139 (86)	139 (86)
	—	198 (123)	198 (123)	198 (123)
	—	—	—	—
	11.8 (38.7)	11.8 (38.7)	11.8 (38.7)	11.8 (38.7)
40	11.0 (36.1)	11.0 (36.1)	11.0 (36.1)	11.0 (36.1)
	2AZ-FE	2GR-FE	2GR-FE	2GR-FE
	16-valve, DOHC with VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i
	88.5 x 96.0 (3.48 x 3.78)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)	94.0 x 83.0 (3.70 x 3.27)
	2362 (144.1)	3456 (210.9)	3456 (210.9)	3456 (210.9)
45	9.8 : 1	10.8 : 1	10.8 : 1	10.8 : 1
	SFI	SFI	SFI	SFI
	87 or more	87 or more	87 or more	87 or more
	118 / 6000 (158 @ 6000), 118 / 6000 (155 @ 6000)*4	200 / 6200 (268 @ 6200)	200 / 6200 (268 @ 6200)	200 / 6200 (268 @ 6200)
	218 / 4000 (161 @ 4000), 214 / 4000 (158 @ 4000)*4	336 / 4700 (248 @ 4700)	336 / 4700 (248 @ 4700)	336 / 4700 (248 @ 4700)
50	12-55	12-55	12-55	12-55
	1200	1200	1200	1200
	1.7	1.7	1.7	1.7
	—	—	—	—
	U250E	U660E	U660E	U660E
55	3.943*5	3.300	3.300	3.300
	2.197*5	1.900	1.900	1.900
	1.413*5	1.420	1.420	1.420
	0.975*5	1.000	1.000	1.000
	0.703*5	0.713	0.713	0.713
60	—	0.608	0.608	0.608
	3.145*5	4.148	4.148	4.148
	3.391	3.685*5	3.685*5	3.685*5
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Solid Disc	Solid Disc	Solid Disc	Solid Disc
65	Duo-servo	Duo-servo	Duo-servo	Duo-servo
	Single, 10"	Single, 10"	Single, 10"	Single, 10"
	—	—	—	—
	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
70	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard
	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type