

■ PERFORMANCE AND SPECIFICATION

1. Performance

Heater	Heat Output	W	6000
	Air Flow Volume	m ³ /h	360
	Power Consumption	W	Maximum 210
Air Conditioning	Cooling Capacity	W	6100
	Air Flow Volume	m ³ /h	530
	Power Consumption	W	Maximum 260

2. Specification

Ventilation and Heater Core	Heater Core	Type	SFA (Straight Flow Aluminum) -II	
		Size W x H x L mm (in.)	201.5 x 150 x 27 (7.9 x 5.9 x 1.1)	
		Fin Pitch mm (in.)	1.5 (0.06)	
	Blower	Motor Type	K70 BMM	
		Fan Type	Semi Sirocco	
		Fan Size Dia. x H mm (in.)	165 x 70 (6.5 x 2.8)	
Air Conditioning	Condenser	Type	MF (Multi-Flow) -IV	
		Size W x H x L mm (in.)	720 x 370.2 x 16 (28.3 x 14.6 x 0.6)	
		Fin Pitch mm (in.)	3.15 (0.12)	
	Evaporator	Type	RS (Revolutionary super-slim Structure)	
		Size W x H x L mm (in.)	266.3 x 251 x 38 (10.5 x 9.9 x 1.5)	
		Fin Pitch mm (in.)	2.6 (0.1)	
	Compressor	Type	2GR-FE	6SBU16
			2AZ-FE	6SEU16
		Pulley	2GR-FE	Steel with Magnetic Clutch
			2AZ-FE	DL (Damper Limiter) without Magnetic Clutch
	Refrigerant	Type	HFC 134a	
		Charge Volume g	450 to 550	