

WHEEL ALIGNMENT STANDARD

1. FRONT WHEEL ALIGNMENT

Standard vehicle height:

for USA and Canada:


Model	Front A – B	Rear C – D
ACV40L-CEAGKA	125 mm (4.92 in.)	54 mm (2.13 in.)
GSV40L-CETGKA	126 mm (4.96 in.)	55 mm (2.17 in.)
ACV40L-AEAGKA	125 mm (4.92 in.)	53 mm (2.09 in.)
GSV40L-AETGKA	126 mm (4.96 in.)	54 mm (2.13 in.)
ACV40L-CEANKA	125 mm (4.92 in.)	54 mm (2.13 in.)
ACV40L-CEMNKA	125 mm (4.92 in.)	53 mm (2.09 in.)
GSV40L-CETNKA	126 mm (4.96 in.)	55 mm (2.17 in.)
ACV40L-AEANKA	125 mm (4.92 in.)	53 mm (2.09 in.)
ACV40L-AEMNKA	125 mm (4.92 in.)	52 mm (2.05 in.)
GSV40L-AETNKA	126 mm (4.96 in.)	54 mm (2.13 in.)
ACV40L-CEASKA	128 mm (5.04 in.)	57 mm (2.24 in.)
ACV40L-CEMSKA	127 mm (5.00 in.)	55 mm (2.17 in.)
GSV40L-CETSKA	129 mm (5.08 in.)	58 mm (2.28 in.)

for Mexico:

Model	Front A – B	Rear C – D
ACV40L-CEAGKA	115 mm (4.53 in.)	40 mm (1.57 in.)
GSV40L-CETGKA	116 mm (4.57 in.)	41 mm (1.61 in.)
ACV40L-CEANKA	115 mm (4.53 in.)	40 mm (1.57 in.)

for General export:

Model	Front A – B	Rear C – D
ACV40L-AEANKW	115 mm (4.53 in.)	38 mm (1.50 in.)
ACV40R-AEANKW	115 mm (4.53 in.)	38 mm (1.50 in.)
ACV40L-AEMNKW	117 mm (4.61 in.)	42 mm (1.65 in.)
ACV40R-AEMNKW	117 mm (4.61 in.)	42 mm (1.65 in.)
GSV40L-AETGKW	117 mm (4.61 in.)	42 mm (1.65 in.)
GSV40R-AETGKW	117 mm (4.61 in.)	42 mm (1.65 in.)



P

C132408

Standard wheel angle:

for USA and Canada:


Model	Inside wheel	Outside wheel (reference)
ACV40L-CEAGKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
GSV40L-CETGKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-AEAGKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
GSV40L-AETGKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-CEANKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-CEMNKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
GSV40L-CETNKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-AEANKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-AEMNKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
GSV40L-AETNKA	$38^{\circ}22' \pm 2^{\circ}$ ($38.37^{\circ} \pm 2^{\circ}$)	$33^{\circ}33'$ (33.55°)
ACV40L-CEASKA	$38^{\circ}42' \pm 2^{\circ}$ ($38.70^{\circ} \pm 2^{\circ}$)	$33^{\circ}46'$ (33.77°)
ACV40L-CEMSKA	$38^{\circ}42' \pm 2^{\circ}$ ($38.70^{\circ} \pm 2^{\circ}$)	$33^{\circ}46'$ (33.77°)
GSV40L-CETSKA	$38^{\circ}18' \pm 2^{\circ}$ ($38.30^{\circ} \pm 2^{\circ}$)	$33^{\circ}32'$ (33.53°)

for Mexico:

Model	Inside wheel	Outside wheel (reference)
ACV40L-CEAGKA	$38^{\circ}18' \pm 2^{\circ}$ ($38.30^{\circ} \pm 2^{\circ}$)	$33^{\circ}41'$ (33.68°)
GSV40L-CETGKA	$38^{\circ}18' \pm 2^{\circ}$ ($38.30^{\circ} \pm 2^{\circ}$)	$33^{\circ}41'$ (33.68°)
ACV40L-CEANKA	$38^{\circ}18' \pm 2^{\circ}$ ($38.30^{\circ} \pm 2^{\circ}$)	$33^{\circ}41'$ (33.68°)

for General export:

Model	Inside wheel	Outside wheel (reference)
for General export	$38^{\circ}42' \pm 2^{\circ}$ ($38.70^{\circ} \pm 2^{\circ}$)	$33^{\circ}46'$ (33.77°)



Standard camber inclination:

for USA and Canada:


Model	Camber	Right-left difference
ACV40L-CEAGKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETGKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEAGKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-AETGKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEANKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEMNKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETNKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEANKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEMNKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-AETNKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEASKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEMSKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETSKA	$-0^{\circ}40' + -45' (-0.67^{\circ} + -0.75^{\circ})$	45' (0.75°) or less

for Mexico:

Model	Camber	Right-left difference
ACV40L-CEAGKA	$-0^{\circ}35' + -45' (-0.58^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETGKA	$-0^{\circ}35' + -45' (-0.58^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEANKA	$-0^{\circ}35' + -45' (-0.58^{\circ} + -0.75^{\circ})$	45' (0.75°) or less

for General export:

Model	Camber	Right-left difference
for General export	$-0^{\circ}30' + -45' (-0.50^{\circ} + -0.75^{\circ})$	45' (0.75°) or less



C132440

Standard caster inclination:

for USA and Canada:

Model	Caster	Right-left difference
ACV40L-CEAGKA	3°00' +−45' (3.00° +−0.75°)	45' (0.75°) or less
GSV40L-CETGKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
ACV40L-AEAGKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
GSV40L-AETGKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
ACV40L-CEANKA	3°00' +−45' (3.00° +−0.75°)	45' (0.75°) or less
ACV40L-CEMNKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
GSV40L-CETNKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
ACV40L-AEANKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
ACV40L-AEMNKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
GSV40L-AETNKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
ACV40L-CEASKA	3°00' +−45' (3.00° +−0.75°)	45' (0.75°) or less
ACV40L-CEMSKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less
GSV40L-CETSKA	2°55' +−45' (2.92° +−0.75°)	45' (0.75°) or less

for Mexico:

Model	Caster	Right-left difference
ACV40L-CEAGKA	2°45' +−45' (2.75° +−0.75°)	45' (0.75°) or less
GSV40L-CETGKA	2°40' +−45' (2.67° +−0.75°)	45' (0.75°) or less
ACV40L-CEANKA	2°45' +−45' (2.75° +−0.75°)	45' (0.75°) or less

for General export:

Model	Caster	Right-left difference
for General export	2°40' +− 45' (2.67° +− 0.75°)	45' (0.75°) or less

Steering axis inclination:

for USA and Canada:

Model	Steering axis inclination	Right-left difference
ACV40L-CEAGKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
GSV40L-CETGKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-AEAGKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
GSV40L-AETGKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-CEANKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-CEMNKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
GSV40L-CETNKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-AEANKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-AEMNKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
GSV40L-AETNKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-CEASKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
ACV40L-CEMSKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less
GSV40L-CETSKA	12°15' +−45' (12.25° +−0.75°)	45' (0.75°) or less

for Mexico:



Model	Steering axis inclination	Right-left difference
ACV40L-CEAGKA	12°00' +−45' (12.00° +−0.75°)	45' (0.75°) or less
GSV40L-CETGKA	12°00' +−45' (12.00° +−0.75°)	45' (0.75°) or less
ACV40L-CEANKA	12°00' +−45' (12.00° +−0.75°)	45' (0.75°) or less

for General export:

Model	Steering axis inclination	Right-left difference
for General export	12°00' +− 45' (12.00°+− 0.75°)	45' (0.75°) or less

Standard Toe-in (total):


A – B:	0 +- 2 mm (0 +- 0.08 in.)
--------	---------------------------



2. REAR WHEEL ALIGNMENT

Standard toe-in:

Toe-in (total)	—
A + B:	0° +- 24' (0° +- 0.4°)
C – D:	4 +- 2 mm (0.16 +- 0.08 in.)



Standard camber:

for USA and Canada:

Model	Camber	Right-left difference
ACV40L-CEAGKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETGKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEAGKA	$-1^{\circ}15' + -45' (-1.25^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-AETGKA	$-1^{\circ}15' + -45' (-1.25^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEANKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEMNKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETNKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEANKA	$-1^{\circ}15' + -45' (-1.25^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-AEMNKA	$-1^{\circ}15' + -45' (-1.25^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-AETNKA	$-1^{\circ}15' + -45' (-1.25^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEASKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEMSKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETSKA	$-1^{\circ}18' + -45' (-1.30^{\circ} + -0.75^{\circ})$	45' (0.75°) or less

for Mexico:

Model	Camber	Right-left difference
ACV40L-CEAGKA	$-1^{\circ}06' + -45' (-1.10^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
GSV40L-CETGKA	$-1^{\circ}06' + -45' (-1.10^{\circ} + -0.75^{\circ})$	45' (0.75°) or less
ACV40L-CEANKA	$-1^{\circ}06' + -45' (-1.10^{\circ} + -0.75^{\circ})$	45' (0.75°) or less

for General export:

Model	Camber	Right-left difference
for General export	$-1^{\circ}00' + -45' (-1.00^{\circ} + -0.75^{\circ})$	45' (0.75°) or less