Appendix for Graphs

謝仁偉 副教授 jenwei@mail.ntust.edu.tw 國立台灣科技大學 資訊工程系 2017 Spring

Jen-Wei Hsieh, CSIE, NTUST




National Lawari University of Science and Technology

Outline

- Biconnected Components
- Activity-on-Vertex (AOV) Networks
- Activity-on-Edge (AOE) Networks

Reference

- Fundamentals of Data Structures in C
 - Ellis Horowitz
 - Sartaj Sahni
 - Susan Anderson-Freed
 - Publisher: Silicon Press2 edition (August 2007)
 - ISBN-10: 0929306406
 - ISBN-13: 978-0929306407
- Extract from Chapter 6 Graphs



Jen-Wei Hsieh, CSIE, NTUST




Connected Components

```
void connected(void)
{ /* determine the connected components of a graph */
    int i;
    for (i=0; i < n; i++)
        if (!visited[i]) {
            dfs(i);
            printf("\n");
        }
}</pre>
Adjacency list: O(n + e)
Adjacency matrix: O(n²)
```

Articulation Point

 An articulation point is a vertex v of G such that the deletion of v, together with all edges incident on v, produces a graph, G', that has at least two connected components.




Jen-Wei Hsieh, CSIE, NTUST



Biconnected Graph

 A biconnected graph is a connected graph that has no articulation points.




Jen-Wei Hsieh, CSIE, NTUST



Biconnected Components

- A biconnected component of a connected undirected graph is a maximal biconnected subgraph, *H*, of *G*.
 - G contains no other subgraph that is both biconnected and properly contains H.




Jen-Wei Hsieh, CSIE, NTUST

TARWAN TECH
National Talwan University of Science and Technology

Find Biconnected Components (1/4)

• Using any depth first spanning tree of G



TATWAN TECH