
Image Processing

Lecture Notes: The Point Processing of Images

Kai-Lung Hua

Point Processing of Images

- m In a digital image, point = pixel.
- m Point processing transforms a pixel's value as function of its value alone;
- m it does not depend on the values of the pixel's neighbors.

Point Processing of Images

- m Brightness and contrast adjustment
- m Gamma correction
- m Histogram equalization
- m Histogram matching
- m Color correction.

4/9/2018

3

Point Processing



- gamma



- brightness




original



+ brightness



+ gamma



histogram mod



- contrast



original



+ contrast



histogram EQ

4/9/2018

4

The Histogram of a Grayscale Image

- ^m Let I be a 1-band (grayscale) image.
- ^m $I(r,c)$ is an 8-bit integer between 0 and 255.
- ^m Histogram, h_I , of I :
 - a 256-element array, h_I
 - $h_I(g)$, for $g = 1, 2, 3, \dots, 256$, is an integer
 - $h_I(g)$ = number of pixels in I that have value $g-1$.


4/9/2018

5

The Histogram of a Grayscale Image




16-level (4-bit) image

lower RHC: number of pixels with intensity g black marks pixels with intensity g

4/9/2018


6

The Histogram of a Grayscale Image



Black marks
pixels with
intensity g


Plot of histogram:
number of pixels with intensity g



4/9/2018


7

The Histogram of a Grayscale Image



Black marks
pixels with
intensity g

Plot of histogram:
number of pixels with intensity g




4/9/2018

8

The Histogram of a Grayscale Image



$h_l(g+1)$ = the number of pixels in I with graylevel g .



4/9/2018

9

The Histogram of a Color Image





- m If I is a 3-band image (truecolor, 24-bit)
- m then $I(r,c,b)$ is an integer between 0 and 255.
- m Either I has 3 histograms:
 - $h_R(g+1)$ = # of pixels in $I(:, :, 1)$ with intensity value g
 - $h_G(g+1)$ = # of pixels in $I(:, :, 2)$ with intensity value g
 - $h_B(g+1)$ = # of pixels in $I(:, :, 3)$ with intensity value g
- m or 1 vector-valued histogram, $h(g, 1, b)$ where
 - $h(g+1, 1, 1)$ = # of pixels in I with red intensity value g
 - $h(g+1, 1, 2)$ = # of pixels in I with green intensity value g
 - $h(g+1, 1, 3)$ = # of pixels in I with blue intensity value g

4/9/2018

10

The Histogram of a Color Image


There is one histogram per color band R, G, & B. Luminosity histogram is from 1 band = $(R+G+B)/3$



4/9/2018

11

The Histogram of a Color Image



4/9/2018

12

Value or Luminance Histograms

The value histogram of a 3-band (truecolor) image, I , is the histogram of the value image,

$$V(r,c) = \frac{1}{3} [R(r,c) + G(r,c) + B(r,c)]$$



Where R , G , and B are the red, green, and blue bands of I .
The luminance histogram of I is the histogram of the luminance image,

$$L(r,c) = 0.299 \cdot R(r,c) + 0.587 \cdot G(r,c) + 0.114 \cdot B(r,c)$$

4/9/2018

13

Value Histogram vs. Average of R,G,&B Histograms



4/9/2018

14

Multi-Band Histogram Calculator in Matlab

```
% Multi-band histogram calculator
function h=histogram(I)

[R C B]=size(I);

% allocate the histogram
h=zeros(256,1,B);

% range through the intensity values
for g=0:255
    h(g+1,1,:) = sum(sum(I==g)); % accumulate
end

return;
```

4/9/2018

15

Multi-Band Histogram Calculator in Matlab

```
% Multi-band histogram calculator
function h=histogram(I)

[R C B]=size(I);

% allocate the histogram
h=zeros(256,1,B);

% range through the intensity values
for g=0:255
    h(g+1,1,:) = sum(sum(I==g)); % accumulate
end
```

Loop through all intensity levels (0-255)
Tag the elements that have value g .
The result is an $R \times C \times B$ logical array that has a 1 wherever $I(r,c,b) = g$ and 0's everywhere else.
Compute the number of ones in each band of the image for intensity g .
Store that value in the $256 \times 1 \times B$ histogram at $h(g+1,1,b)$.


If $B=3$, then $h(g+1,:)$ contains 3 numbers: the number of pixels in bands 1, 2, & 3 that have intensity g .

$\text{sum}(\text{sum}(I==g))$ computes one number for each band in the image.

4/9/2018

16

Point Ops via Functional Mappings



The rule that associates k with g is usually specified with a function, f , so that $f(g) = k$.

4/9/2018

17

Point Ops via Functional Mappings

One-band Image

$$J(r,c) = f(I(r,c)),$$

for all pixels locations (r,c) .

Three-band Image

$$J(r,c,b) = f(I(r,c,b)), \text{ or}$$

$$J(r,c,b) = f_b(I(r,c,b)),$$

for $b = 1,2,3$ and all (r,c) .

4/9/2018

18

Point Ops via Functional Mappings

One-band Image

$$J(r,c) = f(I(r,c)),$$

for all pixels locations (r,c) .

Either all 3 bands are mapped through the same function, f , or ...

Three-band Image

$$J(r,c,b) = f(I(r,c,b)), \text{ or } J(r,c,b) = f_b(I(r,c,b)),$$

for $b = 1, 2, 3$ and all (r,c)

... each band is mapped through a separate function, f_b .

4/9/2018

19

Point Operations using Look-up Tables

A look-up table (LUT) implements a functional mapping.

If $k = f(g)$,
for $g = 0, K, 255$,
and if k takes on
values in $\{0, K, 255\}, K$

... then the LUT that implements f is a 256×1 array whose $(g+1)^{\text{th}}$ value is $k = f(g)$.

To remap a 1-band image, I , to J :

$$J = \text{LUT}(I + 1)$$

4/9/2018

20

Point Operations using Look-up Tables

If I is 3-band, then

- a) each band is mapped separately using the same LUT for each band *or*
- b) each band is mapped using different LUTs – one for each band.


a) $J = \text{LUT}(I + 1)$, *or*

b) $J(:, :, b) = \text{LUT}_b(I(:, :, b) + 1)$ for $b = 1, 2, 3$.

4/9/2018

21

Point Operations = Look-up Table Ops



E.g.:


index	value
...	...
101	64
102	68
103	69
104	70
105	70
106	71
...	...

input output

4/9/2018

22

Look-Up Tables



4/9/2018

23

How to Generate a Look-Up Table

For example:


Let $a = 2$.

Let $x \in \{0, K, 255\}$

$$\sigma(x; a) = \frac{255}{1 + e^{-a(x-127)/32}}$$

Or in Matlab:

```
a = 2;
x = 0:255;
LUT = 255 ./ (1+exp(-a*(x-127)/32));
```



This is just one example.

4/9/2018


24

Point Processes: Increase Brightness



$$J_k(r,c) = \begin{cases} I_k(r,c) + g, & \text{if } I_k(r,c) + g < 255 \\ 255, & \text{if } I_k(r,c) + g > 255 \end{cases}$$

$g \geq 0$ and $k \in \{1, 2, 3\}$ is the band index.



4/9/2018


25

Point Processes: Decrease Brightness



$$J_k(r,c) = \begin{cases} 0, & \text{if } I_k(r,c) - g < 0 \\ I_k(r,c) - g, & \text{if } I_k(r,c) - g \geq 0 \end{cases}$$

$g \geq 0$ and $k \in \{1, 2, 3\}$ is the band index.



4/9/2018


26

Point Processes: Increase Contrast



Let $T_k(r, c) = a[I_k(r, c) - 127] + 127$, where $a > 1.0$

$$J_k(r, c) = \begin{cases} 0, & \text{if } T_k(r, c) < 0, \\ T_k(r, c), & \text{if } 0 \leq T_k(r, c) \leq 255, \\ 255, & \text{if } T_k(r, c) > 255. \end{cases} \quad k \in \{1, 2, 3\}$$



4/9/2018


27

Point Processes: Decrease Contrast



$$T_k(r, c) = a[I_k(r, c) - 127] + 127,$$

where $0 \leq a < 1.0$ and $k \in \{1, 2, 3\}$.



4/9/2018

28


Point Processes: Contrast Stretch



Let $m_l = \min[I(r,c)]$, $M_l = \max[I(r,c)]$,
 $m_j = \min[J(r,c)]$, $M_j = \max[J(r,c)]$.

Then,

$$J(r,c) = (M_j - m_j) \frac{I(r,c) - m_l}{M_l - m_l} + m_j.$$




4/9/2018

29

histograms


Information Loss from Contrast Adjustment



4/9/2018

30

Information Loss from Contrast Adjustment




4/9/2018

31

Point Processes: Increased Gamma



$$J(r, c) = 255 \cdot \left[\frac{I(r, c)}{255} \right]^{1/\gamma} \quad \text{for } \gamma > 1.0$$




4/9/2018

32

Point Processes: Decreased Gamma




$$J(r, c) = 255 \cdot \left[\frac{I(r, c)}{255} \right]^{1/\gamma} \quad \text{for } \gamma < 1.0$$



4/9/2018

33

Gamma Correction: Effect on Histogram



4/9/2018

34

The Probability Density Function of an Image

Let $A = \sum_{g=0}^{255} h_{I_k}(g+1).$

pdf
[lower case]

Note that since $h_{I_k}(g+1)$ is the number of pixels in I_k (the k th color band of image I) with value g , A is the number of pixels in I . That is if I is R rows by C columns then $A = R \times C$.

Then,

$$p_{I_k}(g+1) = \frac{1}{A} h_{I_k}(g+1)$$

This is the probability that an arbitrary pixel from I_k has value g .

is the graylevel probability density function of I_k .

4/9/2018

35

The Probability Density Function of an Image

- $p_{\text{band}}(g+1)$ is the fraction of pixels in (a specific band of) an image that have intensity value g .
- $p_{\text{band}}(g+1)$ is the probability that a pixel randomly selected from the given band has intensity value g .
- Whereas the sum of the histogram $h_{\text{band}}(g+1)$ over all g from 1 to 256 is equal to the number of pixels in the image, the sum of $p_{\text{band}}(g+1)$ over all g is 1.
- p_{band} is the **normalized histogram** of the band.

4/9/2018

36

The Probability Distribution Function of an Image

Let $\mathbf{q} = [q_1 \ q_2 \ q_3] = I(r, c)$ be the value of a randomly selected pixel from I . Let g be a specific graylevel. The probability that $q_k \leq g$ is given by

PDF
[upper case]

$$P_{I_k}(g+1) = \sum_{\gamma=0}^g p_{I_k}(\gamma+1) = \frac{1}{A} \sum_{\gamma=0}^g h_{I_k}(\gamma+1) = \frac{\sum_{\gamma=0}^g h_{I_k}(\gamma+1)}{\sum_{\gamma=0}^{255} h_{I_k}(\gamma+1)},$$

where $h_{I_k}(\gamma+1)$ is the histogram of the k th band of I .

This is the probability that any given pixel from I_k has value less than or equal to g .

4/9/2018

37

The Probability Distribution Function of an Image

Let $\mathbf{q} = [q_1 \ q_2 \ q_3] = I(r, c)$ be the value of a randomly selected pixel from I . Let g be a specific graylevel. The probability that $q_k \leq g$ is given by

Also called CDF
for "Cumulative
Distribution
Function".

$$P_{I_k}(g+1) = \sum_{\gamma=0}^g p_{I_k}(\gamma+1) = \frac{1}{A} \sum_{\gamma=0}^g h_{I_k}(\gamma+1) = \frac{\sum_{\gamma=0}^g h_{I_k}(\gamma+1)}{\sum_{\gamma=0}^{255} h_{I_k}(\gamma+1)},$$

where $h_{I_k}(\gamma+1)$ is the histogram of the k th band of I .

This is the probability that any given pixel from I_k has value less than or equal to g .

4/9/2018

38

A.k.a. Cumulative
Distribution Function.

The Probability Distribution Function of an Image

- $P_{\text{band}}(g+1)$ is the fraction of pixels in (a specific band of) an image that have intensity values less than or equal to g .
- $P_{\text{band}}(g+1)$ is the probability that a pixel randomly selected from the given band has an intensity value less than or equal to g .
- $P_{\text{band}}(g+1)$ is the cumulative (or running) sum of $p_{\text{band}}(g+1)$ from 0 through g inclusive.
- $P_{\text{band}}(1) = p_{\text{band}}(1)$ and $P_{\text{band}}(256) = 1$; $P_{\text{band}}(g+1)$ is nondecreasing.

Note: the Probability Distribution Function (PDF, capital letters) and the Cumulative Distribution Function (CDF) are exactly the same things. Both PDF and CDF will refer to it. However, pdf (small letters) is the *density* function.

4/9/2018

39

Point Processes: Histogram Equalization

Task: remap image I so that its histogram is as close to constant as possible

Let $P_I(\gamma + 1)$

be the cumulative (probability) distribution function of I .

Then J has, as closely as possible, the correct histogram if

$$J(r, c) = 255 \cdot P_I[I(r, c) + 1].$$

The CDF itself is used as the LUT.

all bands
processed
similarly


4/9/2018

40


Point Processes: Histogram Equalization



$$J(r, c) = 255 \cdot P_r(g + 1)$$



before




after

4/9/2018

41


Histogram EQ



4/9/2018

42


Histogram EQ



4/9/2018

43


Histogram EQ



4/9/2018

44

Histogram EQ



4/9/2018

45

Point Processes: Histogram Equalization

Task: remap image I with $\min = m_I$ and $\max = M_I$ so that its histogram is as close to constant as possible and has $\min = m_J$ and $\max = M_J$.

Let $P_I(\gamma + 1)$ be the cumulative (probability) distribution function of I .

Then J has, as closely as possible, the correct histogram if

Using
intensity
extrema

$$J(r, c) = (M_J - m_J) \frac{P_I[I(r, c) + 1] - P_I(m_I + 1)}{1 - P_I(m_I + 1)} + m_J.$$

4/9/2018

46

Point Processes: Histogram Matching

Task: remap image I so that it has, as closely as possible, the same histogram as image J .

Because the images are digital it is not, in general, possible to make $h_I \equiv h_J$. Therefore, $p_I \neq p_J$.

Q: How, then, can the matching be done?

A: By matching percentiles.

4/9/2018

47

Matching Percentiles

... assuming a 1-band image or a single band of a color image.

Recall:

- The CDF of image I is such that $0 \leq P_I(g_I) \leq 1$.
- $P_I(g_I + 1) = c$ means that c is the fraction of pixels in I that have a value less than or equal to g_I .
- $100c$ is the *percentile* of pixels in I that are less than or equal to g_I .

To match percentiles, replace all occurrences of value g_I in image I with the value, g_J , from image J whose percentile in J most closely matches the percentile of g_I in image I .

4/9/2018

48

Matching Percentiles

... assuming a 1-band image or a single band of a color image.


So, to create an image, K , from image I such that K has nearly the same CDF as image J do the following:

If $I(r;c) = g_I$ then let $K(r;c) = g_J$ where g_J is such that

$$P_I(g_I) > P_J(g_J - 1) \text{ AND } P_I(g_I) \leq P_J(g_J).$$

Example:

$I(r;c) = 5$
 $P_I(5) = 0.65$
 $P_J(9) = 0.56$
 $P_J(10) = 0.67$
 $K(r;c) = 10$



4/9/2018

49

Histogram Matching Algorithm

... assuming a 1-band image or a single band of a color image.

```
[R,C] = size(I);
K = zeros(R,C);
g_J = m_J;
for g_I = m_I to M_I
    while g_J < 255 AND P_I(g_I + 1) < 1 AND
          P_J(g_J + 1) < P_I(g_I + 1)
        g_J = g_J + 1;
    end
    K = K + [g_J * (I == g_I)]
end
```

This directly matches image I to image J .

$P_I(g_I + 1)$: CDF of I
 $P_J(g_J + 1)$: CDF of J .
 $m_J = \min J$,
 $M_J = \max J$,
 $m_I = \min I$,
 $M_I = \max I$.



Better to use a LUT.
 See slide 54.

4/9/2018

50

Example: Histogram Matching

Image pdf





4/9/2018

51

Example: Histogram Matching

Image CDF





4/9/2018

52

Example: Histogram Matching

Target pdf




4/9/2018

53

Example: Histogram Matching

Target CDF



4/9/2018

54

Histogram Matching with a Lookup Table

The algorithm on slide [49](#) matches one image to another directly. Often it is faster or more versatile to use a lookup table (LUT). Rather than remapping each pixel in the image separately, one can create a table that indicates to which target value each input value should be mapped. Then

$$K = \text{LUT}[I+1]$$


In *Matlab* if the LUT is a 256×1 matrix with values from 0 to 255 and if image I is of type **uint8**, it can be remapped with the following code:

```
K = uint8(LUT(double(I)+1));
```

4/9/2018

55

LUT Creation



4/9/2018

56

Look Up Table for Histogram Matching

```
LUT = zeros(256,1) ;
```

```
gJ = 0;
```

```
for gI = 0 to 255
```

```
    while PJ(gJ+1) < PI(gI+1) AND gJ < 255
```

```
        gJ = gJ + 1;
```

```
    end
```

```
    LUT(gI+1) = gJ;
```

```
end
```

This creates a look-up table which can then be used to remap the image.

P_I(g_I+1) : CDF of I ,





P_J(g_J+1) : CDF of J,

LUT(g_I+1) : Look- Up Table

4/9/2018

57


Input & Target CDFs, LUT and Resultant CDF



4/9/2018

58


Example: Histogram Matching



4/9/2018

59


Probability Density Functions of a Color Image



4/9/2018

60


Cumulative Distribution Functions (CDF)



4/9/2018

61


Probability Density Functions of a Color Image



4/9/2018

62

Cumulative Distribution Functions (CDF)



4/9/2018

63

Remap an Image to have the Lum. CDF of Another



original



target




luminosity remapped

4/9/2018

64


CDFs and the LUT



4/9/2018

65

Effects of Luminance Remapping on pdfs




Before

After

4/9/2018

66

Effects of Luminance Remapping on CDFs



4/9/2018

67


Remap an Image to have the rgb CDF of Another



4/9/2018

68


CDFs and the LUTs



4/9/2018

69


Effects of RGB Remapping on pdfs



4/9/2018

70

Effects of RGB Remapping on CDFs



4/9/2018

71

Remap an Image: To Have Two of its Color pdfs Match the Third



4/9/2018

72