

---

# Image Processing

Lecture Notes: Spatial Convolution

Kai-Lung Hua

---



---

## Spatial Filtering

Let  $I$  and  $J$  be images such that  $J = T[I]$ .

$T[\cdot]$  represents a transformation, such that,

$$J(r, c) = T[I](r, c) = f\left(\left\{I(u, v) \mid u \in \{r-s, \dots, r, \dots, r+s\}, v \in \{c-d, \dots, c, \dots, c+d\}\right\}\right)$$

That is, the value of the transformed image,  $J$ , at pixel location  $(r, c)$  is a function of the values of the original image,  $I$ , in a  $2s+1 \times 2d+1$  rectangular neighborhood centered on pixel location  $(r, c)$ .

---

---

## Moving Windows

- m The value,  $J(r,c) = T[I](r,c)$ , is a function of a rectangular neighborhood centered on pixel location  $(r,c)$  in  $I$ .
- m There is a different neighborhood for each pixel location, but if the dimensions of the neighborhood are the same for each location, then transform  $T$  is sometimes called a *moving window transform*.

---


9 April 2018

3

---

## Moving-Window Transformations

Neutral  
Buoyancy  
Facility at  
NASA  
Johnson  
Space  
Center



We'll take a  
section of  
this image to  
demonstrate  
the MWT


photo: R.A.Peters II, 1999

---

9 April 2018

4

## Moving-Window Transformations




9 April 2018

5

Pixelize the section to  
better see the effects.

## Moving-Window Transformations




9 April 2018

6

Pixelize the section to  
better see the effects.


## Moving-Window Transformations



9 April 2018

7


## Moving-Window Transformations



9 April 2018

8


## Moving-Window Transformations



9 April 2018

9

## Moving-Window Transformations




9 April 2018

10

## Linear Moving-Window Transformations (*i.e.* convolution)


The output of the transform at each pixel is the (weighted) average of the pixels in the neighborhood.



9 April 2018

11

## Moving-Window Transformations



result of a  $9 \times 9$   
uniform averaging

9 April 2018

12

---

## Convolution: Mathematical Representation

If a MW transformation is *linear* then it is a *convolution*:

$$J(r,c) = [I * h](r,c) = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} I(r-\rho, c-\kappa) h(\rho, \kappa) d\rho d\kappa,$$

for an ideal, Euclidean image, or for a digital image:

$$J(r,c) = [I * h](r,c) = \sum_{\rho=-\infty}^{\infty} \sum_{\kappa=-\infty}^{\infty} I(r-\rho, c-\kappa) h(\rho, \kappa)$$



---

---

## Convolution Mask (Weight Matrix)

- The object,  $h(\rho, \kappa)$ , in the equation is a weighting function, or in the discrete case, a rectangular matrix of numbers.
  - The matrix is the moving window.
  - Pixel  $(r,c)$  in the output image is the weighted sum of pixels from the original image in the neighborhood of  $(r,c)$  traced by the matrix.
  - Each pixel in the neighborhood of  $(r,c)$  is multiplied by the corresponding matrix value — after the matrix is rotated by  $180^\circ$ . (See slide [22](#)).
  - The sum of those products is the value of pixel  $(r,c)$  in the output image
-


## Convolution Masks: Moving Window



9 April 2018

15

## Convolution Masks: Moving Window




9 April 2018

16



## Convolution by Moving Window



9 April 2018


17

### Another example

## Moving Window Transform: Example



original




3x3 average

9 April 2018

18


### Moving Window Transform: Example



9 April 2018

19


### Moving Window Transform: Example



9 April 2018

20


## Moving Window Transform: Example



9 April 2018

21

## Convolution by Rotating and Shifting the Weight Matrix



9 April 2018

14 22

## Symmetric Weight Matrix

<i>f</i>	<i>e</i>	<i>d</i>	<i>e</i>	<i>f</i>
<i>e</i>	<i>c</i>	<i>b</i>	<i>c</i>	<i>e</i>
<i>d</i>	<i>b</i>	<i>a</i>	<i>b</i>	<i>d</i>
<i>e</i>	<i>c</i>	<i>b</i>	<i>c</i>	<i>e</i>
<i>f</i>	<i>e</i>	<i>d</i>	<i>e</i>	<i>f</i>


A symmetric weight matrix is unchanged by rotation through  $180^\circ$ .

9 April 2018

23

## Three ways to compute a convolution

1. Moving window transform as just shown.
2. Shift multiply add.
3. Fourier transform.



9 April 2018

24

---

## Shift-Multiply-Add Approach

- The image is copied 1 time for each element in the convolution mask.
  - Each copy is shifted relative to the original by the displacement of its associated mask element.
  - Each copy is multiplied by the value of its associated mask element.
  - The set of shifted and multiplied images is summed pixel wise.
- 

9 April 2018

25

---

## Convolution by an Impulse

An *impulse* is a digital image, that has a single pixel with value 1; all others have value zero. An impulse at location  $(\rho, \chi)$  is represented by:

$$\delta(r - \rho, c - \chi) = \begin{cases} 1, & \text{if } r = \rho \text{ and } c = \chi \\ 0, & \text{otherwise} \end{cases}$$

If an image is convolved with an impulse at location  $(\rho, \chi)$ , the image is shifted in location down by  $\rho$  pixels and to the right by  $\chi$  pixels.


$$[I * \delta(r - \rho, c - \chi)](r, c) = I(r - \rho, c - \chi).$$


---

9 April 2018

26


## Convolution by an Impulse



9 April 2018

27


## Convolution by Two Impulses



9 April 2018

28


## Convolution by Three Impulses



9 April 2018

29

## Convolution by Five Impulses




9 April 2018

30

## Convolution by Copying, Multiplying, and Shifting the Image


For each element  $h(r_h, c_h)$  in weight matrix,  $h$ , image  $I$  is copied into a zero-padded image,  $P$ , starting at  $(r_h, c_h)$ . Each  $P$  is multiplied by the corresponding weight,  $h(r_h, c_h)$ . All the  $P$  images are summed pixel-wise then divided by the sum of the elements of  $h$ . The result is cropped out of the center of the accumulated  $P$ 's.



9 April 2018

31

## Convolution by Copying, Multiplying, and Shifting the Image



9 April 2018


32



### Convolution by Copying, Multiplying, and Shifting the Image

Each copy of the (entire) image is multiplied by the value of the weight matrix in black square (here, white = 0) before being accumulated (pixelwise) in the padded image

The position of the black square relative to the center of the weight matrix indicates the shift of the original image relative to the middle of the padded image.



In this image, only the pixel in the center is nonzero so only it shows a result when the image is multiplied by a nonzero value


9 April 2018

33

### Convolution by Copying, Multiplying, and Shifting the Image

Each copy of the (entire) image is multiplied by the value of the weight matrix in black square (here, white = 0) before being accumulated (pixelwise) in the padded image



The position of the black square relative to the center of the weight matrix indicates the shift of the original image relative to the middle of the padded image.



In this image, only the pixel in the center is nonzero so only it shows a result when the image is multiplied by a nonzero value

9 April 2018

34




### Convolution by Copying, Multiplying, and Shifting the Image

13x13 image  
convolved by  
6x6 mask.

Image is constant;  
mask has only 6  
nonzero values all  
on the diagonal.

Image is shifted to  
mask location,  
multiplied by value,  
and accumulated.




9 April 2018

37

### Convolution by Copying and Shifting the Image


When done, copy the  
output image from the  
accumulator starting  
at (hrorig, hcorig) and  
ending at (hrorig+R-1,  
hcorig+C-1)



9 April 2018

38

## Convolution Examples: Original Images




9 April 2018

39

$$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

## Convolution Examples: 3×3 Blur




9 April 2018

40

$$\frac{1}{25} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 \end{bmatrix}$$

### Convolution Examples: 5×5 Blur




9 April 2018

41

$$\frac{1}{81} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \end{bmatrix}$$

### Convolution Examples: 9×9 Blur



9 April 2018

42

## Convolution Examples: 17×17 Blur

9 April 2018
43

### Vertical Edge Detection

Image

$r_0$

$I(r_0, c)$   
 $c$

Backward Difference

$r_0$

$I(r_0, c) - I(r_0, c - 1)$   
 $c$

Forward Difference

$r_0$

$I(r_0, c) - I(r_0, c + 1)$   
 $c$

Sum of Differences

$r_0$

$2I(r_0, c) - I(r_0, c - 1) - I(r_0, c + 1)$   
 $c$


255

0

-255

9 April 2018
44


### Symmetric Edge Detection



9 April 2018

45

### Convolution Examples: Original Images




9 April 2018

46

$$\begin{bmatrix} -1 \\ 2 \\ -1 \end{bmatrix}$$

## Convolution Examples: Vertical Difference




9 April 2018

47

$$\begin{bmatrix} -1 & 2 & -1 \end{bmatrix}$$

## Convolution Examples: Horizontal Difference




9 April 2018

48



$$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 4 & -1 \\ 0 & -1 & 0 \end{bmatrix}$$

### Convolution Examples: H + V Diff.




9 April 2018

49

$$\begin{bmatrix} -1 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & -1 \end{bmatrix}$$

### Convolution Examples: Diagonal Difference




9 April 2018

50

$$\begin{bmatrix} 0 & 0 & -1 \\ 0 & 2 & 0 \\ -1 & 0 & 0 \end{bmatrix}$$

## Convolution Examples: Diagonal Difference




9 April 2018

51

$$\begin{bmatrix} -1 & 0 & -1 \\ 0 & 4 & 0 \\ -1 & 0 & -1 \end{bmatrix}$$

## Convolution Examples: D + D Difference




9 April 2018

52

$$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$$


### Convolution Examples: H + V + D Diff.



9 April 2018

53

### Convolution Examples: Original Images



9 April 2018

54