

Focus Media Kuma — OpenAPI Integration Reference

Focus Media Kuma — OpenAPI Integration Reference

Consolidated English reference for the four Focus Media Kuma integration modules:

- 1. **Account API** — bidder account creation and listing
- 2. **Resource API** — queryable catalog of cities, buildings and screen locations
- 3. **Creative API** — creative group submission and audit status tracking
- 4. **Order API** — inventory check, order placement, cancellation, status query, and broadcast strategy

All endpoints use HTTP with `Content-Type: application/json`.

Common HTTP status codes

Code	Name	Description
200	OK	The request was successful.
400	Bad Request	The request could not be interpreted successfully.
401	Unauthorized	The request did not contain correct authentication information.
404	Not Found	The resource does not exist.
429	Too Many Requests	

		The bidder has exceeded the rate limit set by the exchange and must wait before trying again.
500	Internal Service Error	The exchange has encountered technical difficulties.

Common business error codes (`code` field)

code	Description
0	Success
-1	Date parameter error (e.g. past date)
-2	Duration or frequency parameter error
-3	Resource parameter error (invalid city, no sellable locations, duplicate city in order items, fewer valid <code>targetId</code> s than <code>goalLocationNum</code>)
-4	Account configuration error (missing Kuma account config or <code>dspId</code>)
-5	Network / internal / other unknown error
-6	Blocked by publishing lock
-7	Past the last operable time (for placing or cancelling orders)
-8	Inventory insufficient or location lock failed
-9	Contract already approved; cannot operate
-10	Order does not exist
-11	Invalid order status for this operation
-12	Invalid creative (does not exist, not owned by the customer, or not audited)
-13	Broadcast strategy error

1. Account API

1.1 Create Account

Creates a bidder account. The returned `bidderId` is required for all other modules (Creative, Order, Resource).

Endpoint

代码块

1 POST {baseUrl}/v1/authserver/account/create

Request body

Attribute	Type	Description
customerName	string; required	Customer name (property management company name)
productName	string; required	Product line, e.g. <code>SMART_SCREEN</code>
email	string; required	Contact email

Response

Attribute	Type	Description
bidderId	string	Unique identifier returned by the service. The requester must persist it; required when creating orders and creatives.

Example

Request:

代码块

```
1  {
2    "customerName": "XXXX Property Management",
3    "productName": "SMART_SCREEN",
4    "email": "123@3121.com"
5  }
```

Response:

代码块

```
1  {
2    "bidderId": "sadasdasd1231851jasd"
3  }
```

1.2 List Accounts

Endpoint

代码块

```
1  GET {baseUrl}/v1/authserver/account/list
```

Request body

Attribute	Type	Description
productName	string; required	Product line, e.g. SMART_SCREEN
pageNo	integer; required	Page number, > 0
pageSize	integer; required	Page size, > 0

Response

Attribute	Type	Description
bidderId	string	Paginated list of accounts.

Example

Request:

代码块

```
1  {
2    "productName": "SMART_SCREEN",
3    "pageNo": 1,
4    "pageSize": 1
5  }
```

Response:

代码块

```
1  {
2    "totalCount": 1,
3    "totalPage": 1,
4    "pageNo": 1,
5    "pageSize": 1,
6    "result": [{
7      "reportId": "101151",
8      "accountId": "10585df76f9b48afa210e9578fd5180c",
9      "referName": "Demo account",
10     "productName": "SMART_SCREEN",
11     "accountType": "INNER_CUSTOMER",
12     "salesName": "Dai Guangying",
13     "redundancyRate": 0.10,
14     "adCampaignCount": 1
15   }]
16 }
```

2. Resource API

Provides queries for sellable cities, buildings and valid screen locations.

2.1 Objects

2.1.1 City

Attribute	Type	Definition
cityCode	string	City code. Unique identifier returned by the service; required when querying buildings.
cityName	string	City name

2.1.2 Building

Attribute	Type	Definition
buildingId	string	Building ID. Unique identifier returned by the service; required when querying valid locations.
buildingName	string	Building name

2.1.3 Location (screen)

Attribute	Type	Definition
locationId	string	Location ID. Unique identifier returned by the service; required when placing orders.
buildingId	string	Building ID
buildingName	string	Building name
siteName	string	Block / tower name

unitName	string	Unit name
installLocation	string	Physical installation location of the screen
deviceStyleId	string	Device style ID
deviceStyleName	string	Device style name
locationDesc	string	Full location description

2.2 Get all sellable cities

Endpoint

代码块

```
1 GET {baseUrl}/v1/adresource/getAllStandardCities?productName={productName}
```

Query parameters

Attribute	Type	Description
productName	string; required	Product line, e.g. SMART_SCREEN

Example

Request:

```
GET {baseUrl}/v1/adresource/getAllStandardCities?productName=SMART_SCREEN
```

Response:

代码块

```
1 {
2   "success": true,
3   "code": "0",
4   "message": "",
5   "data": [
```

```
6      { "code": "110000000000", "name": "Beijing" },
7      { "code": "310000000000", "name": "Shanghai" }
8    ]
9  }
```

2.3 Get buildings

Returns buildings for a given product line within a single city.

Endpoint

代码块

```
1  POST {baseUrl}/v1/adresource/getBuildingInfos
```

Request body

Attribute	Type	Description
cityId	string; required	Target city ID, e.g. <code>310000000000</code> for Shanghai
productName	string; required	Product line, e.g. <code>SMART_SCREEN</code>
pageNo	integer; required	Page number, > 0
pageSize	integer; required	Page size, > 0

Response

Attribute	Type	Description
totalCount	int	Total count

totalPage	int	Total pages
pageNo	int	Current page
pageSize	int	Page size
data	Building[]	List of buildings

Example

Request:

代码块

```
1  {
2    "cityId": "3100000000000",
3    "productName": "SMART_SCREEN",
4    "pageNo": 1,
5    "pageSize": 2
6  }
```

Response:

代码块

```
1  {
2    "success": true,
3    "code": "0",
4    "message": "",
5    "data": {
6      "totalCount": 374,
7      "totalPage": 374,
8      "pageNo": 1,
9      "pageSize": 1,
10     "result": [
11       { "buildingId": "248", "buildingName": "Dashun Tiancheng" },
12       { "buildingId": "249", "buildingName": "Tiancheng Dashun" }
13     ]
14   }
15 }
```

2.4 Get valid locations for buildings

Endpoint

代码块

```
1 POST {baseUrl}/v1/adresource/getValidLocationInfos
```

Request body

Attribute	Type	Description
cityId	string; required	Standard city ID, e.g. 3100000000000
productName	string; required	Product line, e.g. SMART_SCREEN
targetIds	string[]; required; unique	List of building or location IDs
targetType	string; required	Target type, e.g. BUILDING

Example

Request:

代码块

```
1 {
2   "cityId": "3100000000000",
3   "productName": "SMART_SCREEN",
4   "targetIds": [248],
5   "targetType": "BUILDING"
6 }
```

Response:

代码块

```
1 {
2   "success": true,
3   "code": "0",
4   "message": "",
5   "data": [
```

```

6      {
7          "locationId": "8767383",
8          "buildingId": "248",
9          "buildingName": "Dashun Tiancheng",
10         "siteName": "Tower 1",
11         "unitName": "Unit 1",
12         "installLocation": "Inside lift car #1",
13         "deviceStyleId": "303",
14         "deviceStyleName": "[Smart] 25-inch Digital",
15         "locationDesc": "Dashun Tiancheng / Tower 1 / Unit 1 / Lift car / Lift
#1 / Front"
16     },
17     {
18         "locationId": "8767384",
19         "buildingId": "248",
20         "buildingName": "Dashun Tiancheng",
21         "siteName": "Tower 1",
22         "unitName": "Unit 1",
23         "installLocation": "Inside lift car #2",
24         "deviceStyleId": "288",
25         "deviceStyleName": "[Integrated] 19-inch Digital",
26         "locationDesc": "Dashun Tiancheng / Tower 1 / Unit 1 / Lift car / Lift
#2 / Front"
27     }
28 ]
29 }

```

3. Creative API

3.1 Concepts

- **Material:** a single image or video asset.
- **Creative:** the set of materials for one device style (screen size).
- **Creative Group:** a bundle of creatives across the supported device styles.

Submissions are made at the **creative group** level. One request submits one creative group. The 25-inch smart screen may use either split-screen or full-screen mode within the same creative group.

3.2 Objects

CreativeGroup

Attribute	Type	Definition
id	string	Creative group ID. Not sent by the requester; returned by the service. Required to reference this group later (e.g. attaching to an order, querying details).
duration	float	Duration in seconds. Default 15 . Range 2.5 – 210 , must be a multiple of 2.5 .
lastmod	long	Last-modified Unix timestamp in milliseconds.
creatives	Creative[]; required	List of creatives; one entry per supported device style. Four smart screen styles are supported; if a given style has no real creative, a default material can be uploaded. Every creative's duration must match the group's duration.
audit	Audit	Audit info.

Creative

Attribute	Type	Definition
devicestyle	string; required	Device style (see enum below).
materials	Material[]; required	Materials for this device style. Split-screen requires

		2 materials, full-screen requires 1. The list order is meaningful: for a split-screen 19-inch, index <code>0</code> is the top screen and index <code>1</code> is the bottom screen. In split-screen mode both halves cannot both be video.
--	--	---

Material

Attribute	Type	Definition
id	string; required	Material ID supplied by the requester. Distinct IDs are recommended for distinct materials.
iurl	string; required	Download URL of the material.
filename	string; required	File name; must end with <code>.jpg</code> for images or <code>.mp4</code> for video. Max 60 bytes UTF-8 (screen device constraint). Filenames must be unique across all materials in a single request and across different requests.
display	Display; required	Display metadata.

> Note: For 19-inch screens, materials must be passed in top-screen then bottom-screen order.

Display

Attribute	Type	Definition
mime	string; required	

		MIME type (e.g. <code>video/mp4</code> , <code>image/jpeg</code>).
duration	float	Duration in seconds. Default <code>15</code> .

Audit

Attribute	Type	Definition
status	integer	Audit status code (see enum below).
feedback	string	Audit feedback. Empty when <code>status = 1</code> . A free-form string when <code>status = 502</code> (for internal troubleshooting, do not display to end users). When <code>status = 3</code> or <code>4</code> , returns a JSON-parseable string with per-material audit results (see sample payload).
lastmod	long	Last-modified Unix timestamp in milliseconds.

3.3 Enums

Device Style

Value	Definition
smart19	19-inch smart screen
smart25	25-inch smart screen
smart32	32-inch smart screen
smart55	55-inch smart screen

Audit Status

Value	Definition
1	Pending review. Not playable. Initial state after successful submission; transitions to 3 / 4 / 502 depending on automated validation and manual review.
3	Approved. Playable.
4	Rejected. Not playable. Requester must resubmit to generate a new creative group.
502	Custom state — creative group generation failed. Not playable. Raised on material/spec validation failure or asset-transfer failure. The requester should validate asset format and ensure URLs are readable to avoid this state. Requires resubmission.

3.4 Submit creative group

Each submission creates a new creative group.

Endpoint

代码块

```
1 POST {baseUrl}/management/v1/bidder/{bidderId}/creativeGroups
```

Path parameters

Attribute	Type	Description
bidderId	string; required	Bidder ID (assigned at account creation).

Request body

Attribute	Type	Description
creativeGroup	object; required	<code>CreativeGroup</code> object (without <code>id</code>).

Response

Attribute	Type	Description
creativeGroup	object	Created <code>CreativeGroup</code> (with assigned <code>id</code> and initial <code>audit</code>).

Example

Request — `POST {baseUrl}/management/v1/bidder/496/creativeGroups :`

代码块

```
1  {
2    "duration": 15,
3    "creatives": [
4      {
5        "devicestyle": "smart19",
6        "materials": [
7          {
8            "display": { "mime": "image/jpeg", "duration": 15 },
9            "id": "123",
10           "iurl": "http://cdn.dsp.com/iurls/123.jpg",
11           "filename": "test.jpg"
12         },
13         {
14           "display": { "mime": "video/mp4", "duration": 15 },
15           "id": "456",
```



```

16         "iurl": "http://cdn.dsp.com/iurls/456.mp4",
17         "filename": "test1.mp4"
18     }
19 ]
20 },
21 {
22     "devicestyle": "smart25",
23     "materials": [
24         {
25             "display": { "mime": "video/mp4", "duration": 15 },
26             "id": "789",
27             "iurl": "http://cdn.dsp.com/iurls/789.mp4",
28             "filename": "test3.mp4"
29         }
30     ]
31 },
32 {
33     "devicestyle": "smart32",
34     "materials": [
35         {
36             "display": { "mime": "image/jpeg", "duration": 15 },
37             "id": "901",
38             "iurl": "http://cdn.dsp.com/iurls/901.jpg",
39             "filename": "test4.jpg"
40         }
41     ]
42 },
43 {
44     "devicestyle": "smart55",
45     "materials": [
46         {
47             "display": { "mime": "image/jpeg", "duration": 15 },
48             "id": "103",
49             "iurl": "http://cdn.dsp.com/iurls/103.jpg",
50             "filename": "test5.jpg"
51         }
52     ]
53 }
54 ]
55 }

```

Response:

代码块

```
1 {
```

```
2  "audit": { "lastmod": 1528221112000, "status": 1 },
3  "id": "dfdsdf238293",
4  "lastmod": 1528221112000
5  }
```

3.5 List creative groups with status change in a time range

Returns creative groups whose audit status changed (or that were created) in a given time window. Window size must be ≤ 24 hours.

Endpoint

代码块

```
1  GET {baseUrl}/management/v1/bidder/{bidderId}/creativeGroups?auditStart={auditStart}&auditEnd={auditEnd}
```

Path parameters

Attribute	Type	Description
bidderId	string; required	Bidder ID.

Query parameters

Attribute	Type	Description
auditStart	long; required	Include creative groups whose <code>audit.lastmod</code> $\geq$ <code>auditStart</code> (milliseconds).
auditEnd	long	Include creative groups whose <code>audit.lastmod</code> $<$ <code>auditEnd</code> (milliseconds). Defaults to the current timestamp.

Response

Array of `CreativeGroup` objects.

Example

Request — `GET {baseUrl}/management/v1/bidder/496/creativeGroups?auditStart=1528282813000&auditEnd=1528306992000` :

代码块

```
1  [
2    {
3      "audit": {
4        "feedback": "32-inch material resolution invalid",
5        "lastmod": 1528288587000,
6        "status": 502
7      },
8      "id": "gtry66856h5thy",
9      "lastmod": 1528221112000
10   },
11   {
12     "audit": {
13       "feedback": "[{"id":"19_b1","description":"Violates ad
law","result":0},
{"id":"19_b2","description":"Approved","result":1},
{"id":"25_b1","description":"Approved","result":1},
{"id":"32_b1","description":"Approved","result":1},
{"id":"55_b1","description":"Approved","result":1}]",
14       "lastmod": 1528289509000,
15       "status": 4
16     },
17     "id": "fd56464366",
18     "lastmod": 1528289509000
19   },
20   {
21     "audit": {
22       "feedback": "[{"id":"19_b1","description":"Approved","result":1},
{"id":"19_b2","description":"Approved","result":1},
{"id":"25_b1","description":"Approved","result":1},
{"id":"32_b1","description":"Approved","result":1},
{"id":"55_b1","description":"Approved","result":1}]",
23       "lastmod": 1528289509000,
24       "status": 3
25     },
26     "id": "09897kjpg56",
27     "lastmod": 1528289509000
28   },
29   {
```

```
30     "audit": { "lastmod": 1528306991000, "status": 501 },
31     "id": "34dfdyg63tgrsf",
32     "lastmod": 1528222962000
33   },
34   {
35     "audit": { "lastmod": 1528306991000, "status": 1 },
36     "id": "43545435",
37     "lastmod": 1528222962000
38   }
39 ]
```

3.6 Query single creative group status

Endpoint

代码块

```
1 GET {baseUrl}/management/v1/bidder/{bidderId}/creativeGroups/{id}
```

Path parameters

Attribute	Type	Description
bidderId	string; required	Bidder ID.
id	string; required	Creative group ID returned at submit time.

Example

Request — `GET {baseUrl}/management/v1/bidder/496/creativeGroups/dsfd121`

Response:

代码块

```
1 {
2   "id": "dsfd121",
3   "duration": 15,
4   "audit": {
```

```
5      "feedback": "32-inch material resolution invalid",
6      "lastmod": 1528288587000,
7      "status": 502
8    },
9    "lastmod": 1528288587000
10  }
```

4. Order API

Covers the three order-related modules: inventory query, order management, and broadcast strategy.

4.1 Inventory — inquire sufficient targets

For a single city and a given campaign period, duration and frequency, return the subset of the provided location IDs that have sufficient inventory.

Endpoint

代码块

```
1  POST {baseUrl}/v1/inventory/inquireSufficientTargets
```

Request body

Attribute	Type	Description	Constraints
cityId	string	Standard city ID, e.g. <code>3100000000000</code> for Shanghai	required
startDate	LocalDate	Campaign start date	required; <code>startDate</code> $\geq$ today
endDate	LocalDate	Campaign end date	

			required; startDate ≤ endDate
durationInSecond	BigDecimal	Duration per play (seconds)	required; > 0 , multiple of 15
frequency	int	Plays per day	required; > 0 , multiple of 300
targetIds	string[]	List of location IDs to check	required; unique elements

Example:

代码块

```
1  {
2    "cityId": "3100000000000",
3    "startDate": "2019-11-18",
4    "endDate": "2019-11-24",
5    "durationInSecond": 15,
6    "frequency": 300,
7    "targetIds": ["15750", "15751"]
8  }
```

Response

Attribute	Type	Description
success	boolean	Whether the query succeeded
targetIds	string[]	Location IDs with sufficient inventory
code	string	Business code
message	string	Failure reason if any

代码块

```
1  {
2    "success": true,
3    "code": "0",
4    "message": "",
```

```
5     "targetIds": ["334862"]
6 }
```

4.2 Create order (`createOrder`)

Place an order and lock inventory.

Endpoint

代码块

```
1  POST {baseUrl}/v1/adgroup/createOrder
```

Request body

Attribute		Type	Description	Constraints
bidderId		string	Account ID (obtained at account creation)	
productName		string	Product line, e.g. SMART_SCREEN	
startDate		LocalDate	Campaign start date	required; startDate ≥ today and now ≤ contractual deadline
endDate		LocalDate	Campaign end date	required; startDate ≤ endDate
durationInSecond		BigDecimal	Duration per play (seconds)	required; > 0, multiple of 15
frequency		int	Plays per day	required; > 0, multiple of 300
dsp		boolean	false = non-programmatic, true = programmatic	required
orderItems	cityId	string	Standard city ID — unique key of an order item	required

	targetIds	string[]	List of location IDs for this city	required; unique elements
	goalLocationNum	int	Desired number of locations to lock	required; > 0 and $\leq$ count of valid targetIds

Example:

代码块

```
1  {
2    "bidderId": "123123123sfsaddsadasd",
3    "productName": "SMART_SCREEN",
4    "startDate": "2020-03-16",
5    "endDate": "2020-03-22",
6    "durationInSecond": 15,
7    "frequency": 600,
8    "dsp": false,
9    "orderItems": [
10     {
11       "cityId": "city1",
12       "targetIds": ["1", "2"],
13       "goalLocationNum": 2
14     },
15     {
16       "cityId": "city2",
17       "targetIds": ["1", "2"],
18       "goalLocationNum": 1
19     }
20   ]
21 }
```

Response

Attribute	Type	Description
orderId	string	Order ID
success	boolean	Whether the request succeeded
code	string	Business code
message	string	Failure reason if any

代码块

```
1  {
2    "success": true,
3    "code": "0",
4    "message": "",
5    "orderId": "141964_209232"
6  }
```

4.3 Cancel order (`cancelOrder`)

Subject to the contractual deadline and the publishing lock.

Endpoint

代码块

```
1  POST {baseUrl}/v1/adgroup/cancelOrder
```

Request body

Attribute	Type	Description	Constraints
orderId	string	Order ID	required
bidderId	string	Account ID	

代码块

```
1  {
2    "orderId": "361d67fce69b4772ba0e8f88b99f44f6",
3    "bidderId": "123123123sfsaddsadasd"
4  }
```

Response

代码块

```
1  {
```

```
2  "success": true,
3  "code": "0",
4  "message": ""
5  }
```

4.4 Get order detail (`getOrderDetail`)

Returns full order detail including current locked locations. Only returns orders belonging to the caller.

Endpoint

代码块

```
1  POST {baseUrl}/v1/adgroup/getOrderDetail
```

Request body

Attribute	Type	Description	Constraints
orderId	string	Order ID	required
bidderId	string	Account ID	

代码块

```
1  {
2    "orderId": "1052713_110113",
3    "bidderId": "123123123sfsaddsadasd"
4  }
```

Response

Attribute	Type	Description
success	boolean	Whether the query succeeded
code	string	Business code

message		string	Failure reason if any
orderResult	orderId	string	Order ID
	durationInSecond	BigDecimal	Duration (seconds)
	frequency	int	Plays per day
	startDate	date	Campaign start date
	endDate	date	Campaign end date
	endTime	localTime	Real end time (e.g. when cancelled, this is the cancellation time)
	orderStatus	enum	WAIT / SHOW / FINISH / CANCELLED / TERMINATED (see below)
	dsp	boolean	Whether programmatic
	hasDefaultAdStrategy	boolean	Whether a default broadcast strategy exists
	maxCancelTime	Instant	Latest time the order can be cancelled
	createTime	Instant	Creation time
	orderItems	cityId	City ID
		reservedLocationIds	Currently locked locations; only present when orderStatus is WAIT or SHOW
		targetIds	Location IDs passed at order creation
		goalLocationNum	Desired number of locations

Order status values:

Value	Meaning

WAIT	Awaiting broadcast
SHOW	Currently broadcasting
FINISH	Broadcast finished
CANCELLED	Cancelled
TERMINATED	Terminated (offline operation only)

Example response:

代码块

```
1  {
2    "success": true,
3    "code": "0",
4    "message": "",
5    "orderResult": {
6      "orderId": "141964_209232",
7      "orderStatus": "WAIT",
8      "maxCancelTime": "2021-06-16T08:00:00Z",
9      "createTime": "2021-06-03T09:07:02Z",
10     "hasDefaultAdStrategy": false,
11     "startDate": "2021-06-21",
12     "endDate": "2021-06-27",
13     "durationInSeconds": 15,
14     "frequency": 300,
15     "dsp": false,
16     "endTime": "2021-06-28T00:00:00",
17     "orderItems": [
18       {
19         "cityId": "3100000000000",
20         "goalLocationNum": 4,
21         "targetIds": ["6732146", "6732145", "6732148", "6732147"],
22         "reservedLocationIds": ["6732146", "6732145", "6732148", "6732147"]
23       }
24     ]
25   }
26 }
```

4.5 Create order-level broadcast strategy (`createOrderStrategy`)

Attaches approved creative groups to an order. Last operable time is the same as cancellation (by 4 PM Wednesday). All broadcast strategies within an order must be consistent.

Endpoint

代码块

```
1 POST {baseUrl}/v1/adstrategy/createOrderStrategy
```

Request body

Attribute	Type	Description	Constraints
bidderId	string	Account ID	
orderId	string	Order ID	required
creativeGroupIds	string[]	IDs of approved creative groups	required; when frequency = 300 , maxSize = 6

代码块

```
1 {
2   "bidderId": "123123123sfsaddsadasd",
3   "orderId": "ed01172cdf0c4624becdbe5c02d1104c",
4   "creativeGroupIds": ["c2"]
5 }
```

Response

代码块

```
1 {
2   "success": true,
3   "code": "0",
4   "message": ""
5 }
```

4.6 Create target-level broadcast strategy (`createTargetStrategy`)

Sets the broadcast strategy at the target (building) level. Same operation deadline as cancellation. All strategies within an order must be consistent.

Endpoint

代码块

```
1 POST {baseUrl}/v1/adstrategy/createTargetStrategy
```

Request body

Attribute	Type			Description	Constraints
bidderId	string			Account ID	required
orderId	string			Order ID	required
adTargetSet	cityId	string		Target city	required
	targets	targetId	string	Target ID	required
		targetType	string	Target type, e.g. BUILDING	required
		creativeGroupIds	string[]	Creative group IDs for this target	required
defaultCreativeGroupIds	string[]			Approved default (fallback) creative group IDs	required; when frequency = 300 , maxSize = 6

代码块

```
1 {
2   "adTargetSet": [
3     {
4       "cityId": "5101000000000",
5       "targets": [
6         {
7           "creativeGroupIds": ["143321_C1040002"],
8           "targetId": "6755979",
```

```
9         "targetType": "BUILDING"
10     }
11 ]
12 }
13 ],
14 "defaultCreativeGroupIds": ["143321_C143202"],
15 "orderId": "143321_288366"
16 }
```

Response

代码块

```
1  {
2    "success": true,
3    "code": "0",
4    "message": ""
5  }
```

5. End-to-end integration flow

A typical integration for a property-management publisher goes through the following stages:

1. Bootstrap

- Call `POST /v1/authserver/account/create` once per customer to obtain a `bidderId`. Persist it.

2. Sync catalog (periodically or on demand)

- `GET /v1/adresource/getAllStandardCities` → list of cities.
- `POST /v1/adresource/getBuildingInfos` → buildings per city (paginated).
- `POST /v1/adresource/getValidLocationInfos` → screen locations per building, including `deviceStyleId` / `deviceStyleName` needed to render creatives at the right resolution.

3. Submit creative

- Render and host the creative assets (one per device style).

- `POST /management/v1/bidder/{bidderId}/creativeGroups` to submit a creative group.
- Poll `GET /management/v1/bidder/{bidderId}/creativeGroups?auditStart=...` ($\leq$ 24-hour window) or `GET /management/v1/bidder/{bidderId}/creativeGroups/{id}` until `audit.status = 3` (approved). On `4` or `502`, fix and resubmit to get a new group.

4. Check inventory and place order

- `POST /v1/inventory/inquireSufficientTargets` to filter the candidate location list.
- `POST /v1/adgroup/createOrder` with the filtered targets and a `goalLocationNum` per city.

5. Attach broadcast strategy

- `POST /v1/adstrategy/createOrderStrategy` (order-level) or `POST /v1/adstrategy/createTargetStrategy` (target-level) using one or more approved `creativeGroupIds`.

6. Monitor lifecycle

- Poll `POST /v1/adgroup/getOrderDetail` to observe `orderStatus` transitions (`WAIT` → `SHOW` → `FINISH`), read `reservedLocationIds`, and honor `maxCancelTime`.
- Cancel if needed via `POST /v1/adgroup/cancelOrder` (subject to the publishing lock and contractual deadline).