

Plan Order API

1.Inventory Module

1.1. Query Sufficient Targets (inquireSufficientTargets)

1.1.1 Method Description

Query inventory-sufficient target IDs within a single city for specified delivery period, duration, and frequency.

POST /v1/inventory/inquireSufficientTargets

1.1.2 Request Fields

Property Name	Type	Description	Constraints
cityId	String	Standard city ID (e.g., Shanghai: 3100000000000)	Required
startDate	LocalDate	Start date of delivery period	Required, startDate >= today
endDate	LocalDate	End date of delivery period	Required, startDate <= endDate
durationInSecond	BigDecimal	Duration per play (seconds)	Required, durationInSecond > 0, divisible by 15
frequency	int	Daily playback frequency	Required, divisible by 300
targetIds	String Array	List of target IDs	Required, unique elements

JSON Example:

```
{
```

```
"cityId": "310000000000",
"startDate": "2019-11-18",
"endDate": "2019-11-24",
"durationInSecond": 15,
"frequency": 300,
"targetIds": ["15750", "15751"]
}
```

1.1.3 Response Fields

Property Name	Type	Description
targetIds	String Array	List of available target IDs
code	String	Query status code
message	String	Error reason (if failed)

JSON Example:

```
{
  "success": true,
  "code": "0",
  "message": "",
  "targetIds": ["334862"]
}
```

2. Order Module

2.1. Confirm Ad Placement (createOrder)

2.1.1 Method Description

Create and lock inventory for ad placement.

POST /v1/adgroup/createOrder

2.1.2 Request Fields

Property Name		Type	Description	Constraints
startDate		LocalDate	Delivery start date	Required, >= today & before business deadline
endDate		LocalDate	Delivery end date	Required, >= startDate
durationInSecond		BigDecimal	Playback duration (seconds)	Required, >0, divisible by 15
frequency		int	Daily playback frequency	Required, divisible by 300
dsp		boolean	Programmatic flag	Required
orderItems	cityId	String	Standard city ID	Required
	targetIds	String Array	Target ID list	Required, unique elements
	goalLocationNum	int	Desired number of targets	Required, >0, <= valid targetIds count

JSON Example:

```
{  
  "startDate": "2020-03-16",  
  "endDate": "2020-03-22",  
  "durationInSecond": 15,  
  "frequency": 600,
```

```
"dsp": false,
"orderItems": [
  {
    "cityId": "city1",
    "targetIds": ["1", "2"],
    "goalLocationNum": 2
  },
  {
    "cityId": "city2",
    "targetIds": ["1", "2"],
    "goalLocationNum": 1
  }
]
```

2.1.3 Response Fields

Property Name	Type	Description
orderId	String	Order ID
success	boolean	Operation status
code	String	Response code
message	String	Error reason (if failed)

JSON Example:

```
{
  "success": true,
  "code": "0",
  "message": "",
  "orderId": "141964_209232"
}
```

2.2. Cancel Order (cancelOrder)

2.2.1 Method Description

Cancel order within cancellation deadline (aligned with business cutoff time).

POST /v1/adgroup/cancelOrder

2.2.2 Request Fields

Property Name	Type	Description	Constraints
orderId	String	Order ID	Required

JSON Example:

```
{  
  "orderId": "361d67fce69b4772ba0e8f88b99f44f6"  
}
```

2.2.3 Response Fields

Property Name	Type	Description
success	boolean	Cancellation status
code	String	Response code
message	String	Error reason (if failed)

JSON Example:

```
{  
  "success": true,  
  "code": "0",  
  "message": ""  
}
```

```
"message": ""  
}
```

2.3. Get Order Details (getOrderDetail)

2.3.1 Method Description

Retrieve order details including target assignments and current lock status.

POST /v1/adgroup/getOrderDetail

2.3.2 Request Fields

Property Name	Type	Description	Constraints
orderId	String	Order ID	Required

JSON Example:

```
{  
  "orderId": "1052713_110113"  
}
```

2.3.3 Response Fields

Property Name		Type	Description
success		boolean	Query status
code		String	Response code
message		String	Error reason (if failed)
	orderId	String	orderId
	durationInSecond	BigDecimal	duration,second
	frequency	Int	frequency, times/day
	startDate	date	startDate

orderResult	startDate		date	startDate
	endDate		date	endDate
	endTime		localTime	actual End Time of Delivery (endTime): The completion time of the ad placement. For example, if the order is canceled, endTime reflect the exact timestamp when the cancellation operation was executed
	orderStatus		Enum	WAIT : before schedule starts SHOW : in schedule FINISH :over schedule CANCELLED :cancelled TERMINATED :stopped during schedule
	dsp		boolean	if it is programmatic
	hasDefaultAdStrategy		boolean	if it has default creative to play
	maxCancelTime		Instant	the deadline you can cancel
	createTime		Instant	createTime
	orderItems	cityId	String	Standard city ID
		reservedLocations	String Array	reserved locations list
		targetIds	String Array	Target ID list
		goalLocationNum	int	Desired number of targets

JSON Example:

```
{
  "success": true,
  "code": "0",
  "message": "",
  "orderResult": {
    "orderId": "141964_209232",
    "orderStatus": "WAIT",
    "maxCancelTime": "2021-06-16T08:00:00Z",
    "createTime": "2021-06-03T09:07:02Z",
    "hasDefaultAdStrategy": false,
    "startDate": "2021-06-21",
    "endDate": "2021-06-27",
    "durationInSecond": 15,
    "frequency": 300,
    "dsp": false,
    "endTime": "2021-06-28T00:00:00",
    "orderItems": [
      {
        "cityId": "3100000000000",
        "reservedLocationIds": ["6732146", "6732145", "6732148", "6732147"],
        "targetIds": ["6732146", "6732145", "6732148", "6732147"],
        "goalLocationNum": 4
      }
    ]
  }
}
```

3. Scheduling Module

3.1. Set Order Schedule (createOrderStrategy)

3.1.1 Method Description

Configure scheduling for entire order (last operation time aligned with cancellation deadline).

POST /v1/adstrategy/create

3.1.2 Request Fields

Property Name	Type	Description	Constraints
orderId	String	Order ID	Required
creativeGroupIds	String Array	Approved creative group IDs	Required, max 6 for frequency=300

JSON Example:

```
{ "orderId": "ed01172cdf0c4624becdbe5c02d1104c", "creativeGroupIds": [ "c2" ] }
```

3.1.3 Response Fields

Property Name	Type	Description
success	boolean	Operation status
code	String	Response code
msg	String	Error reason (if failed)

JSON Example:

```
{  
  "success": true,  
  "code": "0",  
  "message": ""}
```

3.2. Set Target-Level Schedule (createTargetStrategy)

3.2.1 Method Description

Configure target-specific scheduling (supports projects, aligned with cancellation deadline).

POST /v1/adstrategy/createTargetStrategy

3.2.2 Request Fields

Property Name			Type	Description	Constraints
orderId			String	Order ID	Required
adTargetSet	cityId		String	Target city	Required
	targets	targetId	String	Target ID	Required
		targetType	String	Target type (e.g., BUILDING)	Required
		creativeGroup	String Array	Creative group IDs	Required
defaultCreativeGroupIds			String Array	Default creative groups (fallback)	Required, max 6 for frequency=300

JSON Example:

```
{
  "adTargetSet": [
    {
      "cityId": "510100000000",
      "targets": [
        {
          "targetId": "6755979",
          "targetType": "BUILDING",
```

```
    "creativeGroupIds": ["143321_C1040002"]
  },
  ],
  "defaultCreativeGroupIds": ["143321_C143202"]
},
],
"orderId": "143321_288366"}
```

3.2.3 Response Fields

Property Name	Type	Description
success	boolean	Operation status
code	String	Response code
msg	String	Error reason (if failed)

JSON Example:

```
{
  "success": true,
  "code": "0",
  "message": ""}
```

Error Codes

Code	Description
0	Success
-1	Invalid date parameters (past time)
-2	Invalid duration/ frequency
-3	Resource errors (invalid city, insufficient targets)
-4	Account configuration issues
-5	Network/ internal errors
-6	Publishing lock restrictions
-7	Exceeded operation deadline
-8	Inventory lock failure
-9	Contract approval restrictions
-10	Order not found
-11	Invalid order status
-12	Invalid creative assets
-13	Scheduling conflicts

