

P4B - R Chapter 2 Quiz

Total questions: 7

Worksheet time: 8mins

Name Class Date

1. The `setwd()` function allows us to check our current working directory, while `getwd()` allows us to change our current working directory.

a) True

b) False
2. Consider the following R code: `read.table("Data/sample.txt", sep=";")`
Which of the following best describes the data in sample.txt?

a) The values in the file are separated by commas

b) The values in the file are separated by a blank space

c) The values in the file are separated by semicolons

d) The values in the file are separated by a Tab
3. Consider the following R code: `read.table("Data/parlament.csv", sep=",")`
What is true about this code?

a) It will give an error because `read.table()` cannot read csv files

b) It will correctly read the file, because `read.table()` is instructed to use commas as separators

c) It will give an error because `read.table()` does not allow commas to be used as a field separator

d) None of the above
4. Which argument in the `read.csv()` function allows you to manually specify the column names of an imported dataset?

a) `col.names=`

b) `header=`

c) `sep=`

d) `row.names=`

5. What is the difference between importing a dataset using the readxl package and the openxlsx package?
- a) readxl returns a data frame, while openxlsx returns a matrix b) readxl returns a list, while openxlsx returns a tibble
- c) Both packages always return a dataframe d) readxl returns a tibble, while openxlsx returns a data frame
6. saveRDS() is used to save a single R object to a file, and readRDS() is used to reload that same object exactly as it was when saved.
- a) True b) False
7. To export a dataset in R as a text file, you can use the function (a) _____, while for a comma-separated file you can use (b) _____. To export an Excel files, you typically use the (c) _____ function from the (d) _____ package, which must first be installed using (e) _____.

Ans. _____

Answers Keys

1. b) False
2. c) The values in the file are separated by semicolons
3. b) It will correctly read the file, because read.table() is instructed to use commas as separators
4. a) col.names=
5. d) readxl returns a tibble, while openxlsx returns a data frame
6. a) True
7. (a) write.table(), (b) write.csv(), (c) write.xlsx, (d) openxlsx, (e) install.packages("openxlsx")