

```

/**Este Proyecto Estudia el Concepto de las Uniones (UNIONS)**/

///Union Definition
// 1. User-defined Datatype
// 2. A collection of variables stored in the same region of memory

#include <stdio.h>
#include <stdlib.h>

int main()
{
    /*differencesBetweenStructsAndUnions();*/
    moreUsesForUnions();
    return 0;
}

/**Este Procedimiento Aborda las Diferencias entre Estructuras y Uniones**/

struct point_struct{ /// In a struct, each element has a separate space in
memory
    int x;           /// Thus, there are 8 bytes in memory for both integers
(4 bytes each)
    int y;
};

union point_union{ /// In a union, each element points toward the same
region in memory
    int x;           /// Thus, there are only 4 bytes in memory for both
integers (4 bytes each)
    int y;           /// Due to this, when modifying one element, every other
element of a union gets modified
};

void differencesBetweenStructsAndUnions()
{
    struct point_struct point1;
    union point_union point2;

    point1.x = 5;
    point1.y = 10;

    printf("point_struct: (%i,%i) \n", point1.x, point1.y);

    point2.y = 9;
}

```

```

    printf("point_union: (%i,%i) \n", point2.x, point2.y);

    point1.y = 15;

    printf("Despues de modificar --> point_struct: (%i,%i) \n", point1.x,
point1.y);

    point2.x = 1;

    printf("Despues de modificar --> point_union: (%i,%i)", point2.x,
point2.y);

    printf("\n \n");
}

/**Este Procedimiento Muestra Otros Usos de las Uniones**/

#include<stdio.h>

typedef union cPerson{ ///Uso de TYPEDEF con UNIONS
    int ID;
    char cName[20];
}person;

void moreUsesForUnions()
{
    int f;

    person person1;
    person *pointerToPerson1; ///Podemos usar punteros que guarden la
direccion de memoria de una UNION
    printf("Ingresa el ID: ");
    scanf("%i", &person1.ID);
    fflush(stdin);

    printf("ID ingresado: %i \n", person1.ID);
    pointerToPerson1 = &person1;
    (*pointerToPerson1).ID = 11; /// Esta es UNA forma de modificar la
informacion de la UNION a la que apunta un puntero
    pointerToPerson1->ID = 12; /// Esta es OTRA forma de modificar la
informacion de la UNION a la que apunta un puntero
    printf("Despues de modificar via punteros --> ID ingresado: %i \n",
person1.ID);

```

```

printf("\n \n");

person personArray[5];
for (f = 0; f < 5; f++)
{
    printf("Ingresa el ID #%i: ", f + 1);
    scanf("%i", &personArray[f].ID);
    fflush(stdin);
}

printf("Impresion de IDs. \n");

for (f = 0; f < 5; f++)
    printf("\tID #%i: %i\n", f + 1, personArray[f].ID);

printf("\n \n");
}

/**Este Procedimiento Muestra como se Define una Union**/

#include<stdio.h>

//Defining the Template
union info{
    char cName[20];
    int age;
};

void definingUnions()
{
    //Defining a Variable of Type UNION INFO
    union info person1;

    printf("\n \n");
}

```