



App Metadata Transport

Release 10.x

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: \${drm-product-code} 10.x

Publication Date: September 28, 2018

Document code: _10.x_mgamtug__en-us

Contents

Contacting Infor.....4

Chapter 1: About App Metadata Transport.....5

Chapter 2: Using App Metadata Transport.....6

 Before using App Metadata Transport.....6

 Importing metadata.....6

 Exporting metadata.....7

 Testing app metadata transport results.....8

 Running App Metadata Transport from a command line interface.....9

Contacting Infor

If you have questions about Infor products, go to Infor Concierge at <https://concierge.infor.com/> and create a support incident.

If we update this document after the product release, we will post the new version on the Infor Support Portal. To access documentation, select **Search > Browse Documentation**. We recommend that you check this portal periodically for updated documentation.

If you have comments about Infor documentation, contact documentation@infor.com.

Chapter 1: About App Metadata Transport

App Metadata Transport allows you to export or import metadata for:

- IDOs
- Property classes
- Custom assemblies
- The Application Event System (AES)
- Replication documents, which include Business Object Documents (BODs), inbound cross references, and outbound cross references
- Critical numbers
- DataViews
- DataView actions
- DataSearch sources from an XML file to a target database
- Form extensions

The utility works by:

- Exporting the metadata from a source database to an XML file; or
- Importing the metadata from an XML file to a target database.

This utility can be run through any of these methods:

- Locate and double-click the AppMetadataTransport.exe file in the folder where the application is installed.
- Run the AppMetadataTransport.exe file from a command line.
- Use the **App Metadata Transport** form in the windows client or web client.

Note: This form is created for instances where the **App Metadata Transport** stand-alone utility cannot be run due to security concerns.

Chapter 2: Using App Metadata Transport

Before using App Metadata Transport

You can export data at any time, because **App Metadata Transport** simply reads data and writes it to an XML file.

However, to avoid potential collisions, you should import data only during periods of non-peak use.

We recommend that you back up the target database before importing any metadata.

Caution: To avoid collisions, do not run multiple instances of this utility.

Importing metadata

To import metadata:

- 1 Open the **App Metadata Transport** stand-alone utility or the form version.
- 2 On the **Action** tab, select the **Import metadata from an XML file to a target database** check box, and then click **Next**.
- 3 On the **Source** tab, specify the **Import File Name**, and then click **Next**.
- 4 On the **Target** tab, select the **Target Configuration**, and then click **Next**.
Note: This tab is not available in the **App Metadata Transport** form.
- 5 On these tabs, select the metadata to transport, and then click **Next**.

Note: For most tabs, you can select none, all, or selected items. You can also select all items that are referenced by selected items, such as IDOs and events.

Tab	Affected data
IDOs	Multiple database tables, such as ido.Collections, ido.Tables, ido.Methods, and others Even though multiple tables are affected, the IDO is imported as a single unit, for example, the ido.Collections record and all its children.
Property Classes	Only data in the ido.PropertyClasses tables
Custom Assemblies	Only data in the ido.CustomAssembly tables

Tab	Affected data
Events, Event Triggers, Event Handlers, and Event Initial States	All the data for a particular Access As value is imported as a unit. This metadata can include multiple events, handlers, and actions, as well as metadata from a number of other event-related tables. Importing this metadata as a unit is necessary because of interdependencies across a number of event-related tables.
Replication Documents	All Business Object Document (BOD), Inbound Cross Reference, and Outbound Cross Reference metadata
Critical Number Categories, Critical Numbers, and Critical Number Drilldowns	Multiple database tables, such as WBCategory, WBKPI, WBDrill-down, and others This metadata can include multiple critical number categories, critical numbers, drilldowns, and multiple related setup tables.
Predefined DataViews, Form DataView Layouts, and DataView Actions	Multiple database tables, including WBDataViews, WBDataViewLayouts, WBDataViewActions, and others This metadata can include multiple DataViews, DataView Layouts, and associated DataView Setup information. DataView Actions can be selected separately for import.
DataSearch Sources	Multiple database tables, such as WBSearchSource, WBSearch-Sourceltem, and others This metadata can include multiple DataSearch Sources and supporting records from DataSearch Setup.
Form Extensions	All the Form Extensions data for a particular Access As value

6 On the **Summary** tab, verify the actions to be performed.

7 Click **Finish**.

Exporting metadata

To export metadata:

- 1 Open the **App Metadata Transport** stand-alone utility or the form version.
- 2 On the **Action** tab, select the **Export metadata from a source database to an XML file** check box, and then click **Next**.
- 3 On the **Source** tab, select the **Source Configuration**, and then click **Next**.
Note: This tab is not available in the **App Metadata Transport** form.
- 4 On the **Target** tab, specify the **Export File Name**, and then click **Next**.
- 5 On these tabs, select the metadata to transport, and then click **Next**.

Note: For most tabs, you can select none, all, or selected items. You can also select all items that are referenced by selected items, such as IDOs and events.

Tab	Affected data
IDOs	Multiple database tables, such as ido.Collections, ido.Tables, ido.Methods, and others Even though multiple tables are affected, the IDO is exported as a single unit, for example, the ido.Collections record and all its children.
Property Classes	Only data in the ido.PropertyClasses tables
Custom Assemblies	Only data in the ido.CustomAssembly tables
Events, Event Triggers, Event Handlers, and Event Initial States	All the data for a particular Access As value is exported as a unit This metadata can include multiple events, handlers, and actions, as well as metadata from a number of other event-related tables. Exporting this metadata as a unit is necessary because of interdependencies across a number of event-related tables.
Replication Documents	All Business Object Document (BOD), Inbound Cross Reference, and Outbound Cross Reference metadata
Critical Number Categories, Critical Numbers, and Critical Number Drilldowns	Multiple database tables, such as WBCategory, WBKPI, WBDrill-down, and others This metadata can include multiple critical number categories, critical numbers, drilldowns, and multiple related setup tables.
Predefined DataViews, Form DataView Layouts, and DataView Actions	Multiple database tables, including WBDataViews, WBDataViewLayouts, WBDataViewActions, and others This metadata can include multiple DataViews, DataView Layouts, and associated DataView Setup information. DataView Actions can be selected separately for export.
DataSearch Sources	Multiple database tables, such as WBSearchSource, WBSearchSourceItem, and others This metadata can include multiple DataSearch Sources and supporting records from DataSearch Setup.
Form Extensions	All the Form Extensions data for a particular Access As value

6 On the **Summary** Tab, verify the actions to be performed.

7 Click **Finish**.

Testing app metadata transport results

To verify that the data was imported successfully, use one of these options:

- Open the XML file and manually compare the file to the resulting target database.
- Run queries on the database.

To run queries on the database:

- 1 Before you import the metadata, create a backup of the target database.
- 2 Import the metadata.
- 3 Restore the backup of the target database under a different name.
- 4 Run queries that compare the original (pre-import) database to the updated (post-import) database to determine what was changed.

Running App Metadata Transport from a command line interface

You can run the **App Metadata Transport** utility from the command line using AppMetadataTransport.exe.

Command line parameters

These are the parameters associated with the utility:

Parameter	Description
-action	Perform a certain activity. Switches include: • import - Import a single metadata object from an XML configuration file. • export - Export a single metadata object to an XML file. • massimport - Import all metadata objects within a specified XML file. This option is available only from a command line. • massexport - Export all metadata objects to a set of XML files. This option is available only from a command line. All IDOs, property classes, and IDO extension class assemblies from the source configuration are exported to the designated folder, each in a separate file. Note: When you execute any of these actions from the command line, the App Metadata Transport utility opens, set up for the designated action.
-sourceConfig	Application configuration name
-targetConfig	Application configuration name
-sourceXML	Source XML file (<i>sourcefilename.xml</i>)
-targetXML	Target XML file (<i>targetfilename.xml</i>)
-commandTimeout	The timeout value for each individual command that runs on the database
-help	Displays a dialog box of available parameters for this utility

Examples

To perform a mass import, use this command:

```
AppMetadataTransport -action massimport -targetConfig  
  configName -sourceXml "C:\sourceFolder"
```

To perform a mass export, use this command:

```
AppMetadataTransport -action massexport -sourceConfig  
  configName -targetXml "C:\destinationFolder"
```