



Infor Mongoose Licensing

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements.

As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor Mongoose 9.03

Publication date: October 18, 2016

Contents

Your License Document	5
License Modules and Tokens	5
Tokens	6
License Administration in Mongoose	6
Associating Users with Modules	7
Named Users vs. Concurrent Logins	7
Licensing in a Multiple Sites per Database Environment	8
System Users with Special Licensing	8
Licensing by Session Type	9
Verifying the License at User Login	9
Verifying the License at Runtime	10
Intranet Licensing	10
More About the License Modules	11
MGCoreTrans Module	11
MGCoreAutomation Module	11
MGDataViews Module	11
MGDeveloper Module	12
MGUserCreatedForms Module	12
MGUserCreatedIDOs Module	12
Licensing Custom Forms and IDOs	12
Licensing for Automation Sessions	13
Registering a Mongoose-Based Application	13
How to Request a License	14

Note: This document applies to Infor Mongoose 9.01 and above.

You may already have had some discussions with your sales representatives about licensing. This document explains the different types of licensing available with Mongoose.

Your License Document

You need a license document to apply your licenses. Infor provides this document in the form of a *.txt file when you purchase an Infor product. The file contains, in an encrypted format, all the information needed to apply your licenses to each application database. However, you must determine what license modules you need, and how many licenses you need for each module, before the license document can be provided.

License Modules and Tokens

Infor Mongoose includes these license modules:

Module	Access Capabilities	Session Type
MGCoreAutomation	IDO Access	IDO
MGCoreTrans	All standard Mongoose forms	Full client
MGDataviews	Forms related to Dataviews, Datasearch, and KPIs	Full client
MGDeveloper	Maintenance forms used for development of IDOs and for customization of SQL tables and columns	Full client

Module	Access Capabilities	Session Type
MGUserCreatedForms	Customer-created forms that are not copied from an existing form	Undefined - suitable for Web form only and Full client
MGUserCreatedIDOs	Customer-created IDOs that are not extending another IDO	IDO

The modules and session types are explained in more detail later in this section.

Tokens

Each module that you purchase has a certain number of "tokens" available for users to consume, based on the number of licenses you purchased for that module. Generally, each user who logs into Mongoose consumes one or more tokens. (There are some exceptions to this rule, as discussed later.) License token consumption occurs when a user logs into the system, and the token is not released until the user logs out.

License Administration in Mongoose

License administration is performed using these Mongoose forms:

- **License Management:** This form indicates the dates when the license begins and ends, which modules are licensed, and how many licensed users you have. This form is where you apply the license to stay current.
- **Licensed Modules:** This form lists the modules for which your company is licensed for the current site.
- **User Modules:** Use this form to associate user names with license modules.
- **License Modules Per User Connection:** This form lists the license module names associated with each current user connection. If Intranet Licensing is enabled, this form also shows the site from which the users are connected. In non-intranet licensed environments, only connections from the current site will be shown. Connected users consume user licenses (tokens) based on the license module to which that user has been assigned, and the session type under which they are logging in (see "Licensing by Session Type" on page 9).
- **License Module Concurrent User Counts:** This form lists all the license module names that are currently associated with a user connection, as well as the total number of users who are consuming a license on each module. Use this form to monitor whether your purchased license count is appropriate for the number of concurrent logins at peak times.
- **Session Management:** Use this form to view current user sessions, and to delete user sessions when necessary. This form also includes a column to indicate the session type.

- **Sites:** If this form indicates that intranet licensing is being used, licenses can only be assigned at the master site for the intranet.
- **Modules for Form:** On this form, you can filter by form name to identify licenses or modules that are required to be able to run that form. You can also filter by license module to identify forms that are associated with that module.

For more information about using any of these forms, see the online help.

Associating Users with Modules

The system administrator associates each user with one or more license modules. When an administrator associates a user with a module, the administrator is granting that user the license rights to use resources contained in that module. For online users, the licensed resources are the forms they run. For WebService and other automated sessions, the licensed resources are IDOs.

License rights are separate from security rights. Just because you grant a user license rights to a resource does not mean that user has security rights to access the resource. Security rights are controlled separately, by assigning users to groups and/or by allowing certain types of access (read, delete, execute, etc.) to specific objects. For more information about permissions, see the online help topic "Assigning Users to Groups."

Depending on whether you have chosen named or concurrent licensing, Mongoose consumes the license tokens in different ways.

Named Users vs. Concurrent Logins

A *named user* license links one user login to one license (through the User Modules form). For example, if you plan to have three users (bobw, jeanp, and miker) running Mongoose, you would request three Mongoose named licenses.

Named license users are only allowed one active login to an Mongoose site, and that login consumes a license. If you try to log in a subsequent time as a named user who still holds an active session, Mongoose requires the active session to be released. However, there is an exception to this: the special Multi-Session user that is provided as part of the license. This special user is described on page 9.

With named user licensing, when you associate a user with a license module, Mongoose verifies that there are remaining tokens for the module not yet associated with a user. A license module token is consumed at the time the user is assigned to that module. If a license module assignment is later removed from a user, that license module token is returned to the pool of available tokens. When the user logs in and attempts to access a form or IDO, Mongoose verifies that the user is associated with at least one license module containing the resource.

In a multiple sites per database environment, each named user can log in once per shared site, which counts as one license token against each module to which that user is assigned.

With *concurrent login* licensing, licenses are assigned to users, but the license check does not occur until users log in. If the number of users logged into a site with a particular license module is equal to the license number limit, and another user tries to log in, the site does not allow that user to log in. Using our example above, if you had two concurrent Mongoose licenses, you could assign that license to three users (bobw, jeanp, and miker). However, only two of them could use the Mongoose license token at a time.

Under concurrent licenses, a user can log into a certain site multiple times, as long as the total number of license tokens currently consumed in Mongoose for any module that applies to that user is less than the licensing limit for that module in that site. (A module applies to a user if that module is assigned to that user and has the same session type as the user's connection - or has a session type of Undefined. For more information about session types, see "Licensing by Session Type" on page 9.)

With concurrent login licensing, you can associate as many users as you want with a module in a site, regardless of how many tokens you have purchased for the module. When a user logs in, Mongoose verifies that there are remaining tokens for each of the modules/session types that apply to that user, and then consumes a token (which reduces the available tokens) for each of those modules for the duration of that user's session. License module tokens consumed during a user's session are returned to the available pool when the user logs off.

Licensing in a Multiple Sites per Database Environment

For a multiple sites per database environment, see the information under "Intranet Licensing" on page 10. The requirements are similar: one license document applies to all sites and named vs. concurrent limits are enforced across all sites. In an intranet licensed environment or a multiple sites per database environment, if a named license user is logged into one site, the user can log into additional sites without having to relinquish the existing session. However, the user cannot have multiple login instances in the same site; the user must relinquish the current session to start another one.

In a one site per database environment where intranet licensing is not used, each site has its own license document and keeps track of its own tokens. Each site has no knowledge of any logins on any other site. If a user is defined in multiple sites and is logged into more than one site, whether concurrent or named, that user uses a license token for each of those logins in each site. (For information about intranet licensing, see "Intranet Licensing" on page 10.)

For one site, all the licenses must be specified as either named or concurrent - you cannot mix them.

System Users with Special Licensing

The following are special cases:

- **SA User:** The "sa" user doesn't require licensing. By default, that user has the ability to open any form and run any process in the site. The "sa" user should be reserved for system administration tasks and should not be used to run multi-site processes. Only one instance of the "sa" user can be logged in at any time, even under a concurrent license.

- **Multi-Session (Concurrent) User:** This capability is designed for WebService automation scenarios, where an application that is accessing the IDO layer may have multiple threads that process simultaneously, with each thread sharing the same configured multi-session user.
Under a named user license, each standard user is only allowed one session per site. The multi-session user gives an administrator one user that can have multiple concurrent sessions. Under a concurrent license, all users except "sa" can have multiple concurrent sessions. Therefore the multi-session user provides no real significance in a concurrent license environment.
When the multi-session user is assigned to a license module, the tokens consumed are the number of concurrent sessions defined for that user. In other words, if the multi-session user is defined by the license to allow seven concurrent sessions, assigning that user to a module consumes seven license tokens for that module. Multi-session users and their concurrent session limits are defined in the license document generated by the vendor. You cannot create or modify a user to be a multi-session user.
- **Infor ION:** ION uses a direct connection to the application when retrieving BODs, so no license token is required.
- **Infor Framework services:** Framework services such as the Replicator use service sessions to connect to the application. The service session does not consume a license.

Licensing by Session Type

Mongoose allows named and concurrent licensing based on session type. Among other benefits, this feature allows named users to be logged in multiple times using different types of sessions, but only consume license modules for the appropriate type of session.

We have associated one of the following session types with each license module, as indicated in the chart on page 5:

- **Full client:** Used for a fully trusted client where form licensing grants permission to the form and all of the IDOs used by that form. This includes smart clients and Web clients where the Web rendering is not in form-only mode.
- **Web form only:** Used for Web clients in form-only mode.
- **IDO:** Used for programmatic (automation) access to the framework IDOs and their methods.
- **Undefined:** No session type is defined.
- Additionally, there is a Service session type that is not associated with any module. The Service session type is used by framework utilities such as TaskMan. Under a service session, access to licensed form and IDO resources is granted without consuming any license tokens.

Verifying the License at User Login

When license checks are made during user logins, only license modules whose session type specification matches the user's current session type are considered.

If the module is associated with a session type, then a license token is only consumed for that module if the module's session type matches the user's connection session type.

Verifying the License at Runtime

After the user has successfully logged in, runtime license checks are made to determine if a certain object (form or IDO) is available to that user, based on the user's licensing and session type. Again, only modules matching the user's current session type are considered.

Otherwise, the session type is considered.

Intranet Licensing

You can choose to set up an intranet with a master site that controls licensing for other sites on the intranet. This consolidates license administration and validation at the master site. One license document applied on the master site can service all of the sites enabled for intranet licensing on that intranet. All named user and concurrent login license checks at each of the participating sites are redirected to the master site for validation.

You can choose which sites on the intranet will use intranet licensing, through a check box on the Sites form.

You can use the Intranet Shared User Tables feature, which requires Intranet Licensing, to create and administer all users for the intranet from the master site. If you select Intranet Licensing but you do not use the Intranet Shared User Tables feature, users must be created at each participating site, and all users from all participating sites must be created at the master site as well.

A *named* user is allowed one login at each participating site on the intranet. If a named user tries to log into the same site that he is already logged into, the system requires the user to cancel the existing session first.

A user with a *concurrent* license can log in as many times on as many sites as needed, up to the license limit. Each of those concurrent logins consumes a license token.

Intranet licensing requires reliable connectivity between all participating sites. If connectivity between an intranet licensing site and its master site goes down, then all subsequent license checks will fail until connectivity is restored, so users will not be able to log in at non-master sites.

After intranet licensing has been turned on for a site, you should not turn it off without good reason. If you do, you must apply license documents to each site where you turn it off. In addition, custom objects at that site may then have incomplete licensing, if the site is not either the master site or the site at which the objects were originally created, because the appropriate licensing records for the object will not exist in the application database at that site.

License information is not replicated and no tables need to be shared specifically for intranet licensing. (However, the sites on the intranet must replicate the Site Admin category, in order to

recognize the master site.) Information about how many sites are logged on using a particular license is stored in the SiteConnectionInformation table, which is kept up-to-date only at the master site.

The Session Management form reflects only the sessions for the local site. If the current site is enabled for intranet licensing, the License Modules per User Connection form shows license module use across all participating sites.

The License Management and User Modules forms are disabled at participating sites other than the master site.

More About the License Modules

MGCoreTrans Module

Most users will be assigned an MGCoreTrans license, which provides access to most forms in Mongoose. (You can then limit individual user's access by setting up group and user authorizations.) This license module is always assigned the session type Full client.

Users with this license can access, edit and delete data or transactions.

MGCoreAutomation Module

This license allows other applications to connect to Mongoose through the IDO layer.

Some integrations require the MGCoreAutomation license module in order to log in to Mongoose and collect data. Infor allows you to request automation licenses equal to the number of MGCoreTrans licenses your company buys.

If you plan to have custom applications connecting to Mongoose through the IDO layer, you may need to buy additional MGCoreAutomation licenses in order to have enough licenses for each application connection. This license module is always assigned the session type IDO.

For more information, see "Licensing for Automation Sessions" on page 13.

MGDataViews Module

Use this license module to allow users to access the DataViews, DataSearch, and Critical Numbers (KPI) forms.

MGDeveloper Module

Request this license if you plan to create or customize IDOs or SQL tables. This module allows the use of Mongoose forms that start with the prefix "IDO" or "SQL" that are used for development. This license module is always assigned the session type Full client.

MGUserCreatedForms Module

This license module is used for customer-created forms that are not copied from an existing form. This license module is assigned the session type Undefined, so it is suitable for Web-form only and Full client sessions.

MGUserCreatedIDOs Module

This license module is used for customer-created IDOs that are not extending another IDO. This license module is assigned the session type IDO.

Licensing Custom Forms and IDOs

If customers add custom forms, copy/extend existing forms, create new IDOs, or extend existing IDOs, they are licensed using the following information in the license document and the ModuleMembers table:

- New customer-created IDOs that do not extend other IDOs are automatically assigned to the MGUserCreatedIDOs license module.
- New customer-created IDOs that extend another IDO are automatically assigned to the license modules to which the base IDO belongs.
- New customer-created forms that are not copied from another form are automatically assigned to the MGUserCreatedForms license module.
- Copied forms are automatically assigned to the license modules to which the source/original form belonged.
- A new form that extends an existing form is automatically assigned to the license modules to which the existing form belonged.

Be aware that, if you have multiple application databases pointing to the same forms database, you must copy the form licensing information to each application database, using FormSync.

Licensing for Automation Sessions

Multi-session users are defined in your license document and are created when the license document is applied. The multi-session user is designed for automation sessions where multiple threads of the calling application may overlap. For example, a web application can call the Mongoose IDOWebService to query data to present. When making a call to the IDO Web Service, the web application supplies a specific user ID, password, and configuration. The web application can have multiple threads executing simultaneously, so it requires multiple concurrent Mongoose sessions.

Automation sessions can be established using the following technologies. Each of these options exposes the same underlying IDO Request interface. The licensing implications of these options vary, as described here:

- SOAP WebService - These calls are synchronous, consuming a license token during the processing.
- COM - These calls are synchronous, consuming a license token during the processing.
- XML - Mongoose utility/web servers provide both synchronous and asynchronous URLs. The calling process must format an IDORequest XML document, and then decide whether to use the synchronous route or asynchronous route:
 - For the synchronous route, an automation session is established for the user specified in the XML, consuming a license that is assigned to that user. (Often this user is assigned a MGCoreAutomation license, because MGCoreAutomation is the only license module that contains all the Mongoose IDOs plus customer-created ones.) The synchronous route allows the calling application to receive the results of the request.
 - For the asynchronous route, although security is checked for the user specified in the XML, no licensing consumption occurs. The processing is performed by the framework service ReplQLListener. XMLs processed this way require a valid user, but that user does not need to take licensing into account, only security.

Registering a Mongoose-Based Application

If you are an Independent Software Vendor (ISV) building a Mongoose application for resale, you must register your application with Infor, so that we can generate license keys for that application.

Note: If you have purchased Mongoose to build applications for your own use, you do not need to register the applications.

Submit the name of your application and the names of your license modules. For each module, specify its session type and form and/or IDO names.

For example, if your application has a customer service module designed for users on normal computers, and a field-service module with a set of forms designed for mobile devices in form-only mode, you could specify these new license modules:

Module	Session Type	Contains these forms and IDOs
CustService	Full client	CSCustomers CSOrders CSParameters etc.
FieldService	Web form only	FSCustomers FSWorkOrders FSParameters etc.

If your application has a requirement to restrict the user logins based on the combination of license module and the type of site, you can use the SiteTypeModuleMap table to set up acceptable combinations of site type and license module. A user can only access a site if the site's "site type" can be used with the license module to which the user is assigned.

You must also provide an addendum to this guide that describes your application's license modules, so that your end users can request the appropriate modules.

How to Request a License

Contact Infor customer service to request your license keys. You will need to specify your SQL Server name and application database name. To find the SQL server name, open the SQL Query Analyzer and enter **Select @@Servername**.

To find the application database name, open SQL server Enterprise Manager. Expand the **Databases** folder to see the names of the databases that include the text **_App**. Those are your Mongoose application databases.

You can then determine the name of the application database within that server that is to be licensed.

Index

A

Authorization 7
Automation license module 11

C

Concurrent login license 8
Custom forms, licensing 12
Custom IDOs, licensing 12

E

Extending an existing form 12

F

FormSync utility 12
Framework service connections 9
Full client session type 9

I

IDO session type 9
Intranet licensing 10
Intranet Shared User Tables form 10
ION connection 9

L

License document 5
License Management form 6
 with master site 11
License module 7
License Module Concurrent User Counts form 6
License Modules per User Connection form 6
 with master site 11
License modules, list of 5
Licensed Modules form 6

M

Master site 10
MGCoreAutomation license module 11

MGCoreTrans license module 11
MGDataViews license module 11
MGDeveloper license module 12
MGUserCreatedForms license module 12
MGUserCreatedIDOs license module 12
ModuleMembers table 12
Modules for Form 7
Multi-session user 9

N

Named user license 7

R

Registering a Mongoose-Based application 13

S

sa user 8
Security 7
Service session type 9
Session Management form 6
 with master site 11
Session type, for each module 5
Session types 9
Site Admin replication category 10
SiteConnectionInformation table 11

T

Tokens, licensing 7

U

Undefined session type 9
User groups 7
User Modules form 6
 with master site 11

W

Web form only session type 9

