



Infor Mongoose Installation Guide

Release 2020.09

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor Mongoose 2020.09

Publication Date: September 17, 2020

Document code: mg_2020.09_mgig_mg_en-us

Contents

Contacting Infor.....	6
Chapter 1: About this guide.....	7
Installation options.....	7
Additional Infor Mongoose documentation.....	8
Signing up for support.....	8
Planning your communication.....	8
Chapter 2: Mongoose installation checklist.....	9
Chapter 3: Prerequisites.....	10
Chapter 4: Installation and basic configuration.....	12
Installing the basic Mongoose components.....	12
About the Infor Mongoose Configuration Wizard.....	13
Using the Express Configuration installation option.....	13
Using the Advanced Configuration installation option.....	15
Configuring the option to search for Office applications.....	18
Specifying databases to create.....	19
Configuring help files installation.....	21
Configuring the IDO Request Web Service.....	22
Configuring the Inbound Queue Web Service.....	23
Configuring Windows services and replication logins.....	24
Merging existing databases into an All-in-One database.....	25
Configuring the Report Server (SSRS reports).....	26
Configuring the Smart Client Deployment server.....	26
Configuring the Token Authentication Web Service.....	28
Configuring translations.....	29
Configuring the Web Client option.....	29
Using the Configuration Manager.....	33

Testing the client.....	33
Chapter 5: Setting up a Cloud Server.....	35
Chapter 6: Setting Up the DMZ Server.....	36
Requirements for a DMZ Server.....	36
Installing components on the DMZ Server.....	37
Using the DMZ Express Configuration option.....	38
Using the DMZ Advanced Configuration option.....	38
Testing the DMZ Server.....	40
Chapter 7: Upgrading Mongoose.....	41
Requirements.....	41
Performing the upgrade.....	41
Synchronizing the Forms databases.....	44
Post upgrade steps.....	45
Troubleshooting the upgrade.....	45
Chapter 8: Post-configuration tasks.....	46
Updating Service Configuration Manager settings.....	47
Setting up application event monitoring.....	47
Setting up Replication monitoring.....	48
Setting up TaskMan monitoring.....	51
Configuring the online help.....	51
Setting the base URL and start page.....	51
Configuring the help middle segment.....	52
Configuring help for on-premises use.....	53
Configuring AD FS.....	53
Creating AD FS relying party trust.....	54
Editing Infor Federations Services (IFS) application settings.....	55
Modifying Mongoose user account settings for AD FS.....	55
Defining your printers.....	55
Setting up report printing.....	56
Configuring email notifications for reports.....	56
Appendix A: Options for Advanced Configurations.....	58
Options for Application Server installations.....	58
Options for DMZ Server installations.....	61

Appendix B: Port configurations.....62

Appendix C: Supported languages.....63

Contacting Infor

If you have questions about Infor products, go to Infor Concierge at <https://concierge.infor.com/> and create a support incident.

The latest documentation is available from docs.infor.com or from the Infor Support Portal. To access documentation on the Infor Support Portal, select **Search > Browse Documentation**. We recommend that you check this portal periodically for updated documentation.

If you have comments about Infor documentation, contact documentation@infor.com.

Chapter 1: About this guide

This guide describes how to install and configure Infor Mongoose, release 10.0.

Installation options

This guide provides a number of different installation options. It is important to understand your options and the terminology used for each.

- **Single-server versus multi-server installation options** - In the past Mongoose installations typically took place with databases residing on one server and the other Mongoose components residing on other servers (usually two). You now have the option to install both the databases and the other Mongoose components on the same server, in a single-server setup.
- **Multiple databases versus All-in-One databases** - In the past, Mongoose installations typically created the four basic databases (Applications, Forms, Objects Metadata, and Form Templates) in separate databases. The preferred method now is to include the four basic databases in a single "All-in-One" database.

While you can still use the old approach, it is much more convenient and economical to use the All-in-One database approach.

In either case, if you intend to use your Mongoose environment for form and application development work, you will still need to create additional databases for your setup. Details are provided in the appropriate chapter and sections.

- **Basic (Application Server) installation** - This is the most common type of installation performed. In the Mongoose installer, it is designated as the **Application Server** option.
This type of installation installs all the parts and pieces required for a Mongoose application to run, optimally from a single server.
- **Cloud Server** installation - This option is rarely used at this time.
- **DMZ Server** installation - This type of installation is used when you want to set up Mongoose without exposing your Application Server directly to the Internet, and without needing to place a load balancer or other hardware between the Application Server and the Internet. In this case, you install a "DMZ" version of Mongoose on the public-facing server and then point that version back to the main Application Server on a different machine.
- **Upgrades** - This guide also explains the requirements and procedures to perform an upgrade to the Mongoose software.

Additional Infor Mongoose documentation

The most current version of all Mongoose documentation is available on the Infor Xtreme support website, and on the Mongoose portal (<https://mongoose.infor.com/portal>).

Signing up for support

If you are not currently on support and would like more information on your support options, please call your customer account representative. If you are not sure who your account representative is, contact Infor Customer Service.

Planning your communication

To make sure the correct analyst is assigned to your case and to expedite the resolution of any questions you might have, please have the following information available when you call us:

- Your company name and phone number
- Version release and point release (Example: 9.03.12)
- Database software version and release, if applicable
- Platform or environment (Example: Windows Server 2012)
- What you were doing when the problem arose
- If you received an error message, the full message text and error number, as applicable
- If you are calling back on an existing case, the case number

Chapter 2: Mongoose installation checklist

This checklist provides a high-level overview of the Infor Mongoose installation process. This checklist provides the actions to take for an on-premises installation.

Use this checklist to help guide in your installation of Mongoose:

✓	Take these actions, in order:
☐	Download the version of the Infor Mongoose .iso file to install from the Download Center.
☐	Verify that you have all the necessary prerequisites installed and configured. See Prerequisites on page 10.
☐	If you are performing an upgrade, make sure you back up your databases and perform the other steps required before the installation. See Requirements on page 41. Then perform the other steps as provided in the section Upgrading Mongoose on page 41.
☐	Install the basic Mongoose components. See Installing the basic Mongoose components on page 12.
☐	Use the Mongoose Configuration Wizard to configure your installation according to your preferred type of installation: - Express Configuration See Using the Express Configuration installation option on page 13. - Advanced Configuration See Using the Advanced Configuration installation option on page 15. - DMZ Server configuration See Setting Up the DMZ Server on page 36.
☐	Use the Configuration Manager to define your applications and configurations. See Using the Configuration Manager on page 33.

Chapter 3: Prerequisites

Mandatory prerequisites

Before you install your Mongoose-based application, you must meet all these prerequisites:

- Windows Server 2019 or Windows Server 2016.
 - Make sure you have the latest Windows updates for your OS. For additional options available for your application, some have prerequisites of their own. For the most part, these prerequisites can be performed either before or after the actual installation of your application, unless otherwise noted.
 - Verify that you have installed **Web Server (IIS)** and all role services except **FTP Server**, which is allowed but not required.
Note: Windows Server 2016 requires **Web Server (all)**, **Management Tools (IIS Management Console)** recommended), and, if you plan to use FTP, **FTP Server**.
 - Verify that you have these Features installed:
 - .NET Framework 3.5
 - .NET Framework 4.6
 - Message Queuing
 - Windows Identity Foundation
- Install the .NET 4.7.2 standard library.
- Verify that you have installed the latest version of a supported Internet browser.

These are the supported browsers:

- Microsoft Edge
- Google Chrome
- Safari
- Firefox

Note: While Firefox is supported in Mongoose and most Mongoose-based applications, it might not be in other Infor products you use in conjunction with Mongoose. For example, it is not supported in some IOS products, such as Infor Ming.le™.

- Install and configure SQL Server 2016, SQL Server 2017, or SQL Server 2019.
Note: You must use either the Standard or Enterprise version of SQL Server. SQL Server Express is not supported.
 - SQL Server can be installed on the same computer on which you plan to install your Mongoose-based application, or it can be installed on another computer.
 - If you plan to have multiple sites in one application database, you need a version of SQL that supports table partitioning. Otherwise, you can use a SQL version that does not support table partitioning.
Note: The term "site," in this context, refers to a configuration of Mongoose that is set up as a "multi-site" configuration, in which you have two or more installations of Mongoose on different servers, in different locations, all communicating with and synchronizing with each other. It

does not refer to the installation of Mongoose on a single server but being accessed from multiple locations using VPN or remote desktop technology.

- Install all **Instance Features**, except **Reporting Services - Native**, unless you plan to produce SSRS reports.

Note: SQL Server 2016 includes an instance feature named **PolyBase Query Service for External Data**. Unless you determine that you need this feature, we recommend that you NOT install it. Doing so can cause problems with the SQL Server installation.

- If you plan to produce SSRS reports, you must also install **Reporting Services - Native**.

Additional options

These options are included in this group:

- If your end users will be using the Windows ("Smart") client, they must be using Windows 10 or later. The Windows client no longer works with other versions of Windows.
- Microsoft's Bulk Copy Program (BCP) utility is now installed automatically. This is installed on the machine on which you will run the Configuration Wizard or the Upgrade Wizard.

This utility is typically installed in a sub directory of the SQL Server installation and is available as a stand-alone download from Microsoft.

- If you want to use AD FS to access the web client, you must configure Infor Federation Services (IFS).

See the *OS Platform Installation Guide*, which is available from the Infor Xtreme support site.

- If you plan to use Mongoose to preview reports, set up a virtual directory in IIS. We recommend that you perform this procedure after you have installed the Mongoose base.
- If you plan to use Network DTC Access, enable that on the machine where your instance of SQL Server resides.
- Additional SQL Server options - If you plan to access the Mongoose from a non-Mongoose connection, then you should verify that these settings have been made for SQL Server:

Note: These settings are made by default during the Mongoose installation. However, if you have copied a database or made some other configuration changes, you might need to reset these options.

- **ANSI warnings**
- **ANSI padding**
- **ANSI nulls**
- **Arithmetic abort**
- **Quoted identifier**
- **xact abort**
- **concat null yields null**

We also recommend that you clear the check box for the **numeric round abort** option.

If you change any of these settings, you must stop and restart SQL Server. Do NOT use the Windows Services utility to stop and restart SQL Server. Instead, use the SQL Server Configuration Manager utility.

- Microsoft Office integration - If you plan to use the Microsoft Office integration feature to display Mongoose data in Office applications, you must give this directory Read and Write permissions for everyone:

`C:/inetpub/wwwroot/ApplicationSearchServiceForOffice`

Chapter 4: Installation and basic configuration

This chapter presents the information to install Mongoose and perform basic configuration for **Application Server** installations.

Mongoose provides these basic installation types:

- Express configuration installation - This installation is almost entirely automated. Databases are automatically created and named; administrator login credentials are implemented; and optionally, a basic configuration is created.
- Advanced configuration installation - This installation requires more manual input. Use this installation option when you need to specify additional options not incorporated in the Express configuration or you require more precise control over what is installed and what is not.

Installing the basic Mongoose components

No matter what kind of installation you intend to perform for Mongoose, all installation options begin with the procedure to install the basic Mongoose components. These are the basic components:

- Registry keys
- Product files
- Web applications
- Windows services

To install these components:

- 1 Extract the installation image obtained from the Download Center.
- 2 Locate the setup.exe file, and run it as Administrator.
- 3 When the **Infor Mongoose Installer** wizard displays, if you want to install the application in a location other than the default, enter the new location.
You can use the **Browse** button to search for the location you want.
- 4 Select **Application Server** and click **Next**.
The next page of the wizard displays four status bars for the installation process (**Registry Keys**, **Product Files**, **Web Applications**, and **Windows Services**).
- 5 Click **Install**.
The installer proceeds to install the components required to build a Mongoose-based application, and then automatically launches the **Infor Mongoose Configuration Wizard**.

If, at this point, you want to view, print, or save the installation log for the process this far, you can close the Configuration Wizard or move its window out of the way, and then click **View Log** in the **Infor Mongoose Installer**.

6 Decide on one of these options:

- To continue with an Express Configuration installation, see [Using the Express Configuration installation option](#) on page 13.
- To continue with an Advanced Configuration installation, see [Using the Advanced Configuration installation option](#) on page 15.

About the Infor Mongoose Configuration Wizard

When the basic Mongoose installer finishes, one of the options offered for follow-up action is the **Infor Mongoose Configuration Wizard**. This wizard is normally run after the basic installation process, to create the databases, configuration, and other components required for a Mongoose-based application.

Of course, you can always create additional databases, configurations, and applications, and you can use the **Infor Mongoose Configuration Wizard** to do it. There might also be need to run this wizard for other, specialized installations (for instance, for a dual token authentication setup, or to merge individual databases into an All-in-One database) that you decide to perform later.

Whatever the case, it is important to realize that, although the wizard is employed primarily for an initial or new Mongoose installation, it can be run any number of times later, to add to or modify the basic Mongoose installation.

Using the Express Configuration installation option

Use the Express Configuration installation option when you want to create a basic configuration, without having to configure every detail at the outset.

Note: Before proceeding with this procedure, make sure you have installed the basic Mongoose components, as described in [Installing the basic Mongoose components](#) on page 12.

To continue with the Express Configuration installation:

- 1** Optionally, in the **Infor Mongoose Configuration Wizard**, clear the **Make new databases** check box.

When this option is cleared, no databases or configurations are created. This is useful when you are performing an upgrade, you already have databases, and you do not want to create additional databases or configurations.

If you elect to perform this step, then all you need do is provide the Windows login credentials and indicate whether you want to use SSL/HTTPS.

You can then skip Step 2.

- 2 Assuming you did not perform the first step here, provide or verify that the correct server and login credentials are provided.

Default values are provided for these credentials when the **Configuration Wizard** is launched. Some of these are read-only, others you can change, depending on the type of login you want to use. In either case, these values are required:

- **SQL Server Name** - Provide the name of your SQL server instance.
- **SQL Server Authentication** - Use this option to indicate whether you want to access the SQL Server databases using the **SQL Server Authentication** method or the **Windows Authentication** method.

If you use the **SQL Server Authentication** method, you must also provide SQL user login credentials in the appropriate fields.

- **SQL User Name** - This field is enabled only if you select the **SQL Server Authentication** option. In this case, you must provide the SQL user name of a user defined in the SQL Server instance you are using for the configuration.

Note: The user specified here must have sufficient permissions in the SQL Server instance. The required permissions are db_creator, db_datareader, db_datawriter, db_ddladmin, and execute.

- **SQL Password** - This field is visible and enabled only if you select the **SQL Server Authentication** option. Provide the SQL user password for the user specified in the **SQL User Name** field.
- **Server Alias** - Use this field to specify a web alias (instead of the default machine name). This value is used as part of the Windows (smart) client deployment URL. It is also used to name the Web Server in the Configuration Manager and to set the **Config Server URL** in the Service Configuration Manager.
- **Database Names Prefix** - Specify the prefix to be used when naming the databases to be created and used for the configuration.
- **Windows User Name** - Specify the name of the Windows user to be used to access the configuration, using the **domain\username** format. This is typically the "Administrator" user login.
- **Windows Password** - Provide the login password for the Windows user.
- **Use SSL/HTTPS** - To specify that the configuration must use security layers in the form of SSL and HTTPS, select this option.
This option applies to web clients, WinStudio ("Smart") clients, and web applications.
- **Create config** - To specify that a basic configuration is to be created, select this option.
If this option is cleared, the wizard creates only the IDs and tables for the configuration, but not the configuration itself.
The configuration uses the server and authentication credentials you used to make connections to the databases.
- **Enable MG sa User** - When this option is selected, the Express Configuration option creates and enables the Mongoose 'sa' user account.
The 'sa' user account must be created and enabled before you can sign in to Mongoose for the first time.
If you select this option, the **Password** field is enabled. Use this field to assign a password to the 'sa' user account. If you do not want to use a password for the 'sa' account, leave this field blank.

- **All-in-One DB** - When this option is selected, the Application database, the Forms database, the Objects database, and the Templates database are all incorporated into a single database. When this option is cleared, each database is created separately.
- **Form Control DBs** - When this option is selected, the Express Configuration option creates the additional databases required for the use of Form Control and a source control system.

3 After verifying that any required login credentials have been provided, click **NEXT**.

The wizard displays a page that lists the actions that will be taken to create the configuration. We recommend that you take a few minutes to review this page before you commit, just to make sure the installation is set to perform the actions you expect.

4 Click **COMMIT**.

The wizard proceeds to create the required databases, tables, scripts, stored procedures, and other elements required for a basic configuration or required by the upgrade (in a case where you performed Step 1).

When finished, the wizard displays a log of all the actions taken to create the configuration. You can save this log as a *.txt file (**SAVE LOG**).

At this point, you have three options:

- Use the **Configuration Manager** to continue/finish setting up your Mongoose configuration. Normally, the Configuration Manager launches automatically, at the end of the basic installation process. If it does not, launch it by clicking **CONFIG MANAGER**. You use the **Configuration Manager** to create configurations that specify the databases you want to access for your applications.
- To open the **Service Configuration Manager**, click **SERVICE MANAGER**.
The **Service Configuration Manager** is used to configure the Windows services used by Mongoose and its utilities. In most cases, you will not need to use the **Service Configuration Manager** until later, when you create additional configurations.
- To close the **Configuration Wizard** without taking any further action at this time, click **FINISH**.

Note: Before you can log in to the configuration, if you did not create the 'sa' user account as part of the original configuration, you must create the 'sa' user account in **Configuration Manager**. Otherwise, you will get an invalid user name/password error message.

To finish configuring your Mongoose system, you must create/modify your configurations and applications.

See the **Configuration Manager** help.

Using the Advanced Configuration installation option

Use the **Advanced Configuration** installation option when you want to exercise more control over what options are implemented and where they are created.

Note: Before proceeding with this procedure, make sure you have installed the basic Mongoose components, as described in [Installing the basic Mongoose components](#) on page 12.

To continue with the **Advanced Configuration** installation:

- 1 In the **Infor Mongoose Configuration Wizard**, select the **Advanced Configuration** option near the bottom of the page.
Note: There is no need to specify any other options on this page.
- 2 Click **NEXT**.
- 3 On the next page, select the components you want to include in your configuration.
Note: Each component is configured on succeeding pages of the wizard. The pages for options that you do not select here are not presented later.
To see a brief description of each component (at the bottom of the page), select that component. For more detailed descriptions, see [Options for Application Server installations](#) on page 58.
- 4 Click **NEXT**.
Assuming you selected the **Application Search Service for Office** option, the wizard displays the page to configure and use this option.
See [Configuring the option to search for Office applications](#) on page 18.
- 5 Click **NEXT**.
Assuming you selected the **Databases** option, the wizard displays the page to create and configure the databases.
- 6 Specify what databases you want to create and make the settings required to access and use them.
See [Specifying databases to create](#) on page 19.
- 7 Click **NEXT**.
Assuming you selected the **End-User/Admin Client Shortcut** option, that option instructs the wizard to install a desktop shortcut on the computer where the client is installed. The field on this page presents the URL that the desktop shortcut will use to access the Infor Framework IDO Request Service.
- 8 Verify that the name of your application server is correct.
- 9 Click **NEXT**.
Assuming you selected the **Help Files** option, the wizard displays the page that allows you to specify what online help files to install.
See [Configuring help files installation](#) on page 21.
- 10 Click **NEXT**.
Assuming you selected the **IDO Request Web Service** option, the wizard displays the page to configure this option.
See [Configuring the IDO Request Web Service](#) on page 22.
- 11 Click **NEXT**.
Assuming you selected the **Inbound Queue Web Service** option, the wizard displays the page to configure this option.
See [Configuring the Inbound Queue Web Service](#) on page 23.
- 12 Click **NEXT**.
Assuming you selected the **Industry Packs and Localizations** option, the wizard displays the page to select those packs and configurations. However, since at this time Mongoose does not have any industry packs or localization packages, the page should not display any options to load.

13 Click NEXT.

Assuming you selected the **Infor Windows Services and Replication** option, the wizard displays the page to provide login information for the various Windows services required by Mongoose.

See [Configuring Windows services and replication logins](#) on page 24.

14 Click NEXT.

Assuming you selected the **Link Databases for Multi-Site Use** option, the wizard displays the page to configure this option.

For information about multi-site configurations, see the *Multi-Site Planning Guide* and the *Multi-Site Implementation Guide*.

15 Click NEXT.

Assuming you selected the **Merge Existing Databases into All-in-One** option, the wizard displays the page to do this.

See [Merging existing databases into an All-in-One database](#) on page 25.

16 Click NEXT.

Assuming you selected the **Reporting Services (SSRS)** option, the wizard displays the page used to configure SSRS reporting.

Note: This option applies only to SSRS reports, which are now deprecated in Mongoose. Instead, we recommend the use of the new Report form type or of DataView reports.

See [Configuring the Report Server \(SSRS reports\)](#) on page 26.

17 Click NEXT.

Assuming you selected the **Smart Client Deployment** option, the wizard displays the page to specify the server that is to serve as the host for Windows (Smart) client deployments. It also specifies settings to configure the smart client deployment.

See [Configuring the Smart Client Deployment server](#) on page 26.

18 Click NEXT.

Assuming you selected the **Token Authentication Web Service** option, the wizard displays the page to specify the IIS application that is to host the Token Authentication functions.

See [Configuring the Token Authentication Web Service](#) on page 28.

19 Click NEXT.

Assuming you selected the **Translations** option, the wizard displays the page to configure translation specifications.

See [Configuring translations](#) on page 29.

20 Assuming you selected the Web Client option, the wizard displays the page to configure the way the web client behaves.

See [Configuring the Web Client option](#) on page 29.

21 Click NEXT.

The wizard displays a page that summarizes your selections and describes what will be processed when you click **COMMIT**. We recommend that you take a moment to review this summary before proceeding.

22 When you are satisfied that your selections are correct, click COMMIT.

The wizard proceeds to process your selections.

When it is finished, the wizard displays a summary of what was done and whether the installation was successful. Any component that failed installation is listed and the cause of the failure is described in a log. You can save this log for analysis (**SAVE LOG**).

Note: After the initial configuration, you can rerun the wizard any number of times required to get the configuration options you want. The **Merge Existing Databases into All-in-One** option, for instance, really can only be run after you have created a set of individual databases to merge; the **Translations** option can only be used after you have created one or more configurations; and so on...

At this point, you have these options:

- To create and edit configurations, you can click **CONFIG MANAGER**.
This launches the Configuration Manager utility.
- To manage the Infor Framework services, click **SERVICE MANAGER**.
This launches the **Service Configuration Manager** utility.

Note: If you have not yet created any Mongoose configurations, there is no point in starting up the **Service Configuration Manager**.

- To close the **Infor Mongoose Configuration Wizard**, click **FINISH**.

Configuring the option to search for Office applications

This section provides information about configuring the **Application Search Service for Office** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Application Search Service for Office** option.

The optional **Application Search Service for Office** allows you to exchange data between Mongoose and Microsoft Office applications. This is helpful if you want to synchronize calendar information, export data to Excel spreadsheets, and so on.

Note: If you plan to use this option to display Mongoose data in Office applications, you must give this directory Read and Write permissions for everyone: `C:/inetpub/wwwroot/ApplicationSearchServiceForOffice`

This service uses an IIS application to exchange data between a Microsoft Office application and your Mongoose application.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.
We recommend that you accept the default value. For information about the other options, consult IIS application pool information on the Internet.
- **IIS Site** - Select the site to assign the IIS application to.

We recommend that you accept the default value, but you can create your own IIS site and use that instead.

- **Embeddable URL Security (optional)** - Leave blank or provide a valid X-Frame-Options value. This option is used to set the value for an X-Frame-Options header, which is used to prevent clickjacking attempts.

These are the options for values in this field:

- To allow only the current website to frame content, leave this field blank, or set the value to **SAMEORIGIN**. **SAMEORIGIN** is the default value if this field is left blank.
- To allow only a single URI to frame the content, enter the URI in this field. This sets the URI as an **ALLOW-FROM** option.
- To prevent the use of content in all frames, set this field to **DENY**.

Note: Not all web browsers support these options. For more information, see topics related to X-Frame-Options on the Internet.

- **Content-Security-Policy (optional)** - Leave blank or provide a valid Content-Security-Policy (CSP).

This option is used to set the value for a Content-Security-Policy (CSP), which is used to prevent and mitigate clickjacking attempts, cross-site scripting, and other code injection attacks.

For examples of how to use this option, see the tooltip for this field.

Specifying databases to create

This section describes how to specify the databases you want to create and configure using the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Create Databases** option. We also assume that you have already decided what kinds of databases you want to create, whether an All-in-One database or various single or combinations of individual databases.

Note: To create an instance of Mongoose that is to be used solely for run-time use (in other words, NOT for form and application development work), you need only four databases: one each for Applications, Forms, Objects, and form Templates. These can be created either as individual databases or, preferably, in one "All-in-One" database.

If you are creating an instance of Mongoose that is also to be used for form and application development work, in addition to these four base databases, you must also create:

- A Master Forms database
- An Archive Forms database
- A Master Form Templates database
- An Archive Form Templates database

We recommend that, if you intend to use the Mongoose configuration for form and application development work, you also create the additional required databases at this time. Create these databases using the **Add Individual Database** option on the **Edit database settings** tab.

For specific information regarding the use of these databases, see the online help for the **Configuration Manager** utility.

To specify databases to create and make the necessary settings for them:

1 On the **Create config** tab, specify these settings:

- In the **Config Name** field, provide the name to be used for your configuration.
This name is used as a prefix for all databases. If you are creating an All-in-One database, it is appended with "_All".
Note: Do not use spaces in your configuration names. Configuration names must conform to the rules for SQL identifiers. We strongly recommend that you begin the configuration name with an alphabetic character, and that you use only alphanumeric characters and underscore characters.
- Optionally, in the **Encryption Key** field, paste the encryption key.
The encryption key is generated in the Configuration Manager utility.
See the topic "Enabling application data encryption" in the Configuration Manager help.
- Optionally, to create individual Forms, Applications, Objects, and Templates databases (rather than creating them as an All-in-One database), select the **Use Separate Databases** option.

2 Perform one of these actions:

- If you are creating an All-in-One database, click **Config with All-in-One Database**.
- If you are creating separate databases, click **Config with Separate Databases**.

The Configuration Wizard adds the specified databases to the list of **Databases to be created**.

3 On the **Edit database settings** tab, specify these settings:

- In the **SQL Server Name** field, verify that the name of your SQL Server instance is the correct one.
If not, select the correct instance from the drop-down list.
- From the **Authentication** drop-down list, select what kind of authentication to use to connect with the database:
 - **Windows Authentication** uses the Windows login credentials of an authorized user. This is typically the machine Administrator login, though not necessarily.
 - **SQL Server Authentication** uses the login credentials of an authorized SQL Server user.
If you select this option, then you must also supply the login credentials of an authorized SQL Server user, in the **SQL Username** field and the **SQL Password** field. The specified user must have sufficient permissions in the SQL Server instance.
The required permissions are **db_creator**, **db_datareader**, **db_datawriter**, **db_ddladmin**, and **execute**.
- From the **SQL Collation** drop-down list, select the type of collation to use in your databases.
Normally, you should use the ****Default Collation**** option. It is beyond the scope of this guide to describe other types of collation, but abundant information on the subject is available on the Internet.
Note: Mongoose only supports case-insensitive collations. We also strongly recommend that database and instance collations be the same.
- Verify that the **New SQL Database Name** field has the **Config Name**, appended with "_App".
- If you want to insert the Mongoose schema into existing databases, select the **Populate DB** option.

When this option is selected, the wizard does not actually create a new database, but only populates an existing database with the schema needed by Mongoose. This is used primarily

in cloud installations, in which the databases are created beforehand and need only to be populated with the schema.

When this option is cleared (the default), the wizard both creates a blank database and then populates it with the required schema.

- 4 Optionally, add any other individual databases you might need. For each additional database, use this sub-procedure:

Note: This sub-procedure applies to the additional databases required for a form and application development environment (as described previously in this topic).

- a From the **Database Type** drop-down list, select the type of database to create.

For a development environment, this would be either **FormsDb** or **TemplatesDb**.

Note: If you want to create an All-in-One database, select **ApplicationDb**, and make sure you select the **All-in-One** option.

- b In the **New SQL Database Name** field, provide a name for the additional database.

Note: Do not use spaces in your configuration names. Configuration names must conform to the rules for SQL identifiers. We strongly recommend that you begin the configuration name with an alphabetic character, and that you use only alphanumeric characters and underscore characters.

For a development environment, we recommend adding the intended use for the database to the name. For example, if the name of your application database is **MYDB**, you could name your master Forms database **MYDB-Master_Forms**; your archive Templates database **MYDB-Archive_Templates**; and so forth.

- c Click **Add Individual Database**.

The Configuration Wizard adds the database to the list of **Databases to be created**.

- 5 On the **Application database site information** tab, provide this information:

Note: Normally, you can leave these at the default settings. You need to provide or change this information only if you are implementing a multi-site setup. If this is the case, consult the *Multi-site Planning Guide* and the *Multi-site Implementation Guide* for your system before proceeding.

Configuring help files installation

This section provides information about configuring the **Help Files** option in the Infor Mongoose Configuration Wizard. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Help Files** option.

The **Help Files** option allows you to specify which sets of online help files to install and displays the default installation location.

- The MongooseCore.zip file contains the help files for both Mongoose runtime operations and developer (Design Mode) operations.
- The MongooseHelp.zip file contains the help files for the various Mongoose utilities (Configuration Manager, Form Control, Form Sync, IDO Runtime Service, and so on).

We recommend that you install both sets of help files, using the default locations specified here. Mongoose makes extensive use of context-sensitive help, both in the base Mongoose application and in the various utilities.

We also recommend that you take note of where the help files are installed by default. This can be helpful if/when you want to update the help files.

Configuring the IDO Request Web Service

This section provides information about configuring the **IDO Request Web Service** option in the Infor Mongoose Configuration Wizard. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **IDO Request Web Service** option.

The **IDO Request Web Service** is required for clients that connect to the IDO Runtime Service using HTTP/HTTPS.

This service uses an IIS application to provide a synchronous URL or HTTP endpoint for processing IDO request XML documents.

Note: Asynchronous requests are handled by the Inbound Queue Web Service.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.
We recommend that you accept the default value. For information about the other options, consult the IIS application pool information on the Internet.
- **IIS Site** - Select the site to assign the IIS application to.
We recommend that you accept the default value, but you can create your own IIS site and use that instead.
- **Embeddable URL Security (optional)** - Leave blank or provide a valid X-Frame-Options value.
This option is used to set the value for an X-Frame-Options header, which is used to prevent clickjacking attempts.

These are the options for values in this field:

- To allow only the current website to frame content, leave this field blank, or set the value to **SAMEORIGIN**. **SAMEORIGIN** is the default value if this field is left blank.
- To allow only a single URI to frame the content, enter the URI in this field. This sets the URI as an **ALLOW-FROM** option.
- To prevent the use of content in all frames, set this field to **DENY**.

Note: Not all web browsers support these options. For more information, see topics related to X-Frame-Options on the Internet.

- **Content-Security-Policy (optional)** - Leave blank or provide a valid Content-Security-Policy (CSP).

This option is used to set the value for a Content-Security-Policy (CSP), which is used to prevent and mitigate clickjacking attempts, cross-site scripting, and other code injection attacks.

For examples of how to use this option, see the tooltip for this field.

- **Config Server URL** - This URL is used internally to configure the URL for the Service Configuration Manager and sets the DataViews binding to either HTTP or HTTPS (depending on the specified URL).
- **Use HTTPS for REST service** - (Optional) When selected, this option specifies that only HTTPS should be used for RESTful services.

You should select this option only if your entire website is set up to use HTTPS.

- **Enable REST Workstation Logon** - (Optional) When selected, this option specifies that a RESTful service can use the user's workstation login credentials to access your application. This option allows the use of the OAuth authentication method with REST calls.

When this option is selected, you must also provide an **OAuth Consumer Key** and an **OAuth Consumer Secret**.

Configuring the Inbound Queue Web Service

This section provides information about configuring the **Inbound Queue Web Service** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Inbound Queue Web Service** option.

The **Inbound Queue Web Service** is required for asynchronous replication XML requests from sites on other intranets. This service acts as a front endpoint for an MSMQ, from which one of the Mongoose services reads and processes the XML documents through to the IDO Runtime service.

This service uses an IIS application to perform this function.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.
We recommend that you accept the default value. For information about the other options, consult the IIS application pool information on the Internet.
- **IIS Site** - Select the site to assign the IIS application to.
We recommend that you accept the default value, but you can create your own IIS site and use that instead.
- **Embeddable URL Security (optional)** - Leave blank or provide a valid X-Frame-Options value.
This option is used to set the value for an X-Frame-Options header, which is used to prevent clickjacking attempts.

These are the options for values in this field:

- To allow only the current website to frame content, leave this field blank, or set the value to **SAMEORIGIN**. **SAMEORIGIN** is the default value if this field is left blank.
- To allow only a single URI to frame the content, enter the URI in this field. This sets the URI as an **ALLOW-FROM** option.

- To prevent the use of content in all frames, set this field to **DENY**.

Note: Not all web browsers support these options. For more information, see topics related to X-Frame-Options on the Internet.

- **Content-Security-Policy (optional)** - Leave blank or provide a valid Content-Security-Policy (CSP).

This option is used to set the value for a Content-Security-Policy (CSP), which is used to prevent and mitigate clickjacking attempts, cross-site scripting, and other code injection attacks.

For examples of how to use this option, see the tooltip for this field.

Configuring Windows services and replication logins

This section provides information about configuring the logins for the Infor Framework Windows services and the Replication services in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Infor Windows Services and Replication** option. We also assume that you know on which servers the services need to run.

For each service listed, to indicate that the service is to be configured when the wizard executes the specified options, select the **Configure** option. Any service that is not selected is not configured, and so, no username or password is required.

For each service that you select to be configured, you have three options:

- Utilize a user account on your network.

Note: If you are using Windows Authentication for your system, you must use this option.

In the **...Account** field, specify a username, using a *domain\user* format, where:

- *domain* is the name of a domain in your network.
- *user* is the username of a user in that domain who is authorized access to all configuration databases.

Then supply the password for the user account.

- Run the service as LocalSystem.

To use this option, simply leave both the **...Account** field and the **...Password** field blank.

- Run the service using NetworkService.

To use this option, enter **NetworkService** in the **...Account** field and leave the **...Password** field blank.

If you want, you can use a single Windows user account for all services. To do this, select the check box labeled **Use the same account for all Windows services** at the top of the page. Then provide the username for the **User Account** (using the guidelines provided above).

Note: When installed and configured, each service name is prefixed with "Infor Framework".

For information about the various services, see [About the services](#) on page 25.

About the services

This table describes the services.

Service name	When to stop or start
Infor Framework Event Service	When you add, edit or delete configurations, or change which configurations are monitored, you might need to stop and restart these services so they recognize the changes. If you change any of this information for a site, you do not need to restart the TaskMan service; however, if you encounter problems, restarting the service might help: Forms Database Name, Intranet Name, Polling Interval, Maximum Concurrent Tasks, Maximum Concurrent Report Tasks, Report URL, TaskMan Path If you change any of this information, you might need to restart the replication services: the Intranet Name for a site, other non-descriptive information about the site or intranet, or the password for a user who is set up in the Sites or Sites/Entities form for use in non-transactional replication.
Infor Framework Replication Queue Listener	
Infor Framework Replicator	
Infor Framework TaskMan	
Infor Framework IDO Runtime Service	Stopping the IDO Runtime Service also stops all dependent services (Event, Inbound Bus, Replication Queue Listener, Replicator, and TaskMan). When restarting the services manually, start the IDO Runtime Service first.
Infor Framework Inbound Bus Service	This service is not affected by configuration changes. The Inbound Bus Service now looks at the same configuration list as the Replicator Service.

Merging existing databases into an All-in-One database

This section provides information about merging a set of individual databases into a single All-in-One database, using the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Merge Existing Databases into All-in-One** option.

This is not an option that you can use for the Mongoose initial installation and configuration, because you do not yet have individual databases to merge. This option is most useful when you have a legacy system that you are updating, in which you installed Mongoose using a traditional setup where the Applications database, the Forms database, the Objects database, and the Templates database were all installed in separate databases.

When you reach this page of the wizard, if you have no sets of databases that you can merge, the **Select Configurations** list is empty. The wizard displays only those configurations that use an individual-database setup.

For each configuration that is listed, when you select the configuration, the Applications, Forms, Objects, and Templates databases is combined into the Applications database. The configuration is then updated to point all database types to that Applications database, which now becomes an All-in-One database.

During the process, if any of the Forms, Objects, or Templates database objects have been modified with changes not included in the database creation zip files, those changes are lost and must be reapplied.

Configuring the Report Server (SSRS reports)

This section provides information about configuring the **Reporting Services (SSRS)** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Reporting Services (SSRS)** option.

Note: This option applies only to SSRS reports and is now required only if you are using SQL Server Reporting Service (SSRS) to produce reports. SSRS reports are now deprecated in Mongoose, so you should use this option only for legacy systems still using SSRS reports.

To configure a report server for use with SSRS reports, you must provide this information:

- **Report Server URL** - In URL format, specify the name of the server to be used for processing reports, and the directory in which the report processing . This is the server on which you installed SSRS.
- **Report Server Parent Folder** - Specify the name of the parent folder for all your report outputs. This is the subfolder where you want to put Mongoose SSRS reports.
- **Reports Directory** - Specify the folder on the local disk in which the .rdl report files are located. This can be used to indicate the report files you want to load.
- **Configure IDO Based Reporting** - This setting is used to load the DLLs and settings that enable you to do IDO-based reports in SSRS.
- **Configure Visual Studio Reporting** - This check box instructs the system to use local installations of Visual Studio when editing reports.

Configuring the Smart Client Deployment server

This section provides information about configuring the **Smart Client Deployment** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Smart Client Deployment** option.

The Smart Client Deployment server hosts the components that end users need to install Mongoose clients on their computers. Mongoose uses an IIS application to host the server and its components.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.
We recommend that you accept the default value. For information about the other options, consult the IIS application pool information on the Internet.
- **IIS Site** - Select the site to assign the IIS application to.

We recommend that you accept the default value, but you can create your own IIS site and use that instead.

- **IIS Security Username** - Specify the name of a user who has access to the `Program Files` directory and authorization to work with IIS applications.

This field defaults to the username you are currently logged in as. If you want, you can specify a different IIS user account.

- **IIS Security Password** - Provide the password of the user specified in the **IIS Security Username** field.
- **ClickOnce Web Server** - Specify the name of the web server that is to host the ClickOnce smart client deployment functionality. You can specify a web server alias for this name.

By default, this field contains the name of the web server you are signed in on, because the wizard assumes that is where you plan to deploy the smart client software from. If necessary, you can change it to a different web server, though, and the resulting **Client Deploy URL** reflects the change.

- **Use HTTPS** - When selected, this option changes the first part of the **Client Deploy URL** to HTTPS (instead of HTTP).

Note: If you select this option, you must enable the default port for HTTPS (443). If you are using HTTP, then enable port 80, the default for HTTP.

Select this option only if your website is set to use HTTPS. Otherwise, you will get errors.

- **Set Remember Config Group Option** - When selected, this option instructs the system to "remember" what configuration group the client is assigned to when it is installed. Then, when the user logs in, the **Sign In** dialog box displays only the configurations assigned to that configuration group.

When this option is cleared, any user who signs in with this client can see all the configurations that exist on the web server.

For more information about configuration groups, see the Configuration Manager online help.

- **Smart Client Name** - Specify the name for the smart client as it will appear on the desktop shortcut and other application shortcuts, as well as in the **Add or Remove Programs** list in the Windows Control Panel.

Keep in mind that if you later change this name (for example, for an update), Windows will no longer recognize the old name, and customers will not receive your updates. Instead, they are required to do a fresh installation of the application.

- **Use Remote IDO Runtime** - When selected, this option instructs the system to use the IDO Runtime Service on a different web server than where the smart client is installed.

Note: This is required for a DMZ setup, where you want to have customers download the smart client from a public-facing server but have the installed client use the IDO Runtime Service on the Web Server where your Application Server is located.

If you are not creating a DMZ setup, you could theoretically use this option to have multiple clients in different locations that all point to a master configuration list on a single server.

If you select this option, the wizard displays the base URL for the web server in the field below this check box. You must supply the name of the web server to use for the IDO Runtime Service in that part of the URL marked `<webserver>`.

- **Client Deploy URL** - This field displays the URL to distribute to your users, from which they can download and install the smart client. You should make a note of this somewhere (in Notepad, for instance) and save it for future reference when distributing it to your users.
Note: This URL is read-only. If you want to change it, you must use the value in the field where the part you want to change is specified.
- **Custom Certificate Path** - Optionally, use this field to specify the path to the directory where an Authenticode certificate resides. If necessary, you can use the ellipses (...) button to browse for the correct path.
This option can be useful when you have your own trusted code-signing certificate that you want to use when your end users install Mongoose.
- **Custom Certificate Password** - If a password is required for your custom certificate to be applied, specify that password here.

Configuring the Token Authentication Web Service

This section provides information about configuring the **Token Authentication Web Service** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Token Authentication Web Service** option.

One option to increase security and control access to your system is to use a token-based authentication service in tandem with the normal application login credentials. With this type of system, users must enter not only their user IDs and passwords, but also a second password, or passcode, obtained from a hardware or software token.

The **Token Authentication Web Service** is required if you are using such a dual authentication system for end user logins. This service uses an IIS application as a host.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.
We recommend that you accept the default value. For information about the other options, consult the IIS application pool information on the Internet.
- **IIS Site** - Select the site to assign the IIS application to.
We recommend that you accept the default value, but you can create your own IIS site and use that instead.
- **Embeddable URL Security (optional)** - Leave blank or provide a valid X-Frame-Options value.
This option is used to set the value for an X-Frame-Options header, which is used to prevent clickjacking attempts.
These are the options for values in this field:
 - To allow only the current website to frame content, leave this field blank, or set the value to **SAMEORIGIN**. **SAMEORIGIN** is the default value if this field is left blank.

- To allow only a single URI to frame the content, enter the URI in this field. This sets the URI as an **ALLOW-FROM** option.
- To prevent the use of content in all frames, set this field to **DENY**.

Note: Not all web browsers support these options. For more information, see topics related to X-Frame-Options on the Internet.

- **Content-Security-Policy (optional)** - Leave blank or provide a valid Content-Security-Policy (CSP).

This option is used to set the value for a Content-Security-Policy (CSP), which is used to prevent and mitigate clickjacking attempts, cross-site scripting, and other code injection attacks.

For examples of how to use this option, see the tooltip for this field.

Configuring translations

This section provides information about assigning languages to configurations, using the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Translations** option.

This is not an option that you can use for the Mongoose initial installation and configuration, because you do not yet have any configurations to which you can assign a language to use in the interface. So, before attempting to use this option in the wizard, do an initial pass with the wizard, create the configurations to which you want to assign language translations, and then run the wizard again for this option.

Once you have one or more configurations to work with, you can then use this page to select a configuration and then specify (from the drop-down list) the language to use in the interface for that configuration.

Note: This configuration applies only to the actual interface. To use the same language for the online help, you must configure that separately from within Mongoose.

Configuring the Web Client option

This section provides information about configuring the **Web Client** option in the **Infor Mongoose Configuration Wizard**. We assume that you have already launched the wizard, selected the **Advanced Configuration** option and then selected the **Web Client** option.

The **Web Client** allows users to access your Mongoose-based application from a web browser. Although the web client has a few limitations, it is the recommended way for users to access the app. This service uses an IIS application as a host.

To configure the IIS application for this option, provide this information:

- **IIS Application Name** - Provide a name for the IIS application.
We recommend that you accept the default value.
- **IIS Application Pool** - Select the application pool where the IIS application is to be created.

We recommend that you accept the default value. For information about the other options, consult the IIS application pool information on the Internet.

- **IIS Site** - Select the site to assign the IIS application to.

We recommend that you accept the default value, but you can create your own IIS site and use that instead.

- **Embeddable URL Security (optional)** - Leave blank or provide a valid X-Frame-Options value.

This option is used to set the value for an X-Frame-Options header, which is used to prevent clickjacking attempts.

These are the options for values in this field:

- To allow only the current website to frame content, leave this field blank, or set the value to **SAMEORIGIN**. **SAMEORIGIN** is the default value if this field is left blank.
- To allow only a single URI to frame the content, enter the URI in this field. This sets the URI as an **ALLOW-FROM** option.
- To prevent the use of content in all frames, set this field to **DENY**.

Note: Not all web browsers support these options. For more information, see topics related to X-Frame-Options on the Internet.

- **Content-Security-Policy (optional)** - Leave blank or provide a valid Content-Security-Policy (CSP).

This option is used to set the value for a Content-Security-Policy (CSP), which is used to prevent and mitigate clickjacking attempts, cross-site scripting, and other code injection attacks.

For examples of how to use this option, see the tooltip for this field.

- **Session Timeout (minutes)** - Specify the amount of time, in minutes, that the web client can sit idle before the system terminates the session.
- **Execution Timeout (seconds)** - Specify the amount of time, in seconds, that the system is to wait before aborting the attempt to execute.
- **Require SSL** - When selected, the web client requires an SSL connection to function. Select this option only if you have specified HTTPS binding for your configuration.
- **Use Remote IDO Runtime** - When selected, this option instructs the system to use the IDO Runtime Service on a different web server than where the web client is installed.

This is required for a DMZ setup, where you want to have customers run the web client from a public-facing server but use the IDO Runtime Service on the Web Server where your Application Server is located.

If you are not creating a DMZ setup, you could theoretically use this option to have multiple clients in different locations that all point to a master configuration list on a single server.

If you select this option, the wizard displays the base URL for the web server in the field beside this check box. You must supply the name of the web server to use for the IDO Runtime Service in that part of the URL marked *<webserver>*.

- **Authentication Type** - From the drop-down list, select the type of authentication to use when logging in users. You have these options:
 - **Built-In Authentication** - When selected, users are prompted for their Mongoose username and password.
 - **IIS Authentication** - When selected, users are prompted for the IIS username and password that has been configured for them to access the web client.

These usernames and passwords are set up by a system/network administrator. The administrator must use the **Workstation Domain/ID** field on the **Users** form in Mongoose to map the IIS username to the Mongoose username.

- **Active Directory Federation Services (AD FS)** - When selected, users are prompted for the Windows Active Directory username and password to access the web client.

These usernames and passwords must be set up by a system/network administrator. The administrator must use the **Workstation Domain/ID** field on the **Users** form in Mongoose to map the Active Directory username to the Mongoose username.

If you choose this option, several more fields are displayed on the screen. They include these:

- **STS Server Name** - This is the server with AD FS / IFS that provides claims-based token management. This name is case sensitive. should be fully-qualified, and must match what is expected in the SSL web server certificate that resides on the STS server.
- **FederationMetadata.Xml Location**- This field is automatically populated after you provide the **STS Server Name**. The syntax is: `https://STSServerName/FolderLocation/FederationMetadata.xml`
- **Federation Service URL** - This field is automatically populated after you provide the **STS Server Name**. The syntax is: `https://STSServerName/adfs/ls`
- **Trust Server URL** - This field is automatically populated after you provide the **STS Server Name**. The syntax is: `https://STSServerName/adfs/services/trust`
- **STS Certification Thumbprint**- Do exactly what this point describes. This number DOES NOT come from IIS. This is the thumbprint property number of the token-signing certificate used within AD FS. You must copy that number and paste it into this field. To get the number, within AD FS, navigate to **Service > Certificates**. Double-click the token-signing certificate and then select **Thumbprint**. The number that appears for the thumbprint is the number you need to paste here. When you copy the number, there is a leading space. Delete that space after pasting it into this field.
- **Application URL** - Provide the application URL.

This name should be fully-qualified and must match what is expected in the SSL web server certificate. The server name part of this URL is case sensitive. This certificate resides on the STS server. Use this syntax: `https://utilityOrApplicationServername/WSWebClient/`

The server name part of this URL is case sensitive, and the URL must have the trailing forward slash (/) at the end.

You should make a note of this URL somewhere (in Notepad, for instance) and save it for future reference when distributing it to your users.

- **PingFederate** - When selected, users are prompted for the PingFederate username and password to access the web client.

If you select this option, you must create and then import an **sp.properties** file.

- To create the **sp.properties** file, click **CREATE FILE** and provide the requested information in the dialog box that opens. This information includes the **Application Name** (name of your Mongoose application); **Application Description**; and the **AppURL** [`http(s)://webServername/WSWebClient`]. Then click **CREATE SP FILE**.
- To import the **sp.properties** file after you create it, click **IMPORT FILE** and then use the **Open** dialog box to navigate to and select the **sp.properties** file you just created.

Note: You must have a valid thumbprint to import the file.

- **Infor Security Token Service (STS)** - When selected, users are not prompted for user login credentials, but are logged in using SSO (Single Sign On).

If you choose this option, several more fields are displayed on the screen. They include these:

- **Infor STS Server Name** - This is the server that provides claims-based token management. This name is case sensitive. should be fully-qualified, and must match what is expected in the SSL web server certificate that resides on the STS server.
- **Federation Metadata URL** - This field is automatically populated after you provide the **Infor STS Server Name**. The syntax is: `https://STSServerName/FolderLocation/FederationMetadata.xml`
- **Federation Service URL** - This field is automatically populated after you provide the **Infor STS Server Name**. The syntax is: `https://STSServerName/inforsts/infor/numericString/idp/wsFed`
- **Entity ID** - This field is automatically populated after you provide the **Infor STS Server Name**. The syntax is: `https://STSServerName/inforsts/infor/numericString`
- **Certificate Thumbprint**- Do exactly what this point describes. This number DOES NOT come from IIS. This is the thumbprint property number of the token-signing certificate used within STS. You must copy that number and paste it into this field. To get the number, within STS, navigate to **Service > Certificates**. Double-click the token-signing certificate and then select **Thumbprint**. The number that appears for the thumbprint is the number you need to paste here. When you copy the number, there is a leading space. Delete that space after pasting it into this field.
- **Application URL** - This field is populated automatically when you select the **Infor Security Token Service (STS)** option.

This name should be fully-qualified and must match what is expected in the SSL web server certificate. The server name part of this URL is case sensitive. This certificate resides on the STS server. Should you need to modify it, use this syntax: `https://applicationServername/WSWebClient/`

The server name part of this URL is case sensitive, and the URL must have the trailing forward slash (/) at the end.

You should make a note of this URL somewhere (in Notepad, for instance) and save it for future reference when distributing it to your users.

- **SET ALLOWED FILE TYPES** - Use this option to allow or restrict the file types that can be served up by the web server. You can allow all file types, allow a restricted list of file types, and add your own additional file types to that list.

When you click this button, a dialog box that allows you to specify which file types are allowed displays. You then have these options:

- By default, all file types are allowed. If this is what you want, do not change any settings in this dialog box and click **OK**.
- To restrict the file types to a pre-designated list of **Allowed File Types**, select the **Restrict File Types** option.

In this case, this list acts as a "white list" in which only the file types on this list can be used and are allowed by the web server.

We strongly recommend that you accept the file types in the **Allowed File Types** list. However, if you want to exclude one or more file types in the list, you can select the types to exclude and then click **REMOVE SELECTED**.

- If, in addition to the pre-designated file types, you have another file type that you would like to include on the **Allowed File Types** list, specify the file extension for that file type in the **Add additional file type** field and then click **ADD**.

When you are finished designating the file types to allow, click **OK**.

Using the Configuration Manager

To function, Infor Mongoose stores and uses specifications that define how an application works in conjunction with several different databases. These sets of specifications are called *configurations*.

A configuration encapsulates all the settings needed to access the databases required by a Mongoose-based application, Form Control, Service Configuration Manager, FormSync, and other framework utilities.

Before users other than the primary Administrator (or 'sa') can open your Mongoose-based applications or Form Control, you must have one or more configurations defined.

Generally, the **Infor Mongoose Configuration Wizard** is used to create the first configuration during the initial installation and configuration of Mongoose. That process was described in the previous two sections of this guide.

Note: As long as you keep the option selected in the **Configuration Wizard** to create a configuration, the first configuration is created during that process. If, however, you clear the option to create the configuration, you will need to use the **Configuration Manager** to create your first configuration. We do NOT recommend this approach.

A configuration consists of these constituents:

- Profiles for run-time application and forms databases (required for all users)
- A specified application (required for all users)
- A profile for an objects database (required for all users)
- A tools logon ID (optional, used only for vendor-level development work)
- Profiles for Form Control databases (optional, used only for vendor-level development work)
- A profile for a source control database (optional, used only for vendor-level form development work and for IDO development work)

For more information, and specific procedures to create and edit additional configurations, see the **Configuration Manager** online help.

Testing the client

During installation/initial configuration, a Windows client is installed on all application servers. The final step in the installation and configuration process is to test this client, to make sure it works properly.

- 1 Optionally, reboot the server before you test the client.
This ensures that all necessary Windows services are started.
- 2 Launch Mongoose.
If you selected the option to install a desktop shortcut, you can double-click that icon. If you did not, you can find a shortcut by navigating to the list of programs/apps on your system (depending on your operating system), and then click the icon for Infor Mongoose.
- 3 In the **User Name** field of the **Sign In** dialog box, enter **sa**.
The first time, and until you create additional user profiles, you must use the 'sa' user login, or another user ID that is already created in SQL Server. If you have not done this, you must use the **Configuration Manager** to create the 'sa' user account before you can sign in.
Note: You cannot, at this point, use the **Use Workstation Login** option.
- 4 Unless you created a password for the 'sa' (or other) authorized user, leave the **Password** field blank.
If you have created a password for the designated user, provide it here.
- 5 From the drop-down list, select the configuration to open.
At this point—if this is the first time you have tried to launch the client—you probably have only one configuration to choose from, the one you created as part of the installation/initial configuration process. If you did not create a configuration as part of the installation process, then you must create one in Configuration Manager before you can log in to Mongoose.
See [Using the Configuration Manager](#) on page 33.
- 6 Click **OK**.
- 7 Take a few moments to explore the Mongoose user interface (UI).
At a minimum, we recommend that you take a look at these features and options:
 - The menu bar, the **Help** menu in particular - The online help has information that can help you understand and know how to use virtually everything else in the UI.
 - The **User Preferences** option on the **View** menu - This is a good way to begin personalizing the UI to your tastes.
 - The **Form** menu - Check out some of the in-built forms.
 - The Design Mode icon on the button bar - If you are planning to do any kind of form or application development work, this is the place to start.

If you can successfully log in to both the Windows client and the web client, then the basic installation is considered successful.

Chapter 5: Setting up a Cloud Server

This type of setup is not currently a common one. It is intended to be used for multi-tenant cloud-specific setups. Essentially, it consists of a pared-down installation that includes fewer files, mostly for Internet security reasons.

If you are interested in pursuing this setup, contact your customer service representative.

Chapter 6: Setting Up the DMZ Server

When you want to set up Mongoose without exposing your Application Server directly to the Internet, and without needing to place a load balancer or other hardware between the Application Server and the Internet, consider installing Mongoose using a "DMZ Server" setup.

Note: A DMZ Server cannot be installed on the same server as the Application Server.

In a DMZ Server setup, the IDO Request Service service and the WSWebClient web application are installed on a machine without all the Application Server components (IDORuntime Service, TaskMan, and so on). This installation is then set up with connections to the Application Server.

When setting up a DMZ Server, use Secure Sockets Layer (SSL) to secure communications between the DMZ Server and the Application Server. This means that the DMZ Server must be set up as an HTTPS server.

Requirements for a DMZ Server

When setting up a DMZ Server installation, these are the requirements for the DMZ Server:

Note: These are in addition to the regular requirements for the Application Server.

Note: We do not require any special ports for the DMZ configuration. The server in the DMZ needs only HTTP/HTTPS access to the application server behind the firewall.

- You must have a server that uses one of these operating systems:
 - Windows Server 2012
 - Windows Server 2016
- You must have .NET Framework version 4.6.1 or later.
- In the Internet Information Services (IIS) Manager:
 - Make sure that the server is set up as an HTTPS server using SSL.
 - Enable Windows Authentication and Basic Authentication.
 - Install the Application Server role and all role services for this role.
 - Install the Web Server (IIS) role and all role services for this role except for the FTP Publishing Service.

The FTP Publishing Service is optional.

- You must have a supported internet browser.

These are the supported browsers:

- Internet Explorer versions 10 and 11

- Chrome
- Edge
- Safari
- Firefox

Note: While Firefox is supported in Mongoose and most Mongoose-based applications, it might not be in other Infor products you use in conjunction with Mongoose. For example, it is not supported in some IOS products, such as Infor Ming.le™.

- If you want to use AD FS to access your web client, you must:
 - Set the **Load User Profile** to **True** under **Process Model** options in IIS.
 - Download and install Windows Identity Foundation version 3.5.
See Microsoft's KB974405 for the download and instructions.
 - Configure Infor Federation Services (IFS).
For additional information, see the *Infor Operating Service Installation Guide* and the *Infor Operating Service Administration Guide*.

Installing components on the DMZ Server

A DMZ Server requires only some of the Mongoose requirements to be installed—only those required to be accessed directly from the Internet. The other components and services are all accessed via an SSL connection to the Application server.

To install the components required for a DMZ Server:

- 1 Download the Mongoose .iso file from the Download Center.
- 2 Find and double-click the setup.exe files in the .iso file.
Run this file as administrator.
- 3 In the **Infor Mongoose Installer** window that opens, select the **DMZ Server** option.
- 4 Click **NEXT**.
- 5 On the next page of the installer, click **Installer**.

The installer proceeds to install the basic components required for the DMZ Server.

When it is finished installing the basic components, the installer automatically launches the **Infor Mongoose Configuration Wizard**. Use this wizard to create the basic DMZ Server configuration.

At this point you have two options:

- **Express Configuration** - Use this option to have the **Infor Mongoose Configuration Wizard** create a basic default configuration.
See [Using the DMZ Express Configuration option](#) on page 38.
- **Advanced Configuration** - Use this option to exercise more explicit control over what options are configured and how they are configured.
See [Using the DMZ Advanced Configuration option](#) on page 38.

Using the DMZ Express Configuration option

Before you can use this procedure, you must run the **Infor Mongoose Installer** for the **DMZ Server** option. This must be done on a different server from the one on which the Application Server is installed.

This procedure assumes that you have already done that and that you are looking at the first page of the **Infor Mongoose Configuration Wizard**.

- 1 In the **Express Configuration** section, verify that the **Windows User Name** field displays the correct user name.
- 2 In the **Windows Password** field, enter the password for the user specified in the **Windows User Name** field.
- 3 Click **NEXT**.
The wizard displays a summary of what actions and components will be configured.
- 4 Click **COMMIT**.

The wizard proceeds to create the required databases, tables, scripts, stored procedures, and other elements required for a DMZ Server configuration.

When finished, the wizard displays a log of all the actions taken to create the configuration. You can save this log as a *.txt file (**SAVE LOG**).

At this point, you have three options:

- Use the **Configuration Manager** to continue/finish setting up your Mongoose configuration. Launch the **Configuration Manager** by clicking **CONFIG MANAGER**. You use the **Configuration Manager** to create configurations that specify the databases you want to access for your applications.
- To open the **Service Configuration Manager**, click **SERVICE MANAGER**.
The **Service Configuration Manager** is used to configure the Windows services used by Mongoose and its utilities. In most cases, you will not need to use the **Service Configuration Manager** until later, when you create additional configurations.
- To close the **Configuration Wizard** without taking any further action at this time, click **FINISH**.

To finish configuring your Mongoose system, you must create/modify your configuration and applications. See the **Configuration Manager** help.

Using the DMZ Advanced Configuration option

Before you can use this procedure, you must run the Infor Mongoose Installer for the **DMZ Server** option. This must be done on a different server from the one on which the Application Server is installed.

This procedure assumes that you have already done that and that you are looking at the first page of the **Infor Mongoose Configuration Wizard**.

- 1 Select the **Advanced Configuration** option.
- 2 Click **NEXT**.
The next page of the wizard displays a list of both the required and optional components to install.
- 3 On the next page, select the components you want to include in your configuration.

Note: The rest of this procedure assumes that you have selected all options. Each component is configured on succeeding pages of the wizard. The pages for options that you do not select are not presented later by the wizard.

To see a brief description of each component (at the bottom of the page), select that component. For more detailed descriptions, see [Options for DMZ Server installations](#) on page 61.

4 Click **NEXT**.

Assuming you selected the **Application Search Service for Office** option, the wizard displays the page to configure and use this option.

See [Configuring the option to search for Office applications](#) on page 18.

5 Verify that the name of your application server is correct.

6 Click **NEXT**.

Assuming you selected the **IDO Request Web Service** option, the wizard displays the page to configure this option.

See [Configuring the IDO Request Web Service](#) on page 22.

7 Click **NEXT**.

Assuming you selected the **Inbound Queue Web Service** option, the wizard displays the page to configure this option.

See [Configuring the Inbound Queue Web Service](#) on page 23.

8 Click **NEXT**.

Assuming you selected the **Smart Client Deployment** option, the wizard displays the page to specify the server that is to serve as the host for Windows (Smart) client deployments. It also specifies settings to configure the smart client deployment.

See [Configuring the Smart Client Deployment server](#) on page 26.

9 Click **NEXT**.

Assuming you selected the **Token Authentication Web Service** option, the wizard displays the page to specify the IIS application that is to host the Token Authentication functions.

See [Configuring the Token Authentication Web Service](#) on page 28.

10 Assuming you selected the Web Client option, the wizard displays the page to configure the way the web client behaves.

See [Configuring the Web Client option](#) on page 29.

11 Click **NEXT**.

The wizard displays a page that summarizes your selections and describes what will be processed when you click **COMMIT**. We recommend that you take a moment to review this summary before proceeding.

12 When you are satisfied that your selections are correct, click **COMMIT**.

The wizard proceeds to process your selections.

When it is finished, the wizard displays a summary of what was done and whether the installation was successful. Any component that failed installation is listed and the cause of the failure is described in a log. You can save this log for analysis (**SAVE LOG**).

At this point, you have these options:

- To create and edit configurations, you can click **CONFIG MANAGER**. This launches the **Configuration Manager** utility.
- To manage the Infor Framework services, click **SERVICE MANAGER**. This launches the **Service Configuration Manager** utility.
Note: If you have not yet created any Mongoose configurations, there is no point in starting up the **Service Configuration Manager**.
- To close the **Infor Mongoose Configuration Wizard**, click **FINISH**.

Testing the DMZ Server

After you install and configure the DMZ Server, test it to make sure it is configured properly, before you distribute access to it.

- 1 On the DMZ Server, open a web browser.
- 2 In the **Address** field, enter the web client URL that you created in the Configuration Wizard and made note of.

This URL uses this format:

```
https://<webServer>/WSWebClient/Default.aspx
```

where <webServer> is the name of the Application Server you want to access.

- 3 Verify that the web client launches properly and accesses the correct configuration.
- 4 Close the tab that displays the web client.
- 5 In the browser **Address** field, enter the Windows (Smart) client URL that you created in the Configuration Wizard and made note of.

This URL uses this format:

```
https://<webServer>/ClientDeploy/Mongoose.application
```

where <webServer> is the name of the Application Server you want to access.

If you are using Internet Explorer, the Windows (Smart) client downloads and launches automatically. If you are using another browser (such as Chrome), you might first be required to download the application and then double-click it to launch the client.

- 6 Verify that the Windows client launches properly and accesses the correct configuration.

Chapter 7: Upgrading Mongoose

This chapter details how to upgrade from one version of Mongoose to another version of Mongoose.

Note: Before performing an upgrade, make sure to back up your database. The upgrade process should not result in a loss of data, but we still highly recommend that you set up a separate test environment on which to perform the upgrade. The test environment should mirror your live environment. Use the test environment to work out any issues and to time the length of the upgrade. Once the upgrade is complete and tested on the test environment, you can perform the upgrade on your production environment.

Requirements

- Back up your databases before applying the upgrade. We cannot be held accountable for any lost data.
- Check the installation guide for the upgrade/update, and verify that you have the minimum requirements for that upgrade/update.
- Prior to the upgrade, disable audit logging on the **Process Defaults** form. This is done by setting the **Enable audit logging** process default to 0 (zero).
Once the upgrade is complete, you can re-enable audit logging on the **Process Defaults** form, which will regenerate all affected triggers. Re-enable it by setting the **Enable audit logging** process default back to 1 (one).
- Verify that you have your Mongoose license available, as licensing must be reapplied after the upgrade.
- Have any add-on packages available for installation, as add-on packages must be reinstalled after the upgrade.

Performing the upgrade

To perform an upgrade to the Mongoose software:

- 1 Read and understand all the requirements listed in the previous section.

The requirements and notes earlier in this chapter are very important. Do not proceed with the upgrade before you have read and are sure you have complied with them all.

- 2 Back up your Mongoose application databases.
- 3 Make sure that all users are logged out of the system.
- 4 Install the new version of the Mongoose software.

This means, at a minimum, a working version that includes the database server piece and the Application server. We recommend you set up a test environment that mirrors your live environment.

- 5 Run the Infor Mongoose Configuration Wizard to update service and option settings.

Note: You can run the Configuration Wizard for any combination of settings and options you want; but you do not necessarily have to create additional databases or configurations. At a minimum, you can update only the WIndows services and the client configurations, by clearing the **Make new databases** option on the first page of the wizard.

- 6 When the Configuration Wizard finishes, run the Service Configuration Manager by clicking the **SERVICE MANAGER** button.

- 7 In the list of Infor apps and utilities, locate the **Infor Database Upgrade** utility and run it as administrator.

This upgrade wizard is required to ensure that any changes to the schema, scripts, stored procedures, and other elements for databases in the upgrade are applied to the original databases for your installation.

- a When the **Infor Upgrade Wizard** launches, on the first page, verify the **Infor Directory**.

Normally, and if you used the default installation path when you first installed Mongoose, the correct directory is displayed by default.

- b Click **NEXT**.

The wizard displays a page in which you can select a **Configuration** to upgrade. This assumes that you have at least one configuration from which to choose.

Note: If this field is active, it displays only configurations that reside on this server. If you do not have a Mongoose configuration on this server, or if you are running the wizard on a dedicated database server, the **Configuration** field is disabled.

- c From the drop-down list, select the configuration to upgrade.

Note: If you have multiple configurations, you must run the Database Upgrade Wizard for each configuration.

- d Click **NEXT**.

The wizard displays the **Select Application Database or All-in-One Database** page, on which you have several options. You can select any or all of these options:

- **Upgrade Application or All-in-One Database** - Selected by default, we recommend that you keep it selected. Otherwise, there is no real point to the upgrade.

Note: If you are upgrading an All-in-One database, this is the only additional option (besides the **Configuration**) that you can select.

- **Merge Four DBs to All-in-One DB** - This option makes sense only if your original application installation consists of four separate databases (Applications, Forms, Objects, Templates). If you select this option, the wizard merges the original four databases into a single All-in-One database.

If you select this option, you must provide the additional information about the original databases and the designation for the new database.

- **Configure Trustworthy and other privileged actions** - Use this option to maintain legacy upgrade actions in cases where Mongoose-based applications need it. These actions

cannot be done in the cloud, as they require SQL instance-wide rights. So, these are not run by default. Mongoose itself doesn't require any of these actions. It could be that you have CLR code in your application and your databases have moved servers before the upgrade. Hence, "Trustworthy" would need to be reset.

- **Master Application Database Reference Required (i.e., this is a subordinate site)** - Use this option to signify which database is the master database.

Note: This option is applicable in situations where you have a master database and one or more subordinate databases where tables are shared. If you happen to migrate one or both databases to new locations, then the internal links get broken. So, if this upgrade is being performed on a subordinate database, then you must first upgrade the master database, and then you can upgrade the subordinate database and include this option.

If you select this option, you must also provide the name of the **SQL Server** on which the master database resides and the name of the **Master Database**.

- e Click **NEXT**.

The next page of the wizard (**Select Forms Database**) allows you to designate which Forms Database (if you have more than one) to which the upgrade is to be applied.

If the original installation uses an All-in-One database, that is the **Database** name that displays by default.

If you have more than one forms database, you must designate which one to apply the upgrade to.

Note: If you have more than one forms database (as in a development environment where you are using Form Control), you must run this wizard again and apply the upgrade in turn to each forms database.

- f Click **NEXT**.

The next page of the wizard (**Select Templates Database**) allows you to designate which Templates Database (if you have more than one) to which the upgrade is to be applied.

If the original installation uses an All-in-One database, that is the **Database** name that displays by default.

If you have more than one templates database, you must designate which one to apply the upgrade to.

Note: If you have more than one templates database (as in a development environment), you must run this wizard again and apply the upgrade in turn to each templates database.

- g Click **NEXT**.

The next page of the wizard (**Select Objects Database**) allows you to designate which objects database (if you have more than one) to which the upgrade is to be applied.

If the original installation uses an All-in-One database, that is the **Database** name that displays by default.

If you have more than one objects database, you must designate which one to apply the upgrade to.

Note: If you have more than one objects database (as in a development environment), you must run this wizard again and apply the upgrade in turn to each objects database.

- h Click **NEXT**.

The wizard displays the **Review Changes** page. You should review the proposed changes before proceeding.

- i Optionally, if you want or need to perform the updates by means of a CLI (Command Line Interface), you can select the **MAKE BATCHFILE** option.
The MAKE BATCHFILE option generates a batch file that allows you to upgrade your databases from a CLI.
 - j When you are satisfied that the upgrade specifications are correct, click **COMMIT**.
- 8** When the upgrade is finished, review the log, especially if errors have occurred.
- 9** If you have other databases to upgrade, when the upgrade finishes, click **FINISH** and run the **Infor Database Upgrade Wizard** again until you have upgraded all applicable databases.
- Note:** If you are using an All-in-One database for which you also created a Form Control master database and a Form Control archive database, you must run the **Database Upgrade Wizard** again to upgrade each of them.
- 10** Once all logs are error-free, regenerate your objects database views from the **Configuration Manager** for configurations which have updated databases.
- Note:** If you provided a configuration name at the beginning of this procedure, the wizard performs this step for you. This step is required only if you did not designate a configuration to upgrade. To do this:
- a Launch the **Configuration Manager** utility for the application server you are upgrading.
 - b Select the configuration you are upgrading.
 - c Click **Edit**.
 - d Select the **Objects Metadata** tab.
 - e Click **Set Objects DB Specification**.
 - f Click **OK**.
- The **Configuration Manager** confirms that your objects database has been updated.
- g Click **OK**.
 - h In the **Edit Configuration** dialog box, again click **OK**.
 - i Close the **Configuration Manager**.
- 11** Use the Windows Administrative Tools, Services, to restart all of the Infor Framework Windows services.
- The system does not recognize the upgrades until these services have been restarted.

After all databases have been upgraded and any objects databases have been updated in the **Configuration Manager**, you must still run the **FormSync** utility before the upgrade can be considered complete.

Synchronizing the Forms databases

Before an upgrade can be considered complete, you must run the FormSync utility for all forms databases you upgraded. This is because the upgrade process itself updates the forms schema and database objects, but not the form objects.

You can use either the stand-alone FormSync utility or the **FormSync** form in Mongoose to do this.

When using FormSync, we recommend that you use:

- The **Temporary source tables** option, if using the stand-alone version.
- The **Separate source/target configurations** option, if using the form version.

See the online help for FormSync.

Post upgrade steps

After you complete an upgrade, there are a number of post-upgrade steps that you might or might not need to perform.

- (Required) Re-apply your license.
- If you use audit logging, re-enable audit logging on the **Process Defaults** form.
- If you have multiple Mongoose sites or any external applications, open the **Replication Management** form. Click **Regenerate Replication Triggers**.
- If you are in a multi-site environment, you must use the **Update _All Tables** form to repopulate tables. Open the **Update _All Tables** form. Execute Filter-in-Place to load the collection (all of the _all tables are selected by default). Click **Repopulate Tables**.

You can perform this step in a single-site environment too, but it is unnecessary.

- Recreate any background tasks that had a status of WAITING that you deleted.

Troubleshooting the upgrade

If you have modified the application database schema by adding new constraints or updating table definitions, you will most likely get an error when you run the upgrade. If initialization data has been updated, this could cause an error. We recommend that you run through a pilot upgrade on a test database to address possible issues. If schema or initialization data issues persist, check the Mongoose Knowledge Base, or contact your service representative.

Chapter 8: Post-configuration tasks

Once you have finished installing the Mongoose software and setting the basic configuration, there are some post-configuration tasks that you should consider doing:

Note: The tasks in this chapter are all, more or less, optional, though some are less optional than others, depending on the setup you are creating. Acquiring and applying a license, for example, is mandatory if you want to create user profiles and allow users access to the system. The Service Configuration Manager settings are mandatory whenever you create a new configuration. And the AD FS settings are required whenever you want to use AD FS for web client logins.

- Acquire and apply a license.

To allow other users (besides the 'sa' user) access to the Mongoose application, you must acquire and apply the necessary licenses. The information and instructions for doing this are in the *Infor Mongoose Licensing* guide.

- Update the **Service Configuration Manager** settings.

This includes configuring Mongoose monitor and handle Application Event System activity, Replication activity (usually for multi-site setups), and TaskMan settings.

These procedures must be done every time you create a new configuration.

See [Updating Service Configuration Manager settings](#) on page 47.

- Optionally, reconfigure the online help.

Once a configuration has been created and the initial configuration tasks completed, you should verify that the online help for Mongoose is working correctly.

See [Configuring the online help](#) on page 51.

- Configure AD FS for logins.

This is required only if you choose to use AD FS for web client logins.

See [Configuring AD FS](#) on page 53.

- Define your system printers.

See [Defining your printers](#) on page 55.

- Set up your system to print reports.

See [Setting up report printing](#) on page 56.

- Configure the system for email notifications for reports.

See [Configuring email notifications for reports](#) on page 56.

Updating Service Configuration Manager settings

When you add configurations with the **Configuration Manager**, you must update the **Service Configuration Manager** utility so that the new configurations are monitored by the Infor Framework services such as TaskMan, Replication, and the Event Service.

To update these services after adding a configuration:

- 1** Launch the **Service Configuration Manager**.
To launch this utility, you can click **SERVICE MANAGER** on the final page of the **Infor Mongoose Configuration Wizard**.
If the wizard has been closed, you can find the utility in the same directory where Mongoose is installed. Double-click the ServiceConfigManager.exe file.
- 2** On the **General** tab, optionally use the **Default Configuration** drop-down list to select a configuration to act as the default configuration for services.
Note: Currently, this default value is being used only by the Replication services.
- 3** Optionally, provide a different URL to a server you want to use as the Configuration Server.
The remaining fields on this tab provide information about what services are installed and where the configuration files reside.
The other three tabs in this utility allow you to add other configurations to be monitored and handled by the **Event Service**, the **Replication** services, and **TaskMan**, respectively.
- 4** Click **Save** and then click **Exit**.

Setting up application event monitoring

Use the **Event Service** tab on the **Service Configuration Monitor** to specify each of the configurations you want to monitor for Application Event System events.

Note: This service applies to application events only, not form events.

- 1** Launch the **Service Configuration Manager** as described in the previous section.
- 2** Select the **Event Service** tab.
- 3** Click **Add**.
- 4** In the **Event Service** dialog box, specify any or all of these settings:
 - **Configuration** - Select the configuration to be monitored.
 - **Sleep (seconds)** - Specify the number of seconds the system is to wait before doing another poll for events. If this field is left blank, the default value is 10 seconds.
For more information, see the online help for the **Service Configuration Manager**.
 - **Max. Threads** - Specify the maximum number of events that can run concurrently in the specified configuration. If this field is left blank, the default value is 5.
For more information, see the online help for the **Service Configuration Manager**.
 - **Orphan Checker Sleep (minutes)** - Specify the number of minutes that the Event Service is to wait between checks for orphaned Discover File actions.

This setting is used only after a Discover File event action has been executed. It determines the frequency at which the **EventActionState.LastWatchedDate** column of each handler that is adjourned on a Discover File event action (waiting for something to change on the file system) is checked against the **Orphan Checker Threshold**. For Orphan Checker usage, see the next entry in this list.

If this field is left blank, the default action is "Do not check for orphans."

- **Orphan Checker Threshold (days)** - Specify the number of days the system should allow an orphaned file to remain orphaned before freeing the Discover File event.

This setting is used only after a Discover File event action has been executed. It determines the age (in days), since its **EventActionState.LastWatchedDate** column was "touched" by the File Toucher; after which a Discover File event action (waiting for something to change on the file system) is freed for watching by another Event Service instance. This is used in case the watching Event Service crashes and can no longer watch the file.

If this field is left blank, the default action is "Do not check for orphans."

- **File Toucher (seconds)** - Specify the frequency, in seconds, that the File Toucher is updated, that is, checked for any changes in the file system.

This setting is used only after a Discover File event action has been executed. It determines the frequency at which the **EventActionState.LastWatchedDate** column is updated for any handlers that are adjourned on a Discover File event action (that is, waiting for something to change on the file system). For Orphan Checker usage, see the previous entry in this list.

If this field is left blank, the default setting is 0.1 (100 milliseconds). This is the only way to set this to less than one second.

- 5 Repeat these steps for all configurations you want the Event Service to monitor.

Typically, we recommend that you do this for all configurations.

- 6 To avoid losing your changes, click **Save**.

The system does not recognize the changes until you stop and restart the services.

Setting up Replication monitoring

Use the **Replication** tab on the **Service Configuration Manager** to specify each of the configurations you want to monitor for Replication activity.

- 1 Launch the **Service Configuration Manager**.
- 2 Select the **Replication** tab.
- 3 In the **Replicator/Inbound Bus Configurations** section, click **Add**.
- 4 In the **Edit Replicator Configuration** dialog box, select the configurations to monitor for the Replication service.
- 5 Optionally, to designate a configuration as the master site, select the **Master Site** option.
- 6 Repeat these steps for all configurations you want the Replicator and the Inbound Bus Service to monitor.

Typically, we recommend that you do this for all configurations.

- 7 Click **OK**.
- 8 In the **Message Editor** field, specify the name of the application that is launched to edit the XML when you click the **Edit** button on the **Message Detail** dialog boxes in the **Replication Management Tool**.
If necessary, use the **Browse** button to locate and select the application.
- 9 In the **Replication Queue Listener Servers** section, click **Add**.
- 10 In the **Edit Queue Server** dialog box, configure the settings for the Replication Queue Listener service. Use this table to specify the settings for each configuration:

Field/Option	Description
Queue Server/Default option	Use this field to set the path to the server that is to be used for queueing inbound and outbound replication documents. If the designated server is to be used as the default server for replication, select the Default option. Generally, by default, this field is set to <code>localhost\private\$</code> which uses the standard private message queues named inbound and outbound on the application server. However, if you have specified a Queue Server Name on the Intranets form, that name is used to build a path. For example, <code>appServer3\private\$MyQueues</code> results in the use of the queue names <code>MyQueues_inbound</code> and <code>MyQueues_outbound</code> .
Dead Messages Directory	Use this field to set the path to the location where invalid outbound messages or messages that have exceeded their retry attempt count are stored.
Use Default Directory	Use this option to tell the replication services to look for invalid outbound messages in the <code>OutboundDeadMessages</code> directory under the default replication directory. When this option is selected, the Dead Messages Directory field is then set to <code>replicationDirectory\Outbound-DeadMessages</code> , where <code>replicationDirectory</code> is the Replication Directory specified below.
Retry Queue Directory	This field specifies where outbound XML content that fails to post to an outbound URL goes. For example, the URL used for some integration action might be down temporarily. The system retries to send them at intervals. When the service starts up so that they can be tried again, the files are read from this folder.
Use Default Directory	When selected, this option tells the system to display the location of the Service Configuration Manager data file.

Field/Option	Description
Site Retry Delay (seconds)	Use this field to specify the number of seconds that are to pass between attempts to deliver queued messages to a site that is not responding. The default value, if this field is not set, is 300 (5 minutes), which is probably ideal for most multi-site setups. In some cases, a short retry delay can affect performance. For example, when the target site's web server is off the network, the POST of the message to the web server may take some time to fail, since it has to go through a fairly long timeout process. During that time, the replication service cannot process requests to any other sites. The Replicator service does not try to resend the entire queue, just the first message in the queue for the site. If the first message goes through, the service then sends the rest of the queue.
Failure Notification	Use these options to specify the method of notification used to indicate when a site is not available or a message is invalid. • None - No notification occurs. This is the default value. • Email - An email is automatically generated with an appropriate error message. This email is sent to the email address specified in the Email Address field. • Event - An Application Event System event is launched. Specify the name of the event in the Event Name field.
Notification Sender Address	Use this field to specify the email address to be used as the "sender" if failure notifications are sent by email or by the Application Event System. For email, this must be a valid Exchange account. For events, this must be a valid system user.
Replication Directory	Use this field to set the path to the folder containing replication subfolders and files.

- 11** Repeat these steps for all configurations you want the Replication Queue Listener Servers service to monitor.

Typically, we recommend that you do this for all configurations.

- 12** Click **OK**.

- 13** To avoid losing your changes, click **Save**.

The system does not recognize the changes until you stop and restart the services.

See

Setting up TaskMan monitoring

Use the **TaskMan** tab on the **Service Configuration Monitor** to set up the TaskMan service. Include entity application databases, because financial reports can be run on them.

To monitor each Applications database on which users will be executing reports, stored procedures, IDO methods, executables, or other background tasks:

- 1 Launch the **Service Configuration Manager**.
- 2 Select the **TaskMan** tab.
- 3 To select a configuration and optionally a DSN, click **Add**.
DSNs are only needed for some custom reports created in previous versions.
- 4 Repeat these steps until you have added all the configurations you want TaskMan to monitor.
Typically, we recommend that you do this for all configurations.
- 5 To avoid losing your changes, click **Save**.
The system does not recognize the changes until you stop and restart the services.
See

Configuring the online help

Mongoose has an extensive system of online help, and most of it can be accessed within the context of your need (that is, context-sensitively). We encourage you and your users to make use of it when working in/with Mongoose and other Mongoose-based applications.

By default, Mongoose is typically configured during installation to access the main online help from the Infor Documentation Central website (<https://docs.infor.com>). We recommend that you keep the default settings, because using the default settings ensures that you always have the latest help available. This is true for both cloud and on-premises installations.

In addition, the Infor Ming.le™ ICUA and context-sensitive Smart Help for Mongoose only work with the help on Infor Documentation Central.

Setting the base URL and start page

This procedure is for the configuration of the base help URL and start page for the Mongoose online help. It involves providing a base help URL and designating the help start page.

These values are pre-populated by default when you install Mongoose. So, in most cases, you should be able simply to verify that these values are correct for your system. This procedure is provided especially for those who want to update, install, and/or use the help files from an alternate location.

- 1 Launch the **Configuration Manager**, and select the **Applications** tab.
- 2 Select an existing application and then click **Edit**.

Note: You can also perform this procedure within the context of creating a new application. For ease of explanation in this procedure, we assume that you already have a configuration created, but the principles are the same.

- 3 In the **Edit Application** dialog box, select the **Options** tab.
- 4 In the **Help Information** section, **Help Server URL** field, enter: `http(s)://helpServerName/mg/10.x/`
where:
 - The first part can be either **http** or **https**, depending on whether your website has been created as an HTTP or HTTPS site; but it must match the designation for your web server.
Note: If using HTTP, then you should enable the port for HTTP (by default, 80). If using HTTPS, then you should enable the port for HTTPS (by default 443).
 - *helpServerName* is the name of the server from which the help files are to be accessed.
 - The final forward slash (/) is required.
- 5 Verify that the **Help Start Page** field value is set to **default.html**.
- 6 Verify that the **Subfolder** field value is set to **mongooseolh**.

Configuring the help middle segment

The middle segment of a help URL designates the language and culture of the set of help files to be accessed. By default, these values are set to **Language/en-US/**, but if you want to view the help in another language you can change these values. Then, if help for the designated culture exists, the help displays in that language. If not, the system reverts to U.S. English (en-US).

To modify this middle segment for an application:

- 1 Launch Mongoose and open the **Language IDs** form.
The middle segment of the help URL is controlled by the entry in the **Help Sub Dir** column. This column displays the name of the subdirectory on the web server that contains the online help for the selected language.
Generally, the **Help Sub Dir** values are the same as for the **Language ID**, which is the "*language-culture*" designation, when translated help files exist for a given language. But, by default, any language for which translations have not been provided set this field to U.S. English (en-US).
For example, the Mexican Spanish version of help files might reside in `C:\inetpub\wwwroot\productname\language\es-MX`.
If you want, you can change this value so that it points to a different language. So, for example, if you wanted the interface to display in French (France), but the help to display in Canadian French, you could change the **Help Sub Dir** for **fr-FR** to **fr-CA**.
- 2 Select the language entry for which you want to redirect the help middle segment.
- 3 In the **Help Sub Dir** column, enter the language-culture value for the language you want to use for the help.

Configuring help for on-premises use

In some cases, you might not want to access the online help from the Infor Documentation Central website. Instead, you might choose to store and use your help on-premises. This might be true for cases like these:

- Your company's firewall does not allow access to outside web sites.
- Your company is not automatically upgrading the application on a regular basis, and you prefer not to see information about new features that you don't yet have installed.

For those (and other similar) cases, we provide the option for you to download and access your help on-premises. Be aware that, if you select this option, this help is never automatically updated. You must manually download and install later versions as required.

If you choose to use a specific, on-premises version of the online help rather than the most current help on Infor Documentation Central, use this procedure:

- 1 Download the help to a local drive:
 - a From the Download Center on the Infor Support Portal, locate and download the help zip file for your version of Mongoose.
By convention, this file is named according to this format:
`mg_version_MongooseCoreHelp_yyyymmdd.zip`
where:
 - *version* is the release number for Mongoose.
 - *yyymmdd* is the date on which the zip file was published.
 - b Copy this help zip file to the application server desktop.
 - c On the application server, go to `C:/inetpub/wwwroot/`, and look for the `MG/10.x/en-us/mongooseolh` subfolder.
Note: If this path and subfolder do not exist, create them. If the `mongooseolh` subfolder exists, delete any files that might be in it.
 - d Unzip the help zip file directly into this subfolder.
Do not install it into any subfolder under that folder.
- 2 Configure the base help URL and start page/file.
See [Setting the base URL and start page](#) on page 51.
- 3 On a client, open your web browser, clear the cache, and allow popups.
- 4 In Mongoose, select **Help > Contents and Search**.

The help contents should display in the browser window.

Configuring AD FS

The information in this section is necessary only if you chose to use AD FS for the web client. If you did not choose to use AD FS for the web client, you can skip this topic.

For additional information about installation and set up of AD FS and IFS, see the *Infor Operating Service Installation Guide* and the *Infor Operating Service Administration Guide*. The administration guide includes, among other things, how to create an IFS security group to link an application to IFS users.

Creating AD FS relying party trust

Infor Federation Services (IFS) comes with a utility named IFSCONFIGURATION.exe. This is a .NET application that uses the WS-Discovery protocol to communicate with the IFS Configuration Service. Use this utility to set up both AD FS and IFS correctly with your application's setting. For this tool to work properly, the CA certificate must be imported into the Trusted Root Certification Authorities store for the computer account.

- 1 Run IFSCONFIGURATION.exe as administrator on your AD FS/IFS server.

This starts the discovery process.

- 2 Once the utility finds your installation of IFS, expand the **Application** tab and enter the **Name**, **Type**, **URL**, **Description**, and **Relying Party Identifier**.

The **URL** and **Relying Party Identifier** should be the same: the URL to the web client. What you enter into both of these fields must use this syntax: `https://serverName/WSWebClient/`

Note: Keep these facts in mind:

- HTTPS is required.
- The server name must match what was used in the SSL certificate. The name is case-sensitive.
- The specific page is dropped and the trailing forward slash (/) remains.

- 3 Click **Add/Replace**.

- 4 In the AD FS Management tool, open **Relying Party Trusts**.

- 5 Edit the **Identifier** and **Endpoint URL** to have the same value. The value must use this syntax: `https://utilityOrApplicationServerName/WSWebClient/`

The `utilityOrApplicationServerName` part of this URL is case sensitive, and the URL must have the forward slash (/) at the end.

- 6 To extend the session token lifetime (to avoid overly short session limitations), perform these steps:

- a Open a Windows PowerShell prompt.

- b Add the AD FS 2.0 snap-in to the Windows PowerShell session:

```
PS > Add-PSSnapin Microsoft.Adfs.PowerShell
```

- c Configure the relying party token lifetime:

```
PS > Get-ADFSRelyingPartyTrust -Name "relyingParty"
```

```
PS > Set-ADFSRelyingPartyTrust -Targetname "relyingParty" -TokenLifetime ##
```

where:

- `relyingParty` is the name of the relying party that you created.
- `##` is the maximum number of minutes to allow a session to continue.

Editing Infor Federations Services (IFS) application settings

- 1 On the server where you have IFS installed, launch IFS.
- 2 Verify that the **URL** and the **Relying Party Identifier** have the same value.
The value must follow this syntax: `https://utilityOrApplicationServerName/WSWebClient/`
Note: Keep these facts in mind:
 - HTTPS is required.
 - The server name must match what was used in the SSL certificate. The name is case-sensitive.
 - The specific page is dropped and the trailing forward slash (/) remains.
- 3 Verify that the application's status is **Active**.

Modifying Mongoose user account settings for AD FS

When using AD FS authentication, the Mongoose user account must be matched up with a domain account. To do this:

- 1 In Mongoose, open the **Users** form.
- 2 Verify that, for each user accessing Mongoose by means of AD FS, the value in the **User ID** field matches the value in the **Workstation Domain/ID** field.
Do not enter the domain prefix in the **Workstation Domain/ID** field, because this is already known; only the user's account ID is needed.
The first time a user logs into the Mongoose web client using AD FS, there are two sign-in dialog boxes: An AD FS sign-in page and then a Mongoose sign-in page.
- 3 To eliminate the need for the second login dialog box, perform these steps:
 - a Optionally, on the Mongoose **Sign In** dialog box, select the **Use Workstation Login** option.
Note: If you use this option, you do not provide a username or password. Skip to sub-step d.
 - b Provide the Mongoose username.
 - c Leave the **Password** field blank.
 - d Select the desired configuration.
 - e Click **Sign In**.

Defining your printers

Note: When you define the printers, you must be logged in as the same user under which Task Manager is running.

Before you can print reports, you must define, on the Application Server, each printer that will be used to print Mongoose reports. See your operating system documentation for more information about defining printers.

Once the printers are defined on the Application Server, use the **Printers** and **Report Options** forms to further configure and define them for your users. For more information, see the online help.

Setting up report printing

- 1 On the **Intranets** form, **Reports\TaskMan** tab, specify values for at least these fields:
 - **Intranet** - Provide a name for the intranet, or for test purposes, you can leave it at the default, **DEMO**.
 - **TaskMan Path** - (On the **General** tab) Enter this path: `\\appServerName\Framework` where *appServerName* is the name of your Application Server.
 - **Output** - Select the type of output to use for the "printed" (published) reports.
 - **Preview** - Select the type of output to use for the preview of the reports.
- 2 On the **Sites** form, specify values for these fields:
 - **Site** - Specify the name of the site.
Unless you are setting up a site in a multi-site setup, this is probably **DEFAULT**.
 - **Site Name** - Enter a name that matches the **Intranet** name you chose in the previous step.
 - Verify that the **Database Name** field displays the correct application database name.
 - Verify that the **Forms Database Name** field contains the name of the correct forms database.
- 3 Stop the Infor Framework IDO Runtime Service, which also shuts down dependent services.
- 4 Restart the services, starting with the Infor Framework IDO Runtime Service.

Configuring email notifications for reports

To configure TaskMan to send email notifications for reports:

- 1 Launch Mongoose, if it is not already running.
- 2 Open the **Sites** form and execute Filter-in-Place.
To execute Filter-in-Place, either click the Filter In Place icon on the icon bar, or select **Actions > Filter > Execute in Place (F4)**.
- 3 Click on the row in the grid that represents your site.
- 4 Select the **System Info** tab.
- 5 Right-click the **Intranet Name** field and select **Details...**
This launches the **Intranets** form.
- 6 On the Intranets form, select the **General** tab.
- 7 Make sure the **Send Email Notification** check box is selected.
- 8 Close both the **Sites** and the **Intranets** forms.
- 9 Set up each report where notifications are required.

Report outputs are specified using the **Background Task Devinitions** form and other forms. For the specific settings and procedures to set up report outputs, see the appropriate topics in the main online help.

Appendix A: Options for Advanced Configurations

The Advanced Configuration installation option in the Infor Mongoose Configuration Wizard provides two sets of components you can include in your configuration: **Required** and **Optional**. The tables in this appendix provide more detailed information about what is included in each component. The options available depend on what type of installation you are performing:

- For Application Server installations, see [Options for Application Server installations](#) on page 58.
- For DMZ Server installations, see [Options for DMZ Server installations](#) on page 61.

Options for Application Server installations

The Advanced Configuration installation option in the **Infor Mongoose Configuration Wizard** provides two sets of components you can include in your configuration: **Required** and **Optional**. These tables provide more detailed information about what is included in each component option for an Application Server installation:

Table 1: Required components

Component	Description
Databases	In the past, Mongoose-based applications normally required the use of at least four databases: the Application database, the Forms database, the Objects database, and the Templates database. These databases can now exist within a single database (an All-in-One configuration); or they can still reside as separate databases for each type. Only the Templates database is considered optional. Note: If you plan to do form and application development work in Mongoose, you will need four additional Forms databases: • A Master Forms database • A Master Form Templates database • An Archive Forms database • An Archive Templates database

Component	Description
Help files	The online help for Mongoose-based applications consists of two sets of help files: - The core Mongoose help set contains the main online documentation for Mongoose. It contains help files for both end users and for application and form developers. This help is no longer delivered with Mongoose, but rather exists on a central Infor documentation website. You can always access the current version of the core help from this website (https://docs.infor.com/mg/10.x/en-us/mongooseolh/default.html). If you do not want to access the core Mongoose help from the website, you can download the zip file from the Download center and install it locally. - The Mongoose utility help files are installed during a typical Mongoose installation. These help files contain information for the various Mongoose-related utilities (Configuration Manager, Service Configuration Manager, Form Control, Form Sync, and others. These files are available only from an on-premises installation. Multi-tenant cloud installations do not have access to the utilities, so they do not need to have these available.
IDO Request web service	This component provides access to the IDO Runtime Windows service by clients, such as the Windows ("smart") client, connecting via HTTP. This service provides a synchronous URL or HTTP endpoint for processing IDO request XML documents.
Inbound Queue web service	This component is used by the replication system to accept requests from sites on other intranets and allows for asynchronous replication between the sites.
Infor Windows services and replication	This component sets the account credentials for use by the Windows services and the replication system. These are the Windows services included: - Infor Framework Event Service - Infor Framework IDO Runtime Service - Infor Framework Inbound Bus Service - Infor Framework Replication Queue Listener - Infor Framework Replicator - Infor Framework Taskman
Smart client deployment	This component allows the server to act as a Windows ("smart") client deployment server, which means that users can connect to this server using a web browser and install the Windows client on their computers.
Web client	This component allows the server to act as a web client server. This means that you can access the configuration and application from a web browser, using a special URL.

Table 2: Optional components

Component	Description
Application Search Service for Office	This component allows you to exchange data between Mongoose and Microsoft Office applications. This is helpful if you want to synchronize calendar information, export data to Excel spreadsheets, and so on.
End-user/admin client shortcut	This component creates a shortcut for Mongoose on the desktop of Windows clients. Without this component, desktop shortcuts are not created when the client is installed.
Industry packs and localizations	This component is used to install industry packs and localizations. Mongoose does not currently have any industry packs or localization packages, so there is no point in selecting this option.
Link databases for multi-site use	If you plan to use a multi-site configuration, you must install this component, which allows the databases from different sites to be linked. Select this option only if you are creating and configuring a multi-site setup.
Merge existing databases into all-in-one	This component allows you to merge the databases in a multi-database configuration into a single All-in-One database. This is useful when you have already created a setup with the four individual required databases—Application, Forms, Objects, and Templates. It allows you to combine them into a single database, as in an All-in-One configuration. For obvious reasons, this is not an option to use for an initial installation and configuration.
Reporting services (SSRS)	This component is required only if you are using SQL Server Reporting Service (SSRS) to produce reports. SSRS reports are now deprecated, so you should use this option only for legacy systems still using SSRS reports.
Token Authentication web service	This component is required only if you are using a token authentication system for user logins. Token authentication is used in tandem with Mongoose authentication as a dual authentication system. For more information, see the online help for setting up token authentication.
Translations	This component is required only if you plan to use a language other than U.S. English when using the configuration. This option causes the entire user interface to display in the other language. Note: This configuration applies only to the actual interface. To use the same language for the online help, you must configure that separately from within Mongoose.

Options for DMZ Server installations

The Advanced Configuration installation option in the Infor Mongoose Configuration Wizard provides two sets of components you can include in your configuration: **Required** and **Optional**. These tables provide more detailed information about what is included in each component option for a DMZ Server installation:

Table 3: Required components

Component	Description
IDO Request Web Service	This component provides access to the IDO Runtime Windows service by clients, such as the Windows ("smart") client, connecting via HTTP. This service provides a synchronous URL or HTTP endpoint for processing IDO request XML documents.
Inbound Queue Web Service	This component is used by the Replication system to accept requests from sites on other intranets and allows for asynchronous replication between the sites.
Smart Client Deployment	This component allows the server to act as a Windows ("smart") client deployment server, which means that users can connect to this server using a web browser and install the Windows client on their computers.
Web Client	This component allows the server to act as a Web Client Server. This means that you can access the configuration and application from a web browser, using a special URL.

Table 4: Optional components

Component	Description
Application Search Service for Office	This component allows you to exchange data between Mongoose and Microsoft Office applications. This is helpful if you want to synchronize calendar information, export data to Excel spreadsheets, and so on.
Token Authentication Web Service	This component is required only if you are using a token authentication system for user logins. Token authentication is used in tandem with Mongoose authentication as a dual authentication system. For more information, see the online help for setting up token authentication.

Appendix B: Port configurations

This appendix addresses default port settings for Mongoose installations.

These are the default port settings for Mongoose installations:

Setting for:	Default port:	Comments
HTTPS	443	This setting is required for Mongoose to function. Optionally, depending on how your configurations are set up, you can use the HTTP port.
HTTP	80	Use this setting only if your configurations are set up to use HTTP instead of HTTPS.
SQL	1433	This setting is required for Mongoose to function.
SMTP	25, 465, and 587	These settings are required only if you are using SMTP features.
SFTP	22	This setting is required only if you are using SFTP features.
IDM	9443	This setting is required only if you are using IDM Reporting and File Storage features.

Appendix C: Supported languages

This appendix provides a list of the languages that are included with and supported "out of the box" with Mongoose.

Name of country	Language	ISO code
Argentina	Spanish (Argentinian)	es-AR 11274
Brazil	Portuguese	pt-BR 1046
Bulgaria	Bulgarian	bg-BG 1026
Canada	French (Canadian)	fr-CA 3084
Chile	Spanish (Chilean)	es-CL 13322
China	Chinese (Simplified)	zh-CN 2052
Columbia	Spanish (Columbian)	es-CO 9226
Czech Republic	Czech	cs-CZ 1029
Denmark	Danish	da-DK 1030
Ecuador	Spanish (Ecuadorian)	es-EC 12298
Finland	Finnish	fi-FL 1035
France	French (France)	fr-FR 1036
Germany	German	de-DE 1031
Hungary	Hungarian	hu-HU 1038
Israel	Hebrew	he-IL 1037
Italy	Italian	it-IT 1040
Japan	Japanese	ja-JP 1041
Korea, Republic of	Korean	ko-KR 1042
Mexico	Spanish (Mexican)	es-MX 2058
Netherlands	Dutch	nl-NL 1043
Norway	Norwegian (Bokmal)	nb-NO 1044
Poland	Polish	pl-PL 1045
Portugal	Portuguese (Portugal)	pt-PT 2070

Name of country	Language	ISO code
Romania	Romanian	ro-RO 1048
Russian Federation	Russian	ru-RU 1049
Saudi Arabia	Arabic	ar-SA 1025
Slovenia	Slovenian	sl-SI 1066
Spain	Spanish (Spain)	es-ES 1034
Sweden	Swedish	sw-SE 1053
Thailand	Thai	th-TH 1054
Turkey	Turkish	tr-TR 1055
United States	English (US)	en-US 1033
Venezuela	Spanish (Venezuelan)	es-VE 8202
Vietnam	Vietnamese	vi-VN 1066