

Homework 3 - Integer Programming

Adv. Analytics and Metaheuristics

Daniel Carpenter and Iker Zarandona

March 2022

Contents

1 - Problem 1	2
1.1 Mathematical Formulation	2
1.2 Code and Output	4
2 - Problem 2	6
2.1 Mathematical Formulation (Part a)	6
2.2 Code and Output (Part a)	8
2.3 Problem 2 b	10
2.4 Code and Output (Part b)	10
3 - Problem 3	12
3.1 Mathematical Formulation	12
3.2 Code and Output	15

1 - Problem 1

1.1 Mathematical Formulation

1.1.1 Sets

Set Name	Description
<i>GENERATORS</i>	Set of generators i that can be used (A,B,C)
<i>PERIODS</i>	2 possible periods p (1, 2) in the production day

1.1.2 Parameters

Parameter Name	Description
S_i	Fixed cost to start a generator ($i \in GENERATORS$) in the entire day
F_i	Fixed cost to operate a generator ($i \in GENERATORS$) in any period
C_i	Variable cost per megawatt to operator a generator ($i \in GENERATORS$) in any period
U_i	Max. megawatts generated for generator ($i \in GENERATORS$) in any period
$demand_p$	Total demanded megawatts for period ($p \in PERIODS$)
M	Large constant to map watts used by each generator ($i \in GENERATORS$)

1.1.3 Decision Variables

Variable Name	Description
$watts_{i,p}$	<i>Integer variable:</i> Number of watts to produce per generator ($i \in GENERATORS$) per period ($p \in PERIODS$)
$x_{i,p}$	<i>Binary variable:</i> 1 if a generator ($i \in GENERATORS$) is in period p ($p \in PERIODS$), 0 if not turned on at all
y_i	<i>Binary variable:</i> 1 if a generator ($i \in GENERATORS$) is used, 0 if not turned on at all

1.1.4 Objective Function

$$\text{minimize cost : } \sum_{i \in GENERATORS} \left((\sum_{p \in PERIODS} (watts_{i,p}) \times C_i) + (F_i \times \sum_{p \in PERIODS} x_{i,p}) + (S_i \times y_i) \right)$$

1.1.5 Constraints

C1: For each period, meet the demanded megawatts

$$\text{requiredWatts : } \sum_{i \in GENERATORS} (watts_{i,p}) = demand_p, \forall p \in PERIODS$$

C2: For each generator, don't surpass the allowable megawatts

$$\text{upperBound : } \sum_{p \in PERIODS} (watts_{i,p}) \leq U_i, \forall i \in GENERATORS$$

C3: For each generator, map decision variables together to account for the fixed costs in a given day S_i

$$\text{mapVars : } \sum_{p \in PERIODS} (watts_{i,p}) \leq M_i \times y_i, \forall i \in GENERATORS$$

C4: For each generator and period, map decision variables y and $watts$ together to account for the fixed costs in a per period p

$$\text{mapVars2 : } watts_{i,p} \leq M_i \times x_{i,p}, \forall i \in GENERATORS, p \in PERIODS$$

C5 Non-negativity or Binary restraints of decision variables

$$watts_{i,p} \geq 0$$

$$x_{i,p}, y_i \in (0, 1)$$

1.2 Code and Output

1.2.1 Code

```
F:\group23_HW3_p1.mod X
C:\Users\danielcarpenter>OneDrive - the Chidlaw Nation\Documents>GitHub>OU-DSA>Metaheuristics>03 - Homework>HW 03>AMPL Mod
1 # Homework 3 - Integer Programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarandona
4 # March 2022
5 # Problem 1
6
7 reset; # Reset globals
8 options solver cplex; # Using cplex for simplex alg
9
10 # SETS =====
11 set GENERATORS; # Set of generators to use
12 set PERIODS; # Periods in the day
13
14 # PARAMETERS =====
15 param S (GENERATORS) >= 0; # Fixed cost to start
16 param F (GENERATORS) >= 0; # Fixed cost to operate
17 param C (GENERATORS) >= 0; # Variable cost per megawatt
18 param U (GENERATORS) >= 0; # Upper bound on megawatts in a day
19 param M (GENERATORS) >= 0; # Map decision variables
20 param demand (PERIODS) >= 0; # Megawatts required per period
21
22 # DECISION VARIABLES =====
23 var watts {GENERATORS, PERIODS} >= 0 integer; # Megawatts to use
24 var x {GENERATORS, PERIODS} binary; # Map to watts for fixed daily costs
25 var y {GENERATORS} binary; # Map to watts for fixed daily costs
26
27 # OBJECTIVE FUNCTION =====
28 minimize cost:
29 (sum{i in GENERATORS} (sum{p in PERIODS} watts[i,p])*C[i])
30 + (sum{i in GENERATORS} F[i]*sum{p in PERIODS} x[i,p])
31 + (sum{i in GENERATORS} S[i]*y[i]);
32
33 # CONSTRAINTS =====
34
35 # C1: For each period, meet the demanded megawatts
36 subject to requiredWatts {p in PERIODS}:
37 (sum{i in GENERATORS} watts[i,p]) = demand[p];
38
39 # C2: For each generator, don't surpass the allowable megawatts
40 subject to upperBound {i in GENERATORS}:
41 (sum{p in PERIODS} watts[i,p]) <= U[i];
42
43 # C3: For each generator, map decision variables together to account for the
44 fixed costs in a given day S1
45 subject to mapVars {i in GENERATORS}:
46 (sum{p in PERIODS} watts[i,p]) <= M[i] * y[i];
47
48 # C4: For each generator and period, map decision variables y and watts together
49 to account for the fixed costs in a per period p
50 subject to mapVars2 {i in GENERATORS, p in PERIODS}:
51 watts[i,p] <= M[i] * x[i,p];
52
53 # CONTROLS =====
54 data group23_HW3_p1.dat;
55 solve;
56
57 print;
58 print "Which generators are used?";
59 display y;
60
61 print "Which periods were the generators used?";
62 display x;
63
64 print "Optimal Amount of Megawatts for each generator and period:";
65 display watts;
66
```

```
F:\group23_HW3_p1.dat X
C:\Users\danielcarpenter>OneDrive - the Chidlaw Nation\Documents>GitHub>OU-DSA>Metaheuristics>03 - Homework>HW 03>AMPL Mod
1 # Homework 3 - Integer Programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarandona
4 # March 2022
5 # Problem 1
6
7 # SETS =====
8 set GENERATORS := A B C; # Set of generators to use
9 set PERIODS := 1 2; # Periods in the day
10
11 # PARAMETERS =====
12
13 # S: Fixed cost to start a generator (i in GENERATORS) in the entire day
14 # F: Fixed cost to operate a generator (i in GENERATORS) in any period
15 # C: Variable cost per megawatt to operate a generator (i in GENERATORS) in any period
16 # U: Max. megawatts generated for generator (i in GENERATORS) in any period
17 # M: Value to map watts used by each generator (i in GENERATORS)
18 # M: Set to be slightly over the max megawatts per day
19 param: S F C U M :=
20 A 3000 700 5.00 2100 2200
21 B 2000 500 4.00 1800 1900
22 C 1000 900 7.00 3000 3100
23 ;
24
25 # Total demanded megawatts for period (p in PERIODS)
26 param demand :=
27 1 2900
28 2 3900
29 ;
```

1.2.2 Output

```
ampl: model 'C:\Users\daniel.carpenter\OneDrive - the Chickasaw
CPLEX 20.1.0.0: optimal integer solution; objective 46100
7 MIP simplex iterations
0 branch-and-bound nodes

which generators are used?
y [*] :=
A 1
B 1
C 1
;

which periods were the generators used?
x :=
A 1 0
A 2 1
B 1 0
B 2 1
C 1 1
C 2 0
;

Optimal Amount of Megawatts for each generator and period:
watts :=
A 1 0
A 2 2100
B 1 0
B 2 1800
C 1 2900
C 2 0
;
```

1.2.2.1 Analysis of the Output

- The minimized cost is \$46,100
- Generator A , B , and C run
- Generator C runs in period 1. Generator A and B run in period 2
- Generator A produces 2,100 megawatts in total
- Generator B produces 1,800 megawatts in total
- Generator C produces 2,900 megawatts in total

2 - Problem 2

2.1 Mathematical Formulation (Part a)

2.1.1 Sets

Set Name	Description
<i>PRODUCTS</i>	5 types of landscaping and construction products (e.g., cement, sand, etc.) labeled product (p) A, B, C, D , and E
<i>SILOS</i>	8 different silos s that each product must be stored in ($1, 2, \dots, 8$)

2.1.2 Parameters

Parameter Name	Description
$cost_{s,p}$	Cost of storing <i>one ton</i> of product $p \in PRODUCTS$ in silo $s \in SILOS$
$supply_p$	Total supply <i>in tons</i> available of product $p \in PRODUCTS$
$capacity_s$	Total capacity <i>in tons</i> of silo $s \in SILOS$. Can store products.
M	Variable to map <i>decision variable</i> $tonsOfProduct_{p,s}$ to $isStored_{p,s}$. Uses big M method.

2.1.3 Decision Variables

Variable Name	Description
$tonsOfProduct_{p,s}$	<i>Tons</i> of product $p \in PRODUCTS$ to store in silo $s \in SILOS$. Non-negative.
$isStored_{p,s}$	<i>Binary variable</i> indicating if product $p \in PRODUCTS$ is stored in silo $s \in SILOS$.

2.1.4 Objective Function

$$\text{minimize } costOfStorage : \sum_{p \in PRODUCTS} \sum_{s \in SILOS} tonsOfProduct_{p,s} \times cost_{p,s}$$

2.1.5 Constraints

C1: For each silo s , the *tons* of the supplied product p must be less than or equal to the capacity limit of silo s

$$meetCapacity : \sum_{p \in PRODUCTS} tonsOfProduct_{p,s} \leq capacity_s, \forall s \in SILOS$$

C2: For each product p , must use all of the total product that is available

$$useAllProduct : \sum_{s \in SILOS} tonsOfProduct_{p,s} = supply_p, \forall p \in PRODUCTS$$

C3: For each silo s and product p ,

$$oneProductInSilo : \sum_{p \in PRODUCTS} isStored_{p,s} = 1, \forall s \in SILOS$$

C4: Map the decision variables together using the Big M method

$$mapVars : tonsOfProduct_{p,s} \leq M \times isStored_{p,s}, \forall p \in PRODUCTS, \forall s \in SILOS$$

C5 Non-negativity or Binary restraints of decision variables

$$tonsOfProduct_{p,s} \geq 0$$

$$isStored_{p,s} \in (0, 1)$$

2.2 Code and Output (Part a)

2.2.1 Code

```
F group23_HW3_p2.mod M X  Untitled-1
C:\Users\danielcarpenter> OneDrive - the Chickasaw Nation > Documents > GitHub > OU-DSA > Metaheuristics > 03 - Homework > HW 03 > AMPL Models
1 # Homework 3 - Integer programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarazonda
4 # March 2022
5 # Problem X
6
7 reset; # Reset globals
8 options solver cplex; # Using cplex for simplex alg
9
10 # SETS =====
11 set PRODUCTS; # The 5 products
12 set SILOS; # The 8 silos for storage
13
14 # PARAMETERS =====
15 param cost {PRODUCTS, SILOS}; # Cost of storing product in silo
16 param supply {PRODUCTS}; # Supply of products
17 param capacity {SILOS}; # Capacity of the silos
18 param M; # Map decision variables together
19
20 # DECISION VARIABLES =====
21 var tonsOfProduct {PRODUCTS, SILOS} >= 0; # Amount of each product p to store in silo s
22 var isStored {PRODUCTS, SILOS} binary; # If a product is stored in a silo or not
23
24 # OBJECTIVE FUNCTION =====
25
26 minimize costOfStorage:
27 sum(p in PRODUCTS, s in SILOS) tonsOfProduct[p,s] * cost[p,s];
28
29 # CONSTRAINTS =====
30
31 # C1: For each silo s, the tons of the supplied product p must be less than or equal to
32 # the capacity limit of silo s
33 subject to meetCapacity {s in SILOS}:
34 (sum(p in PRODUCTS) tonsOfProduct[p,s]) <= capacity[s];
35
36 # C2: For each product p, must use all of the total product that is available
37 subject to useAllProduct {p in PRODUCTS}:
38 (sum(s in SILOS) tonsOfProduct[p,s]) == supply[p];
39
40 # C3: Only one product can be in a silo
41 subject to oneProductInSilo {s in SILOS}:
42 sum(p in PRODUCTS) isStored[p,s] == 1;
43
44 # C4: Map decision variables together
45 subject to mapVars {p in PRODUCTS, s in SILOS}:
46 tonsOfProduct[p,s] <= M * isStored[p,s];
47
48 # CONTROLS =====
49 data group23_HW3_p2.dat;
50 solve;
51
52 print;
53 print "Which silo(s) stores what product?";
54 display isStored;
55
56 print "Optimal tons of product allocated to each silo:";
57 display tonsOfProduct;
```

```
F group23_HW3_p2.dat M X
C:\Users\danielcarpenter> OneDrive - the Chickasaw Nation > Documents > GitHub > OU-DSA > Metaheuristics > 03 - Homework > HW 03 > AMPL Models
1 # Homework 3 - Integer programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarazonda
4 # March 2022
5 # Problem X
6
7 # SETS =====
8
9 set PRODUCTS := A B C D E; # 5 types of products
10 set SILOS := 1 2 3 4 5 6 7 8; # 8 different silos to store product p
11
12 # PARAMETERS =====
13
14 # Cost of storing one ton of product p in silo s
15 param cost:
16
17   1 2 3 4 5 6 7 8 :=
18 A 1 2 2 1 4 4 5 3
19 B 2 3 3 3 1 4 5 2
20 C 3 4 1 2 1 4 5 1
21 D 1 1 2 2 3 4 5 2
22 E 1 1 1 1 1 1 5 5
23
24 # Supply of each product that is available
25 param supply :=
26 A 75
27 B 50
28 C 25
29 D 80
30 E 20
31
32 # Capacity of each silo
33 param capacity :=
34 1 25
35 2 25
36 3 30
37 4 60
38 5 80
39 6 85
40 7 100
41 8 50
42
43 # Variable to map decision variable tonsOfProduct p,s to
44 # isStored p,s. Value is slightly more than the capacity of each silo.
45 param M := 200;
```


2.2.2 Output (Part a)

```
ampl: model 'C:\Users\daniel.carpenter\OneDrive - the Chickasaw Nation\D
CPLEX 20.1.0.0: optimal integer solution; objective 320
48 MIP simplex iterations
0 branch-and-bound nodes
```

which silo(s) stores what product?

```
isStored [*,*] (tr)
:   A   B   C   D   E   :=
1   1   0   0   0   0
2   0   0   0   1   0
3   0   0   1   0   0
4   1   0   0   0   0
5   0   1   0   0   0
6   0   0   0   0   1
7   0   0   0   1   0
8   0   0   0   1   0
;
```

Optimal tons of product allocated to each silo:

```
tonsOfProduct [*,*] (tr)
:   A   B   C   D   E   :=
1   25   0   0   0   0
2   0   0   0   25  0
3   0   0   25  0   0
4   50   0   0   0   0
5   0   50  0   0   0
6   0   0   0   0  20
7   0   0   0   5   0
8   0   0   0  50  0
;
```

2.2.2.1 Analysis of the Output

- Minimized loading cost for 250 tons of 5 products over the 8 silos is 320 (problem does not state cost units).
- Product *A* stores 25 tons in *silo* 1 and 50 tons in *silo* 4
- Product *B* stores 50 tons in *silo* 5
- Product *C* stores 25 tons in *silo* 3
- Product *D* stores 25 tons in *silo* 2, 5 tons in *silo* 7, and 50 tons in *silo* 8
- Product *E* stores 20 tons in *silo* 6

2.3 Problem 2 b

- Create a new objective that also minimizes the distance between capacity and stored tons of product
- *For each silo, minimize the variance between the total capacity and the tons of product*

$$\text{minimize capacityActualVariance : } \text{capacity}_s - \sum_{p \in \text{PRODUCTS}} \text{tonsOfProduct}_{p,s}, \forall s \in \text{SILOS}$$

2.4 Code and Output (Part b)

2.4.1 Code

```

group23_HW3_p2.2.mod
1 # Homework 3 - Integer Programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarandona
4 # March 2022
5 # Problem X
6
7 reset; # Reset globals
8 options solver cplex; # Using cplex for simplex alg
9
10 # SETS =====
11 set PRODUCTS; # The 5 products
12 set SILOS; # The 8 silos for storage
13
14 # PARAMETERS =====
15 param cost {PRODUCTS, SILOS}; # Cost of storing product in silo
16 param supply {PRODUCTS}; # Supply of products
17 param capacity {SILOS}; # Capacity of the silos
18 param M; # Map decision variables together
19
20 # DECISION VARIABLES =====
21 var tonsOfProduct {PRODUCTS, SILOS} >= 0; # Amount of each product p to store in silo s
22 var isStored {PRODUCTS, SILOS} binary; # If a product is stored in a silo or not
23
24 # OBJECTIVE FUNCTION =====
25
26 # Minimize the cost of the storage
27 minimize costOfStorage:
28   sum(p in PRODUCTS, s in SILOS) tonsOfProduct[p,s] * cost[p,s];
29
30 # For each silo, minimize the variance between the total capacity and the tons of product
31 minimize capacityActualVariance(s in SILOS):
32   capacity[s] - sum(p in PRODUCTS) tonsOfProduct[p,s];
33
34 # CONSTRAINTS =====
35
36 # C1: For each silo s, the tons of the supplied product p must be less than or equal to
37 # the capacity limit of silo s
38 subject to meetCapacity {s in SILOS}:
39   (sum(p in PRODUCTS) tonsOfProduct[p,s]) <= capacity[s];
40
41 # C2: For each product p, must use all of the total product that is available
42 subject to useAllProduct {p in PRODUCTS}:
43   (sum(s in SILOS) tonsOfProduct[p,s]) == supply[p];
44
45 # C3: Only one product can be in a silo
46 subject to oneProductInSilo {s in SILOS}:
47   sum(p in PRODUCTS) isStored[p,s] == 1;
48
49 # C4: Map decision variables together
50 subject to mapVars {p in PRODUCTS, s in SILOS}:
51   tonsOfProduct[p,s] <= M * isStored[p,s];
52
53 # CONTROLS =====
54 data group23_HW3_p2.2.dat;
55 solve;
56
57 print;
58 print "Which silo(s) stores what product?";
59 display isStored;
60
61 print "Optimal tons of product allocated to each silo:";
62 display tonsOfProduct;
63
64
group23_HW3_p2.2.dat
1 # Homework 3 - Integer Programming
2 # Adv. Analytics and Metaheuristics
3 # Daniel Carpenter and Iker Zarandona
4 # March 2022
5 # Problem X
6
7 # SETS =====
8
9 set PRODUCTS := A B C D E; # 5 types of products
10 set SILOS := 1 2 3 4 5 6 7 8; # 8 different silos to store product p
11
12 # PARAMETERS =====
13
14 # Cost of storing one ton of product p in silo s
15 param cost:
16   1 2 3 4 5 6 7 8 :=
17   A 1 2 2 1 4 4 5 3
18   B 2 3 3 3 1 4 5 2
19   C 3 4 1 2 1 4 5 1
20   D 1 1 2 2 3 4 5 2
21   E 1 1 1 1 1 1 5 5
22 ;
23
24 # Supply of each product that is available
25 param supply :=
26   A 75
27   B 50
28   C 25
29   D 80
30   E 20
31 ;
32
33 # Capacity of each silo
34 param capacity :=
35   1 25
36   2 25
37   3 30
38   4 60
39   5 80
40   6 85
41   7 100
42   8 50
43 ;
44
45 # Big M Scaler for mapping decision variables in binary prog.
46 param M := 1000;
  
```

2.4.2 Output (Part b)

```
ampl: model 'C:\Users\daniel.carpenter\OneDrive - the Chickasaw
CPLEX 20.1.0.0: optimal integer solution; objective 320
48 MIP simplex iterations
0 branch-and-bound nodes
Objective = costOfStorage
|
which silo(s) stores what product?
isStored [*,*] (tr)
:   A   B   C   D   E   :=
1   1   0   0   0   0
2   0   0   0   1   0
3   0   0   1   0   0
4   1   0   0   0   0
5   0   1   0   0   0
6   0   0   0   0   1
7   0   0   0   1   0
8   0   0   0   1   0
;

Optimal tons of product allocated to each silo:
tonsOfProduct [*,*] (tr)
:   A   B   C   D   E   :=
1   25   0   0   0   0
2   0   0   0   25   0
3   0   0   25   0   0
4   50   0   0   0   0
5   0   50   0   0   0
6   0   0   0   0   20
7   0   0   0   5   0
8   0   0   0   50   0
;
```

2.4.2.1 Analysis of the Output

- The optimal cost actually stays the same, but the amount of iterations to get to that solution is much more.
- The values of the decision variables are the same.

3 - Problem 3

3.1 Mathematical Formulation

3.1.1 Parameters

Parameter Name	Description
theDemand	The demanded amount of products
M	Large scaler that is not inf, used for logical constraints via Big M Method
mcWII	Marginal cost component of WII. Set to \$4.95
availWII	Amount of WII that is available. Set to 18,000
mcWRS	Marginal cost component of WRS. Set to \$2.30
fixWRS	Fixed Cost component of WRS. Set to 20,000
availWRS	Amount of WRS that is available. Set to 14,000
mcWE1	If we buy from WRS, then Marg. cost for WE set to \$3.95
mcWE2	If we do not buy from WRS, then Marg. cost for WE set to \$4.10
availWE	Amount of WE that is available. Set to 7,000
mcWU	Marginal cost component of WU. Set to 4.25
availWU	Amount of WU that is available. Set to 22,000
minBuyAmt	Must buy at least 15k of WU. Set to 15,000
mcWOW1	Marginal cost of 9.50 for WOW 3000 upper bound
mcWOW1Upper	3000 upper bound
mcWOW2	Marginal cost of 4.90 for WOW 3000 + 6000 = 9000 upper bound
mcWOW2Upper	3000 + 6000 = 9000 upper bound
mcWOW3	Marginal cost of 2.75 for WOW Cannot exceed 25000 due to supply

mcWOW3Upper Cannot exceed 25000 due to supply 25000

3.1.2 Decision Variables

3.1.2.1 Main Decision Variables:

Variable Name	Description
WII	Amount of product <i>WOW</i> to produce
WRS	Amount of product <i>WRS</i> to produce
WU	Amount of product <i>WU</i> to produce
WE	Amount of product <i>WE</i> to produce
WE1	Decision variable associated with 3.95 marginal cost for <i>WE</i>
WE2	Decision variable associated with 4.10 marginal cost for <i>WE</i>
WOW	Amount of product <i>WOW</i> to produce
d1WOW	Piece wise component 1 of var <i>WOW</i>
d2WOW	Piece wise component 2 of var <i>WOW</i>
d3WOW	Piece wise component 3 of var <i>WOW</i>

3.1.2.2 Binary Helper Decision Variables:

Variable Name	Description
yWRS1	Used for fixed <i>WRS</i> cost if used
yWRS	Used if <i>WRS</i> is selected
yWII	Used if <i>WII</i> is selected
yWE1	Used if <i>WE1</i> is selected
yWE2	Used if <i>WE2</i> is selected
z	Used to activate only one constraint for <i>WE</i> (below)
yWU	Used for fixed cost if <i>WU</i> used
y1WOW	To model piecewise cost for var <i>WOW</i>
y2WOW	To model piecewise cost for var <i>WOW</i>

3.1.3 Objective Function

minimizecost :

$$\begin{aligned} & mcWII * WII \\ & + fixWRS * yWRS1 + mcWRS * WRS \\ & + mcWE1 * WE1 + mcWE2 * WE2 \\ & + mcWU * WU \\ & + mcWOW1 * d1WOW + mcWOW2 * d2WOW + mcWOW3 * d3WOW \end{aligned}$$

3.1.4 Constraints

Description	Constraint
Upper bound on WII production	$upperBoundWII : WII \leq availWII$
Upper bound on WU production	$upperBoundWU : WU \leq availWU$
Upper bound on WE production	$upperBoundWE : WE \leq availWE$
Upper bound and map to WRS via Big M	$map_yWRS1 : WRS \leq$ $availWRS \times yWRS1$
Map the W vars to the y binary	$mapWE1 : WE1 \leq M \times yWE1$
" "	$mapWE2 : WE2 \leq M \times yWE2$
Map the WRS vars to the y binary	$mapWRS : WRS \leq M \times yWRS$
Map the WII vars to the y binary	$mapWII : WII \leq M \times yWII$
WE: If buy from WRS, then can do WE1. (Use of Mz to choose one constraint)	$ifWRS_ThenWE1 : yWRS \leq$ $yWE1 + M \times z$
WE: If $WE2$, cannot do WII . (Use of Mz to choose one constraint)	$ifWRS_thenNotWII :$ $yWE2 + yWII \leq 1 + M \times (1 - z)$
WE: If $WE1$, then cannot do $WE2$, Must choose one	$only1WE : yWE1 + yWE2 \leq 1$
WE: Finally, set WE to the sum of $WE1$ and $WE2$ for the final output	$setWE : WE = WE1 + WE2$
WU: Buy at least min amount	$buyAtLeastMin : WU \leq$ $availWU \times yWU$
WU: Under the upper bound	$map_yWU : WU \geq minBuyAmt \times yWU$
WOW: connect WOW with $d1WOW$, $d2WOW$, and $d3WOW$;	$X_{WOW} : WOW =$ $d1WOW + d2WOW + d3WOW$
WOW: ensure that the piece wise costs are used correctly,	$piece1a : mcWOW1Upper \times y1WOW \leq$ $d1WOW$
WOW: First Piece (Between 0 and Upper)	$piece1b : d1WOW \leq mcWOW1Upper$
WOW: Second Piece (Between last piece and Upper)	$piece2a : mcWOW2Upper \times y2WOW \leq$ $d2WOW$
WOW: Second Piece (Between last piece and Upper)	$piece2b : d2WOW \leq$ $mcWOW2Upper \times y1WOW$
WOW: Third Piece (Between last piece and Upper)	$piece3 : d3WOW \leq$ $mcWOW3Upper \times y2WOW$
WOW: Cannot go over upper	$upperBoundWOW : WOW \leq$ $mcWOW3Upper$
Meet the total demand	$meetTheDemand : WII + WRS +$ $WE + WU + WOW \geq theDemand$

CX: Non-negativity of Decision Vars

3.2 Code and Output

3.2.1 Code

```
group23_HW3_p3.mod X
C:\Users\daniel.carpenter> OneDrive - the Chickasaw Nation\Documents\GitHub\OU-DSA\Metaheuristics\03 - Homework 3
1  # Homework 3 - Integer Programming
2  # Adv. Analytics and Metaheuristics
3  # Daniel Carpenter and Iker Zarandona
4  # March 2022
5  # Problem 3
6
7  reset;                # Reset globals
8  options solver cplex; # Using cplex for simplex alg
9
10 # GLOBAL PARAMETERS =====
11 param theDemand := 55000; # The demanded amount of products
12 param M         := 10000000; # Large scaler that is not inf
13
14 # WII - Basic Marginal Cost Model =====
15
16     # PARAMETERS -----
17     param mcWII := 4.95; # Marginal cost compnent of WII
18     param availWII := 18000; # Amount of WII that is available
19
20     # DECISION VARIABLES -----
21     var WII >= 0; #amt of product WOW to produce
22
23     # CONSTRAINTS -----
24     s.t. upperBoundWII: WII <= availWII;
25
26 # END OF WII - Basic Marginal Cost Model =====
27
28
29 # WRS - Marginal Cost + Fixed Cost Model =====
30
31     # PARAMETERS -----
32     param mcWRS := 2.30; # Marginal cost compnent of WRS
33     param fixWRS := 20000; # Fixed Cost component of WRS
34     param availWRS := 14000; # Amount of WRS that is available
35
36     # DECISION VARIABLES -----
37     var WRS >= 0; # amt of product WRS to produce
38     var yWRS1 binary; # Binary used for fixed cost if used
39
40     # CONSTRAINTS -----
41     s.t. map_yWRS1: WRS <= availWRS * yWRS1; # Upper bound and map
42
43 # END OF WRS - Basic Marginal Cost Model =====
44
45
46 # WE - Basic Marginal Cost Model =====
47
48     # PARAMETERS -----
49     param mcWE1 := 3.95; # If buy from WRS, m. cost for WE
50     param mcWE2 := 4.10; # Else m. cost for WE
51     param availWE := 7000; # Amount of WE that is available
52
53     # DECISION VARIABLES -----
54     # WE decision vars
55     var WE1 >= 0; # Decision variable associated with $3.95 marginal cost
56     var WE2 >= 0; # Decision variable associated with $4.10 marginal cost
57     var WE >= 0; # Decision variable for final output
58
59     # Binary Vars to see what product is selected
60     var yWRS binary; # If WRS is selected
61     var yWII binary; # If WII is selected
62     var yWE1 binary; # If WE is selected
63     var yWE2 binary; # If WE is selected
64     var z binary; # Activates only one constraint
65
```


group23_HW3_p3.mod X

C:\Users\daniel.carpenter> OneDrive - the Chickasaw Nation > Documents > GitHub > OU-DSA > Metaheuristics > 03 - Homework > HW

```
66 # CONSTRAINTS -----
67 # Map binary variables to show selection of products
68 s.t. mapWE1: WE1 <= M * yWE1; # Map the W vars to the y binary
69 s.t. mapWE2: WE2 <= M * yWE2; # ""
70 s.t. mapWRS: WRS <= M * yWRS; # ""
71 s.t. mapWII: WII <= M * yWII; # ""
72
73 # Logical Constraints
74 # If buy from WRS, then can do WE1. (Use of Mz to choose one constraint)
75 s.t. ifWRS_ThenWE1: yWRS <= yWE1 + M*z;
76
77 # If WE2, cannot do WII. (Use of Mz to choose one constraint)
78 s.t. ifWRS_thenNotWII: yWE2 + yWII <= 1 + M*(1-z);
79
80 # If WE1, then cannot do WE2, Must choose one
81 s.t. only1WE: yWE1 + yWE2 <= 1;
82
83 # Finally, set WE to the sum of WE1 and WE2 for the final output
84 s.t. setWE: WE == WE1 + WE2;
85
86 s.t. upperBoundWE: WE <= availWE; # Meet the upper bound limit
87
88 # END OF WE - Basic Marginal Cost Model =====
89
90
91 # WU - Marginal Cost + Fixed Cost Model =====
92
93 # PARAMETERS -----
94 param mcWU := 4.25; # Marginal cost compnent of WU
95 param availWU := 22000; # Amount of WU that is available
96 param minBuyAmt := 15000; # Must buy at least 15k
97
98 # DECISION VARIABLES -----
99 var WU >= 0; # amt of product WU to produce
100 var yWU binary; # Binary used for fixed cost if used
101
102 # CONSTRAINTS -----
103 s.t. buyAtLeastMin: WU <= availWU * yWU; # Buy at Least min amount
104 s.t. map_yWU: WU >= minBuyAmt * yWU; # Under the upper bound
105
106 # END OF WU - Basic Marginal Cost Model =====
107
108
109 # WOW - Piecewise Linear Cost Model =====
110
111 # PARAMETERS -----
112
113 #assume the Linear costs for decision variable WOW are as follows
114 #cost = 9.50 for 0 <=WOW < 3000
115 #cost = 4.90 for 3000 <=WOW < 9000
116 #cost = 2.75 for 9000 <=WOW < INFINITY
117
118 param mcWOW1 := 9.50; param mcWOW1Upper := 3000; # 3000 upper bound
119 param mcWOW2 := 4.90; param mcWOW2Upper := 6000; # 3000 + 6000 = 9000 upper bound
120 param mcWOW3 := 2.75; param mcWOW3Upper := 25000; # Cannot exceed 25000 due to supply
121 # DECISION VARIABLES -----
122 var WOW >= 0; #amt of product WOW to produce
123
124 var d1WOW >= 0; # piecewise component 1 of var WOW
125 var d2WOW >= 0; # piecewise component 2 of var WOW
126 var d3WOW >= 0; # piecewise component 3 of var WOW
127
128 var y1WOW binary; #to model piecewise cost for var WOW
129 var y2WOW binary; #to model piecewise cost for var WOW
130
131
```

group23_HW3_p3.mod X

C:\Users\daniel.carpenter> OneDrive - the Chickasaw Nation > Documents > GitHub > OU-DSA > Metaheuristics > 03 - Homework > HW

```
131
132     # CONSTRAINTS -----
133
134     #connect WOW with d1WOW, d2WOW, and d3WOW;
135     s.t. X_WOW: WOW = d1WOW + d2WOW + d3WOW;
136
137     #ensure that the piece wise costs are used correctly,
138     #i.e., you have to use all of d1WOW before you use d2WOW,...
139     # First Piece (Between 0 and Upper)
140     s.t. piece1a: mcWOW1Upper*y1WOW <= d1WOW;
141     s.t. piece1b: d1WOW <= mcWOW1Upper;
142
143     # Second Piece (Between Last piece and Upper)
144     s.t. piece2a: mcWOW2Upper*y2WOW <= d2WOW;
145     s.t. piece2b: d2WOW <= mcWOW2Upper*y1WOW;
146
147     # Third Piece (Between Last piece and Upper)
148     s.t. piece3: d3WOW <= mcWOW3Upper*y2WOW;
149
150     # Cannot go over upper
151     s.t. upperBoundWOW: WOW <= mcWOW3Upper;
152
153     # END OF WOW - Piecewise Linear Cost Model =====
154
155     # Last Constraint: Must meet the demand
156     s.t. meetTheDemand: WII + WRS + WE + WU + WOW >= theDemand;
157
158
159     # =====
160     # OBJECTIVE FUNCTION
161     # =====
162
163     minimize cost:      mcWII*WII                # WII: Variable cost only
164                        + fixWRS*yWRS1 + mcWRS*WRS # WRS: Fixed plus variable
165                        + mcWE1*WE1  + mcWE2*WE2   # WE: Continguit mc based on scenario
166                        + mcWU*WU                # WU: Restricted range to over 15k
167                        + mcWOW1*d1WOW + mcWOW2*d2WOW + mcWOW3*d3WOW # WOW: Piecewise
168                        ;
169
170
171     # CONTROLS =====
172
173     solve;
174
175     print;
176     printf "Demand\t| WII\t| WRS\t| WE\t| WU\t| WOW\t| Total Cost";
177     printf "\n%s\t %s\t %s\t %s\t %s\t %s\t %f", theDemand, WII, WRS, WE, WU, WOW, cost;
178     print;
179
180
```

3.2.2 Output

Summary table of Output

Demand	WII	WRS	WE	WU	WOW	Total Cost
5000	0	0	5000	0	0	19750.000000
10000	3000	0	7000	0	0	42500.000000
25000	4000	14000	7000	0	0	99650.000000
35000	0	14000	6000	15000	0	139650.000000
45000	0	14000	6000	0	25000	177800.000000
50000	4000	14000	7000	0	25000	201550.000000
55000	0	14000	1000	15000	25000	221800.000000

Snapshots of Compilation

```

ampl: model 'C:\Users\daniel.carpenter\OneDrive - the Chickasaw Nation\Documents\
CPLEX 20.1.0.0: optimal integer solution; objective 19750
3 MIP simplex iterations
0 branch-and-bound nodes

```

Demand	WII	WRS	WE	WU	WOW	Total Cost
5000	0	0	5000	0	0	19750.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
10000	3000	0	7000	0	0	42500.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
25000	4000	14000	7000	0	0	99650.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
35000	0	14000	6000	15000	0	139650.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
45000	0	14000	6000	0	25000	177800.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
50000	4000	14000	7000	0	25000	201550.000000

Demand	WII	WRS	WE	WU	WOW	Total Cost
55000	0	14000	1000	15000	25000	221800.000000