

Movies Complete

Example moviefun can be browsed at
<https://github.com/apache/tomee/tree/master/examples/moviefun>

Help us document this example! Click the blue pencil icon in the upper right to edit this page.

AddInterceptor

```
package org.superbiz.injection.tx;

import javax.interceptor.AroundInvoke;
import javax.interceptor.InvocationContext;

/**
 * @version $Revision$ $Date$
 */
public class AddInterceptor {

    @AroundInvoke
    public Object invoke(InvocationContext context) throws Exception {
        // Log Add
        return context.proceed();
    }
}
```

DeleteInterceptor

```
package org.superbiz.injection.tx;

import javax.interceptor.AroundInvoke;
import javax.interceptor.InvocationContext;

/**
 * @version $Revision$ $Date$
 */
public class DeleteInterceptor {

    @AroundInvoke
    public Object invoke(InvocationContext context) throws Exception {
        // Log Delete
        return context.proceed();
    }
}
```

Movie

```
package org.superbiz.injection.tx;

import javax.persistence.Entity;

@Entity
public class Movie {

    private String director;
    private String title;
    private int year;

    public Movie() {
    }

    public Movie(String director, String title, int year) {
        this.director = director;
        this.title = title;
        this.year = year;
    }

    public String getDirector() {
        return director;
    }

    public void setDirector(String director) {
        this.director = director;
    }

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public int getYear() {
        return year;
    }

    public void setYear(int year) {
        this.year = year;
    }

}
```

Movies

```
package org.superbiz.injection.tx;

import javax.annotation.security.PermitAll;
import javax.annotation.security.RolesAllowed;
import javax.ejb.Stateful;
import javax.ejb.TransactionAttribute;
import javax.ejb.TransactionAttributeType;
import javax.interceptor.Interceptors;
import javax.persistence.EntityManager;
import javax.persistence.PersistenceContext;
import javax.persistence.PersistenceContextType;
import javax.persistence.Query;
import java.util.List;

//START SNIPPET: code
@Stateful
public class Movies {

    @PersistenceContext(unitName = "movie-unit", type = PersistenceContextType
.TRANSACTION)
    private EntityManager entityManager;

    @RolesAllowed({"Employee", "Manager"})
    @TransactionAttribute(TransactionAttributeType.REQUIRED)
    @Interceptors(AddInterceptor.class)
    public void addMovie(Movie movie) throws Exception {
        entityManager.persist(movie);
    }

    @RolesAllowed({"Manager"})
    @TransactionAttribute(TransactionAttributeType.MANDATORY)
    @Interceptors(DeleteInterceptor.class)
    public void deleteMovie(Movie movie) throws Exception {
        entityManager.remove(movie);
    }

    @PermitAll
    @TransactionAttribute(TransactionAttributeType.SUPPORTS)
    public List<Movie> getMovies() throws Exception {
        Query query = entityManager.createQuery("SELECT m from Movie as m");
        return query.getResultList();
    }
}
```

ReadInterceptor

```
package org.superbiz.injection.tx;

import javax.interceptor.AroundInvoke;
import javax.interceptor.InvocationContext;

/**
 * @version $Revision$ $Date$
 */
public class ReadInterceptor {

    @AroundInvoke
    public Object invoke(InvocationContext context) throws Exception {
        // Log Delete
        return context.proceed();
    }
}
```

persistence.xml

```
<persistence xmlns="http://java.sun.com/xml/ns/persistence" version="1.0">

    <persistence-unit name="movie-unit">
        <jta-data-source>movieDatabase</jta-data-source>
        <non-jta-data-source>movieDatabaseUnmanaged</non-jta-data-source>
        <class>org.superbiz.injection.tx.Movie</class>

        <properties>
            <property name="openjpa.jdbc.SynchronizeMappings" value=
"buildSchema(ForeignKeys=true)"/>
        </properties>
    </persistence-unit>
</persistence>
```

MoviesTest

```
package org.superbiz.injection.tx;

import junit.framework.TestCase;

import javax.annotation.security.RunAs;
import javax.ejb.EJB;
import javax.ejb.Stateless;
import javax.ejb.TransactionAttribute;
```

```

import javax.ejb.TransactionAttributeType;
import javax.ejb.embeddable.EJBContainer;
import java.util.List;
import java.util.Properties;
import java.util.concurrent.Callable;

import static javax.ejb.TransactionAttributeType.REQUIRES_NEW;

/**
 * See the transaction-rollback example as it does the same thing
 * via UserTransaction and shows more techniques for rollback
 */
//START SNIPPET: code
public class MoviesTest extends TestCase {

    @EJB
    private Movies movies;

    @EJB(beanName = "TransactionBean")
    private Caller transactionalCaller;

    @EJB(beanName = "NoTransactionBean")
    private Caller nonTransactionalCaller;

    protected void setUp() throws Exception {
        final Properties p = new Properties();
        p.put("movieDatabase", "new://Resource?type=DataSource");
        p.put("movieDatabase.JdbcDriver", "org.hsqldb.jdbcDriver");
        p.put("movieDatabase.JdbcUrl", "jdbc:hsqldb:mem:moviedb");

        EJBContainer.createEJBContainer(p).getContext().bind("inject", this);
    }

    private void doWork() throws Exception {

        movies.addMovie(new Movie("Quentin Tarantino", "Reservoir Dogs", 1992));
        movies.addMovie(new Movie("Joel Coen", "Fargo", 1996));
        movies.addMovie(new Movie("Joel Coen", "The Big Lebowski", 1998));

        List<Movie> list = movies.getMovies();
        assertEquals("List.size()", 3, list.size());

        for (Movie movie : list) {
            movies.deleteMovie(movie);
        }

        assertEquals("Movies.getMovies()", 0, movies.getMovies().size());
    }

    public void testWithTransaction() throws Exception {
        transactionalCaller.call(new Callable() {

```

```

        public Object call() throws Exception {
            doWork();
            return null;
        }
    });
}

public void testWithoutTransaction() throws Exception {
    try {
        nonTransactionalCaller.call(new Callable() {
            public Object call() throws Exception {
                doWork();
                return null;
            }
        });
        fail("The Movies bean should be using TransactionAttributeType.MANDATORY"
);
    } catch (javax.ejb.EJBException e) {
        // good, our Movies bean is using TransactionAttributeType.MANDATORY as we
want
    }
}

public static interface Caller {
    public <V> V call(Callable<V> callable) throws Exception;
}

/**
 * This little bit of magic allows our test code to execute in
 * the scope of a container controlled transaction.
 */
@Stateless
@RunAs("Manager")
@TransactionAttribute(REQUIRES_NEW)
public static class TransactionBean implements Caller {

    public <V> V call(Callable<V> callable) throws Exception {
        return callable.call();
    }
}

@Stateless
@RunAs("Manager")
@TransactionAttribute(TransactionAttributeType.NEVER)
public static class NoTransactionBean implements Caller {

    public <V> V call(Callable<V> callable) throws Exception {
        return callable.call();
    }
}

```

```
}
```

Running

----- T E S T S -----

```
Running org.superbiz.injection.tx.MoviesTest
Apache OpenEJB 4.0.0-beta-1    build: 20111002-04:06
http://tomee.apache.org/
INFO - openejb.home = /Users/dblevins/examples/movies-complete
INFO - openejb.base = /Users/dblevins/examples/movies-complete
INFO - Using 'javax.ejb.embeddable.EJBContainer=true'
INFO - Configuring Service(id=Default Security Service, type=SecurityService,
provider-id=Default Security Service)
INFO - Configuring Service(id=Default Transaction Manager, type=TransactionManager,
provider-id=Default Transaction Manager)
INFO - Configuring Service(id=movieDatabase, type=Resource, provider-id=Default JDBC
Database)
INFO - Found EjbModule in classpath: /Users/dblevins/examples/movies-
complete/target/classes
INFO - Found EjbModule in classpath: /Users/dblevins/examples/movies-
complete/target/test-classes
INFO - Beginning load: /Users/dblevins/examples/movies-complete/target/classes
INFO - Beginning load: /Users/dblevins/examples/movies-complete/target/test-classes
INFO - Configuring enterprise application: /Users/dblevins/examples/movies-complete
INFO - Configuring Service(id=Default Stateful Container, type=Container, provider-
id=Default Stateful Container)
INFO - Auto-creating a container for bean Movies: Container(type=STATEFUL, id=Default
Stateful Container)
INFO - Configuring Service(id=Default Stateless Container, type=Container, provider-
id=Default Stateless Container)
INFO - Auto-creating a container for bean TransactionBean: Container(type=STATELESS,
id=Default Stateless Container)
INFO - Configuring Service(id=Default Managed Container, type=Container, provider-
id=Default Managed Container)
INFO - Auto-creating a container for bean org.superbiz.injection.tx.MoviesTest:
Container(type=MANAGED, id=Default Managed Container)
INFO - Configuring PersistenceUnit(name=movie-unit)
INFO - Auto-creating a Resource with id 'movieDatabaseNonJta' of type 'DataSource for
'movie-unit'.
INFO - Configuring Service(id=movieDatabaseNonJta, type=Resource, provider-
id=movieDatabase)
INFO - Adjusting PersistenceUnit movie-unit <non-jta-data-source> to Resource ID
'movieDatabaseNonJta' from 'movieDatabaseUnmanaged'
INFO - Enterprise application "/Users/dblevins/examples/movies-complete" loaded.
INFO - Assembling app: /Users/dblevins/examples/movies-complete
INFO - PersistenceUnit(name=movie-unit,
```



```

provider=org.apache.openjpa.persistence.PersistenceProviderImpl) - provider time 402ms
INFO - Jndi(name="java:global/movies-
complete/Movies!org.superbiz.injection.tx.Movies")
INFO - Jndi(name="java:global/movies-complete/Movies")
INFO - Jndi(name="java:global/movies-
complete/TransactionBean!org.superbiz.injection.tx.MoviesTest$Caller")
INFO - Jndi(name="java:global/movies-complete/TransactionBean")
INFO - Jndi(name="java:global/movies-
complete/NoTransactionBean!org.superbiz.injection.tx.MoviesTest$Caller")
INFO - Jndi(name="java:global/movies-complete/NoTransactionBean")
INFO -
Jndi(name="java:global/EjbModule1013462002/org.superbiz.injection.tx.MoviesTest!org.su
perbiz.injection.tx.MoviesTest")
INFO -
Jndi(name="java:global/EjbModule1013462002/org.superbiz.injection.tx.MoviesTest")
INFO - Created Ejb(deployment-id=Movies, ejb-name=Movies, container=Default Stateful
Container)
INFO - Created Ejb(deployment-id=NoTransactionBean, ejb-name=NoTransactionBean,
container=Default Stateless Container)
INFO - Created Ejb(deployment-id=TransactionBean, ejb-name=TransactionBean,
container=Default Stateless Container)
INFO - Created Ejb(deployment-id=org.superbiz.injection.tx.MoviesTest, ejb-
name=org.superbiz.injection.tx.MoviesTest, container=Default Managed Container)
INFO - Started Ejb(deployment-id=Movies, ejb-name=Movies, container=Default Stateful
Container)
INFO - Started Ejb(deployment-id=NoTransactionBean, ejb-name=NoTransactionBean,
container=Default Stateless Container)
INFO - Started Ejb(deployment-id=TransactionBean, ejb-name=TransactionBean,
container=Default Stateless Container)
INFO - Started Ejb(deployment-id=org.superbiz.injection.tx.MoviesTest, ejb-
name=org.superbiz.injection.tx.MoviesTest, container=Default Managed Container)
INFO - Deployed Application(path=/Users/dblevins/examples/movies-complete)
INFO - EJBContainer already initialized. Call ejbContainer.close() to allow
reinitialization
Tests run: 2, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 2.418 sec

Results :

Tests run: 2, Failures: 0, Errors: 0, Skipped: 0

```