

DADSTORM

A simple, fault-tolerant and real-time stream processing system

DAD 2016-2017

Group 12:

Daniel Fermoselle nº 78207

João Marçal nº 78471

Tiago Rodrigues nº 78692

Abstract

DADSTORM is a simple but reliable stream processing system. It's mainly used by Instituto Superior Tecnico Students.

The main features are: the 3 possible semantics of tuple processing it can have, fault-tolerance to f faults per operator with a synchronous model of detection, 3 modes of tuple routing and last but not the least 5 types of operators. This system is composed by a Puppet Master, Process Creation Service, Operators with their Replicas, Tuples and ThreadPools.

1 Introduction

Nowadays with the rising interest on big data streaming information is getting more and more important and we want to process that data as fast as possible even though existing the possibility of having faults. In order to get that information in a reliable way we developed DADSTORM. This system is reliable through the passive replication we use, allowing us to get tolerance to f faults using just $f+1$ replicas.

Our system process tuples based on the type of operator which can be UNIQ, COUNT, DUP, FILTER and CUSTOM. With these operators we can get the data processed in a way that let us get the information we want.

2 Programming Model

In this section, we provide a high-level overview of the programming model, highlighting the key concepts.

In DADSTORM data is represented as string Tuples, i.e, a collection of strings.

To begin with we have a puppet master who will start all the operators on all the machines with the help of the process

```
% This configuration file describes four operators that are used to compute the reach of a URL on Twitter.
%
% Semantics at-most-once | at-least-once | exactly-once
Semantics at-most-once
%
% LoggingLevel Full | Light
LoggingLevel Full
%
% The following lines define an operator.
% OPERATOR ID input ops SOURCE OP ID/FILEPATH... SOURCE OP ID/FILEPATH
% rep fact REP_FACTOR routing primary/ha/primary/random
% address URL1...URLn
% operator spec OPERATOR_TYPE OPERATOR_PARAMS... OPERATOR_PARAMS
%
OP1 input ops tweeters.data rep fact 2 routing hashing() address tcp://1.2.3.4:11000/rep, tcp://1.2.3.5:11000/rep operator spec FILTER 3,*,*,"www.technico.ulisboa.pt"
OP2 input ops OP1 rep fact 2 routing random address tcp://1.2.3.4:11000/rep, tcp://1.2.3.5:11000/rep operator spec CUSTOM mylib.dll,QueryFollowersFile,queryFollowers
OP3 input ops OP2 rep fact 2 routing hashing() address tcp://1.2.3.4:11000/rep, tcp://1.2.3.5:11000/rep operator spec UNIQ 1
OP4 input ops OP3 rep fact 1 routing primary address tcp://1.2.3.10:11000/rep operator spec COUNT
%
% The following commands can be sent by a PuppetMaster to the stream processing nodes:
% Start OPERATOR ID: tells the OPERATOR ID operator to start processing tuples.
% Interval OPERATOR ID X ms: the operator should sleep X milliseconds between consecutive events.
% Status: make all nodes on the system to print its current status.
% Crash OPERATOR ID REP ID: force a process, i.e. a replica of an operator, to crash.
% Freeze OPERATOR ID REP ID: after receiving Freeze, the process continues replicating messages but stops processing them.
% Unfreeze OPERATOR ID REP ID: a frozen process is back to normal execution. It processes all previous pending messages.
% Wait x ms: This command instructs the puppet master to sleep for x milliseconds.
% before reading and executing the following command in the script file.
Interval OP1 500
Start OP1
Start OP2
Start OP3
Start OP4
Status
% Crash OP1 0 crashes replica 0 of OP1
Crash OP1 0
% Freeze OP2 1 freezes replica 1 of OP2
Freeze OP2 1
Wait 10000
% Unfreeze OP2 1 unfreezes replica 1 of OP2
Unfreeze OP2 1
Status
```

Figure 1. An example of a config file.

creation service this last will already be located in all the machines that will run operator replicas.

The puppet master has an intuitive interface inside which we have a box where we can introduce a path to a configuration file (see figure 1) to start all the operator's replicas as well as their inputs, routing, operator spec and address.

The tuples are stored inside a file that will be accessed by the first operator of the stream. The operators are composed by replicas which can be located inside different machines. All the replicas might fail but we assure f fault tolerance to silent failures for each operator. We assume that none of the first operator replicas can fail and that there is at least one replica alive per operator, in order to guarantee that to be possible we have to have at least $f+1$ replicas for each operator, being f the number of faults of each operator.

A quick overall. So first of all we start the puppet master which will through the configuration file introduced and with the help of the process creation service create all the operator's replicas. Then the replicas of the first operator will read the .dat file which has the beginning tuples to be processed. After this initialization all the replicas will re-

ceive tuples and process them, sending the result to the next operators, unless it is a replica of the last operator this one don't send anything just processes tuples.

To finish this section the user of our system doesn't have to worry about how the system is distributing the operations, the user just has to create the configuration file and let the puppet master read then just execute and all the data will be processed, getting in the end the desired information.

3 DADSTORM Abstractions

In this section we will talk a little bit about the abstractions we created for this system, beginning with the tuple and all its variations, having an overview about the operator, the replicas. To finish the section we will talk about the parser, the RepInfo and the ConfigInfo.

3.1 Tuple

Tuple, this is one of the most important abstractions of our system if not the most one. The Tuple is a possible infinite collection of strings, it also has a unique id to be used when the tuple processing semantics requires so. The tuples are processed and when this happen it is created another tuple having as content the result of processing the previous tuple.

To help mostly the processing semantics we created also 3 more variations of the tuple, which are: AckTuple, TimerTuple and Tuple2TupleProcessed.

The AckTuple is no more than a tuple associated with the url of the replica who sent the tuple this url can be used in the future.

The TimerTuple is a tuple associated with a timer of the limit the tuple has to be acked otherwise it'll be resent.

Last but not the list there is the Tuple2TupleProcessed this abstraction contains 2 tuples, the first tuple when processed by some replica generates the second tuple, this association can be useful first to compare if the tuple was already processed and then to return the result of processing the first tuple if necessary.

3.2 Operators and Replicas

In this section we will talk mostly about replicas because they are simply what an operator is.

A replica basically is an object that reads tuples from possibly infinite inputs, processes and finally sends them to the next replicas in the chain.

Each replica has a thread pool which will have 2 threads one for reading tuples and processing them and another thread to send the processed tuples to the next replicas. Each thread has a circular buffer in which the tuples will be waiting to

be read and processed or sent. The replicas also have a RepInfo that will be defined below. A replica also has a status, TODO FINISH

3.3 Parser

The parser is an abstraction used by the puppet master in order to process the configuration file, this parser receives the path to the configuration file and gives to the puppet master an array of ConfigInfo with all the information of the operators and its replicas as well as the list of commands that the puppet master will have to execute.

TODO VERIFICAR

3.4 RepInfo

RepInfo is an abstraction that basically gives all the information that a replica of an operator has to know. It has the notion of replica routing, its parameters as well as the urls of the replicas to which will be sent tuples, the url of the replica, the operator spec i.e what operation the replica will perform, the id of the replica, the sibling replicas i.e the replicas from the same operator.

In short the RepInfo has all the information that a replica needs to know.

TODO SERA NECESSARIO ADICIONAR MAIS COISAS?

3.5 ConfigInfo

This abstraction is almost the same as the RepInfo but for the puppet master. It's through the ConfigInfo that the puppet master can know how to start the replicas with which properties that in the correct time will be sent to the replicas inside the RepInfo

3.6 Failure Recovery

To guarantee failure recovery some of the previous abstractions will be used, but how this is done will be explained in section 4. Some recovery techniques use the Timer Tuples as well as the RepInfo as we will see below.

4 Architecture and Implementation

In this section we will describe in more detail what each component of the architecture of our solution does and how it was implemented.

4.1 Tuple

As said in section 3.1 the tuple is the base of our whole system. The tuple contains a collection of strings and an

unique id, this id is composed by the operator name concatenated with the replica index plus an unique id inside that replica. This first basic tuple is sent between replicas and gets changed every time it's processed. The AckTuple is the first sub-type of tuples and each operator saves an array list with this object until the tuple is acked, this sub-type plus the TimerAck which has the timer to receive ack before resend the tuple work together to guarantee that the tuple is at least received once. Now the last sub-type of tuple is Tuple2TupleProcessed this tuple saves the pair ;Tuple, TupleProcessed; and it's used as a method to let the replica know if the tuple was already processed comparing the id's of the tuple receive and all the pairs Tuple2TupleProcessed saved in an array in each replica.

4.2 Operators and Replicas

The notion of operator is as said before a little bit abstracted as a collection of replicas, that being said in this subsection we will only talk about replicas.

The key of the replicas is to maintain state as well as tracking all the tuples.

Replicas are implemented as object which have a few structures inside: one threadpool, one RepInfo, one status and a few array lists that will be explained in the end of this subsection.

First of all the threadpool, this attribute maintains a reference to access the replica threadpool that has 2 threads: one to read and process and another to send tuples. Each of this threads has a circular buffer where the tuples are stored while waiting to be consumed. When the circular buffer gets full it will block until there is a consume. One of the threads will be constantly running a ConsumeRead method that consumes tuples from the circular buffer reads it and with the replica operator spec processes it, after that, the tuple is sent to the circular buffer of the thread which is always running a ConsumeProcessed method, this thread will take a tuple from its circular buffer and with the replica is going to send to the right next replica.

The RepInfo this structure has a lot of information for one replica(this replica), more specifically: **routing**, the type of routing for this replica, **routingParam**, the parameters of the tuple to in which the routing will be applied in this replica, **nextRouting**, the type of reouting for the possible next replicas, **nextRoutingParam**, the parameters of the tuple to in which the routing will be applied in the possible next replicas, **operatorSpec**, the type of this replica operator, **operatorParam**, the parameters of the tuple on which this replica operatorSpec will be applied, **sendInfoUrls**, the urls of the next replicas, **port**, this replica port, **loggingLvl**, the type of logging that the system is configured for, **input**, the input operators or file of this replica, this is mainly used to get the file.dat, **pmsUrl**, the url of the pup-

pet master, **siblingsUrls**, the urls of the other replicas of the same operator, **myUrl**, the url of this replica, **semantics**, the semantics the system is running, **receiveInfoUrls**, the urls of the replicas which can send tuples to this replica, **operatorId** the id of this replica's operator. With all this information the system can know which replicas should have the copy of the state in case of failure (siblings), which replicas will receive the tuples processed (sendInfoUrls), the type of operator (operator spec).

The status of a replica indicates if it's working or not and there is also information about the replica being frozen.

4.3 Puppet Master

4.4 Process Creation Service

4.5 Failure Recovery

5 Discussion

6 Production Experiences

7 Evaluation

8 Conclusion